

GENERAL ABBREVIATIONS

ABV	ABOVE	I	
AD	AREA DRAIN	ID	INSIDE DIAMETER
AFF	ABOVE FINISHED FLOOR	IE	INSIDE ELEVATION
AP	ACCESS PANEL	IND	INDIRECT WASTE
		INV	INVERT
B		IV	INDUSTRIAL WASTE VENT
BFP	BACK FLOW PREVENTER	IW	INDUSTRIAL WASTE
BMT	BASEMENT		
BWV	BACKWATER VALVE	J	
		JP	JOCKEY PUMP
C		L	
CFS	CUBIC FEET PER SECOND	LAV	LAVATORY
CI	CAST IRON		
CLG	CEILING	M	
CO	CLEANOUT	MH	MANHOLE
COG	CLEANOUT TO GRADE	MR	WOP RECEPTOR
CONC	CONCRETE	MV	MIXING VALVE
CONN	CONNECTION		
CONT	CONTINUATION	N	
CP	CONCRETE PIPE	(N)	NEW
CTL	COUNTERTOP LAVATORY	CN	NORMALLY CLOSED
CTS	COUNTERTOP SINK	NIC	NOT IN CONTRACT
CW	DOMESTIC COLD WATER	NO	NORMALLY OPEN
CWW	CLEAR WATER WASTE		
		O	
D		ORWC	OVERFLOW RAINWATER CONDUCTOR
D	DRY SPRINKLER PIPE		
DB	DIALYSIS BOX	P	
DF	DRINKING FOUNTAIN	PD	PUMP DISCHARGE
DN	DOWN	PH	PENTHOUSE
DOM	DOMESTIC	PIV	POST INDICATOR VALVE
DP	DEEP	PO	PLUGGED OUTLET
DR	DRAIN	PRV	PRESSURE REDUCING VALVE
DSP	DRY STANDPIPE	PS	PLUMBING SECTION
DSN	DOWNSPOUT NOZZLE		
DT	DRUM TRAP	R	
DV	DRAIN VALVE	(R)	REMOVE
DWG	DRAWING	RCP	REINFORCED CONCRETE PIPE
DWP	DOMESTIC WATER PUMP	RD	ROOF DRAIN
		RWC	RAIN WATER CONDUCTOR
E			
(E)	EXISTING TO REMAIN	S	
EL	ELEVATION	S	SOIL
ES	ELECTRICAL SECTION	SN	SANITARY
EWC	ELECTRIC WATER COOLER	SF	SQUARE FEET
EXP COMP	EXPANSION COMPENSATOR	SHR	SHOWER
		SIAM	SIAMESE
F		SK	SINK
FA	FIRST AID	SP	STANDPIPE
FAI	FRESH AIR INLET	SPR	SPRINKLER
FC	FLOW CONTROL	SS	SERVICE SINK
FD	FLOOR DRAIN	SWDR	SAFE WASTE DRAIN
FDV	FIRE DEPARTMENT VALVE		
FDVC	FIRE DEPARTMENT VALVE CABINET	T	
FEC	FIRE EXTINGUISHER CABINET	TP	TRIPLE ALARM PANEL
FH	FIRE HYDRANT	TB	THRUST BLOCK
FHC	FIRE HOSE CABINET	TE	TOP ELEVATION
FHR	FIRE HOSE RACK	TP	TRAP PRIMER
FIN FL	FINISHED FLOOR	TW	TEMPERED WATER
FL	FLOOR	TZV	TRIPLE ZONE VALVE BOX
FP	FIRE PUMP		
FS	FLOW SWITCH	U	
FU	FIXTURE UNIT(S)	UR	URINAL
FV	FLUSH VALVE		
		V	
G		V	VENT
GH	GROUND HYDRANT	VB	VACUUM BREAKER
GPM	GALLON PER MINUTE	VI	VIBRATION ISOLATOR
GRWC	GREEN ROOF RAINWATER CONDUCTOR	VO	VALVED OUTLET
GS	GENERAL SECTION	VTR	VENT THROUGH ROOF
H		W	
HD	HUB DRAIN	W	WASTE
HDR	HEADER	WC	WATER CLOSET
HP	HORSEPOWER	WCO	WALL CLEANOUT
HVAC	HEATING, VENTILATION, AIR CONDITIONING	WF	WASH FOUNTAIN
HW	DOMESTIC HOT WATER	WH	WALL HYDRANT
HWG	HOT WATER GENERATOR	WHA	WATER HAMMER ARRESTOR
HWR	HOT WATER RETURN	WSP	WET STANDPIPE

SYMBOL LEGEND

— S —	SANITARY DRAIN		HWR BALANCING SYSTEM
— — — — —	(SANITARY) VENT PIPE		BALANCING VALVE
— RWC —	STORM DRAIN		CHECK VALVE
— — — — —	DOMESTIC COLD WATER		VALVE IN DROP
— — — — —	DOMESTIC HOT WATER		GAS COCK
— — — — —	DOMESTIC HOT WATER RETURN		SHUT-OFF VALVE (BALL VALVE)
— CO2 —	CARBON DIOXIDE		SHUT-OFF VALVE
— N2O —	NITROUS OXIDE		MONITORED FIRE VALVE
— N2 —	NITROGEN		THROTTLING VALVE
— WAGD —	WASTE ANESTHETIC GAS DISPOSAL		PIPE GUIDE
— NG —	GAS (NATURAL)		OUTSIDE WALL HYDRANT
— PD —	PUMP DISCHARGE PIPING		POST INDICATOR VALVE
— F —	FIRE MAIN		PRESSURE REGULATING VALVE
— A —	MEDICAL AIR		PRESSURE GAUGE & COCK
— VAC —	VACUUM		PRESSURE TEMPERATURE RELIEF (SAFETY) VALVE
— O2 —	OXYGEN		THREE-WAY VALVE
— SP —	SPRINKLER MAIN/BRANCH		TWO-WAY VALVE
— PA —	PRE-ACTION PIPE		DIRECTION OF FLOW
— D —	DRY PIPE		EXPANSION JOINT
— TP —	TRAP PRIMER PIPING		PIPE ANCHOR
— T —	TEMPERED WATER PIPING		PITCH OF PIPE DOWN
	PLUMBING RISER SOIL STACK DESIGNATION		SERVICE RISER-DOWN
	PLUMBING RISER VENT STACK DESIGNATION		SERVICE RISER-UP
	PLUMBING RISER RAINWATER CONDUCTOR STACK DESIGNATION		STRAINER W/GATE VALVE W/NIPPLE & CAP
			STRAINER
			UNION OR FLANGED CONNECTION
			POINT OF CONNECTION NEW TO EXISTING
			HOT WATER RECIRC. PUMP
			CLEANOUT

NOTE: NOT ALL ABBREVIATIONS AND SYMBOLS SHOWN ARE UTILIZED

PLUMBING GENERAL NOTES

1. REFER TO ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS OF ALL EQUIPMENT, ROOF DRAINS AND FIXTURES.
2. PROVIDE ACCESSIBLE CLEANOUTS AT THE BASE OF ALL SANITARY STACKS AND AT THE BASE OF ALL VERTICAL RAINWATER CONDUCTORS.
3. ALL EXCAVATION SHALL BE PERFORMED IN STRICT COMPLIANCE WITH THE REGULATIONS OF [OSHA] THE OCCUPATIONAL SAFETY AND HEALTH ASSOCIATION.
4. PLUMBING PIPING SHALL NOT BE RUN THROUGH ELECTRICAL ROOMS, TELECOMMUNICATIONS ROOMS, OR ELEVATOR MACHINE ROOMS. EXCEPT FOR BRANCH PIPING SERVING EQUIPMENT IN THESE ROOMS.
5. ALL PENETRATIONS THROUGH FIRE RATED CONSTRUCTION SHALL BE FIRE STOPPED IN ACCORDANCE WITH SPECIFICATION.
6. UNLESS NOTED OTHERWISE ALL DRAINAGE PIPING SHALL HAVE A MINIMUM 0.01 SLOPE EXCEPT PIPING 3" AND SMALLER WHICH SHALL HAVE A 0.02 SLOPE.
7. ALL FLOOR DRAINS SHALL BE PROVIDED WITH A TRAP PRIMER CONNECTION. PROVIDE A 1/2" COPPER LINE EXTENDED FROM TRAP PRIMER AS SPECIFIED TO THE PRIMER CONNECTION.
8. ALL DOMESTIC HOT WATER RETURN BRANCH CONNECTIONS SHALL BE EQUIPPED WITH A BALL VALVE, CHECK VALVE, AND BALANCING VALVE.
9. PLUMBING CONTRACTOR SHALL COORDINATE HIS WORK WITH THE WORK OF ALL OTHER CONTRACTORS PRIOR TO START OF PLUMBING SYSTEM INSTALLATION.
10. ALL DRAIN GRATES, CLEANOUT COVERS, AND OTHER FINISH-EXPOSED COMPONENTS SHALL BE PROTECTED FROM DAMAGE. DAMAGED COMPONENTS SHALL BE REPLACED BY CONTRACTOR AT NO ADDITIONAL COST TO CONTRACT.
11. DRAINAGE PIPING CLEANOUTS SHALL BE LOCATED IN UNFINISHED ROOMS, STORAGE ROOMS, CLOSETS, AND JANITOR'S CLOSETS WHERE POSSIBLE. EXTEND FLOOR CLEANOUTS FROM MAIN DRAIN TO THESE ROOMS. CLEANOUT LOCATIONS IN FINISHED ROOMS ARE TO BE SUBMITTED TO ARCHITECT FOR REVIEW PRIOR TO INSTALLATION.
12. PLUMBING CONTRACTOR SHALL COORDINATE HIS WORK WITH THE WORK OF ALL OTHER CONTRACTORS PRIOR TO START OF PLUMBING SYSTEM INSTALLATION.
13. ALL EXPOSED STORM PIPING TO BE INSULATED SHALL HAVE A WHITE FINISH.
14. ALL DIMENSIONS AND EXISTING CONDITIONS SHALL BE CHECKED AND VERIFIED BY THE CONTRACTOR AT THE SITE BEFORE PROCEEDING WITH ANY WORK.
15. MECHANICAL CONTRACTOR SHALL COORDINATE THE LOCATIONS OF FLOOR DRAINS IN MECHANICAL ROOMS WITH HVAC EQUIPMENT.
16. THE PLUMBING CONTRACTOR SHALL ROUGH-IN AND MAKE FINAL CONNECTIONS TO ALL OTHER FURNISHING EQUIPMENT. FINAL CONNECTIONS SHALL INCLUDE DOMESTIC HOT AND COLD WATER, FUEL GAS, DIRECT SANITARY WASTE CONNECTIONS, AND INDIRECT SANITARY WASTE CONNECTIONS FROM EQUIPMENT TO RECEPTOR. THE PLUMBING CONTRACTOR SHALL MAKE ALL CONNECTIONS IN ACCORDANCE WITH THE REQUIREMENTS OF THE APPLICABLE CODES.
17. PROVIDE ALL NECESSARY TEMPORARY OR PERMANENT CAPS OR PLUGS FOR PIPING. DO NOT LEAVE PIPING OPEN ENDED.
18. PRIOR TO STARTING CONSTRUCTION, DETERMINE EXACT INVERT ELEVATION, SIZE, DEPTH, AND LOCATION OF EXISTING UTILITIES WHERE CONNECTIONS ARE TO BE MADE OR INTERSECTIONS OCCUR. NOTIFY DESIGN PROFESSIONAL OF ANY DISCREPANCY BETWEEN DRAWINGS AND ACTUAL FIELD CONDITIONS. WORK BACK TOWARD BUILDING FROM UTILITY CONNECTION FOR ALL PIPING SYSTEMS.
19. MECHANICAL CONTRACTOR SHALL COORDINATE THE LOCATIONS OF FLOOR DRAINS IN MECHANICAL ROOMS WITH HVAC EQUIPMENT.
20. PIPING RISING WITHIN A STORY DESIGNATED AS "RISE" PIPING RISING TO ANOTHER STORY IS NOTED AS "RISE" PIPING DROPPING WITHIN A STORY IS NOTED AS "DROP" PIPING DROPPING TO ANOTHER STORY IS NOTED AS "DOWN".
21. PRESSURE PIPING, STORM PIPING, AND VENT PIPING SHOWN ON RESPECTIVE FLOOR PLANS OCCUR ABOVE THE FLOOR OR IS TO CEILING UNLESS OTHERWISE NOTED.
22. WASTE PIPING SHOWN ON RESPECTIVE FLOOR PLANS OCCUR BELOW FLOOR OR ABOVE CEILING BELOW UNLESS OTHERWISE NOTED.
23. BRANCH TAKE OFF'S SHALL CONNECT TO THE TOP OF MAIN PIPE WHENEVER POSSIBLE.
24. HOSE BIBBS AND WALL HYDRANTS SHALL BE MOUNTED 3'-0" ABOVE FINISHED / GRADE FLOOR EXCEPT WHERE INSTALLED UNDER COUNTERS / LAVS OR UNLESS NOTED OTHERWISE.
25. PROVIDE WATER HAMMER ARRESTORS SIZED PER PLUMBING DRAINAGE INSTALLATION REQUIREMENTS FOR ALL FLUSH WALL FIXTURES AND ELECTRONIC FAUCETS.
26. LOCATION OF NEW PLUMBING PIPING PENETRATIONS IN THE EXISTING BUILDING SHALL BE CAREFULLY COORDINATED. NEW PENETRATIONS SHALL NOT DROP THRU SLAB RIBS OR CONCRETE BEAMS.
27. INSTALLATION SHALL COMPLY WITH ALL REQUIREMENTS OR ASHRAE STANDARD 90.1 - 2019, SERVICE WATER HEATING.

DRAWING INDEX

P-001	PLUMBING GENERAL NOTES
PD100	TYPICAL EXISTING BARRACK DEMOLITION PLANS
P-100	TYPICAL LATRINE PLAN
P-101	TYPICAL LATRINE PLAN
P-102	BOILER BUILDING PLAN
P-500	PLUMBING DETAILS
P-601	PLUMBING SCHEDULE
P-701	DOMESTIC WATER RISER DIAGRAM
P-702	SANITARY AND VENT RISER DIAGRAM



**US Army Corps
of Engineers ®**

[illegible]



JACOBS / EWING COLE	US ARMY CORPS OF ENGINEERS		DESIGNED BY: BLH	ISSUE DATE: DECEMBER 15, 2020
			DRAWN BY: BHT	SOLICITATION NO.:
			CHECKED BY: JK	CONTRACT NO.: W912DS-19-0010
			SUBMITTED BY: BK	
		DATE: 12/15/20	DESIGNED BY: BLH	
		DRAWN BY: BHT	CHECKED BY: JK	
		SUBMITTED BY: BK	ISSUE DATE: 12/15/20	

WEST POINT, NY
REVITALIZATION OF CAMP BUCKNER

PLUMBING GENERAL NOTES

SHEET ID

P-001



SEE ARCHITECTURAL AND STRUCTURAL DRAWINGS FOR WALLS
AND FLOOR SLAB PENETRATION REPAIRS LEFT AFTER
FIXTURES AND PIPES ARE REMOVED.

- 1 REMOVE WATER CLOSET AND ALL ASSOCIATED VALVES AND PIPING.
- 2 REMOVE URINAL AND ALL ASSOCIATED VALVES AND PIPING.
- 3 REMOVE LAVATORY AND ALL ASSOCIATED VALVES AND PIPING.
- 4 REMOVE SHOWER, MIXING VALVES AND ALL ASSOCIATED VALVES AND PIPING. REMOVE SHOWER DRAINS AND ASSOCIATED PIPING.


[illegible]


JACOBS / EWING COLE	US ARMY CORPS OF ENGINEERS		DESIGNED BY: BLH	ISSUE DATE: DECEMBER 15, 2020
			DRAWN BY: BLH	SOLICITATION NO.:
			CHECKED BY: TK	CONTRACT NO.: W912DS-13-0-010
			SUBMITTED BY: BK	
			SIZE: ANSI D	

WEST POINT, NY
REVITALIZATION OF CAMP BUCKNER

TYPICAL EXISTING BARRACK DEMOLITION PLANS

SHEET ID
PD100





G

PLUMBING FIXTURE SCHEDULE

Type Mark	FIXTURE	MOUNTING	MANUFACTURER NAME & MODEL	MINIMUM CONNECTION SIZE					DESCRIPTION
				SS	V	CW	HW	TW	
				0"	0"	0"	0"	0"	
P-1	WATER CLOSET	FLOOR MOUNTED	TOILET: AMERICAN STANDARD, MODEL 3690.001, FLUSH VALVE: ROYAL 115-1.28	4"	2"	1"	0"	0"	VITREOUS CHINA, FLOOR MOUNTED WALL OUTLET, 1.28 GPF, ELONGATED BOWL
P-2	LAVATORY	WALL HUNG	SINK: KOHLER, MODEL K-2035-4, FAUCET MODEL LK423L4	1 1/2"	1 1/2"	1/2"	1/2"	0"	VITREOUS CHINA, 4" CENTER, OVAL BASIN WITH OVERFLOW DRAIN
P-3	WASHOUT URINAL	WALL MOUNTED	URINAL: ACORN, MODEL 1713, FLUSH VALVE: MODEL FVL1.0 GPF	1 1/2"	1 1/2"	3/4"	3/4"	0"	14 GAGE, TYPE 304 STAINLESS STEEL, EXTERIOR SATIN FINISH, DOME STRAINER AND P-TRAP.
P-4	3 SHOWER HEAD UNIT	WALL MOUNTED	BRADLEY, MODEL WS-3W	0"	0"	3/4"	3/4"	0"	18 GAGE, TYPE 304 STAINLESS STEEL, SOAP DISH, 2.0 GPM.
P-5	ELECTRIC WATER COOLER	WALL MOUNTED	HAWSEY TAYLOR, MODEL HTHB-HAC8BLSS-WF	1 1/2"	1 1/2"	1/2"	0"	0"	BI-LEVEL WITH BOTTLE FILLER, SENSOR ACTIVATED
P-6	MOP SINK	FLOOR MOUNTED	FIAT, MODEL TSBCR100					0"	TERRAZZO, 12" HIGH CURBS, STAILLESS STEEL DRAIN BODY
FD-1	FLOOR DRAIN	FLOOR	JOSAM, MODEL 3000-A	3"	1 1/2"	0"	0"	0"	ADJUSTABLE FLOOR DRAIN, ROUND STRAINER
HB-1	HOSE BIBB	WALL MOUNTED	J.R. SMITH, 5670	0"	0"	1/2"	0"	0"	PROVIDE VACUUM BREAKER WITH THE HOSE BIBS.
SD-1	SHOWER DRAIN	FLOOR	JOSAM, MODEL R SERIES	4"	0"	0"	0"	0"	RECTANGULAR DRAIN, SECURED GRATE, VANDAL PROOF SCREWS

F

HOT WATER CIRCULATING PUMP SCHEDULE

Type Mark	LOCATION	BASIS OF DESIGN		SYSTEM	GPM	PUMP HEAD (FT H2O)	RPM	ELECTRICAL DATA			NOTES
		MANUFACTURER	MODEL					HP	PH	Hz	
HWRP-1	BOILER BUILDING	BELL & GOSSETT	E-60 SERIES	DOMESTIC HOT WATER SYSTEM	15	28	1750	0.500	3	60	BRONZEL BODY, INLINE PUMP

E

PLUMBING EXPANSION TANK SCHEDULE

TYPE MARK	LOCATION	BASIS OF DESIGN		SYSTEM	TYPE	TANK VOLUME (gal)	ACCEPTANCE VOLUME (gal)	DIAMETER	HEIGHT	PRESSURE (psi)		NOTES
		MANUFACTURER	MODEL							PRE-CHARGE	MAX OPERATING	
ET-1	BOILER BUILDING	A.O. SMITH	PMET-14	DOMESTIC HOT WATER SYSTEM	PRE-CHARGE D	14.00	10.50	16"	16"	38	150	IAPMO APPROVED

D

MIXING VALVE SCHEDULE

TYPE MARK	LOCATION	BASIS OF DESIGN	SYSTEM	GPM	WATER TEMPERATURE		PIPE SIZE			NOTES
		MANUFACTURER			IN	OUT	CW IN	HW IN	TW OUT	
MV-1	BOILER BUILDING	HOLBY	HOT WATER SYSTEM	126	140 °F	120 °F	2"	2"	2"	CONSTRUCTED ENTIRELY OF BRONZE AND COPPER.

D

BACKFLOW PREVENTER SCHEDULE

Type Mark	FLOW	CW CONNECTION	MANUFACTURER	MODEL	DESCRIPTION
BFP-1	127 GPM	3"	ZURN	MODEL 375	REDUCED PRESSURE TYPE BACKFLOW PREVENTER, DUCTILE IRON, LEAD FREE CONSTRUCTION

C

WATER HAMMER ARRESTER SCHEDULE

MARK	FIXTURE UNITS	PIPE SIZE	HEIGHT	DIAMETER	NOTES
WHA-A	1-11	1/2"	2.62"	3.25"	COPPER LEAD FREE, PISTON TYPE
WHA-B	12-32	3/4"	2.97"	3.25"	COPPER LEAD FREE, PISTON TYPE
WHA-C	33-60	1"	3.59"	3.25"	COPPER LEAD FREE, PISTON TYPE
WHA-D	61-113	1"	5.14"	3.25"	COPPER LEAD FREE, PISTON TYPE
WHA-E	114-154	1"	5.52"	3.25"	COPPER LEAD FREE, PISTON TYPE
WHA-F	155-330	1"	6.67"	3.25"	COPPER LEAD FREE, PISTON TYPE

B

A



**US Army Corps
of Engineers ®**

[illegible]

JACOBS / EWING COLE <i>A Joint Venture</i>	DESIGNED BY: DRAWN BY: BLH	ISSUE DATE: DECEMBER 15, 2020
	CHECKED BY: JK	SOLICITATION NO.: CONTRACT NO.: W912DS-19-0010
	SUBMITTED BY: SIZE: ANSI D	

WEST POINT, NY
REVITALIZATION OF CAMP BUCKNER

PLUMBING SCHEDULE

SHEET ID

P-601

REFER TO SHEET P-001 FOR ABBREVIATIONS, SYMBOLS AND
PROJECT GENERAL NOTES.

[illegible]

JACOBS / EWING COLE	US ARMY CORPS OF ENGINEERS	
	<i>A Joint Venture</i>	
DESIGNED BY: BLH	DRAWN BY: BLH	CHECKED BY: JK
SUBMITTED BY: JK	CONTRACT NO.: W912DS-19-0070	SOLICITATION NO.: DECEMBER 15, 2019
SIZE: ANSI D		

WEST POINT, NY
REVITALIZATION OF CAMP BUCKNER
DOMESTIC WATER RISER DIAGRAM

P-701

G

F


E

D

C

B

A



GENERAL NOTES:

1. REFER TO SHEET P-001 FOR ABBREVIATIONS, SYMBOLS AND PROJECT GENERAL NOTES.
2. PROVIDE VENT THRU ROOF (VTR) WITH A VENT CAP AND MESH SCREEN TO PREVENT ANIMALS AND VERMIN FROM ENTERING AND AND NESTING IN THE SYSTEM.



**U.S. Army Corps
of Engineers®**

[illegible]

JACOBS / EWING COLE	A Joint Venture				
	BLH				DECEMBER 15, 2020
	DRAWN BY:				SOLICITATION NO.:
	CHECKED BY:				CONTRACT NO.:
	JK				W91ZDS-14-2-010
	SUBMITTED BY:				
	BK				
	SIZE:				
	ANSI D				

REVITALIZATION OF CAMP BUCKNER

SANITARY AND VENT RISER DIAGRAM

SHEET ID

P-702