PLUMBING FIXTURE SCHEDULE								
TAG	SYMBOLS		FIXTURES	PLUMBING CONNECTIONS				DESCRIPTION
	PLAN	ELEVATION	TIVIONES	WASTE	VENT	COLD WATER	HOT WATER	
P-1			WATER CLOSET WALL HUNG	4"	2"	1½"	_	TOILET; MAKE: AMERICAN STANDARD MODEL: 3351.101AF WALL MILLENIUM FLOWISE 1.28 GPF FLUSHOMETER TOILET SYSTEM 1.28 GPF WALL-MOUNT ELONGATED FLUSHOMETER VALVE TOILET, ADA COMPLIANT, 1½" INLET SPUD, FULLY GLAZED 2½" TRAPWAY. AMERICAN STANDARD FLUSHOMETER SELECTRONIC FLOWISE MODEL 6065.122 1.28 GALLONS PER FLUSH, ELECTRONIC FLUSH VALVE, HARD-WIRED, FULLY MECHANICAL MANUAL OVERRIDE BUTTON, AUTOMATIC FLUSH AFTER 24 HOURS OF NON-USE, 3-SECOND FLUSH DELAY, 1" IPS SCREWDRIVER BAK-CHECK ANGLE STOP, VANDAL RESISTANT STOP CAP, ADJUSTABLE TAILPIECE, INTEGRAL VACUUM BREAKER AND 1½" SPUD COUPLING PROVIDE WALL CARRIER SIMILAR TO WATTS ISCA-101-R & ISCA-131 FOR BACK TO BACK INSTALLATION & ROUTING OF WASTE HORIZONTAL WITHIN CHASE.
P-2			URINAL	2"	2"	1"	_	URINAL; MAKE: AMERICAN STANDARD MODEL: DECORUM FLOWISE 0.5 GPF HIGH EFFICIENCY URINAL 0.5 GPF VITREOUS CHINA URINAL, ADA COMPLIANT, ¾" INLET SPUD, OUTLET CONNECTION THREADED 2" INSIDE, PROVIDE WALL CARRIER. AMERICAN STANDARD FLUSHOMETER SELECTRONIC FLOWISE MODEL 6062.002 0.125 GALLONS PER FLUSH, ELECTRONIC FLUSH VALVE, HARD—WIRED, FULLY MECHANICAL MANUAL OVERRIDE BUTTON, AUTOMATIC FLUSH AFTER 24 HOURS OF NON—USE, 3—SECOND FLUSH DELAY, 1" IPS SCREWDRIVER BAK—CHECK ANGLE STOP, VANDAL RESISTANT STOP CAP, ADJUSTABLE TAILPIECE, INTEGRAL VACUUM BREAKER AND 1½" SPUD COUPLING. SEE ARCHITECTS DRAWINGS FOR MOUNTING HEIGHTS. LAVATORY; MAKE: KOHLER
P-3			COUNTERTOP LAVATORY	2"	2"	1/2"	1/2"	MODEL: K-2189-1 LADENA 20%"x14%"x8%" DROP-IN MOUNT BATHROOM SINK, RECTANGULAR BASIN WITH CURVED BOTTOM, NO FAUCET HOLES; REQUIRES WALL OR COUNTER MOUNT FAUCET. FAUCET; MAKE: AMERICAN STANDARD MODEL: 2064.195 SENSOR OPERATED PROXIMITY LAVATORY FAUCET, HARD-WIRED AC, 0.5 GPM PCA, VR MULTI-LAMINAR SPRAY. PROVIDE THERMOSTATIC MIXING VALVE 605XTMV10701.
P-4			SHOWER	2"	1-1/2"	1/2"	1/2"	SHOWER; MAKE: AMERICAN STANDARD MODEL: T675.507.002 COLONY SOFT COLLECTION COLONY SOFT FLOWISE SHOWER TRIM KIT. POLISHED CHROME FINISH, METAL LEVER HANDLES, 1.5 GPM MAX FLOW. SHOWER PAN; MAKE: ZORO MODEL: G 2245680, 36"x36" TERRAZZO SHOWER PAN FOR TILED WALL APPLICATION.
NFHB	井	工	HOSE BIB	_	_	_	_	IN UNFINISHED SPACES, WASHDOWN FAUCET SHALL BE POLISHED CHROME—PLATED WALL FAUCET WITH ½" MALE INLET AND ¾" HOSE THREAD OUTLET: CHICAGO #5 WITH #E27 VACUUM BREAKER OR ACCEPTABLE EQUIVALENT.
FD-1		$\overline{}$	FLOOR DRAIN	3"	2"	_	_	FOR TRAFFIC AREA OF GOLF CART STORAGE & MAINT. GARAGE: WADE #W-1210-27 WITH CAST IRON BODY, CAST IRON DRAINAGE FLANGE, SEDIMENT BUCKET, FLASHING COLLAR, 12" ROUND HEAVY DUTY CAST IRON GRATE. PROVIDE PROSET TRAP GUARD.
FD-2		<u>\</u>	FLOOR DRAIN	3"	2"	_	_	FOR MECHANICAL AREA: WADE #W-1100-STD5-1-27 WITH 5" ROUND ADJUSTABLE NICKEL-BRASS STRAINER, CAST IRON BODY, CAST IRON DRAINAGE FLANGE, FLASHING CLAMP, AND SEDIMENT BUCKET. PROVIDE PROSET TRAP GUARD.
FD-3		\	FLOOR DRAIN	3"	2"	_	_	FOR BATHROOMS: WADE #W-1100-STD5-1-27 WITH 5" ROUND ADJUSTABLE NICKEL-BRASS STAINER, CAST IRON BODY, CAST IRON DRAINAGE FLANGE, FLASHING CLAMP, AND SEDIMENT BUCKET.
NOTES:								

1.) REFER TO ARCHITECTURAL DRAWINGS FOR FIXTURE, QUANTITY, LOCATIONS, & MOUNTING HEIGHTS.



IN CHARGE OF JW

CHECKED BY RG

MADE BY AMB

IT IS A VIOLATION OF NYS LAW FOR ANY PERSON TO ALTER THIS DOCUMENT IN ANY WAY, UNLESS ACTING UNDER THE DIRECTION OF A LICENSED PROFESSIONAL ENGINEER. IF A DOCUMENT BEARING THE SEAL ON AN ENGINEER IS ALTERED, THE ALTERING ENGINEER SHALL AFFIX TO THE DOCUMENT THEIR SEAL AND THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNATURE AND THE DATE OF SUCH ALTERATION, AND A SPECIFIC DESCRIPTION OF THE ALTERATION.