					EQUIPMENT LIST (MILSTD 1691)					
				SECTION		PLUMBING	ELECTRICAL	MEDICAL GAS (NFPA 99)	MISCELLANEOUS GAS	NON-MEDICAL GAS MISCELLANEOUS
JSN \1014	NAME Telephone, Wall Mounted w Speaker	QTY 6	ACQ/INS	NUMBER	DESCRIPTION Telephone, wall mounted, 1 line, with speaker.	- PLUI	- EE	. MED		
1030	Locker, 2 Person, Over-Under	8	VC		Two person locker, double tier, 72Hx12Wx18D. This unit includes hooks for coats and hats. Door equipped with safety guard handles. Designed for storage of coats, hats, and other personal belongings. Other width and depths are available.	-	-	-	- -	
1066	Mirror, Float Glass	31	CC	10 28 00	A high quality 1/4" polished float glass mirror 36X18, framed in a one-piece, bright polished, stainless steel channel frame with 90° mitered corners. All edges of the mirror are protected by absorbing filler strips. Mirror has a galvanized steel back with integral horizontal hanging brackets and wall hanger for concealed mounting. For mounting above single wall mounted lavatories located in toilet	-	-	-	- -	
1080	Mirror, Posture, Wall Mounted	8	CC		areas, Doctors examination offices, etc. May also be used above double lavatories, either wall or countertop mounted, found in restroom areas. Wall mounted posture mirror. Consists of a 1/4" plate glass in a sturdy corrosion resistant frame with water proof back. For educational and therapy programs.	-	-	_		
1203	Lift, Patient, Ceiling Lift, Patient, Ceiling	4	CC	11 73 00	An overhead ceiling mounted rail system specifically designed for bariatric patient lifting and movement within a patient room. The system will consist of recessed or ceiling mounted primary and secondary rails, lift motor with carriage, patient harness o An overhead ceiling mounted rail system specifically designed for bariatric patient lifting and movement within a patient room. The system will consist of recessed or ceiling mounted primary and	-	- A	-		
.1203	Lili, Paueri, Celling	25		117300	secondary rails, lift motor with carriage, patient harness or seat, and a hand controller or control box with charger (other charging options may be available). System will facilitate lifting and movement of patient to and from bed, to stretcher, chair, bathroom or other requirements. Lifting capacity is 1000 pounds. Custom design of track layout by manufacturer is essential to meet individual facility	•	A			
4995	Table, Diaper Changing, Wall Mounted	1	CC	10 28 00	requirements. Wall mounted diaper changing table for use in public restrooms. Unit is a fold down system that folds upward when not in use for minimal intrusion into the room. Changing surface is contoured and has safety belt to insure that an infant will not fall from the table. Table is designed to hold no less than 250 pounds static weight. Closed dimensions are approximately 21" H x 36" W x 5" D. Open dimensions vary according to style. One system's open dimensions are 15 " high, 32" wide and 19" deep.	-	-	-		- -
15030 15047	Bench, Stall, Shower, Built In Cabinet, Medicine	29 56	CC	10 28 00	Shower bench; built-in. Eighteen (18) gauge stainless steel frame with anchors built-in into the wall. Size and shape as required. Medicine cabinet mounted in wall with a mirror front. Approximate size 15" W x 25" H x 4" D.	-	-	-		
A5075 A5077	Dispenser, Soap Dispenser, Hand Sanitizer, Hands Free	46	VV	10 20 00	Disposable soap dispenser. One-handed dispensing operation. Designed to accommodate disposable soap cartridge and valve. A touch free wall-mounted hand sanitizer dispenser. For use throughout a healthcare facility. Unit does not include the sanitizing liquid. Units are battery operated.	-	-	-		
\5080	Dispenser, Paper Towel, SS, Surface Mounted	39	VV		A surface mounted, satin finish stainless steel, single-fold, paper towel dispenser. Dispenser features: tumbler lock; front hinged at bottom; and refill indicator slot. Minimum capacity 400 single-fold paper towels. For general purpose use throughout the facility.	-	-	-	-	
5082	Dispenser, Paper Towel, Sensor, Hands Free	12	CC		A surface mounted, sensor activated, automatic, roll paper towel dispenser. The unit dispenses a paper towel automatically only when hands are place in position below the dispenser for maximum sanitation and hygiene. May include adjustable settings for sheet length, time delay, and sensor range. Unit is battery operated or with optional AC power adapter.	-	-	-	-	
5090	Dispenser, Sanitary Napkin, SS, Surface Mounted	3	CC	10 28 00	A surface mounted, satin finish stainless steel, sanitary napkin disposal. Disposal features a flip-up cover, secured to the container by a heavy duty stainless steel piano-hinge. Disposal may be secured to wall or toilet partition. For general purpose use in female toilet stalls or rooms and uni-sex toilet rooms.	-	-	-	- -	
5106	Waste Disposal Unit, Sharps with Glove Dispenser	2	VV		The unit is designed for the disposal of sharps and complies with OSHA guidelines for the handling of sharps. It shall house a 5 quart container and be capable of being mounted on a wall. It shall have a glove dispenser attached. The unit shall be secured by a locked enclosure.	-	-	-		
5107	Dispenser, Glove	4	VV		Examination three (Small Medium, Large) glove dispenser box for wall mounting. Fabricated of either cold rolled steel with a white baked enamel finish, plastic or acrylic. Hardware not included, Option	-	-	-		
5109	Grab Bar, 1-1/4" Dia., SS, 2 Wall, W/C Accessible	6	CC	10 28 00	3 powder coated steel. A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall toilet stall/ room, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for	-	-	-		
\5110	Grab Bar, Shower Use	87	CC	10 28 00	selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab par shall comply with partier-free accessibility guidelines for structural strength. For typical water closet applications in toilet stalls and rooms where ADA (American's With Disabilities Act) requirements must be met. A 1-1/4" diameter, satin finish stainless steel, peened gripping surface, 2 wall shower, grab bar with concealed mounting flanges. Snap over flanges are provided to conceal mounting screws. A					
13110	Glab bar, Shower use	01		10 20 00	selection of mounting kits and concealed anchor devices are available from the manufacturers for different types of installations. Grab bar shall comply with barrier-free accessibility guidelines for structural strength. For typical applications in shower stalls where ADA (American's With Disabilities Act) requirements must be met.	-	-	-	- -	- -
.5115 .5145	Grab Bar, Flip-Up Hook, Garment, Double	56 29	CC	10 28 00 10 28 00	A heavy duty flip-up safety rail for use in rest rooms. The grab bar will be constructed of stainless steel and will extend approximately 30" from the wall when in the extended position. A surface mounted, satin finish stainless steel, double garment hook. Equipped with a concealed mounting bracket that is secured to a concealed wall plate. For general purpose use throughout the	-	-	-	-	
		29		10 28 00	facility to hang various items of apparel.	-		-		
5162	Shelf, Fold Down, Stainless Steel	1	CC	40.00.00	Fold down utility shelf fabricated of stainless steel. The shelf is normally installed in female toilet compartments for the placement of a purse or package. The shelf is surfaced mounted and will automatically return to it's upright position when the object is removed.	-	-	-		
5170	Rod, Shower, with Curtain	30	CC	10 28 00	A concealed mounted, 1" outside diameter, satin finish stainless steel, shower curtain rod with white vinyl shower curtain (72" H) and SS shower curtain hooks. Rod and curtain available in various widths. For general purpose use at shower stall or bathtub locations. Pricing based upon standard shower stall dimensions of 36" x 36" and a standard curtain height of 72". Rod installed by CC, Curtain provided by the VA.	-	-	-	- -	- -
5180	Track, Cubicle, Surface Mounted, With Curtain	29	CC	10 21 23	Surface mounted cubicle track, with curtain. Track constructed of thick extruded aluminum. Equipped with self lubricating carriers, beaded drop chain hooks, and flame resistant curtain. To include removable end caps. Designed to be suspended around patient areas where privacy is needed. Price listed is per foot of the track, curtains to be priced per quote.	-	-	-		
5195	Dispenser, Toilet Tissue, SS, 1-Roll, Surface Mounted	30	CC	10 28 00	A concealed surface mounted, single roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates one standard-core toilet tissue roll through 5" in diameter. Spindle is chrome plated plastic with a heavy-duty internal spring and turns freely for non-controlled delivery. For general purpose use in restrooms.	-	-	-		
5200	Dispenser, Toilet Tissue, SS, 2-Roll, Surface Mounted	3	CC	10 28 00	A concealed surface mounted, double roll, satin finish stainless steel, toilet tissue dispenser. Unit accommodates two standard-core toilet tissue rolls through 5" in diameter. Spindles are chrome plated plastic with a heavy-duty internal spring and turn freely for non-controlled delivery. For general purpose use in restrooms.	-	-	-	-	
5205	Bar, Towel	28	CC	10 28 00	A surface mounted, satin finish stainless steel, 1" diameter, towel bar. Support posts and flanges are one piece, chrome-plated, cast heavy brass with satin finish. Towel bar shall not rotate within support posts. Available in 18", 24" and 30" widths. For general purpose use in shower or bathtub rooms. Pricing based upon a suggested standard width of 18".	-	-	-		
5212	Bracket, Television, Wall-Mounted, Tilt/Angle	32	CC	11 52 71	A wall mounted, tilt/angled TV bracket for 37" to 80" TVs. Mount will be a universal and VESA compliant unit with a load capacity of up to 130 lbs.	-	-	-	-	
5220	Bracket, Television, Wall-Backing Artwork. Decorative With Frame	32	CC	11 52 71	Wall mounted television bracket backing which provides additional support and strength for the installation of the television bracket. Option available for interior or exterior plate and sized for 12" 16" or 24" stud spacing. This JSN is to be used for determining and defining locations of decorative artwork.	-	-	-		
6046 6330	Intercom - Room To Room	7	CC		Intercom for local communication between rooms. May be used for areas such as a seclusion ante-room to the seclusion room or other areas such as the accelerator caves and the accelerator control area.	-	A	-	-	
02D0 03E0	Cabinet, Base, 4-Drawer Cabinet, U-C-B, 1 Shelf, 1 Drawer, 2 DO	2	CC	12 32 00	Standing height under counter base cabinet with four full width drawers of equal height. Also referred to as a drawer cabinet. For general purpose use throughout the facility. Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For	-	-	-	<u>- .</u>	
		4			general purpose use throughout the facility.	-	-	-		
03F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO	16	CC	12 32 00	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	-	-	-		
	Cabinet, Sink, U/C/B, 2 Door	1	CC	12 32 00	Standing height under counter base sink cabinet. 36" H x 30" W x 22" D with two solid hinged doors. Also referred to as a double-door sink cabinet. For general purpose use throughout the facility where a sink is to be used. Coordinate actual clear cabinet dimension with the actual outside dimension of sink that is specified to ensure that they are compatible.	-	-	-		
04E0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO	1	CC	12 32 00	Standing height under counter base cabinet with an adjustable shelf and a full width drawer above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	-		-		
04F0	Cabinet, U/C/B, 1 Shelf, 2 Half DR, 2 DO	6	CC	12 32 00	Standing height under counter base cabinet with an adjustable shelf and two half width drawers above solid hinged doors. Also referred to as a combination cabinet or a drawer and cupboard cabinet. For general purpose use throughout the facility.	-	-	-		
04Q0	Cabinet, ADA Sink, Wall-Mounted	/	CC	12 32 00	Wall mounted sink support cabinet for drop-in sink with vertical fascia and angled ADA profile, also referred to as ADA sink cabinet. Removable front panel to permit access to plumbing. Medium density M-3 particle board core construction faced with high pressure vertical grade decorative plastic laminate on exposed surfaces and melamine on semi-exposed and concealed surfaces; plastic laminate edge banding. Includes all attaching hardware including support rail.	-	-	-	- -	- -
09F0M	Cabinet, U/C/B, 2 Half Drawer, 2 Door	28	CC	12 32 00	Sitting height under counter base cabinet, 30" H x 36" W x 22" D with two half width drawers above solid hinged doors. Also referred to as a combination cabinet or drawer and cupboard cabinet. For general purpose use throughout the facility.	-	-	-	- .	
E031	Cabinet, W/H, 2 Shelf, 2 DO, Non-Sloping Top	17	CC	12 32 00	Wall hung cabinet with two adjustable shelves and solid hinged doors. Also referred to as a solid hinged double door wall case (appropriate door hinge configuration to be indicated on equipment elevation drawings).	-	-	-	- .	- -
E031M	Cabinet, W/H, 2 DO, Non-Sloping Top	8	CC	12 32 00	Wall hung cabinet with two adjustable shelves and solid hinged doors. Also referred to as a solid hinged double door wall case (appropriate door hinge configuration to be indicated on equipment elevation drawings).	-	-	-	- .	- -
S230	Sink, SS, Double Compartment	6	CC	22 40 00	Double compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For general purpose use throughout the facility.	D	-	-	- -	- -
S240	Sink, SS, Single Compartment	2	CC	22 40 00	Single compartment stainless steel sink, drop-in, self-rimming, ledge-type, connected with a drain and provided with a mixing faucet. It shall also be provided with pre-punched fixture holes on 4" center, integral back ledge to accommodate deck-mounted fixtures, brushed/polished interior and top surfaces, and sound deadened. Recommended for use in suspended or U/C/B sink cabinets having a high plastic laminate or Chemsurf laminate countertop/work surface. Coordinate actual outside sink dimensions with the actual clear dimension of cabinet specified to ensure that they are compatible. For	D	-	-		
T020	Countertop, Solid Surface	8	CC	12 36 00	general purpose use throughout the facility. A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product.	-	-	-		- -
T020	Countertop, Solid Surface	6	CC	12 36 00	Standard thickness of 1", and a 4" butt backsplash/curb. Also A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring	-	-	-		- -
TOOF	Countarion Colid Curfoco with Cink	40	00	10.26.00	optimum physical and chemical resisting properties.					
T025	Countertop, Solid Surface, with Sink	18	CC	12 36 00	A solid, nonporous countertop approximately 36"W x 22"D with a undercounter sink combination. The countertop is an acrylic-based solid surface product with a standard thickness of 1", and a 4" butt backsplash/curb. Surfaces will be easy to clean and maintain. Also referred to as a work surface or work top with sink. Available in a choice of colors, depths and sink shapes. Used for various applications in patient rooms, restrooms and throughout the facility. Usually a part of a casework interior design program. Unit does not include the drain and faucet.	-	-	-	- -	- -
T025	Countertop, Solid Surface, with Sink	10	CC	12 36 00	A solid, nonporous countertop with a smooth seamless appearance. Easy to clean and maintain and with proper cleaning does not support the growth of mold. An acrylic-based solid surface product. Standard thickness of 1", and a 4" butt backsplash/curb. Also referred to as a work surface or work top. Available in a choice of colors and depths. Used in lab and other hospital areas requiring	-	-	-	- .	- -
0063	Workstation, L-Shaped w Peninsula, Wall Mtd	3	VV		optimum physical and chemical resisting properties. THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips 2 Lockable Flipper Units 2 Shelves, Storage/Display 2 Lights 1 Tackboard 2 Tool Rails 2 Paper Trays 1 Diagonal Tray 1 Cantilevered Work	-	A	_		
0224	Worksurface, Computer, O/H Cab, Wall Mtd, 60" W	6	VV		Surface 1 Peninsula Work Surface 1 Adjustable Keyboard Tray 1 Mobile Pedestal, Box/File 1 Pencil Drawer 1 Cpu Holder THIS TYPICAL INCLUDES: 3 Vertical Hanging Strips; 2 Lockable Flipper Units; 2 Shelves, Storage/Display; 2 Lights; 1 Tack Board; 2 Tool Rails; 2 Paper Trays; 1 Diagonal Tray; 1 Cantilevered Work	_	A			
0903	Locker, Supply, w Shelves	4	VV		Surface; 1 Adjustable Keyboard Tray; 1 Stationary Pedestal, Box/Box/File THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an E0921 to transport the locker from place to place.	-	- A	-		
	Locker, Supply, W Snelves Locker, Supply, General	4	VV		THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Supply Locker 1 Drawer, 9"H 4 Tray/Shelves Drawer Organizers Consider the need for an Eug21 to transport the locker from place to place. THIS TYPICAL INCLUDES: 1 Wall Mounted Rail 1 Locked Storage Container 2 Tray/Shelves 1 Drawer, 3"H 3 Drawers, 6"H 2 Drawers, 9"H 1 Tray/Shelf Divider Drawer Organizer Bins Consider the need for an E0921 to transport the locker from place to place.	-	-	-	- -	- -
0945	Cart, Computer, Mobile, 36"H x 32"W x 22"D	2	VV		THIS TYPICAL INCLUDES: 1 Cart Body, w/Computer Support, Style-A Narrow, w/Raised Edge Top; 1 Flip-Up Shelf; 1 Sharps Container Holder; 1 Wastebasket; 1 Chart Holder; 2 Drawers, 3"H	-	-	-		
0957	Cart, Medication, Mobile	5	VV		(76mm); 2 Drawers, 6"H (152mm); 3 Accessory Rail, Side Drawer Organizer Bins. THIS TYPICAL INCLUDES: 1 cart body, style-A narrow, w/raised edge top; 1 lock bar; 2 accessory rails, side; 1 wastebasket; 1 sharps container holder; 1 flip-up shelf; 1 flashlight holder; 1 wall lock; 2 drawers, 3"H; 1 locked drawer, 6"H w/locked lid; 3 8 hin cassette assembly and drawer organizer hins.	-	-	-		
	Bookcase, 3 Shelf	2	VV		drawers, 3"H; 1 locked drawer, 6"H w/locked lid; 3 8-bin cassette assembly and drawer organizer bins. Freestanding open metal shelf book case, approximately 60" high X 36" wide X 18" deep with three (3) adjustable shelves and four (4) non-marking floor glides.	-	-	-		
		28	l W	1	Upholstered side chair approximately 32" high X 19" wide X 23" deep with floor glides. Seat is non-tilting and without arms.	-	-		- -	- -
	Side Chair without Arms Chair, Dining Room	42	VV		Dining room chair with glides. Chair has straight legs with cushioned cloth or vinyl seat. Drafting chair approximately 47" high X 20" wide X 20" deep with rotary stool and a 5 (five) star base with casters. Padded seat and back. Foot ring adjusts with chair.					

JSN	NAME	QTY	ACQ/INS	SECTION NUMBER	DESCRIPTION	PLUMBING	ELECTRICAL	MEDICAL GAS (NFPA 99)	MISCELLANEOUS GAS	NON-MEDICAL GAS
	r, Recliner	28	W		Reclining chair, 46" high X 33" wide X 40"deep with arms, straight leg base and floor glides or lockable two (2) inch casters. Seat, back and foot rest are foam padded and upholstered with woven textile fabric or vinyl.		·	-	-	-
0275 Chair	r, Swivel, High Back	19	W		Highback contemporary swivel chair, 41" high X 23" wide X 23" deep with five (5) caster swivel base and arms. Chair may be used at desks or in conference rooms. Back and seat are foam padded and upholstered with either woven textile fabric or vinyl.	-	-	-	-	-
	r, Waiting Room, Single r, with Hair Dryer	1	VV		Single seat waiting room chair with foam padded seat and back. Upholstered with either woven fabric textile or vinyl. Arms and floor glides included. Salon dryer chair made of a wooden frame with padded cushions and durable arm rests. The Chair is covered with a vinyl-like material. The chair should fit most standard dryers. A standard dryer should have low/medium/high settings with a maximum of 145 degrees F. Dryer can be purchased separately (included as part of this JSN).	-	- A	-	-	-
321 Chair	r, Salon	1	W		Salon chair made of high density polyurethane foam black cushions, armrests, foot rest, chrome steel frame and chrome stainless steel base. Chair has 360 degree swivel rotation with pneumatically adjustable height.	-	-	-	-	-
	, Upholstered net, Bedside	4 55	VV		Executive sofa with woven fabric textile or vinyl upholstery, foam padded arms, steel spring and foam rubber backs and seats, and floor glides. Bedside cabinet for storage of both the patient's personal items and small patient support items. Approximately 31" high X 21" wide X 19" deep with one (1) drawer and one (1) closed storage closet.	-	-	-	-	-
	n, Open Shelves	28	CC	12 32 00	Drawer is removable so interior can be sanitized. May come in a 3 drawer version. Freestanding clean linen cabinet used in the residential living environment. Made of solid wood and veneer. Typical features include 2-3 doors, storage shelves and 2-3 drawers.	-	-	-	-	-
	set, Mop, With Wringer, 26 Quart drobe, Patient Clothing	2 28	VV	12 32 00	Mobile mop bucket / wringer combination, approximately 35" H x 17" W x 22" D with four 2" casters. Total capacity is 26 quarts. Unit used for general hard surface floor maintenance. Clothing wardrobe for storage of patient clothing in a LDR/ LDRP or patient rooms. This item is selected to match the resuscitation Armoire, JSN F0550, if used, in finish and style.	-	-	-	-	-
	K, Dresser Combo	28	CC	12 32 00	This unit is a combination desk and attached dresser. The desk may include a shelf or drawer for a computer keyboard tray and a minimum of 30" knee space. The dresser component typically has 2 large or 3 medium sized drawers. Finish should be selected to be complimentary to adjacent accent furniture.	-	-	-	-	-
36 Table	e, Computer, Small e, Coffee, Round	2 2	W		Small sized computer table/workstation, approximately 35" high X 36" wide X 30" deep with enough surface for a CPU, monitor and keyboard. Round shaped coffee table approximately 36 W x 18 H. Table is made of wood with tapered legs and should be complimentary to adjacent accent furniture.	-	-	-	-	-
80M Table	e, Occasional, Lamp e, Dining	38	VV		Occasional lamp table (end table) approximately 20" high X 27" wide X 27" deep with choice of finishes (wood, oak veneer, or high pressure laminate). Work table approximately 29" high X 60" wide X 30" deep with top and four (4) non-folding legs.	-	-	-	-	-
	e, Dining ket, Wastepaper, Fire Resistant	59	VV		Dining table. Round 42" diameter or square 42" X 42". Used in dining facilities and can comfortably seat up to four (4) persons. Wastepaper basket, fire resistant, approximately 40 quart capacity. This unit is used to collect and temporarily store small quantities of paper refuse in patient rooms, administrative areas and nursing stations. Size and shape varies depending on the application and manufacturer selected.	-	-	-	-	-
	ket, Wastepaper, Step-On	3 2	W		"Step-on" wastepaper basket with inner liner and foot petal activated flip top.	-	-	-	-	-
	te Receptacle Trash, 44 Gallon	2	VV		Rectangular steel waste receptacle with step-on lid and 24 gallon capacity. The receptacle is used to collect and temporarily store small quantities of paper refuse. Can be used in restrooms, patient areas, laboratories, pharmacies, etc. Forty four (44) gallon trash can, 32" high X 24" diameter, with lid. Used to collect and transport refuse from a point of origin to point of disposal (example: from soiled utility or a nursing unit to the trash	-	-	-	-	-
	Resident	28	VV		compactor at housekeeping). Single bed, approximately 18" high X 83" wide X 40" deep. Bed is used for non-inpatient stay activities (testing, visitor/staff sleeping).	-		-	-	-
	p, Table, With Shade k, Battery, 12in Dia	32 28	VV		Table lamp, 27-34" high X 6" wide X 6" deep with linen shade. Convenience outlet required at point of use. Clock, 12" diameter. Round surface, easy to read numbers with sweep second hand. Wall mounted unit for use when impractical to install a fully synchronized clock system. Battery operated, (batteries	-	_	-	-	-
	cise Machine, Elliptical	1	VV		not included). An elliptical training machine to simulate stair climbing, walking or running without causing excessive pressure to the joints and to decrease risk of impact injuries. Provides a non-impact cardiovascular workout in a gym or in rehabilitation exercise protocols in a physical therapy clinic. The unit includes upper body handlebars for a total workout. The elliptical can be self-powered by user generated motion or electric powered to adjust motion and for supplying electronic consoles and resistance systems. Some models have optional direct or telemetric pulse monitoring. Database electrical	-	-	-	-	-
52 Brew	ver, Coffee, Auto, Elect, 3 Burner, Front/Back	3	VV		specifications are for those models which require power. Refer to the manufacturers' specifications to verify electrical requirements. Space saving front to back automatic coffee maker. This unit includes a heating tank, connection for a cold water supply, decanter service with three burners, funnel and a water flow controller. The unit is used for semi-automatic coffee brewing in cafeterias and commercial institutions. The unit automatically shuts off the water flow when enough has passed through to fill the pot. The unit is normally provided plumbed with a hot water faucet to the side for making other hot drinks (tea, cider, cocoa, etc.). The database height dimension does not include the clearance for coffee decanters warming on the upper burners.	J	A	-	-	-
50 Toas	ster, Pop-Up, 4 Slice, Electric	1	VV		Four (4) slice, electric pop-up toaster. The toaster casing is made from stainless steel and can produce up to 290 slices/hr. This is used to toast sliced bread in food service kitchens and hospital cafeteria operations. Several electrical power configurations are available; some may require special wall receptacles. Refer to manufacturers' specifications.	-	С	-	-	-
30 Reco	order-Player, Digital, Video, DVD	3	VV		Professional medical grade DVD video recorder/player. Approximately 5" high X 10" wide X 14" deep. Meets NTSC and PAL standards and employs MPEG2 video compression. Capable of high speed picture search, direct recording into available disc space and recording and playback on various DVD formats. Audio uses Dolby digital format. Convenience outlet required at point of use.	-	A	-	-	-
	vision, Flat Screen	28	CC	11 52 71	Flat screen television with approximately 32" to 40' diagonal screen size. The TV will have built-in speakers, NTSC tuner, a 16:9 wide screen aspect ratio, a minimum of 1280 x 768 resolution and a remote control.	-	A	-	_	-
	vision, HDTV, Large Screen, 60in definition (HDTV) multimedia flat panel	2	CC	11 52 71 11 52 71	A high definition (HDTV) multimedia, slim design, 60"W to 65"W color television. The TV will have a 16.9 wide screen aspect ratio with full HD 1080p resolution and HDMI connections. TV may be LED, Plasma or LCD. TV will include a stand. High definition (HDTV) multimedia flat panel LED 40" class display television. The TV will have a 16:9 wide screen aspect ratio, minimum of 1920 x 1080 display resolution, digital tuner, minimum	-	A A	-	-	
	ving, Storage, Wire	14	W	11 32 71	refresh rate of 60Hz, minimum of two HDMI ports and 1 USB port ENERGY STAR certified. Stationary, wire, shelving unit. Unit has fully adjustable shelves constructed of stainless steel. For use in general purpose storage areas. Shelving is provided in various sizes and configurations. Price	- -		-	<u>-</u>	<u>-</u>
	per, Linen, Mobile, w-Lid	34	W		provided is for a unit approximately 74"H x 18"D x 48"W with four shelves. Mobile linen hamper with hand or foot operated lid. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Holds 25" hamper bags. Mounted on ball bearing casters. For linen	-	-	-	-	
72 Fram	ne, Infectious Waste Bag with Lid	2	W		transport in hospitals and clinics. Frame for an infectious waste collection bag. Made of heavy tubular stainless steel with heavy gauge welded steel platform. Adjust to hold 18" or 25" trash bags. Mounted on ball bearing casters and	-	-	-	+	
	ket, Infectious Waste, Step-On	2	W		includes permanently mounted hinged lid. Provides means of bagging infectious waste at point of waste generation. A biohazard waste container with a step-on lid. The container will have a capacity of approximately 12 gallons and be made of a fire safe material.	-	-	-	<u> </u>	-
	ibution System, Medication, Automatic cher, Mobile, CRS, 9 Position	2 2	W		An automated dispensing system that provides controlled dispensing, inventory and security. Size and cost will vary dependent on number of modules selected. Mobile stretcher. All corrosion resistant stainless steel construction. It consists of a tubular frame with side rails, a 9-position hydraulic base with pneumatic fowler adjustment, and a 2" pad. Unit is mounted on 8" conductive casters. Designed for patient transport as well as for minor surgical procedures.	B -	- -	-	-	-
25 Chair	r, Exam/Treatment, With Motor	1	W		Exam/treatment chair with motor. Chair is electrically powered and can be positioned for a wide range of procedures. Unit is mounted on a 24"(approx) iron casting base with foot controls on both sides of the chair. Chair is equipped with footrests and fully adjustable headrest and armrests. It is used in hospitals, clinics, or office settings for examinations, treatments, and minor procedures.	-	Α	-	-	-
15 Cond	ditioner, Cold Treatment Pack	2	W		Refrigeration unit for twelve cold therapy packs. Unit features thermostatic temperature control, automatic defrosting and refrigeration grade insulation. Interior chamber is designed to facilitate periodic cleaning. Smaller capacity models are available.	-	Α	-	-	-
74 Ultras	sound	2	W		Ultrasound unit in combination with a neuromuscular stimulator; unit can deliver both types of treatments simultaneously or individually. The ultrasound unit operates at one or more frequencies. The electrotherapy portion of the instrument can operate at set voltages or continuously variable across a range. Depending on the ultrasound frequency and electrotherapy voltage, the clinician selects one	-	Α	-	-	-
B5M Exerc	cise, Treadmill	1	W		of several treatment unit heads. Some models feature microprocessor controls, data collection, data correlation and data downloading for analysis over time. Battery powered electromyograph, temperature or skin conductance unit for monitoring progress and effort in rehabilitation sessions. Unit has a single or dual channels and provides sound and/or visual feedback to the patient. Electrical requirements are for separate battery recharging unit.	-	D	-	-	-
40 Physi	sical therapy parallel bars	1	W		Physical therapy parallel bars. Unit can have manual or electrically powered adjustments. Bar height is adjustable from 25" to 40" and the bar width is adjustable from 16" to 25". Hand rails are chrome plated 1-1/2" steel tubing. Walking aisle is a minimum of 24" wide and finished in natural wood or covered with vinyl matting. Database information reflects 10' or 12' bar length electrically powered units.	-	-	-	-	-
00 Eyew	vash, Wall Mounted, Hands-Free	4	СС	22 40 00	Wall mounted emergency eye wash station. The flow of water from the unit is activated by hand. Upon initiation of water flow the unit will operate hands free to provide streams of water to clear foreign particles or dilute caustic liquids from the eyes in emergency situations. Used in laboratories and areas of the hospital where employees are subject to foreign bodies or liquid material to the eyes.	В	-	-	-	-
70 Lavat	tory, Viteous China	28	CC	22 40 00	An undercounter or countertop mounted vitreous china lavatory (approximate bowl size 6"x17"x14") with gooseneck spout, wrist blade handles, and grid drain. Counter top mounted lavatory to be self rimming with mounting kit provided. Undercounter lavatory to have unglazed rim with a mounting kit also provided. For general purpose use in vanity tops in public, patient and staff toilet rooms.	D	-	-	-	-
	tory, Viteous China	8	CC	22 40 00	Wall mounted, slab type, vitreous china, lavatory (approximate bowl size 7"x15"x10") with: faucet holes on 4" centers; gooseneck spout; wrist blade handles; and grid strainer. It shall be suitable for use in clinics, offices, washrooms or patient care area.	D	-	-	-	-
	, Shampoo, Porcelain , Mop, Molded Stone	2	CC	22 40 00 22 40 00	High gloss porcelain wall mounted shampoo bowl for hair washing. Includes fixture, wall mount, spray nozzle with hose, strainer and water control fixture. Mop service sink approximately 10"H x 36"W x 24"D. Also called a mop service basin and a mop receptor. Unit is made of molded stone and is a one piece item. It shall include a service faucet hose,	D D	-	-	-	-
10 Show	wer, Hand-Held	29	CC	22 40 00	hose bracket and mop hanger. Used in utility rooms for cleaning mops and floor cleaning equipment. A complete, barrier-free, single hand-held, personal shower system. The shower system includes: pressure balanced mixing valve with high temperature limit stop; personal hand shower; shower hose; wall supply; and slide bar. For general purpose use throughout the facility in shower stalls.	D	-	-	-	
Sink,	, Flushing Rim, China	2	СС	22 40 00	Flushing rim sink approximately 18" H x 26" D x 22" W. Also called a clinic service sink. Unit is constructed of vitreous china with an integral flushing rim. It includes: faucet with a fork brace; 6 inch wrist control handles; plain end spout with bucket hook; stainless steel spring type front rim guard; and grid drain. If it is to be floor mounted, a base must be provided. Unit is used in utility rooms to clean	D	-	-	-	-
50 Toilet	st, Wall Hung, Siphon Jet	29	CC	22 40 00	equipment and materials. Siphon jet water closet/ toilet. This unit is wall hung with an elongated bowl, top spud flushometer, seat with open front and check hinge, and carrier. Used in restrooms throughout the health care	В	-	-	-	-
66 Toilet	et, Floor Mounted, Bariatric	2	CC	22 40 00	facility. A floor mounted, flush valve toilet with an elongated front and a load capacity of 1,000 pounds. The toilet with be vitreous china with a 1.28 or 1.6 Gpf low water consumption rate with a rear outlet. See manufacturer's literature for recommended flush valves and toilet seats.	В	-	-	-	-
	Maker, Flaked, With Dispenser	2	VC	22 40 00	Ice maker dispenser approximately 71" H x 19"D x 24"W. This unit provides flaked ice and cooled water automatically. The unit has a daily capacity up to 650 pounds and a 100 pound capacity stainless steel storage compartment with water station. Unit may be free-standing or counter-mounted, automatic load ice dispenser for food service and healthcare use. The unit is used in healthcare institutions and various commercial food service operations for dispensing ice.	В	В	-	-	-
	gerator, U/C or F/S, 5 Cu Ft gerator-Freezer, 2 Door	3	VC		Utility refrigerator approximately 35" H x 24" W x 26" D. The unit has a two tray ice cube cooling system. The refrigerator fits standard architectural dimensions for undercounter installation. The unit is perfect for use in nurses' station, wards, and laboratories, pharmacies or wherever space is limited. This is a 10 cubic foot frostless top mount refrigerator/freezer combination that is used in households or other areas where general purpose storage of perishable items is required.	-	A A	-	-	
IOM Refriç	<u> </u>	3	VC		Two sectional refrigerator approximately 84" H x 53" W x 37"D. This unit is two sections with two separate stainless steel doors. The doors are self-closing with safety stops. This refrigerator is used for general storage in commercial kitchens, hospitals and schools.	-	A	-	-	-
)1 Exerc	cise Bike	1	W		A stationary bicycle (also known as exercise bicycle, exercise bike, spinning bike, or exercycle) is a device used as exercise equipment for indoor cycling. It includes a saddle, pedals, and some form of handlebars arranged as on a (stationary) bicycle.	-	Α	-	-	-
)2 Loun	ng mounted window roller shade nge Chair, Outdoor	1 20	CC	12 24 13	Roller shades mounted to the ceiling. Seating specifically designed for outdoor use	-	-	-	-	-
	e, Occasional, Outdoor , Outdoor	10 2	VV		Table specifically designed for outdoor use Seating specifically designed for outdoor use	-	-	-	-	-
05 Medi	ical Cylinder r, Dining, Outdoor	23	VV		Storage vessel, which is either held under pressure in gas cylinders Seating specifically designed for outdoor use	-	-	-	<u></u>	-
07 Table	e, Dining, Outdoor enser, Ice and Water	1 3	VV VV		Table specifically designed for outdoor use Countertop ice and water dispenser produces up to 125 lbs of consumer-preferred Chewblet® ice per day, while holding 15 lbs of ice in storage. Includes sanitary, capacitive touch dispensing, and a	- - B	- - A	-	- -	<u>-</u> -
·	om Millwork Reception Desk	1	CC	12 32 00	unique drainless design that refreezes melt water from the storage hopper, allowing this model to be installed virtually anywhere there is water and electricity available. CUSTOM MILLWORK RECEPTION DESK WITH PLASTIC LAMINATE FACADE AND BOX/BOX/FILE AND SOLID SURFACE WORK AND TRANSACTION COUNTERS. POWER/TEL/DATA AT	-	A	-	-	-
	essed Memory Box	28	CC	12 32 00	WORK HEIGHT. RECESSED MEMORY BOX. STAINED WOOD FRAME AND DOOR WITH GLASS. LOCKING. TWO GLASS INTERIOR SHELVES. FABRIC BACK.	_		_		

EQUIPMENT LIST (MILSTD 1691)

RESPONSIBI	LITY:	PLUMBING:	ELECTRICAL:	MEDICAL GAS:	MISCELLANEOUS GAS:	NON-MEDICAL GAS:	MISCELLANEOUS:
Acquisition Code CFCI VC GFCI VV GFGI L_RE Leased R GFGI	Contractor Furnished Contractor Installed. Equipment purchased and installed by the contractor. VA Furnished Contractor Installed. Equipment is provided by the Government and installed by the Contractor (used for major imaging and OR equipment). VA Furnished VA Installed. Equipment purchased and installed by the Government. I or Rented Other. Equipment leased or rented and installed by the Government. Reuse. These are existing equipment assets that will be transferred and reused and may be a relocation cost associated with them.	Code Description A Hot and cold water B Cold water and drain C Hot water and drain D Cold and hot water and drain E Treated water and drain F Cold, hot and treated water and drain G Cold and treated water and drain H Hot and treated water and drain I Drain only J Cold water only	Code Description A 120 volt, conventional outlet B 120 volt, special outlet C 208/220 volt D 120 and 208/220 volt E 440 volt, 3 phase F Special electrical requirements (includes, but is not limited to emergency power, multiple power connections, etc.) G 208/220 volt, 3 phase	Code Description A Oxygen B Vacuum C Air, low pressure D Air, high pressure E Oxygen and medical air H Oxygen, vacuum and medical air J Vacuum and HP air K Medical air	Code Description A Steam B Nitrogen gas C Nitrous oxide D Nitrogen and nitrous oxide gas E Carbon dioxide gas F Liquid carbon dioxide G Liquid nitrogen H Instrument Air	Code Description A Natural gas B Liquid propane gas C Methane D Butane E Propane F Hydrogen gas G Reserved H Acetylene gas	Code Description A Earth ground B Lead lined walls C Remote alarm ground D Empty conduit with pull cord E Vent to atmosphere F Special gas requirements G Liquid gas requirements H RF/Magnetic shielding J Wall/ceiling support required K Empty conduit/pull cord & wall/ceiling support required M Earth ground and wall/ceiling support required P Lead lined walls and wall/ceiling support required T CAT 6 wire to nearest Telecommunications Room

Revisions:

VA FORM 08 - 6231

CONSULTANT

NORRIS DESIGN
Planning | Landscape Architecture | Branding

Landscape Architect
418 North Toole Avenue
Tucson, AZ 85701

(520) 622-9565 Josh Orth., PLA

Protective Design Specialist 240 West 35th St. Suite 1004 New York, NY 10001 (212) 967-4890 Corrine Tan, SE

HINMAN C.S.Davidson,Inc.

Structural
315 West James Street, Suite 102
Lancaster, PA 17603
(717) 481-2991
Jason Vannoy, SE, PE MEP 550 North Reo Street, Suite 203 Tampa, FL 33609 (813) 289-4700 Nicholas Stephenson, PE

A/E: TRIPLE C - The A/E Group 201 E. Jefferson Street, Suite 200 Syracuse, NY 13202 (315) 484-5958 Mat Perkins





Office of Construction and Facilities Management						
VA	U.S. Department of Veterans Affairs					

EQUIPMENT SCHEDULE	ISSUED FO CONSTRUCT
proved:	

Project Title Project Number NEW COMMUNITY LIVING 620-334 **Building Number** CENTER CLC Location Drawing Number 2094 Albany Post Road, Montrose, NY 10548 Q-601