



**AREA "B"
FOUNDATION PLAN**
SCALE: 1" = 30'-0"

NOTES:
1. FINISH FLOOR REFERENCE ELEVATION = 100'-0".
2. TOP OF INTERIOR COLUMN FOOTING ELEVATION = 99'-0" U.N.O.
3. TOP OF EXTERIOR FOOTING ELEVATION = 99'-0" U.N.O.
4. COORDINATE ALL DOOR OPENINGS AND LOCATIONS WITH ARCHITECTURAL DRAWINGS.
5. VERIFY LOCATION OF ALL FOOTING STEPS WITH PANEL DRAWINGS PRIOR TO CASTING FOOTINGS.
6. Hatched area indicates 10 MIL VAPOR BARRIER UNDER SLAB ON GRADE.
7. REINFORCE WITH #4 @ 4'-0" ON CENTER.
8. VERIFY LOCATION OF BLOCK OUTS FOR DOWNSPOUTS WITH PLUMBING DRAWINGS PRIOR TO CASTING FOOTINGS.
9. 6" CMU REINF. #4 @ 24" O.C. FULL HEIGHT. SEE DETAIL SHEET F2.2.
10. PROVIDE DOWEL BASKETS AT ALL SLAB JOINTS. PROVIDE JOINT FILLER IN SPEED BAY JOINTS ONLY.

WALL FOOTING SCHEDULE		
MARK	FOOTING SIZE	FOOTING REINFORCEMENT
WF1	2'-0"x3'-2"	3 - #4 CONT. TOP & BOT. #4 @ 60" O.C.
WF2	3'-6"x3'-2"	5 - #4 CONT. TOP & BOT. #4 @ 36" O.C.
WF3	3'-6"x3'-2"	SEE DETAIL 3/F2.2

COLUMN FOOTING SCHEDULE		
MARK	FOOTING SIZE	FOOTING REINFORCEMENT
F5.50	5'-6"x5'-6"x1'-0"	6 - #5 E.H. BOT.
F5.75	5'-6"x5'-6"x1'-0"	6 - #5 E.H. BOT.
F16.00	16'-0"x16'-0"x3'-4"	16 - #5 E.H. TOP & BOT.

