


Reconstruction To:
JV Forrestal Elementary School
Sargent Elementary School
South Ave Elementary School
Rombout Middle School
Beacon High School
Bus Maintenance Facility
Addition and Alteration to:
Glenham Elementary School
Beacon City School District
Beacon, New York

SED Control No. 13-02-00-01-0-002-021
SED Control No. 13-02-00-01-0-008-020
SED Control No. 13-02-00-01-0-003-016
SED Control No. 13-02-00-01-0-004-023
SED Control No. 13-02-00-01-0-020-012
SED Control No. 13-02-00-01-5-018-006

SED Control No. 13-02-00-01-0-006-022



Drawing List	Rombout Middle School	Beacon City High School	Common
GENERAL		CODE COMPLIANCE	CIVIL
G002 Title Sheet	STRUCTURAL	FG350 Code Compliance Review	ZC500 Site Details
G100 Symbols and Abbreviations	ES130 Partial Framing Plans - Area F Schedules, and Details	FG351 Code Compliance First Floor Key Plan	ZC501 Site Details
		FG352 Code Compliance Second Floor Key Plan	ZC502 Site Details
			ZC503 Site Details
Rombout Middle School	MECHANICAL	ARCHITECTURAL	
CODE COMPLIANCE	EM051 First Floor and Second Floor Key Plans	FA100 First Floor Demolition Plan - Area A	
EG350 Code Compliance Review and Vintage Key Plan	EM100 First Floor Demolition Plan - Partial Area A, Area B and Partial Area C	FA101 First Floor Demolition Plan - Area G	
EG351 Code Compliance First Floor Key Plan	EM101 First Floor Demolition Plans - Area D and Partial Area F	FA102 Second Floor Demolition Plan - Area C	
EG352 Code Compliance Second Floor Key Plan	EM101 First Floor Demolition Plans - Area D and Partial Area F Roof Demolition Plan - Partial Area F	FA130 First Floor Plan - Area A	
		FA131 First Floor Plan - Area G	
		FA133 Second Floor Plan - Area C	
HAZARDOUS MATERIALS	EM130 First Floor Plan - Partial Area A, Area B and Partial Areas C and E	FA160 First Floor Reflected Ceiling Plan Area A	
EH100 Asbestos Abatement	EM131 First Floor Plans - Area D and Partial Area F and Roof Plan - Area D and Partial Areas C and F	FA161 First Floor Reflected Ceiling Plan Area G	
		FA162 Second Floor Reflected Ceiling Plan Area C	
SURVEY / MAPPING	EM500 Details and Controls	FA400 Enlarged Plans - Area A	
EV001 Topographic Survey	EM600 Schedules and Controls	FA401 Enlarged Plans and Sections - Area G	
		FA402 Enlarged Second Floor Plan Area C	
CIVIL	ELECTRICAL	FA600 Door Schedule, Door, Window and Wall Types, and Details	
EC100 Site Demolition and Soil Erosion and Sediment Control Plan	EE001 Site Electrical Plan	FA920 Enlarged Plans and Elevations	
EC120 Site Layout and Landscape Plan	EE100 First Floor Demolition Plan - Area A		
EC130 Site Grading and Utility Plan	EE101 First Floor Demolition Plan - Areas B and E		
EC500 Site Details	EE102 First Floor Demolition Plan - Areas C and D	STRUCTURAL	
EC501 Site Details	EE103 First Floor Demolition Plan - Area F	FS130 Partial Foundation and Framing Plan - Area G	
	EE104 Second Floor Demolition Plan - Areas B and D	FS500 Typical Details	
	EE130 First Floor Lighting, Power & Communications Plan - Area A		
ARCHITECTURAL	EE131 First Floor Lighting, Power & Communications Plan - Areas B and E	MECHANICAL	
EA050 Roof Key Plan	EE132 First Floor Lighting, Power & Communications Plan - Areas C and D	FM051 First Floor Key Plan	
EA100 First Floor Demolition Plan - Area A	EE133 First Floor Lighting, Power & Communications Plan - Area F	FM052 Second Floor Key Plan	
EA101 First Floor Demolition Plan - Area B and E	EE134 Second Floor Lighting, Power & Communications Plan - Areas B and D	FM100 Partial Plans and Sections - Area G	
EA102 First Floor Demolition Plan - Area C and D	EE160 Roof Power Plan - Areas C, D, E and F	FM101 Partial Second Floor Plans - Area C	
EA103 First Floor Demolition Plan - Area F	EE400 Enlarged Lighting Plans - Areas A and B	FM500 Details and Schedule	
EA104 Second Floor Demolition Plan - Area B and D	EE401 Enlarged Power & Communications Plans - Areas A and B		
EA130 First Floor Plan - Area A	EE500 Details	ELECTRICAL	
EA131 First Floor Plan - Area B	EE501 Details	FE050 First Floor Key Plan	
EA132 First Floor Plan - Area C and D	EE600 Schedules	FE051 Second Floor Key Plan	
EA133 First Floor Plan - Area F		FE400 First Floor Enlarged Plans	
EA160 First Floor Reflected Ceiling Plan - Area A	PLUMBING	FE401 First Floor Enlarged Plans	
EA161 First Floor Reflected Ceiling Plan - Area B and E	EP050 First Floor Key Plan	FE402 Second Floor Enlarged Plans	
EA162 First Floor Reflected Ceiling Plan - Area C and D	EP400 Enlarged Art Room Plans	FE500 Details	
EA163 First Floor Reflected Ceiling Plan - Area F	EP401 Enlarged Science Room Plans	FE501 Details	
EA164 Second Floor Reflected Ceiling Plan - Area B and D	EP402 Enlarged Kitchen Plans, Schedule and Details		
EA190 Roof Plan and Details		PLUMBING	
EA400 Enlarged Plans and Details		FP050 First Floor Key Plan	
EA600 Door Schedule, Door, Frame and Wall Types, and Details		FP400 Enlarged Science Room Plans and Details	
		FP401 Enlarged Area G Plans, Details and Schedules	
EA920 Enlarged Plans		FP402 Enlarged Mechanical Room F302 Plan	
EA921 Enlarged Plans			
EA930 Miscellaneous Details			

Drawn By: Author	Date: 10/28/2022	Drawing Number: AA130
Project No.: 279180-22004		

BUILDING DESIGNATOR
 DISCIPLINE DESIGNATOR
 SHEET TYPE DESIGNATOR
 SHEET SEQUENCE DESIGNATOR



TETRA TECH
ARCHITECTS & ENGINEERS

Architecture Engineering Planning for High Performance Facilities

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

Volume 2 of 2

Set No.

BID SET

279180-22004

10/28/2022

ing Number:

G002

BID SET PRINTED AUGUST 8, 2023

	SPOT ELEVATION
	TOP OF CURB ELEVATION
	BOTTOM OF CURB ELEVATION
	EXISTING SPOT ELEVATION
	CONTOUR
	EXISTING CONTOUR
	SOIL TEST BORING
	TEST PIT LOCATION
	TREE OR SHRUB
	TREE OR SHRUB TO REMAIN
	TREE OR SHRUB TO BE REMOVED
	ASPHALT PAVING OR TOP COURSE
	HEAVY-DUTY ASPHALT PAVING
	REMOVE AND REPLACE ASPHALT PAVING
	CONCRETE PAVING
	CONCRETE SECTION
	CURBING
	CURBING TO REMAIN
	CURBING TO BE REMOVED
	FENCING
	FENCING TO REMAIN
	FENCING TO BE REMOVED
	SILT FENCING
	TEMPORARY CONSTRUCTION FENCING
	HAY BALES

	EXISTING TO REMAIN
	DEMOLITION WORK
	NEW WORK IN EXISTING (MATERIAL INDICATION VARIES)
	NEW WORK (MATERIAL INDICATION VARIES)
	CMU AND BRICK CAVITY WALL
	CMU WALL
	GYPSUM BOARD PARTITION W/ METAL STUD WALL
	OPERABLE PARTITION
	DOOR NUMBER (ROOM NO W/ DOOR NO)
	WINDOW TYPE
	RELOCATED EQUIPMENT FURNITURE OR CASEWORK NUMBER
	PARTITION TYPE

INDICATES AREA IS EXISTING

INDICATES SLAB IS DERESSED OR RECESSED

TOP OF FTG. ELEVAT. FROM DATUM

CONTINUOUS FTG.

FOUNDATION WALL

BM. POCKET ELEVATION FROM DAT

STEPPED FOOTING

INDICATES PIER TYPE

P1 (-8)

TOP OF PIER ELEVATION FROM DATUM

F4 [-3'-0"]

TOP OF FOOTING ELEVATION FROM DAT

INDICATES FOOTING REFER TO FOOTING SCHEDULE

INDICATES A FRAME ROOF OR FLOOR OF COORD SIZE AND LOCATION

RD





INDICATES FRAMED OPNG IS FOR


AERIC VENT		B
BLOW DOWN		D
WATER SUPPLY		A
WATER RETURN		A
GLYCOL SUPPLY		D
GLYCOL RETURN		A
WASTE DRAIN		B
CSEER WATER SUPPLY		B
CSEER WATER RETURN		B
SUPPLY		B
COL RETURN		E
COL SUPPLY		B
OMP SUPPLY		2
OMP RETURN		2
ER SUPPLY		3
ER RETURN		3
LED WATER SUPPLY		3
LED WATER RETURN		3
SSURE STEAM		S
SSURE CONDENSATE		M
SSURE STEAM WET D) CONDENSATE		F
CAL. EQUIPMENT MAKE- WATER(NON-POTABLE)		G
GRANT SUCTION		T
GRANT LIQUID		C
GRANT HOT GAS		C
CHARGE		P
EXG. DUCT, VENT		P

LIGHT FIXTURE # DENOTES TYPE		CABLE TRAY - LADDER TYPE
LIGHT FIXTURE # DENOTES TYPE		CABLE TRAY - BASKET TYPE
REFITROFITTED LIGHT FIXTURE AS NOTED	SR	SURFACE RACEWAY TYPE AS DESCRIBED ON DWGS.
COMBINATION EXIT/EMERGENCY LIGHT # DENOTES TYPE		COMMUNICATION INTERCOM
EMERGENCY LIGHT W/BATTERY PACK # DENOTES TYPE		CEILING MOUNT SPEAKER
EMER. LIGHT/WALL MOUNT # DENOTES TYPE		WALL MOUNT SPEAKER
EMERGENCY FIXTURE # DENOTES TYPE		VOLUME CONTROL
EMERGENCY FIXTURE # DENOTES TYPE		HORN SPEAKER
EXIT LIGHT - CEILING MOUNTED # DENOTES TYPE		PROGRAM BELL
EXIT LIGHT - WALL MOUNTED # DENOTES TYPE		FLOOR BOX
DAYLIGHT SENSOR		DOOR RELEASE
AREA OF RESCUE LIGHT FIXTURE # DENOTES TYPE		SECURITY ALARM HORN
POLE MOUNTED SITE LIGHT # DENOTES TYPE		SECURITY SENSOR GB - GLASS BREAK MO - MOTION DETECTOR SD - SOUND DETECTOR
LIGHT SWITCH (LINE VOLTAGE) 3 - 3 WAY 4 - 4 WAY		SECURITY DOOR CONTACT
LOW VOLTAGE LIGHTING CONTROL		SECURITY SYSTEM KEYPAD # DENOTES DESIGNATION
EMERGENCY SHUNT RELAY		SECURITY CAMERA # DENOTES DESIGNATION
OCCUPANCY SENSOR		SECURITY REQUEST TO EXIT BELL
VACUANCY SENSOR		LOW-VOLTAGE POWER SUPPLY # DENOTES DESIGNATION
PHOTO CELL		SECURITY ELECTRIC LOCKING HARDWARE
LIGHTING CONTROL		DOOR INTERCOM CALL STATION # DENOTES DESIGNATION
FIRE ALARM MANUAL PULL STATION		ACCESS CONTROL CARD READER # DENOTES DESIGNATION
FLUE ARM		ADA PUSH BUTTON
		SECURITY CCTV MONITOR
		SECURITY LOCKING BUTTON

[illegible]

NOTE: REFER TO FINISH PLANS FOR ROOM FINISH KEY AND ADDITIONAL ABBREVIATIONS AND SYMBOLS																					
AC	ASBESTOS ABATEMENT CONTRACTOR	BO	BY OTHERS	CONST	CONSTRUCTION	EC	EXPANSION BOLT	FRA	FRESH AIR	ID	INSIDE DAMPER	MAT	MATERIAL	PL	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SUSPENDED	VERM	VERMULITE
AD	AUTOMATIC AIR DAMPER	BD	BOTTOM OF DUCT	CONT	CONTINUOUS	EF	ELECTRICAL CONTRACTOR	FRC	FIRE RESISTANT COATING	IE	INVERT ELEVATION	MAU	MAKE UP AIR UNIT	PLM	PLASTIC LAMINATE	RO	ROUGH-IN	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AS	ASBESTOS ABATEMENT CONTRACTOR	BSP	BOTTOM OF STEEL	COORD	COORDINATE	EFB	FIBERGLASS REINFORCED FLOORING	MAC	MASONRY CONTRACTOR	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AC	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDINATE	EFS	EXTERIOR INSULATION SYSTEM	FRT	FIRE RETARDANT	INCL	INCLUDE (D) (ING)	MAU	MAKE UP AIR UNIT	PLM	PLASTER, PROPERTY LINE	RHC	REHEAT COIL	SUSP	SHEET VINYL, STEAM VENT	VERT	VERTICAL
AD	AUTOMATIC AIR DAMPER	BOL	BOTTOM OF LUG	COORD	COORDIN																

Rev. No.:	Date:	Description:
		
complex world		
Tetra Tech Engineers, Architects & Landscape Architects, P.C.		
	TETRA TECH ARCHITECTS & ENGINEERS	
Beacon City School District Beacon, New York		
Reconstruction To: JV Forrestal Elementary School, Sargent Elementary School South Ave Elementary School, Rombout Middle School Beacon High School, Bus Maintenance Facility <u>Addition and Alteration to: Glenham Elementary School</u>		
Symbols and Abbreviations		
Drawn By: TIAE	Date: 10/28/2022	Drawing Number: 
Project No.: 279180-22004		



Code Compliance Review

PROJECT LOCATION:
88 MATTEAWAN ROAD, BEACON, NEW YORK 12508
BOUNDED BY MATTEAWAN ROAD TO THE NORTH AND ROBERT CAHILL DRIVE TO THE SOUTH.

PROJECT DESCRIPTION:
THIS PROJECT INCLUDES RENOVATION OF APPROXIMATELY 38,418 SF OF SPACE ON THE FIRST AND SECOND FLOOR.

WORK GENERALLY CONSISTS OF THE FOLLOWING:
ALTERATIONS - LEVEL 1
• REPLACE CORRIDOR CEILINGS
• REPLACE SELECTED ROOF AREAS
• REPLACE GREASE INTERCEPTOR
• UPGRADE EMERGENCY LIGHTING
• UPGRADE LIGHTING

ALTERATIONS - LEVEL 2
• ADD MECHANICAL VENTILATION TO CLASSROOMS
• UPGRADE SCIENCE ROOMS
• UPGRADE ART ROOMS
• COURTYARD LEARNING SPACE

APPLICABLE CODES AND STANDARDS:
BASED ON THE NEW YORK STATE UNIFORM FIRE PREVENTION AND BUILDING CODE INCLUDING APPLICABLE 2018 ICC CODES AND 2020 BUILDING CODES of NYS, AND ICC A117.1-2017 STANDARD FOR ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES.

REFER TO PROJECT MANUAL FOR REQUIREMENTS STATED IN "NYCRR 155 REGULATIONS OF THE COMMISSIONER OF EDUCATION".

BUILDING DATA:

BUILDING: ROMBOUT MIDDLE SCHOOL
88 MATTEAWAN ROAD
BEACON, NY 12508

DESCRIPTION: TWO STORY MASONRY AND REINFORCED CONCRETE BUILDING.

YEAR BUILT: 1962
ADDITIONS: 1965, 1975, 1986 AND 2005

BUILDING AREA: 1ST FLOOR 122,556 SQFT
2ND FLOOR 23,074 SQFT
TOTAL GROSS AREA= 145,630 SQFT

CODE DATA SUMMARY:

USE GROUP: E : EDUCATION

CONSTRUCTION TYPE -
EXISTING: IIB

FIRE SAFETY: NO AUTOMATIC SPRINKLER SYSTEM PROVIDED.
NO SELF CONTAINED SYSTEMS AT FABRICATED PAINT BOOTH AND DUST COLLECTION SYSTEM.

WORK AREA:
LOCATION AREA % OF TOTAL
1ST FLOOR 20,888 SQFT 17.0%
2ND FLOOR 3,798 SQFT 16.5%

CORRIDOR DOORS: ALL CORRIDOR DOORS SCHEDULED TO BE REPLACED SHALL HAVE MINIMUM FIRE DOOR ASSEMBLY RATING OF 20 MINUTES IN ACCORDANCE WITH SECTION 716.5

PATH OF CODE COMPLIANCE:

2018 IBC CODES AND 2020 EXISTING BUILDING CODE of NYS
301.1.2 WORK AREA COMPLIANCE METHOD

CHAPTER 5 - CLASSIFICATION OF WORK
503 ALTERATION - LEVEL 1 (CHAPTER 7)
504 ALTERATION - LEVEL 2 (CHAPTER 8)

NEW CONSTRUCTION WILL COMPLY WITH REQUIREMENTS OF 2018 ICC CODES AND 2020 BUILDING CODES of NYS

ACCESSIBLE ROUTE AND ACCESSIBLE ENTRANCES:
FOR EXTERIOR ACCESSIBLE ROUTE AND ACCESSIBLE ENTRANCES - SEE EG300.

EXIT TRAVEL DISTANCE (PER TABLE 1017.2):
FOR EXIT TRAVEL DISTANCE - SEE EG351.

STAIR AND OTHER EXIT WIDTH CALCULATIONS (PER 1005.3.1 AND 1005.3.2):
FOR EXIT TRAVEL DISTANCE - SEE EG351


CORRIDOR ENCLOSURES (PER TABLE 1020.1):
FOR CORRIDOR FIRE RESISTANCE - SEE ENLARGED PLANS, PARTITION TYPES AND DOOR SCHEDULE.
ALL CROSS CORRIDOR PARTITIONS ARE SMOKE PARTITIONS AND EXTEND FROM FINISH FLOOR TO DECK ABOVE.

General Code Notes


- A. REFER TO CODE COMPLIANCE DRAWINGS FOR ADDITIONAL CODE COMPLIANCE INFORMATION.
- B. COORDINATE WITH FLOOR PLANS, WALL SECTIONS AND PARTITION TYPES FOR RATED WALL TYPES AND LOCATIONS. IMMEDIATELY NOTIFY ARCHITECT OF ANY WALL RATING DISCREPANCIES BETWEEN EG351 AND EG352 DRAWINGS AND FLOOR PLANS.
- C. ALL WALLS, INCLUDING AT CORRIDORS, SHALL EXTEND COMPLETELY TO THE UNDERSIDE OF DECKING, SUPPORTING STRUCTURE OR ROOF ABOVE, TYPICAL UNLESS NOTED OTHERWISE.
- D. AT AREAS OF PROJECT WORK, COMPLETELY SEAL ALL PENETRATIONS REQUIRED TO COMPLY WITH FIRE RESISTANCE RATINGS IDENTIFIED ON THE EG351 AND EG352 DRAWINGS. REGARDLESS IF WALL IS NEW OR EXISTING, TYPICAL UNLESS NOTED OTHERWISE.
- E. PROVIDE APPLIED FIREPROOFING TO ALL BEAMS, JOISTS AND STRUCTURAL STEEL ELEMENTS AT ALL FIRE BARRIERS, FIRE PARTITIONS, AND OTHER RATED WALLS WHERE INDICATED ON DRAWINGS, AND THAT ARE NOT COMPLETELY PROTECTED WITHIN THE RATED CONSTRUCTION. PROTECTION OF SUCH ELEMENTS SHALL MATCH THE RATING OF THE WALL THAT THE ELEMENTS ARE CONTAINED WITHIN.
- F. ALL CMU CONSTRUCTION SHALL MEET FIRE RESISTANCE REQUIREMENTS INDICATED. PROVIDED BLOCK TYPE AS REQUIRED TO COMPLY WITH UL DESIGN NUMBERS AND WALL RATINGS INDICATED, REGARDLESS IF NOTED AS SUCH ON PLAN DETAILS.

General Notes

- A. DO NOT SCALE DRAWINGS TO OBTAIN DIMENSIONS.
- B. TAKE FIELD MEASUREMENTS TO FIT THE WORK PROPERLY. VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS IN THE FIELD.
- C. REFER INCONSISTENCIES TO ARCHITECT PRIOR TO COMMENCING THE WORK IN AFFECTED AREA.
- D. ITEMS ARE SHOWN DIAGRAMMATICALLY ON DRAWINGS. VERIFY SPACE REQUIREMENTS AND DIMENSIONS TO FIT THE WORK PROPERLY.
- E. NOTES SHOWN ON ONE DRAWING APPLY TO ALL SIMILAR DRAWINGS.
- F. DO NOT DISTURB CONSTRUCTION SUSPECTED OF CONTAINING HAZARDOUS MATERIAL. IF ENCOUNTERED, IMMEDIATELY NOTIFY ARCHITECT, CONSTRUCTION MANAGER AND OWNER.



S.E.D. Control No. 13-02-00-01-0-004-023



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Code Compliance Review and Vintage Key Plan

Drawn By: TLG Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004
EG350



General Notes

- A. DO NOT SCALE DRAWINGS TO OBTAIN DIMENSIONS.
- B. TAKE FIELD MEASUREMENTS TO FIT THE WORK PROPERLY. VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS IN THE FIELD.
- C. REFER INCONSISTENCIES TO ARCHITECT PRIOR TO COMMENCING THE WORK IN AFFECTED AREA.
- D. ITEMS ARE SHOWN DIAGMATICALLY ON DRAWINGS. VERIFY SPACE REQUIREMENTS AND DIMENSIONS TO FIT THE WORK PROPERLY.
- E. NOTES SHOWN ON ONE DRAWING APPLY TO ALL SIMILAR DRAWINGS.
- F. DO NOT DISTURB CONSTRUCTION SUSPECTED OF CONTAINING HAZARDOUS MATERIAL. IF ENCOUNTERED, IMMEDIATELY NOTIFY ARCHITECT, CONSTRUCTION MANAGER AND OWNER.


General Code Notes

- A. REFER TO CODE COMPLIANCE DRAWINGS FOR ADDITIONAL CODE COMPLIANCE INFORMATION.
- B. COORDINATE WITH FLOOR PLANS, WALL SECTIONS AND PARTITION TYPES FOR RATED WALL TYPES AND LOCATIONS. IMMEDIATELY NOTIFY ARCHITECT OF ANY WALL RATING DISCREPANCIES BETWEEN EG351 AND EG352 DRAWINGS AND FLOOR PLANS.
- C. ALL WALLS, INCLUDING AT CORRIDORS, SHALL EXTEND COMPLETELY TO THE UNDERSIDE OF DECKING, SUPPORTING STRUCTURE OR ROOF ABOVE, TYPICAL UNLESS NOTED OTHERWISE.
- D. AT AREAS OF PROJECT WORK, COMPLETELY SEAL ALL PENETRATIONS REQUIRED TO COMPLY WITH FIRE RESISTANCE RATINGS IDENTIFIED ON THE EG351 AND EG352 DRAWINGS, REGARDLESS IF WALL IS NEW OR EXISTING, TYPICAL UNLESS NOTED OTHERWISE.
- E. PROVIDE APPLIED FIREPROOFING TO ALL BEAMS, JOISTS AND STRUCTURAL STEEL ELEMENTS AT ALL FIRE BARRIERS, FIRE PARTITIONS, AND OTHER RATED WALLS WHERE INDICATED ON DRAWINGS, AND THAT ARE NOT COMPLETELY PROTECTED WITHIN THE RATED CONSTRUCTION. PROTECTION OF SUCH ELEMENTS SHALL MATCH THE RATING OF THE WALL THAT THE ELEMENTS ARE CONTAINED WITHIN.
- F. ALL CMU CONSTRUCTION SHALL MEET FIRE RESISTANCE REQUIREMENTS INDICATED. PROVIDED BLOCK TYPE AS REQUIRED TO COMPLY WITH UL DESIGN NUMBERS AND WALL RATINGS INDICATED. REGARDLESS IF NOTED AS SUCH ON PLAN DETAILS.

Legend

ALL WALLS, INCLUDING CORRIDOR WALLS, EXTEND TO THE ROOF DECK OR FLOOR DECK ABOVE UNLESS NOTED OTHERWISE.

- 2-HOUR FIRE BARRIER
- 1-HOUR FIRE PARTITION
- COMMON EGRESS PATH
- XX NUMBER OF OCCUPANTS IN EACH SPACE, UNO
- (XX) NUMBER OF OCCUPANTS ALONG EGRESS PATH
- XX-XX* TOTAL EGRESS DISTANCE PER PATH
- NEW FIRE EXTINGUISHER LOCATION
- EXISTING FIRE EXTINGUISHER LOCATION
- RESUE WINDOW
- ALTERATION LEVEL 1 WORK AREA
- ALTERATION LEVEL 2 WORK AREA



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Code Compliance First Floor Key Plan

Drawn By: Date: Drawing Number:


Project No.: 279180-22004 EG351

ASBESTOS ABATEMENT NOTES

ASBESTOS ABATEMENT CONTRACTOR IS RESPONSIBLE FOR TOTAL AND COMPLETE REMOVAL AND DISPOSAL OF ASBESTOS CONTAINING (ACM) FLOOR TILES AT LOCATIONS INDICATED.



ASBESTOS ABATEMENT CONTRACTOR IS RESPONSIBLE FOR TOTAL AND COMPLETE REMOVAL AND DISPOSAL OF ASBESTOS CONTAINING (ACM) FLOOR TILES AND MASTIC ON CEMENTITIOUS SLAB.

REFER TO SPECIFICATION SECTION 020800 - SECTION 3.17 FOR A DESCRIPTION OF THE WORK.



ROMBOUT ELEMENTARY - FIRST FLOOR ABATEMENT PLAN

QUALITY ENVIRONMENTAL SOLUTIONS
& TECHNOLOGIES, INC.
1376 NYS ROUTE 9
WAPPINGERS FALLS, NY 12590
TEL.: (845) 298-6031



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description
1	5-13-22	ISSUE SET Submittal




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Asbestos Abatement

Drawn By: TTAE	Date: 10/26/2022	Drawing Number: EH100
Project No.: 279180-22004		



General Notes

- A. DO NOT SCALE DRAWINGS TO OBTAIN DIMENSIONS.
- B. TAKE FIELD MEASUREMENTS TO FIT THE WORK PROPERLY. VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS IN THE FIELD.
- C. REFER INCONSISTENCIES TO ARCHITECT PRIOR TO COMMENCING THE WORK IN AFFECTED AREA.
- D. ITEMS ARE SHOWN DIAGRAMMATICALLY ON DRAWINGS. VERIFY SPACE REQUIREMENTS AND DIMENSIONS TO FIT THE WORK PROPERLY.
- E. NOTES SHOWN ON ONE DRAWING APPLY TO ALL SIMILAR DRAWINGS.
- F. DO NOT DISTURB CONSTRUCTION SUSPECTED OF CONTAINING HAZARDOUS MATERIAL. IF ENCOUNTERED, IMMEDIATELY NOTIFY ARCHITECT, CONSTRUCTION MANAGER AND OWNER.




Roof Key Notes


- 1 PROVIDE ROOF DRAIN INSERT AT EXISTING ROOF DRAIN - SEE DETAIL 3/EA190.
- 2 TAPERED INSULATION CRICKET (TYP) SLOPE 1/2"/FT. TYP ALL SIDES. VERIFY LENGTH IN FIELD. WIDTH AS INDICATED ON PLAN AND TYPICAL AT ALL CURB PENETRATIONS.
- 3 REPLACE EXPANSION JOINT AT EXISTING LOCATION. HEIGHT AS REQUIRE TO ACCOMMODATE ROOF THICKNESS - SEE DETAIL 6/EA190 .
- 4 FLASH INTO EXISTING FULLY ADHERED EPDM ROOF SYSTEM TO COMPLY WITH ALL MANUFACTURE'S WARRANTY REQUIREMENTS - SEE DETAIL 4/EA190 SIMILAR.
- 5 MATCH TAPERED INSULATION HEIGHT AND TIE IN ROOF MEMBRANE.
- 6 ROOF VERTICAL TRANSITION DETAIL WITH FASCIA AT UPPER ROOF LEVEL APPROXIMATE HEIGHT INDICATED ON PLAN - SEE DETAIL 5/EA190.
- 7 PROVIDE BASE/COUNTER FLASHING BELOW EXISTING THROUGH-WALL FLASHING - SEE DETAIL 7/EA190.
- 8 PROVIDE ROOF OPENING AND INSTALL ROOF CURB FURNISHED BY MECHANICAL CONTRACTOR. SEE DETAIL 11/EA190

EXISTING CONDITIONS:

- 1. TYPICAL AT (F' WINGS) LOW ROOF AREAS - REFER TO PLAN TEST CUT LOCATIONS #1:
- FULLY ADHERED EPDM MEMBRANE.
- TAPERED POLYISOCYANURATE INSULATION - THICKNESS VARIES BETWEEN 3" TO 5" - MECHANICALLY ATTACHED.
- TAR PAPER.
- CORRUGATED METAL ROOF DECK - FLAT.



Key Plan
N.T.S.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:
-----------	-------	--------------



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Roof Key Plan

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EA050	



1 First Floor Demolition Plan - Area A
1/8" = 1'-0"


Demolition Key Notes

- 1G REMOVE INTERIOR PARTITION FULL-HEIGHT, PORTION AS INDICATED OR AS REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF PARTITION REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FLOOR FINISH.
- 1H PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PROVIDE LINTEL PER LINTEL SCHEDULE. SEE STRU DRAWINGS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
- 8A REMOVE WINDOW COMPLETELY. PREPARE OPENING TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
- 8B REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
- 8C REMOVE DOOR AND HARDWARE ONLY - EXISTING FRAME TO REMAIN. PREPARE FOR NEW DOOR WHERE SCHEDULED.
- 9A REMOVE CEILING SYSTEM AND/OR SOFFIT SYSTEM IN ITS ENTIRETY. CLEAN, SALVAGE AND PROTECT FOR RE-USE.
- 9B REMOVE PORTION OF CEILING SYSTEM AND/OR SOFFIT SYSTEM, TO EXTENT REQUIRED TO PERFORM NEW WORK. CAREFULLY TRIM CEILING GRID TO REMAIN.
- 9C REMOVE CEILING- OR WALL-MOUNTED ACOUSTICAL TREATMENTS IN THEIR ENTIRETY.
- 9Dx REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.

SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS):
A. QUARRY TILE
B. VAT/VCT
H. TERRAZZO.
- 9E REMOVE WALL BASE AND ASSOCIATED MASTIC ONLY - EXISTING FLOOR FINISH TO REMAIN. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- 9F REMOVE PAINTED FINISH (INCLUDING RUST AND DEBRIS) ONLY TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK - EXISTING WALLS TO REMAIN. PREPARE SURFACE FOR FINISH AND PAINT.
- 10A REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TACK BOARDS AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
- 10B REMOVE, SALVAGE AND PROTECT EXG TEACHING SURFACE. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
- 10C REMOVE LOCKERS IN THEIR ENTIRETY INCLUDING BASE, SOFFIT AND WALL CONSTRUCTION ABOVE. PATCH EXPOSED SURFACES TO MATCH ADJACENT SURFACES/FINISHES.
- 12A REMOVE CASEWORK, SHELVING AND ASSOCIATED COMPONENTS IN THEIR ENTIRETY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
- 12B REMOVE DISPLAY CASEWORK (INCLUDING ALL ASSOCIATED COMPONENTS). PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
- 12C REMOVE, SALVAGE AND PROTECT EXG BASE AND WALL CASEWORK. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
- 12D REMOVE WINDOW TREATMENTS ONLY - WINDOW SYSTEM TO REMAIN.

General Demolition Notes

- A. - - - - REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
 - 1. DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 - 2. DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE A LEADER POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 - 3. DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE SPACE IDENTIFIED BY THAT LEADER.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNERS AGENT(S) IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.
- E. EXISTING WINDOW-MOUNTED A/C UNITS SHALL BE REMOVED AND STORED BY OWNER PRIOR TO START OF DEMOLITION WORK.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Area A

Drawn By: TLG Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004 EA100



1 First Floor Demolition Plan - Area B
1/8" = 1'-0"




2 First Floor Demolition Plan - Area E
1/8" = 1'-0"

General Demolition Notes

- A. - - - - REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
 - 1. DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 - 2. DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE A LEADER POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 - 3. DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE SPACE IDENTIFIED BY THAT LEADER.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNER'S AGENT(S) IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.
- E. EXISTING WINDOW-MOUNTED A/C UNITS SHALL BE REMOVED AND STORED BY OWNER PRIOR TO START OF DEMOLITION WORK.


Demolition Key Notes

- 1G REMOVE INTERIOR PARTITION FULL-HEIGHT, PORTION AS INDICATED OR AS REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF PARTITION REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FLOOR FINISH.
 - 1H PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PROVIDE LINTEL PER LINTEL SCHEDULE. SEE STRU DRAWINGS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
 - 9A REMOVE WINDOW COMPLETELY. PREPARE OPENING TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - 9B REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - 9C REMOVE DOOR AND HARDWARE ONLY - EXISTING FRAME TO REMAIN. PREPARE FOR NEW DOOR WHERE SCHEDULED.
 - 9A REMOVE CEILING SYSTEM AND/OR SOFFIT SYSTEM IN ITS ENTIRETY. CLEAN, SALVAGE AND PROTECT FOR RE-USE.
 - 9B REMOVE PORTION OF CEILING SYSTEM AND/OR SOFFIT SYSTEM, TO EXTENT REQUIRED TO PERFORM NEW WORK. CAREFULLY TRIM CEILING GRID TO REMAIN.
 - 9C REMOVE CEILING - OR WALL-MOUNTED ACOUSTICAL TREATMENTS IN THEIR ENTIRETY.
 - 9D REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS):
A. QUARRY TILE.
B. VATICOT.
H. TERRAZZO.
- 9E REMOVE WALL BASE AND ASSOCIATED MASTIC ONLY - EXISTING FLOOR FINISH TO REMAIN. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
 - 9F REMOVE PAINTED FINISH (INCLUDING RUST AND DEBRIS) ONLY TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK - EXISTING WALLS TO REMAIN. PREPARE SURFACE FOR FINISH AND PAINT.
 - 10A REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TACK BOARDS AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - 10B REMOVE, SALVAGE AND PROTECT EXG TEACHING SURFACE. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
 - 10D REMOVE LOCKERS IN THEIR ENTIRETY INCLUDING BASE, SOFFIT AND WALL CONSTRUCTION ABOVE. PATCH EXPOSED SURFACES TO MATCH ADJACENT SURFACES/FINISHES.
 - 12A REMOVE CASEWORK, SHELVING AND ASSOCIATED COMPONENTS IN THEIR ENTIRETY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
 - 12B REMOVE DISPLAY CASEWORK (INCLUDING ALL ASSOCIATED COMPONENTS) PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
 - 12C REMOVE, SALVAGE AND PROTECT EXG BASE AND WALL CASEWORK. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
 - 12D REMOVE WINDOW TREATMENTS ONLY - WINDOW SYSTEM TO REMAIN.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Area B and E

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EA101	




Demolition Key Notes

- (1G) REMOVE INTERIOR PARTITION FULL-HEIGHT, PORTION AS INDICATED OR AS REQUIRED TO PERFORM SCHEDULED WORK AT ALL AREAS OF PARTITION REMOVAL. LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FLOOR FINISH.
- (1H) PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PROVIDE UNTEL PER UNTEL SCHEDULE. SEE STRU DRAWINGS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
- (8A) REMOVE WINDOW COMPLETELY. PREPARE OPENING TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
- (8B) REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
- (8C) REMOVE DOOR AND HARDWARE ONLY - EXISTING FRAME TO REMAIN. PREPARE FOR NEW DOOR WHERE SCHEDULED.
- (9A) REMOVE CEILING SYSTEM AND/OR SOFFIT SYSTEM IN ITS ENTIRETY. CLEAN, SALVAGE AND PROTECT FOR RE-USE.
- (9B) REMOVE PORTION OF CEILING SYSTEM AND/OR SOFFIT SYSTEM, TO EXTENT REQUIRED TO PERFORM NEW WORK. CAREFULLY TRIM CEILING GRID TO REMAIN.
- (9C) REMOVE CEILING- OR WALL-MOUNTED ACOUSTICAL TREATMENTS IN THEIR ENTIRETY.
- (9D) REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS):**
A. QUARRY TILE.
B. VAT/VCT.
H. TERRAZZO.
- (9E) REMOVE WALL BASE AND ASSOCIATED MASTIC ONLY - EXISTING FLOOR FINISH TO REMAIN. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- (9F) REMOVE PAINTED FINISH (INCLUDING RUST AND DEBRIS) ONLY TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. EXISTING WALLS TO REMAIN. PREPARE SURFACE FOR FINISH AND PAINT.
- (10A) REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TACK BOARDS AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
- (10B) REMOVE, SALVAGE AND PROTECT EXG TEACHING SURFACE. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
- (10C) REMOVE LOCKERS IN THEIR ENTIRETY INCLUDING BASE, SOFFIT AND WALL CONSTRUCTION ABOVE. PATCH EXPOSED SURFACES TO MATCH ADJACENT SURFACES/FINISHES.
- (12A) REMOVE CASEWORK, SHELVING AND ASSOCIATED COMPONENTS IN THEIR ENTIRETY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
- (12B) REMOVE DISPLAY CASEWORK (INCLUDING ALL ASSOCIATED COMPONENTS). PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
- (12C) REMOVE, SALVAGE AND PROTECT EXG BASE AND WALL CASEWORK. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
- (12D) REMOVE WINDOW TREATMENTS ONLY - WINDOW SYSTEM TO REMAIN.

General Demolition Notes


- A. - - - - - REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
- DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 - DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE A LEADER POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 - DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE SPACE IDENTIFIED BY THAT LEADER.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNER'S AGENT(S) IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.
- E. EXISTING WINDOW-MOUNTED A/C UNITS SHALL BE REMOVED AND STORED BY OWNER PRIOR TO START OF DEMOLITION WORK.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Area C
and D

Drawn By: TLG Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004
EA102



	REMOVE INTERIOR PARTITION FULL-HEIGHT. PORTION AS INDICATED OR AS REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF PARTITION REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATION OF JUMP OFF TO REVEAL FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MATCH SURFACE LEVEL. PREPARE FOR FLOOR FINISH.
1H	PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PROVIDE Lintel PER Lintel SCHEDULE. SEE STRU DRAWINGS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
8A	REMOVE WINDOW COMPLETELY. PATCH OPENING TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
8B	REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
8C	REMOVE DOOR AND HARDWARE ONLY - EXISTING FRAME TO REMAIN. PREPARE FOR NEW DOOR WHERE SCHEDULED.
9A	REMOVE CEILING SYSTEM AND/OR SOFFIT SYSTEM IN ITS ENTIRETY. CUT, SAW, PATCH AND PROTECT FOR RE-USE.
9B	REMOVE PORTION OF CEILING SYSTEM AND/OR SOFFIT SYSTEM TO EXTENT REQUIRED TO PATCH AREA OF WALLS. CAREFULLY TRIM CEILING GRID TO REMAIN.
9C	REMOVE CEILING- OR WALL-MOUNTED ACoustICAL TREATMENTS IN THEIR ENTIRETY.
9D	REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATION OF SCHEDULED WORK. PATCH EXPOSED SURFACES TO MATCH SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALL TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
	SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS): A. QUARRY TILE. B. VAT/VCT. H. TERRAZZO.
9E	REMOVE WALL BASE AND ASSOCIATED MASTIC ONLY - EXISTING FLOOR FINISHES AND CHAIR MOULDING PATTERNS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
9F	REMOVE PAINTED FINISH (INCLUDING RUST AND DEBRIS) ONLY TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK - EXISTING WALLS TO REMAIN. PREPARE SURFACE FOR FINISH AND PAINT.
10A	REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TAPE MEASURES AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
10B	REMOVE, SALVAGE AND PROTECT EXG TEACHING SURFACE. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
10D	REMOVE LOCKERS IN THEIR ENTIRETY INCLUDING BASE, SOFFIT AND WALL CONSTRUCTION ABOVE. PATCH EXPOSED SURFACES TO MATCH ADJACENT SURFACES/FINISHES.
12A	REMOVE CASEWORK, SHELVING AND ASSOCIATED COMPONENTS IN THEIR ENTIRETY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
12B	REMOVE DISPLAY CASEWORK (INCLUDING ALL ASSOCIATED COMPONENTS). PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
12C	REMOVE, SALVAGE AND PROTECT EXG BASE AND WALL CASEWORK. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
12D	REMOVE WINDOW TREATMENTS ONLY - WINDOW SYSTEM TO REMAIN.

- A. -----REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
 - 1. DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 - 2. DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE AN ARROW POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 - 3. DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE ENTIRE SPACE COVERED BY THE TAGS.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNER'S REPRESENTATIVE IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.
- E. EXISTING WINDOW-MOUNTED A/C UNITS SHALL BE REMOVED AND STORED BY OWNER PRIOR TO START OF DEMOLITION WORK.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:



Tetra Tech Engineers, Architects
& Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Area F

Drawn By: TLG	Date: 10/28/2022	Drawing Number: EA103
Project No.: 279180-22004		



1 Second Floor Demolition Plan - Area B - By Alternate No. 10
1/8" = 1'-0"


2 Second Floor Demolition Plan - Area D - - By Alternate No. 7
1/8" = 1'-0"

Demolition Key Notes

- (1G) REMOVE INTERIOR PARTITION FULL-HEIGHT, PORTION AS INDICATED OR AS REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF PARTITION REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FLOOR FINISH.
 - (1H) PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO ENLARGE SCHEDULED WORK. PROVIDE UNTEL PER UNTEL SCHEDULE. SEE STRU DRAWINGS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
 - (8A) REMOVE WINDOW COMPLETELY. PREPARE OPENING TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (8B) REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (8C) REMOVE DOOR AND HARDWARE ONLY - EXISTING FRAME TO REMAIN. PREPARE FOR NEW DOOR WHERE SCHEDULED.
 - (9A) REMOVE CEILING SYSTEM AND/OR SOFFIT SYSTEM IN ITS ENTIRETY. CLEAN, SALVAGE AND PROTECT FOR RE-USE.
 - (9B) REMOVE PORTION OF CEILING SYSTEM AND/OR SOFFIT SYSTEM, TO EXTENT REQUIRED TO PERFORM NEW WORK. CAREFULLY TRIM CEILING GRID TO REMAIN.
 - (9C) REMOVE CEILING- OR WALL-MOUNTED ACOUSTICAL TREATMENTS IN THEIR ENTIRETY.
 - (9D) REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS):
A. QUARRY TILE.
B. VAT/VCT.
H. TERRAZZO.
- (9E) REMOVE WALL BASE AND ASSOCIATED MASTIC ONLY - EXISTING FLOOR FINISH TO REMAIN. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
 - (9F) REMOVE PAINTED FINISH (INCLUDING RUST AND DEBRIS) ONLY TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. EXISTING WALLS TO REMAIN. PREPARE SURFACE FOR FINISH AND PAINT.
 - (10A) REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TACK BOARDS AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (10B) REMOVE, SALVAGE AND PROTECT EXG TEACHING SURFACE. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
 - (10D) REMOVE LOCKERS IN THEIR ENTIRETY INCLUDING BASE, SOFFIT AND WALL CONSTRUCTION ABOVE. PATCH EXPOSED SURFACES TO MATCH ADJACENT SURFACES/FINISHES.
 - (12A) REMOVE CASEWORK, SHELVING AND ASSOCIATED COMPONENTS IN THEIR ENTIRETY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
 - (12B) REMOVE DISPLAY CASEWORK (INCLUDING ALL ASSOCIATED COMPONENTS). PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH CASEWORK DRAWINGS.
 - (12C) REMOVE, SALVAGE AND PROTECT EXG BASE AND WALL CASEWORK. DELIVER TO OWNER'S STORAGE LOCATION FOR THEIR RE-USE.
 - (12D) REMOVE WINDOW TREATMENTS ONLY - WINDOW SYSTEM TO REMAIN.

General Demolition Notes

- A. - - - -REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
 - 1. DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 - 2. DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE A LEADER POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 - 3. DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE SPACE IDENTIFIED BY THAT LEADER.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNERS AGENT(S) IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.
- E. EXISTING WINDOW-MOUNTED A/C UNITS SHALL BE REMOVED AND STORED BY OWNER PRIOR TO START OF DEMOLITION WORK.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:
-----------	-------	--------------



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Second Floor Demolition Plan - Area B and D

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EA104	




1 First Floor Plan - Area A
1/8" = 1'-0"

General Plan Notes

- A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
- B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL, TYPICAL UNLESS NOTED OTHERWISE.
- ALL EXTERIOR WALLS SHALL BE WALL/PARTITION TYPE EW4, TYPICAL UNLESS NOTED OTHERWISE.
 - ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.

Keyed Plan Notes

- 1 INSTALL LOUVER FURNISHED BY OTHERS AT NEW OPENING. COORDINATE WITH MECHANICAL DRAWINGS.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Plan - Area A

Drawn By: TLG Date: 10/28/2022 Drawing Number: EA130
Project No.: 279180-22004




General Plan Notes

- A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
- B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL, UNLESS NOTED OTHERWISE.
1. ALL EXTERIOR WALLS SHALL BE WALL/PARTITION TYPE EW4, TYPICAL UNLESS NOTED OTHERWISE.
 2. ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.

Keyed Plan Notes

- 1 INSTALL LOUVER FURNISHED BY OTHERS AT NEW OPENING.
COORDINATE WITH MECHANICAL DRAWINGS.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023



complex world | CLEAR SOLUTIONS

**Tetra Tech Engineers, Architects
& Landscape Architects, P.C.**



TETRA TECH
ARCHITECTS & ENGINEERS


Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Plan - Area B

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EA13

EA131



General Plan Notes

- A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
- B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL. TYPICAL UNLESS NOTED OTHERWISE.
- ALL EXTERIOR WALLS SHALL BE WALL/PARTITION TYPE EW4, TYPICAL UNLESS NOTED OTHERWISE.
 - ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.

Keyed Plan Notes

- 1 INSTALL LOUVER FURNISHED BY OTHERS AT NEW OPENING. COORDINATE WITH MECHANICAL DRAWINGS.

Room Finish Key


- EF EPOXY FLOORING - POURED
RF RESINOUS FLOORING - EPOXY
LVT LUXURY VINYL TILE
MCS MOISTURE CONTROL SYSTEM
N NO WORK REQUIRED
P PAINT SURFACE(S) INCLUDING SOFFITS
RB RUBBER BASE
T1 TERRAZZO - TYPE 1 - POURED EPOXY
TB TERRAZZO BASE - PRECAST
VCT1 VINYL COMPOSITION TILE - TYPE 1

- SEE REFLECTED CEILING PLAN
INDICATED CHANGE IN FLOOR FINISH

NOTE: ALL FINISHES LISTED MAY NOT BE REQUIRED FOR THIS PROJECT

FINISHES SHOWN IN ROOM FINISH BOX ARE FOR ALL WALLS AND ENTIRE FLOOR AND CEILING. REFER TO EACH ROOM FOR MORE INFORMATION.

RM#	
CLG*	WALL
FLR	BASE



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Plan - Area C and D

Drawn By: TLG Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004

EA132



A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.

B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL, TYPICAL UNLESS NOTED OTHERWISE.

1. ALL EXTERIOR WALLS SHALL BE WALL/PARTITION TYPE EW4, TYPICAL UNLESS NOTED OTHERWISE.
2. ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.

1 INSTALL LOUVER FURNISHED BY OTHERS AT NEW OPENING.
COORDINATE WITH MECHANICAL DRAWINGS.




Rev. No.:	Date:	Description:
-----------	-------	--------------




M	Reconstruction to: Rombout Middle School
---	---

N	Drawn By: TLG	Date: 10/28/2022	Drawing Number:
	Project No.: 279180-22004		EA133

EA133



1 First Floor Reflected Ceiling Plan - Area A
1/8" = 1'-0"



General Ceiling Notes


- LIGHTING AND OTHER CEILING-MOUNTED FIXTURES ARE SHOWN FOR DRAWING CLARITY. COORDINATE ALL CEILING WORK PRIOR TO INSTALLATION OF CEILING GRID.
- CEILING HEIGHT IS 9'-0" ABOVE FINISHED FLOOR (UNO).
- CENTER CEILING-MOUNTED ITEMS (LIGHTS, GRILLES, DETECTORS, SPRINKLER HEAD, ETC) WITHIN THE CEILING PANELS AND GRIDS UNLESS THE PANELS ARE SCORED. CENTER ITEMS WITHIN THE PATTERN OF SCORED PANELS.
- PROVIDE EXPANSION JOINT (EJ) COVERS IN CEILINGS AND SOFFITS AT EJ LOCATIONS.
- PROVIDE CONTROL JOINTS IN GYPSUM BOARD CEILINGS AND SOFFITS AS DETAILED ON DRAWINGS (MAXIMUM 20'-0" OC, EVENLY SPACED, TYP UNO).
- PATCH CEILING SYSTEMS TO REMAIN THAT HAVE BEEN DISTURBED BY SCHEDULED WORK TO MATCH ADJACENT CONSTRUCTION PRIOR TO PAINTING.
- (X | 9'-0") DESIGNATES BOTTOM OF CEILING ABOVE FINISHED FLOOR AT THAT POINT UNO. DESIGNATION "ME" INDICATES MATCH EXISTING CEILING HEIGHT.
- AT ALL LOCATIONS OF GYPSUM CEILINGS - PROVIDE 24" X 24" CONCEALED FLANGE ACCESS DOOR REGARDLESS OF LOCATION OR REQUIREMENT FOR ACCESS TO EQUIPMENT.

Ceiling Types

- | | | |
|----|-------|--|
| A1 | X'-X" | ACOUSTIC PANEL CEILING |
| A2 | X'-X" | ACOUSTIC PANEL CEILING |
| A4 | X'-X" | ACOUSTIC PANEL CEILING |
| B | X'-X" | PAINTED 1/2" GYPSUM CEILING ON SUPPORT MATERIALS (GRID SUSPENSION SYSTEM, TYP UNO) |
| F | X'-X" | PAINTED EXPOSED STRUCTURAL SYSTEM, SUPPORT MATERIALS AND FASTENERS, MECHANICAL SYSTEM, ELECTRICAL ITEMS AND PIPING |

NOTE: AT AREAS WITH "X", THE INTENT IS TO MATCH EXISTING. VERIFY IN FIELD.

AREA OF A2 CEILING TYPE



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

First Floor Reflected Ceiling Plan - Area A

Drawn By: TTAE	Date: 10/28/2022	Drawing Number: EA160
Project No.: 279180-22004		



1 First Floor Reflected Ceiling Plan - Area B
1/8" = 1'-0"



2 First Floor Reflected Ceiling Plan - Area E
1/8" = 1'-0"

General Ceiling Notes


- LIGHTING AND OTHER CEILING-MOUNTED FIXTURES ARE SHOWN FOR DRAWING CLARITY. COORDINATE ALL CEILING WORK PRIOR TO INSTALLATION OF CEILING GRID.
- CEILING HEIGHT IS 9'-0" ABOVE FINISHED FLOOR (UNO).
- CENTER CEILING-MOUNTED ITEMS (LIGHTS, GRILLES, DETECTORS, SPRINKLER HEAD, ETC.) WITHIN THE CEILING PANELS AND GRIDS UNLESS THE PANELS ARE SCORED. CENTER ITEMS WITHIN THE PATTERN OF SCORED PANELS.
- PROVIDE EXPANSION JOINT (EJ) COVERS IN CEILINGS AND SOFFITS AT EJ LOCATIONS.
- PROVIDE CONTROL JOINTS IN GYPSUM BOARD CEILINGS AND SOFFITS AS DETAILED ON DRAWINGS (MAXIMUM 20'-0" OC, EVENLY SPACED, TYP UNO).
- PATCH CEILING SYSTEMS TO REMAIN THAT HAVE BEEN DISTURBED BY SCHEDULED WORK TO MATCH ADJACENT CONSTRUCTION PRIOR TO PAINTING.
- (X) 9'-0" DESIGNATES BOTTOM OF CEILING ABOVE FINISHED FLOOR AT THAT POINT UNO. DESIGNATION "ME" INDICATES MATCH EXISTING CEILING HEIGHT.
- AT ALL LOCATIONS OF GYPSUM CEILINGS - PROVIDE 24" X 24" CONCEALED FLANGE ACCESS DOOR REGARDLESS OF LOCATION OR REQUIREMENT FOR ACCESS TO EQUIPMENT.

Ceiling Types

- (A1 X'-X") ACOUSTIC PANEL CEILING
- (A2 X'-X") ACOUSTIC PANEL CEILING
- (A4 X'-X") ACOUSTIC PANEL CEILING
- (B X'-X") PAINTED 1/2" GYPSUM CEILING ON SUPPORT MATERIALS (GRID SUSPENSION SYSTEM, TYP UNO)
- (F X'-X") PAINTED EXPOSED STRUCTURAL SYSTEM, SUPPORT MATERIALS AND FASTENERS, MECHANICAL SYSTEM, ELECTRICAL ITEMS AND PIPING

NOTE: AT AREAS WITH "+/-", THE INTENT IS TO MATCH EXISTING, VERIFY IN FIELD.

AREA OF A2 CEILING TYPE



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Reflected Ceiling Plan -
Area B and E


Drawn By:
TLG
Project No.:
279180-22004

Date:
10/28/2022

Drawing Number:


EA161

BID SET



- General Ceiling Notes**
- A. LIGHTING AND OTHER CEILING-MOUNTED FIXTURES ARE SHOWN FOR DRAWING CLARITY. COORDINATE ALL CEILING WORK PRIOR TO INSTALLATION OF CEILING GRID.
 - B. CEILING HEIGHT IS 9'-0" ABOVE FINISHED FLOOR (UNO).
 - C. CENTER CEILING-MOUNTED ITEMS (LIGHTS, GRILLES, DETECTORS, SPRINKLER HEAD, ETC) WITHIN THE CEILING PANELS AND GRIDS UNLESS THE PANELS ARE SCORED. CENTER ITEMS WITHIN THE PATTERN OF SCORED PANELS.
 - D. PROVIDE EXPANSION JOINT (EJ) COVERS IN CEILINGS AND SOFFITS AT EJ LOCATIONS.
 - E. PROVIDE CONTROL JOINTS IN GYPSUM BOARD CEILINGS AND SOFFITS AS DETAILED ON DRAWINGS (MAXIMUM 20'-0" OC, EVENLY SPACED, TYP UNO).
 - F. PATCH CEILING SYSTEMS TO REMAIN THAT HAVE BEEN DISTURBED BY SCHEDULED WORK TO MATCH ADJACENT CONSTRUCTION PRIOR TO PAINTING.
 - G. (X) 9'-0" DESIGNATES BOTTOM OF CEILING ABOVE FINISHED FLOOR AT THAT POINT UNO. DESIGNATION "ME" INDICATES MATCH EXISTING CEILING HEIGHT.
 - H. AT ALL LOCATIONS OF GYPSUM CEILINGS - PROVIDE 24" X 24" CONCEALED FLANGE ACCESS DOOR REGARDLESS OF LOCATION OR REQUIREMENT FOR ACCESS TO EQUIPMENT.

- Ceiling Types**
- A1 (X-X') ACOUSTIC PANEL CEILING
 - A2 (X-X') ACOUSTIC PANEL CEILING
 - A4 (X-X') ACOUSTIC PANEL CEILING
 - B (X-X') PAINTED 1/2" GYPSUM CEILING ON SUPPORT MATERIALS (GRID SUSPENSION SYSTEM, TYP UNO)
 - F (X-X') PAINTED EXPOSED STRUCTURAL SYSTEM, SUPPORT MATERIALS AND FASTENERS, MECHANICAL SYSTEM, ELECTRICAL ITEMS AND PIPING
- NOTE: AT AREAS WITH "+/-", THE INTENT IS TO MATCH EXISTING, VERIFY IN FIELD.
- AREA OF A2 CEILING TYPE



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Reflected Ceiling Plan -
Area C and D

Drawn By: TLG Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004
EA162




1 First Floor Reflected Ceiling Plan - Area F
1/8" = 1'-0"

- ### General Ceiling Notes
- A. LIGHTING AND OTHER CEILING-MOUNTED FIXTURES ARE SHOWN FOR DRAWING CLARITY. COORDINATE ALL CEILING WORK PRIOR TO INSTALLATION OF CEILING GRID.
 - B. CEILING HEIGHT IS 9'-0" ABOVE FINISHED FLOOR (UNO).
 - C. CENTER CEILING-MOUNTED ITEMS (LIGHTS, GRILLES, DETECTORS, SPRINKLER HEAD, ETC) WITHIN THE CEILING PANELS AND GRIDS UNLESS THE PANELS ARE SCORED. CENTER ITEMS WITHIN THE PATTERN OF SCORED PANELS.
 - D. PROVIDE EXPANSION JOINT (EJ) COVERS IN CEILINGS AND SOFFITS AT EJ LOCATIONS.
 - E. PROVIDE CONTROL JOINTS IN GYPSUM BOARD CEILINGS AND SOFFITS AS DETAILED ON DRAWINGS (MAXIMUM 20'-0" OC, EVENLY SPACED, TYP UNO).
 - F. PATCH CEILING SYSTEMS TO REMAIN THAT HAVE BEEN DISTURBED BY SCHEDULED WORK TO MATCH ADJACENT CONSTRUCTION PRIOR TO PAINTING.
 - G. (X) 9'-0" DESIGNATES BOTTOM OF CEILING ABOVE FINISHED FLOOR AT THAT POINT UNO. DESIGNATION "ME" INDICATES MATCH EXISTING CEILING HEIGHT.
 - H. AT ALL LOCATIONS OF GYPSUM CEILINGS - PROVIDE 24" X 24" CONCEALED FLANGE ACCESS DOOR REGARDLESS OF LOCATION OR REQUIREMENT FOR ACCESS TO EQUIPMENT.

- ### Ceiling Types
- A1 X-X" ACOUSTIC PANEL CEILING
 - A2 X-X" ACOUSTIC PANEL CEILING
 - A4 X-X" ACOUSTIC PANEL CEILING
 - B X-X" PAINTED 1/2" GYPSUM CEILING ON SUPPORT MATERIALS (GRID SUSPENSION SYSTEM, TYP UNO)
 - F X-X" PAINTED EXPOSED STRUCTURAL SYSTEM, SUPPORT MATERIALS AND FASTENERS, MECHANICAL SYSTEM, ELECTRICAL ITEMS AND PIPING


NOTE: AT AREAS WITH "1/2", THE INTENT IS TO MATCH EXISTING. VERIFY IN FIELD.

AREA OF A2 CEILING TYPE



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

First Floor Reflected Ceiling Plan - Area F

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EA163	



1 Second Floor Reflected Ceiling Plan - Area B - By Alternate No. 10
1/8" = 1'-0"



2 Second Floor Reflected Ceiling Plan - Area D - By Alternate No. 7
1/8" = 1'-0"

General Ceiling Notes


- A. LIGHTING AND OTHER CEILING-MOUNTED FIXTURES ARE SHOWN FOR DRAWING CLARITY. COORDINATE ALL CEILING WORK PRIOR TO INSTALLATION OF CEILING GRID.
- B. CEILING HEIGHT IS 9'-0" ABOVE FINISHED FLOOR (UNO).
- C. CENTER CEILING-MOUNTED ITEMS (LIGHTS, GRILLES, DETECTORS, SPRINKLER HEAD, ETC) WITHIN THE CEILING PANELS AND GRIDS UNLESS THE PANELS ARE SCORED. CENTER ITEMS WITHIN THE PATTERN OF SCORED PANELS.
- D. PROVIDE EXPANSION JOINT (EJ) COVERS IN CEILINGS AND SOFFITS AT EJ LOCATIONS.
- E. PROVIDE CONTROL JOINTS IN GYPSUM BOARD CEILINGS AND SOFFITS AS DETAILED ON DRAWINGS (MAXIMUM 20'-0" OC, EVENLY SPACED, TYP UNO).
- F. PATCH CEILING SYSTEMS TO REMAIN THAT HAVE BEEN DISTURBED BY SCHEDULED WORK TO MATCH ADJACENT CONSTRUCTION PRIOR TO PAINTING.
- G. (X) (9'-0") DESIGNATES BOTTOM OF CEILING ABOVE FINISHED FLOOR AT THAT POINT UNO. DESIGNATION "ME" INDICATES MATCH EXISTING CEILING HEIGHT.
- H. AT ALL LOCATIONS OF GYPSUM CEILINGS - PROVIDE 24" X 24" CONCEALED FLANGE ACCESS DOOR REGARDLESS OF LOCATION OR REQUIREMENT FOR MENT.

Ceiling Types



- A1 X-X" ACOUSTIC PANEL CEILING
- A2 X-X" ACOUSTIC PANEL CEILING
- A4 X-X" ACOUSTIC PANEL CEILING
- B X-X" PAINTED 1/2" GYPSUM CEILING ON SUPPORT MATERIALS (GRID SUSPENSION SYSTEM, TYP UNO)
- F X-X" PAINTED EXPOSED STRUCTURAL SYSTEM, SUPPORT MATERIALS AND FASTENERS, MECHANICAL SYSTEM, ELECTRICAL ITEMS AND PIPING


NOTE: AT AREAS WITH "A1", THE INTENT IS TO MATCH EXISTING. VERIFY IN FIELD.

AREA OF A2 CEILING TYPE




S.E.D. Control No. 13-02-00-01-0-004-023


		
complex world CLEAR SOLUTIONS		
Tetra Tech Engineers, Architects & Landscape Architects, P.C.		
BID SET		
 TETRA TECH ARCHITECTS & ENGINEERS		
Beacon City School District Beacon, New York		
Reconstruction to: Rombout Middle School		
Second Floor Reflected Ceiling Plan - Area B and D		
Drawn By: TTAE	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EA164




1 Roof Plan
1/8" = 1'-0"




6 Expansion Joint Detail
1 1/2" = 1'-0"




10 Roof Vent Pipe Detail
1 1/2" = 1'-0"




7 Base Flashing Details
1 1/2" = 1'-0"




12 Hot Flue Pipe Detail
1 1/2" = 1'-0"




11 Equipment Curb Detail
1 1/2" = 1'-0"




9 Enlarged Base/Counter Flashing Detail
6" = 1'-0"




8 Enlarged Flashing Detail - Surface Mounted at Vertical Termination
6" = 1'-0"




2 Roof System RS-1
1 1/2" = 1'-0"



3 Roof Drain Insert Detail
1 1/2" = 1'-0"



4 Roof Tie In Detail at Expansion Joint
1 1/2" = 1'-0"



5 Roof Transition Detail
1 1/2" = 1'-0"

Legend

AREA OF TAPERED INSULATION (TYP).

EXISTING ROOF AREA - NO WORK

ROOF DRAIN INSERT IN EXISTING ROOF DRAIN (TYP). PROVIDE TAPERED SUMP.

EXPANSION JOINT (TYP).

DIRECTION AND DEGREE OF DOWNWARD SLOPE OF TAPERED INSULATION (MINIMUM 1/8"FT, TYP).

DIRECTION OF DOWNWARD SLOPE OF TAPERED INSULATION CRICKET (1/2"FT, TYP UNO).

TOTAL THICKNESS OF INSULATION.


ROOF SYSTEM TYPE RS-X.

TEST CUT LOCATION, REFER TO EXISTING CONDITIONS NOTES

Roof Key Notes

- PROVIDE ROOF DRAIN INSERT AT EXISTING ROOF DRAIN - SEE DETAIL 3/EA190.
- TAPERED INSULATION CRICKET (TYP) SLOPE 1/2"FT. TYP ALL SIDES. VERIFY LENGTH IN FIELD, WIDTH AS INDICATED ON PLAN AND TYPICAL AT ALL CURB PENETRATIONS.
- REPLACE EXPANSION JOINT AT EXISTING LOCATION, HEIGHT AS REQUIRE TO ACCOMMODATE ROOF THICKNESS - SEE DETAIL 6/EA190.
- FLASH INTO EXISTING FULLY ADHERED EPDM ROOF SYSTEM TO COMPLY WITH ALL MANUFACTURER'S WARRANTY REQUIREMENTS - SEE DETAIL 4/EA190 SIMILAR.
- MATCH TAPERED INSULATION HEIGHT AND TIE IN ROOF MEMBRANE.
- ROOF VERTICAL TRANSITION DETAIL WITH FASCIA AT UPPER ROOF LEVEL APPROXIMATE HEIGHT INDICATED ON PLAN - SEE DETAIL 5/EA190.
- PROVIDE BASE/COUNTER FLASHING BELOW EXISTING THROUGH-WALL FLASHING - SEE DETAIL 7/EA190.
- PROVIDE ROOF OPENING AND INSTALL ROOF CURB FURNISHED BY MECHANICAL CONTRACTOR. SEE DETAIL 11/EA190

- EXISTING CONDITIONS:**
- TYPICAL AT (F' WINGS) LOW ROOF AREAS - REFER TO PLAN TEST CUT LOCATIONS #1.
 - FULLY ADHERED EPDM MEMBRANE.
 - TAPERED POLYISOCYANURATE INSULATION - THICKNESS VARIES BETWEEN 3" TO 5" - MECHANICALLY ATTACHED.
 - TAR PAPER.
 - CORRUGATED METAL ROOF DECK - FLAT.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description

complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET


TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

Roof Plan and Details


Drawn By: TLG	Date: 10/28/2022	Drawing Number: EA190
Project No.: 279180-22004		




2 First Floor Area B Enlarged Science Rooms Plan
1/4" = 1'-0"



3 Locker Plan Detail
3/4" = 1'-0"




1 First Floor Area A Enlarged Art Rooms Plan
1/4" = 1'-0"



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
Beacon, New York





















Reconstruction to:
Rombout Middle School

Enlarged Plans and Details

Drawn By: TTAE	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EA400

GENERAL NOTES:
VERIFY ALL DIMENSIONS IN THE FIELD

SPECIFIC NOTES:
- NOT APPLICABLE



A. HARDWARE ON DOORS FROM SPACES OF PUPIL OCCUPANCY SHALL BE A TYPE WHICH WILL ALWAYS PERMIT THE DOOR TO BE OPENED FROM THE INSIDE WITHOUT DIRECT MANIPULATION OF ANY TYPE LOCKING DEVICE.

B. METAL VISION PANEL TRIM SHALL BE PAINTED SAME COLOR AS DOOR FRAMES.

C. ALL HM FRAMES IN CMU WALLS SHALL BE GROUTED SOLID.

D. APPLY CONTINUOUS JOINT SEALANT TO ALL JOINTS BETWEEN FRAMES AND WALLS, TYP. AL.

E. PAINT ALL HM DOORS AND FRAMES IN ACCORDANCE W/ SECTION 09500.

F. PROVIDE UNITS AT ALL DOOR AND WINDOW OPENINGS IN ACCORDANCE WITH SCHEDULE ON STRUCTURAL DWGS.

G. PROVIDE MARBLE THRESHOLDS AT ALL TOILET ROOMS WHERE ADJACENT FINE IS CERAMIC TILE. REFER TO DETAIL 11/A2828.

H. VERIFY SIZES OF ALL EXISTING OPENINGS IN SCHEDULE PRIOR TO FIRST SUBMISSION OF SHOP DRAWINGS. NOTIFY ARCHITECT IF ANY ARE LESS THAN CODE MINIMUM HEIGHT OF 6'-6". ASSUME FOR BIDDING ALL EXISTING OPENINGS ARE AS NOTED IN THE SCHEDULE (VIF, TYP).


J. MATERIAL DESIGNATION KEY:

FRP FIBERGLASS REINFORCED PLASTIC
HM HOLLOW METAL
WD WOOD
AL ALUMINUM
STL STEEL
EXX EXISTING

L. ADDITIONAL DOOR SCHEDULE DESIGNATIONS:

- + EXISTING TO REMAIN
- NOT APPLICABLE
- == NOT APPLICABLE OR TO BE COORDINATED WITH STOREFRONT FRT

- A. INSULATING GLASS UNITS SHALL BE TYPE C/PCE/F, TYP UNO.
- B. RESCUE UNIONS ARE INDICATED BY THE DESIGNATION "RW".
- C. PROVIDE ALL ALUMINUM FLASHINGS, RECEIVERS, TRIM AND SILLS REQUIRED FOR A COMPLETE AND FINISHED INSTALLATION REGARDLESS OF IF SHOWN ON DRAWINGS.
- D. REFER TO WINDOW TREATMENTS AS SHOWN ON DRAWINGS.
- E. GLAZING SYSTEMS FRAME TYPE KEY:
 - C ALUMINUM CURTAIN WALL
 - F HOLLOW METAL
 - S ALUMINUM STOREFRONT
 - W ALUMINUM WINDOWS
- F. PROVIDE INTERNAL STEEL REINFORCEMENT TO WINDOW, STOREFRONT AND CURTAIN WALL SYSTEMS AS REQUIRED TO COMPLY WITH WIND LOADING OR OTHER DESIGN CRITERIA, OR AS RECOMMENDED BY MANUFACTURER.
- G. ALUMINUM WINDOW, STOREFRONT AND CURTAIN WALL FRAME EXTRUSIONS ARE INTENDED TO BE GENERIC GRAPHIC REPRESENTATIONS ONLY.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:
-----------	-------	--------------



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Door Schedule, Door, Frame and Wall Types, and Details

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EA600



Room Finish Key

EF	EPOXY FLOORING - POURED
RF	RESINOUS FLOORING - EPOXY
LVT	LUXURY VINYL TILE
MCS	MOISTURE CONTROL SYSTEM
N	NO WORK REQUIRED
P	PAINT SURFACE(S) INCLUDING SOFFITS
RB	RUBBER BASE
T1	TERRAZZO - TYPE 1 - POURED EPOXY
TB	TERRAZZO BASE - PRECAST
VCT1	VINYL COMPOSITION TILE - TYPE 1

SEE REFLECTED CEILING PLAN

INDICATED CHANGE IN FLOOR FINISH

NOTE: ALL FINISHES LISTED MAY NOT BE REQUIRED FOR THIS PROJECT

RM#	
CLG*	WALL
FLR	BASE

FINISHES SHOWN IN ROOM FINISH BOX ARE FOR ALL WALLS AND ENTIRE FLOOR AND CEILING. REFER TO EACH ROOM FOR MORE INFORMATION.

Window Treatment Key

INDICATES AREAS OF WINDOW TREATMENTS

Window Treatment Notes

THIS DRAWING IS FOR LOCATION OF WINDOW TREATMENTS ONLY. SPECIFICATIONS SECTION AND ARCH. DRAWINGS FOR SIZES AND ADDITIONAL PRODUCT INFORMATION.

SHADE SIZES SHALL BE COORDINATED WITH WINDOWS, INCLUDING ALL RESCUE WINDOW REQUIREMENTS.

REFER TO DRAWING EA930 FOR GENERAL FINISH NOTES

REFER TO DRAWING EA930 FOR CASEWORK NOTES

Key Plan

N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description

Beacon City School District
Beacon, New York

complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.

BID SET

TETRA TECH


ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Enlarged Plans

Drawn By: TTAE	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EA920	



Room Finish Key	
EF	EPOXY FLOORING - POURED
RF	RESINOUS FLOORING - EPOXY
LVT	LUXURY VINYL TILE
MCS	MOISTURE CONTROL SYSTEM
N	NO WORK REQUIRED
P	PAINT SURFACE(S) INCLUDING SOFFITS
RB	RUBBER BASE
T1	TERRAZZO - TYPE 1 - POURED EPOXY
TB	TERRAZZO BASE - PRECAST
VCT1	VINYL COMPOSITION TILE - TYPE 1

SEE REFLECTED CEILING PLAN	
INDICATED CHANGE IN FLOOR FINISH	
NOTE: ALL FINISHES LISTED MAY NOT BE REQUIRED FOR THIS PROJECT	
FINISHES SHOWN IN ROOM FINISH BOX ARE FOR ALL WALLS AND ENTIRE FLOOR AND CEILING. REFER TO EACH ROOM FOR MORE INFORMATION.	
RM#	
CLG*	WALL
FLR	BASE


Window Treatment Key	
INDICATES AREAS OF WINDOW TREATMENTS	

Window Treatment Notes

THIS DRAWING IS FOR LOCATION OF WINDOW TREATMENTS ONLY. SPECIFICATIONS SECTION AND ARCH. DRAWINGS FOR SIZES AND ADDITIONAL PRODUCT INFORMATION.

SHADE SIZES SHALL BE COORDINATED WITH WINDOWS, INCLUDING ALL RESCUE WINDOW REQUIREMENTS.

REFER TO DRAWING EA930 FOR GENERAL FINISH NOTES
REFER TO DRAWING EA930 FOR CASEWORK NOTES



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School


Enlarged Plans

Drawn By: Author	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EA921	


1 First Floor Area B Enlarged Science Rooms Plan
1/4" = 1'-0"




5 General Science B119
1/4" = 1'-0"




8 Greenhouse 121A
1/4" = 1'-0"




4 Greenhouse 121A
1/4" = 1'-0"




7 General Science B119
1/4" = 1'-0"




10 Terrazzo Base at New Opening
1 1/2" = 1'-0"




3 Prep 120B
1/4" = 1'-0"






































2 Prep 120B
1/4" = 1'-0"




6 General Science B119
1/4" = 1'-0"



9 General Science B119
1/4" = 1'-0"






KEYED NOTES:

- 1 BY ALT. NO. 7: REMOVE CEILING CUH FACEPLATE. SAND BLAST, PAINT AND REINSTALL CUH FACEPLATE. COORDINATE WITH CEILING REPLACEMENT.
- 2 BY ALT. NO. 10: DISCONNECT GRILLE FROM DUCTWORK. STORE GRILLE FOR REUSE. COORDINATE WITH CEILING REPLACEMENT. REINSTALL AND RECONNECT GRILLE IN CEILING. PROVIDE DUCT MODIFICATIONS AS REQUIRED.
- 3 BY ALT. NO. 10: REMOVE (UNDUCTED) GRILLE FROM CEILING. STORE GRILLE FOR REUSE. COORDINATE WITH CEILING REPLACEMENT. REINSTALL GRILLE IN CEILING.

General Notes


- A. THE FOLLOWING GENERAL NOTES APPLY TO ALL "EM" SERIES DRAWINGS.
- B. REFER TO ALL CONTRACT DOCUMENTS, DRAWINGS AND SPECIFICATIONS, FOR DETAILED STANDARDS AND REQUIREMENTS.
- C. REPORT UNSAFE OR UNSATISFACTORY CONDITIONS IN WRITING TO ARCHITECT AND RESOLVE ISSUES BEFORE PROCEEDING.
- D. WORK INCLUDES ALL LABOR AND MATERIALS REQUIRED TO PROVIDE COMPLETE WORKING SYSTEMS.
- E. COORDINATE PHASING REQUIREMENTS AT JOB MEETINGS AND ON WORK SCHEDULES.
- F. DO NOT SCALE DRAWINGS. PIPING AND DUCTWORK ARE SHOWN DIAGRAMMATICALLY. IT IS NOT POSSIBLE TO SHOW EVERY TRANSITION, FITTING, ASPECT RATIO CHANGE, ETC. PROVIDE AS REQUIRED TO FIT WITHIN STRUCTURAL CONSTRAINTS. EXAMINE CONDITIONS UNDER WHICH THE WORK IS TO BE PERFORMED AND VERIFY ALL ACCESS, LOCATIONS, DIMENSIONS, ARRANGEMENTS, ELECTRICAL CHARACTERISTICS AND INTERFERENCE IN THE FIELD PRIOR TO BID.
- G. VERIFY EXTENT OF CEILING WORK SHOWN ELSEWHERE IN THE CONTRACT DOCUMENTS. PROVIDE FOR ADDITIONAL CEILING SYSTEM REMOVAL, PROTECTION, AND REINSTALLATION AS REQUIRED FOR CONTRACT WORK.
- H. DEMOLITION DRAWINGS SHOW THE GENERAL SCOPE OF ITEMS AND SYSTEMS TO BE REMOVED. IT IS NOT THE INTENT TO SHOW ALL ITEMS TO BE REMOVED. FIELD VERIFY AND REMOVE ALL ASSOCIATED ITEMS BACK TO POINT OF CONTINUED SERVICE. UNLESS OTHERWISE NOTED, VERIFY WHAT ALL EQUIPMENT SERVES PRIOR TO REMOVAL.
- I. GIVE ALL REMOVED EQUIPMENT TO THE OWNER. DELIVER ON SITE WHERE DESIGNATED BY THE OWNER. PROMPTLY REMOVE FROM THE SITE AND LEGALLY DISPOSE OF ANY SUCH ITEMS DECLINED BY OWNER.
- J. IF UNANTICIPATED MECHANICAL, ELECTRICAL, OR STRUCTURAL CONFLICTS ARE ENCOUNTERED, INVESTIGATE AND REPORT BOTH NATURE AND EXTENT OF THE CONFLICT. RE-ROUTE WORK AS REQUIRED.
- K. CUT, DRILL, OR OTHERWISE CREATE OPENINGS AS NEATLY AS POSSIBLE. AS REQUIRED FOR THE INDICATED CONTRACT WORK, PROVIDE SUPPORT AS REQUIRED FOR AND USE METHODS LEAST LIKELY TO DAMAGE ELEMENTS TO REMAIN. PRIOR TO WORK, VERIFY LOCATIONS OF ALL STRUCTURAL MEMBERS INCLUDING CROSS BRACING, ELECTRICAL WIRING, PLUMBING, ETC. PROMPTLY NOTIFY ARCHITECT OF ANY CONFLICTS. DO NOT CUT ANY STRUCTURAL MEMBERS OR OTHER SERVICES UNTIL SPECIFICALLY DIRECTED TO DO SO. PENDING RECEIPT OF DIRECTION, REARRANGE SCHEDULE AS NECESSARY TO CONTINUE OVERALL JOB PROGRESS WITHOUT DELAY.
- L. PATCH ALL DISTURBANCES RESULTING FROM DEMOLITION OR NEW WORK TO MATCH SURROUNDING SURFACES. PATCH FOLLOWING DEMOLITION, AND AGAIN FOLLOWING WORK, WHERE HOLES REMAIN FROM REMOVALS, INFILL AND PATCH TO MATCH UNLESS HOLE IS TO BE REUSED.
- M. PROTECT ALL CONTRACT EQUIPMENT. ELEMENTS TO REMAIN, OWNER'S BELONGINGS, AND EQUIPMENT TO BE REUSED OR RETAINED BY OWNER DURING ALL CONTRACT WORK. AT NO ADDITIONAL COST TO OWNER, REPAIR OR REPLACE ITEMS WHICH ARE DAMAGED.
- N. THOROUGHLY CLEAN FOLLOWING DEMOLITION AND BEFORE BEGINNING CONTRACT INSTALLATIONS. THOROUGHLY CLEAN AGAIN DURING AND FOLLOWING CONTRACT WORK AS REQUIRED. LEAVE ALL WORK AREAS CLEANER THAN FOUND. LEGALLY DISPOSE OF ALL CONSTRUCTION DEBRIS.
- O. PROVIDE TEMPORARY PIPING, DUCT, HEAT, WEATHERPROOFING, ETC. TO SERVICES TO REMAIN UNTIL PERMANENT INSTALLATIONS CAN BE MADE.
- P. ALL EXCESS MATERIALS AND SCRAPS ARE CONTRACTOR'S PROPERTY. PROMPTLY REMOVE FROM SITE UNLESS SPECIFICALLY DIRECTED OTHERWISE.
- Q. EXISTING HVAC COMPONENTS IN THIS BUILDING MAY CONTAIN, BE IN PROXIMITY TO, OR, WORK ON THEM MAY CAUSE DISTURBANCE OF, ASBESTOS CONTAINING OR OTHER HAZARDOUS MATERIALS. REFER TO ADJACENT SERIES DRAWINGS AND SPECIFICATIONS COMPLETE FOR ADDITIONAL INFORMATION.
- R. SEAL ALL FLOOR, WALL AND CEILING PENETRATIONS PER FIRE-RESISTANCE RATINGS NOTED ON E-C-SERIES DRAWINGS, BUT NOT LESS THAN 1-HOUR, AND IN ACCORDANCE WITH SECTION 07 84 13 - PENETRATION FIRESTOPPING. THIS INCLUDES ALL NEW PENETRATIONS AND EXISTING UNFIRESTOPPED PENETRATIONS CREATED BY REMOVALS, AS REQUIRED TO PERFORM THE WORK.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor and Second Floor Key Plans

Drawn By: JPF1/pgm	Date: 10/28/2022	Drawing Number: EM051
Project No.: 279180-22004		




1 First Floor Demolition Plan - Partial Area A, Area B and Partial Area C
1/8" = 1'-0"

General Notes

A. REFER TO EM051 FOR GENERAL NOTES.


KEYED DEMOLITION NOTES:

- 1 REMOVE THERMOSTAT AND ASSOCIATED ACCESSORIES.
- 2 REMOVE FINNED TUBE RADIATION OR CONVECTOR AND ALL ASSOCIATED ACCESSORIES COMPLETE. REMOVE TERMINAL HWS/HWR PIPING BACK TO WALL CHASE AND PREPARE FOR RECONNECTION.
- 3 UNIT VENTILATOR TO REMAIN.
- 4 FINNED TUBE RADIATION OR CONVECTOR TO REMAIN.
- 5 WALL GRILLE TO REMAIN.
- 6 REMOVE UNIT HEATER AND ALL ASSOCIATED ACCESSORIES COMPLETE.
- 7 CAREFULLY REMOVE KILN EXHAUST HOOD, FAN, WALL SUPPORTS AND ASSOCIATED ACCESSORIES FOR REUSE.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Partial
Area A, Area B and Partial Area C


Drawn By: JPF1/pgm	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EM100	



2 First Floor Demolition Plan - Partial Area F
1/8" = 1'-0"



3 Roof Demolition Plan - Partial Area F
1/8" = 1'-0"




1 First Floor Demolition Plan - Area D
1/8" = 1'-0"

General Notes

A. REFER TO EM051 FOR GENERAL NOTES.

KEYED DEMOLITION NOTES:

- 1 REMOVE THERMOSTAT AND ASSOCIATED ACCESSORIES. PREPARE FOR RECONNECTION.
- 2 REMOVE FINNED TUBE RADIATION OR CONVECTOR AND ALL ASSOCIATED ACCESSORIES COMPLETE. REMOVE TERMINAL HWS/HWR PIPING BACK TO WALL CHASE AND PREPARE FOR RECONNECTION.
- 3 WALL GRILLE TO REMAIN.
- 4 FINNED TUBE RADIATION OR CONVECTOR TO REMAIN.
- 5 REMOVE WALL GRILLE. PREPARE DUCT FOR RECONNECTION.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Demolition Plans - Area D
and Partial Area F
Roof Demolition Plan - Partial Area F

Drawn By:
JPF/l/pgm


Date:
10/28/2022

Drawing Number:

Project No.:
279180-22004

EM101

BID SET



2 First Floor Plan - Partial Area E
1/8" = 1'-0"


1 First Floor Plan - Partial Area A, Area B and Partial Area C
1/8" = 1'-0"

General Notes

A. REFER TO EM051 FOR GENERAL NOTES.

KEYED NOTES:

- 1 EXTEND HWS/R PIPING AS REQUIRED TO MAKE CONNECTION AND PIPE PER DETAIL.
- 2 CONNECT SPACE TEMPERATURE SENSOR TO EXISTING WIRING.
- 3 PROVIDE LOUVER AND OA INTAKE SLEEVE AND SECURE PER DETAIL. REFER TO ARCHITECTURAL DRAWINGS FOR WALL OPENING AND LOUVER INSTALLATION.
- 4 EXTEND 1" HWS/R FROM POC TO UV AND PIPE PER DETAIL.
- 5 REINSTALL KILN EXHAUST HOOD, FAN, SUPPORTS AND ACCESSORIES. PROVIDE 4" HARD DUCT VENT UP THROUGH ROOF WITH GOOSENECK.
- 6 REPLACE CONTROL VALVE (SIZED FOR FLOWRATE PROVIDED) FOR RADIANT HEATING EQUIPMENT AND PROVIDE CONTROLS.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School


First Floor Plan - Partial Area A, Area B
and Partial Areas C and E

Drawn By: JPF/1/pgm	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EM130


BID SET




3 First Floor Plan - Partial Area F
1/8" = 1'-0"



4 Roof Plan - Partial Area C and Area D
1/16" = 1'-0"



1 First Floor Plan - Area D
1/8" = 1'-0"




2 Roof Plan - Partial Area F
1/8" = 1'-0"

General Notes

A. REFER TO EM051 FOR GENERAL NOTES.

KEYED NOTES:

- EXTEND HWS/R PIPING AS REQUIRED TO MAKE CONNECTION AND PIPE PER DETAIL.
- CONNECT SPACE TEMPERATURE SENSOR TO EXISTING WIRING.
- PROVIDE LOUVER AND OA INTAKE SLEEVE AND SECURE PER DETAIL. REFER TO ARCHITECTURAL DRAWINGS FOR WALL OPENING AND LOUVER INSTALLATION.
- REPLACE CONTROL VALVE (SIZED FOR FLOWRATE PROVIDED) FOR RADIANT HEATING EQUIPMENT AND PROVIDE CONTROLS.
- 18x32 SA AND 18x32 RA UP TO RTU-1.
- CONNECT 18x16 RA TO EXG 26x10.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world
CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Plans - Area D and Partial
Area F and Roof Plan - Area D and
Partial Areas C and F

Drawn By:
JPF/1/pgm



Date:
10/28/2022

Drawing Number:


Project No.:
279180-22004

EM131

BID SET




14 UV - Hot Water - Valve Control w/ FTR




15 Rooftop Unit - Heat Pump

NTS




10 Equipment Curb

NTS




11 Ceiling UV Hanger Detail

NTS




12 Duct Mounted Heating Coil - Hot Water - Valve Control

NTS




13 Fin Tube Radiation - Hot Water - 2-Way Control Valve

NTS




8 Duct Detail

NTS




5 Fin Tube Radiation Piping Schematic

NTS




9 FCU/UV Hot Water With FTR Piping Schematic

NTS




6 Storm Louver Detail

NTS




4 RHC/UV Hot Water Piping Schematic

NTS




5 Fin Tube Radiation Piping Schematic

NTS





6 Storm Louver Detail

NTS




7 Roof Curb Cap Detail

NTS




1 Insulation Shield and Blocking

NTS




1 Insulation Shield and Blocking

NTS




2 Acoustically Lined Roof Curb Detail

NTS



3 Floor Mounted Unit Ventilator


NTS



TEMPERATURE CONTROLS SYMBOLS LIST

AI	ANALOG IN
AO	ANALOG OUT
COM	COMMUNICATIONS PORT
CS	AIRBORNE CONTAMINANT SENSOR
DI	DIGITAL IN
DM	DAMPER MOTOR
DO	DIGITAL OUT
EMCS	ENERGY MANAGEMENT CONTROL SYSTEM
F	FLOW (WATER/AIR)
FM	FLOW METER
FS	AIR FLOW SENSOR
FZ	FREEZE STAT
H	HUMIDITY SENSOR
HL	HIGH LIMIT
KWH	KILOWATT HOUR METER
LL	LOW LIMIT
MS	MANUAL SWITCH STOP / START
P	PRESSURE SENSOR
ΔP	DIFFERENTIAL PRESSURE
PS	POSITION SENSOR
S/S	STOP / START
SD	SMOKE DETECTOR
ST	STATUS
START	STARTER
T	ADJUSTABLE THERMOSTAT
TS	TEMPERATURE SENSOR
VFD	VARIABLE FREQUENCY DRIVE
WS	WATER SENSOR
%	PERCENT
ES	END SWITCH
BS	BOILER SWITCH

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17															
PACKAGED ROOFTOP UNIT (RTU) SCHEDULE																															
DWG LABEL	DESIGN MAKE: TRANE MODEL	SERVES	SIZE	SUPPLY AIR (CFM)	MIN. OA (CFM)	EAT (°F)	HEATING DATA		COOLING DATA						SUPPLY FAN		COMPRESSOR DATA		ELECTRICAL DATA			REFRIGERANT TYPE	OPER. WEIGHT (lbs)	NOTES							
							AMBIENT DB (°F)	HEATING TYPE	HEATING CAPACITY (MBH)	EDB (°F)	EWB (°F)	LWB (°F)	AMBIENT DB (°F)	TC (MBH)	SC (MBH)	ESP (IN. WG)	RPM	HP	TYPE	COMP. 1 (RLA)	COMP. 2 (RLA)				MCA	MOP	VOLT.	PH			
RTU-1	WHC120H3R0A	BAND REH F157 AND VOCAL F153, OFFICES F155, F155A, F155B	10 TON	3500	1600	39.4	9.1	6.9	HEAT PUMP	62.7	80.7	68.0	59.1	57.5	96.4	122.4	87.4	0.60	1392	2.75	SCROLL	17.6	16.0	49	60	208 V	3	R-410a	16.0	1617	1-4
NOTES: 1. PROVIDE LOW LEAK ECONOMIZER WITH MOTORIZED RELIEF, 2" MERV8. 2. PROVIDE FIELD OR FACTORY NEMA 3R DISCONNECT SWITCH. 3. PROVIDE TRANSFORMER AND POWERED GFCI SERVICE OUTLET (WIRED IN FRONT OF DISCONNECT SWITCH). 4. PROVIDE 24" ROOF CURB.																															



HOT WATER PRIMARY PUMP CONTROL

BUILDING HEATING PUMP SPEED CONTROL.

- CONTROL THE VARIABLE FREQUENCY DRIVES TO VARY THE POWER FREQUENCY TO THE BUILDING HEATING PUMPS P-7/P-8/P-8 AND P-4/P-5. THE GENERAL CONTROL SCHEME IS TO MINIMIZE PUMP POWER AND RPM WHILE KEEPING THE MOST DEMANDING ZONE SATISFIED.
- CONTROL THE DRIVE'S FREQUENCY USING THE COMBINED INPUT TO THE EMCS FROM THE PERCENTAGE OPEN POSITION OF ALL CONTROL VALVES MODULATING FLOW OF WATER TO THEIR RESPECTIVE LOADS. MAINTAIN A REAL TIME LOG OF THE PERCENTAGE OPEN POSITION OF ALL PRIMARY/ SECONDARY WATER CONTROL VALVES.
 - WHEN BOTH THE HEATING SYSTEM IS ENABLED AT THE OWS AND ON CALL FOR BUILDING HEAT AS DEFINED BY A QV WEIGHTED AVERAGE HEATING WATER VALVE POSITION OF AT LEAST 15% OPEN (ADJ. AT OWS), START A BUILDING HEATING VARIABLE SPEED PUMP (P-7/P-8/P-8 AND P-4/P-5) AND CONTROL AS FOLLOWS. ON INITIAL START OF PUMP, RAMP TO MINIMUM FREQUENCY OF 15HZ (ADJ.) ADJUST DURING COMMISSIONING TO MINIMUM VALUE RECOMMENDED BY MANUFACTURER.
 - WHEN ANY (ENABLED) CONTROL VALVE, OR THE AVERAGE OF ANY ADJUSTABLE NUMBER OF THE MOST DEMANDING VALVES, IS CALLING FOR MORE THAN 90% OPEN POSITION, RAMP THE VARIABLE SPEED DRIVE TO INCREASED AT THE RATE, (ADJUSTABLE AT THE OWS) OF +8HZ PER MINUTE.
 - WHEN NO (ENABLED) CONTROL VALVE IS CALLING FOR MORE THAN 90% OPEN POSITION, OR THE AVERAGE OF ANY ADJUSTABLE NUMBER OF THE MOST DEMANDING VALVES IS CALLING FOR NO MORE THAN 90% OPEN POSITION, RAMP THE VARIABLE FREQUENCY DRIVE TO DECREASED POWER FREQUENCY AT THE RATE (ADJUSTABLE AT THE OWS) OF -2HZ PER MINUTE.
 - IF ANY CONTROL VALVE REMAINS MOST OPEN AS THE CRITICAL ZONE AT MORE THAN DOUBLE THE FREQUENCY (ADJ.) OF THE NEXT MOST CRITICAL ZONE, INITIATE AN ALARM AT THE OWS, INCLUDING PROMPTS TO INVESTIGATE THE PROBLEM BY REBALANCING, ADJUSTING SETPOINTS, ETC.. ALLOW FOR ANY SUCH ZONES TO BE DISABLED FROM THE CALCULATIONS RAMPING THE DRIVE UNTIL THE PROBLEM IS CORRECTED (BUT ENSURE THAT IT STILL IS ENABLED TO OPEN ON CALL FOR HEAT).
 - MEASURE THE LOOP FLOWRATE VIA DIFFERENTIAL PRESSURE SENSORS PLACED 2/3 OUT IN SYSTEM.

- PROVIDE MANUAL OVERRIDES AT THE DRIVES AS REQUIRED TO PERMIT TEMPORARY MANUAL ADJUSTMENT OF SUPPLY WATER FLOW. IF THIS OCCURS, THE CONTROL PANEL ALARM SYSTEM SHALL INITIATE A PROPERLY ANNUNCIATED ALARM CONDITION.


- THE EMCS SHALL HAVE AUTOMATIC, ADJUSTABLE, LEAD LAG CAPABILITY TO PERMIT SWITCHING BETWEEN PUMPS. IF THE LEAD PUMP CANNOT MAINTAIN THE REQUIRED FLOW, THE EMCS SHALL SWITCH LEAD AND LAG PUMPS AND CAUSE AN ALARM TO BE OUTPUT TO THE OWS.

BOILER RETURN WATER TEMPERATURE CONTROL:

- MODULATE THE 3-WAY MIXING VALVE TO MAINTAIN MINIMUM 120 DEG. F RETURN WATER TEMPERATURE TO PROVIDE PROTECTION AGAINST THERMAL SHOCK FOR THE BOILERS

1 Hot Water Pump Control

NTS



EXHAUST/RELIEF FAN - VARIABLE SPEED - SEQUENCE OF OPERATIONS:

- OCCUPIED MODE:
 - OPEN THE FAN DAMPER. PROVIDE A DIFFERENTIAL PRESSURE SENSOR MEASURING THE DIFFERENCE BETWEEN THE AVERAGE SPACE PRESSURE IN SPACES SERVED BY THE ASSOCIATED VENTILATION EQUIPMENT AND THE ADJACENT CORRIDOR AIR PRESSURE. MODULATE THE EXHAUST/RELIEF FAN VSD AS REQUIRED TO MAINTAIN THE OCCUPIED SPACES AT A SLIGHT POSITIVE PRESSURE OF +0.01 TO +0.05"WG (ADJUSTABLE) RELATED TO THE ADJACENT CORRIDOR. THE EXHAUST/RELIEF FAN SPEED SHALL NOT EXCEED THE MAXIMUM SPEED DETERMINED BY THE AIR BALANCER TO DELIVER THE ECONOMIZER (MAXIMUM) CFM AS SCHEDULED FOR THE RELIEF/EXHAUST FAN.
- UNOCCUPIED MODE:
 - THE FAN SHALL BE OFF AND AUTOMATIC AIR DAMPER SHALL BE CLOSED.
- WARM-UP MODE:
 - THE FAN SHALL BE OFF AND AUTOMATIC AIR DAMPER SHALL BE CLOSED.
- SAFETIES:
 - UPON A FAILURE OF THE FAN, AS SENSED BY A CURRENT SENSING STATUS SWITCH, AN ALARM SHALL BE ACTIVATED.

2 Variable Speed Exhaust/Relief Fan

NTS

UNIT VENTILATOR (UV) SCHEDULE

EQUIP NO.	LOCATION	MODEL NO.	SA CFM	MIN. OA	HEATING DATA				HW COIL		ESP (IN. WG)	RPM	MOTOR QTY	MOTOR SIZE (HP)	ELECTRICAL				NOTES	
					NO. ROW	EAT (°F)	LAT (°F)	CAP (MBH)	GPM	(FT. HD)					V/PH	FLA	MCA	MOP		
UV-A108	ART A108	HUVC150	1150	490	2	42.2	113.6	85.2	4.3	2.36	0.00	870	1	1	120V/1Ø	12.0	15.0	25	1.3-8.10	
UV-A110	ART A110	HUVC200	1730	570	2	47.0	107.8	108.9	5.5	3.66	0.00	875	1	1	120V/1Ø	12.0	15.0	25	1.3-8.10	
UV-B115	CLASS B115	VUVE125	990	400	2	41.8	112.6	75.9	3.8	2.25	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-B117	CLASS B117	VUVE125	990	400	2	41.8	112.6	75.9	3.8	2.25	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-B119	GEN SCI B119	HUVC200	1730	520	2	48.9	108.4	106.5	5.3	3.52	0.00	875	1	1	120V/1Ø	12.0	15.0	25	1.3-8.10	
UV-B121	GEN SCI B121	HUVC200	1730	520	2	48.9	108.4	106.5	5.3	3.52	0.00	875	1	1	120V/1Ø	12.0	15.0	25	1.3-8.10	
UV-B124	GEN SCI B124	HUVC200	1730	560	2	47.4	107.8	108.9	5.5	3.66	0.00	875	1	1	120V/1Ø	12.0	15.0	25	1.3-8.10	
UV-C130	CLASS C130	VUVE125	990	400	2	41.8	112.6	75.9	3.8	2.25	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D132	CLASS D132	VUVE150	1140	510	2	41.4	115.0	91.0	4.6	3.94	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D134	CLASS D134	VUVE150	1140	440	2	45.1	116.4	88.1	4.4	3.76	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D135	CLASS D135	VUVE125	990	410	2	41.2	112.3	76.3	3.8	2.27	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D136	CLASS D136	VUVE125	990	420	2	40.5	112.0	76.8	3.8	2.3	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D137	CLASS D137	VUVE125	990	410	2	41.2	112.3	76.3	3.8	2.27	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D138	CLASS D138	VUVE125	990	420	2	40.5	112.0	76.8	3.8	2.3	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D139	CLASS D139	VUVE125	990	420	2	40.5	112.0	76.8	3.8	2.3	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
UV-D140	CLASS D140	VUVE150	1140	440	2	45.1	116.4	88.1	4.4	3.76	0.00	1120	2	0.25	120V/1Ø	7.0	9.0	15	1.2-4-7.9.10	
NOTES:																				
1. DESIGN BASIS: TRANE			5.	HOT WATER COIL CONDITIONS: EWT=180°F, LWT=120°F										9.		UNIT 21-1/4" DEEP W/CLOSED PIPE TUNNEL.				
2. FLOOR MOUNTED UNIT			6.	ADJUST UV FAN SPEED TO PROVIDE SCHEDULED SUPPLY AIR QUANTITY.										10.		NEMA 1 DISCONNECT SWITCH				
3. CEILING MOUNTED UNIT			7.	VERIFY PIPE AND ELECTRICAL LEFT/RIGHT HAND CONNECTIONS PRIOR TO ORDERING.																
4. PROVIDE 1" MERV13 FILTER.			8.	PROVIDE RETURN AIR BOTTOM INLET GRILLE.																

FAN (PRE-) SCHEDULE

DWG LABEL	SERVES	TYPE	MODEL NO.	FAN DATA						ELECTRICAL					NOTES
				MIN CFM	MAX CFM	SP (IN.WG)	SONES	RPM	TIP SPEED (FPM)	DRIVE	BHP	HP	FLA	V/PH	
PRE-D132	CLASS D132	DOWNBLAST CENTRIFUGAL	165C17D	580	1210	0.25	3.8	613	2650	DIRECT (EC)	0.08	1/8	1 A	120 V/1ø	1-4
PRE-C130	CLASS C130	DOWNBLAST CENTRIFUGAL	150C17D	400	990	0.25	3.7	671	2640	DIRECT (EC)	0.065	1/8	1 A	120 V/1ø	1-4
NOTES:															
1. DESIGN BASIS: LOREN COOK															
2. PROVIDE 14" CURB.															
3. PROVIDE NEMA 1 DISCONNECT.															
4. SONES, TIP SPEED AND BHP ARE MAXIMUM ALLOWABLE. CFM, SP AND OPENING ARE MINIMUM ALLOWABLE.															

REHEAT COIL (RHC) SCHEDULE

DWG LABEL	SERVES	LOCATION	EQUIP SERVED	MODEL NO.	DUCT SIZE	FACE AREA	FACE VELOCITY	TUBE WALL THICKNESS	NO ROWS	AIRFLOW	AIRSIDE DATA				HYDRONIC DATA				NOTES
											APD (in-wg)	EAT (°F)	LAT (°F)	HEATING CAPACITY (MBH)	HW S (°F)	HWR (°F)	GPM	WPD (RH2O)	
RHC-1	VOCAL F153, OFFICES F155, F155A, F155B	OFFICE F155	RTU-1	D5WB	36x12	3.00 SF	583 FPM	0.020	1	1750 CFM	0.16	45.0	75.0	56.94	160	120	2.9	0.5	1-2
RHC-2	BAND REH F157	OFFICE F155B	RTU-1	D5WB	36x12	3.00 SF	583 FPM	0.020	1	1750 CFM	0.16	45.0	75.0	56.94	160	120	2.9	0.5	1-2
NOTES:																			
1. DESIGN MAKE: TRANE																			
2. COILS SHALL HAVE SAME SIDE CONNECTIONS.																			


VARIABLE FREQUENCY DRIVE (VFD) SCHEDULE

DWG LABEL	SERVES	DESIGN MAKE- ABB MODEL NO.	MOTOR HP	AMP.	MOTOR (KW)	VOLT.	FREQ. (Hz)	UL ENCLOSURE	NO. OF PULSES	CONSTRUCTION TYPE	NOTES
VFD-P-4	P-4	ACH550-PDR-012A-4	5	24.2	5.6	208	60	UL Type 12 - NEMA 12	6	PDR = Drive, Disconnect	1-2
VFD-P-5	P-5	ACH550-PDR-012A-4	5	24.2	5.6	208	60	UL Type 12 - NEMA 12	6	PDR = Drive, Disconnect	1-2
VFD-P-7	P-7	ACH550-PDR-012A-4	5	24.2	5.6	208	60	UL Type 12 - NEMA 12	6	PDR = Drive, Disconnect	1-2
VFD-P-8	P-8	ACH550-PDR-012A-4	5	24.2	5.6	208	60	UL Type 12 - NEMA 12	6	PDR = Drive, Disconnect	1-2
VFD-P-9	P-9	ACH550-PDR-012A-4	5	24.2	5.6	208	60	UL Type 12 - NEMA 12	6	PDR = Drive, Disconnect	1-2

NOTES:

1. BUILT IN 5% INPUT IMPEDANCE

2. OUTPUT CABLE (WHEN CABLE IS GREATER THAN 50 FT)



Keyed Notes cont'd.:

- 6 REMOVE POWER CIRCUITRY TO CEILING HUNG UNIT HEATER COMPLETE BACK TO SOURCE.
- 7 REMOVE SPECIAL OUTLET FOR KILN, SALVAGE, CLEAN AND STORE OUTLET FOR REINSTALLATION. REMOVE POWER CIRCUITRY COMPLETE BACK TO SOURCE.

Keyed Notes:

- 1 REMOVE LUMINAIRE(S) AND CIRCUITRY COMPLETE BACK TO SOURCE.
- 2 REMOVE WALL OR CEILING MOUNTED EMERGENCY LIGHT. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.
- 3 REMOVE LIGHT SWITCH(ES) CONTROLLING CORRIDOR LUMINAIRES. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT. PROVIDE BLANK COVER PLATE.
- 4 REMOVE, CLEAN AND STORE CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. TAG CIRCUITRY FOR RE-USE.
- 5 REMOVE ELECTRICAL DEVICES SHOWN. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX, DEVICE OR SWITCH OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.

Demolition General Notes cont'd

- G. ALL DEVICES THAT ARE SCHEDULED TO BE REMOVED, CLEANED, STORED AND RE-INSTALLED SHALL BE TESTED PRIOR TO REMOVAL. IF ANY DEVICES IS NOT IN WORKING ORDER, NOTIFY ENGINEER AND OWNER'S REPRESENTATIVE PRIOR TO REMOVAL.


Demolition General Notes

- A. ALL ELECTRICAL DEVICES INTERFERING WITH DEMOLITION WORK SHALL BE DISCONNECTED AND REMOVED, UNLESS OTHERWISE NOTED. EXISTING CIRCUIT WIRING SHALL BE REMOVED BACK TO SOURCE AND PANEL DIRECTORIES MODIFIED ACCORDINGLY.
- B. ANY DEVICE INTERFERING WITH DEMOLITION WORK NOT SHOWN ON THESE DRAWINGS SHALL NOT BE REMOVED WITHOUT WRITTEN AUTHORIZATION FROM THE OWNER'S REPRESENTATIVE OR THE ENGINEER.
- C. ALL ELECTRICAL DEMOLITION WORK SHALL BE PROPERLY COORDINATED WITH ALL OTHER TRADES.
- D. EC IS SOLELY RESPONSIBLE FOR THE SAFE HANDLING AND DISPOSAL OF ALL REMOVED LUMINAIRES AND BALLASTS THAT MAY CONTAIN PCBs (POLYCHLORINATED BIPHENYLS), IN ACCORDANCE WITH ALL APPLICABLE EPA, OSHA, FEDERAL, STATE, AND LOCAL CODES AND LAWS.
- E. EC IS SOLELY RESPONSIBLE FOR THE SAFE HANDLING AND DISPOSAL OF ALL REMOVED FLUORESCENT LIGHT TUBES THAT MAY CONTAIN MERCURY, IN ACCORDANCE WITH ALL APPLICABLE EPA, OSHA, FEDERAL, STATE, AND LOCAL CODES AND LAWS.
- F. AT ALL CORRIDORS WHERE NEW CEILINGS ARE BEING INSTALLED, DISCONNECT AND REMOVE DEVICES AS INDICATED, TAG EXISTING WIRING FOR REUSE.

General Notes

- A. COORDINATE ALL ELECTRICAL WORK AND POWER OUTAGES WITH OWNER AND OTHER TRADES PRIOR TO THE START OF CONSTRUCTION. NO POWER OUTAGES SHALL OCCUR WITHOUT OWNER'S PRIOR KNOWLEDGE AND CONSENT.
- B. REFER TO DRAWING G100 FOR STANDARD SYMBOLS AND ABBREVIATIONS.
- C. AT ALL CORRIDORS WHERE NEW CEILINGS ARE BEING INSTALLED, REINSTALL DEVICES ON NEW CEILINGS AS SHOWN ON NEW WORK DRAWINGS AND EXTEND/MODIFY EXISTING CIRCUITRY AS NECESSARY.
- D. CIRCUIT WIRING FOR ALL LIGHTING CIRCUITS SHALL BE IN 1/2" EMT CONDUIT (MIN) OR TYPE MC CABLE CONCEALED ABOVE CEILINGS AND IN WALLS (REFER TO SPECIFICATION SECTION 26 05 33 FOR LOCATIONS WHERE MC CABLE IS ACCEPTABLE). ALL CIRCUIT CONDUCTORS SHALL BE #12AWG COPPER (MIN) 90°C THIN THERMOPLASTIC INSULATION.
- E. CIRCUIT EXIT AND EMERGENCY LUMINAIRES TO UNSWITCHED HOT LEGS OF LIGHTING CIRCUIT OF THE AREA BEING SERVED BY OR ADJACENT TO THE LUMINAIRE. REFER TO PLANS AND DETAILS FOR MINIATURE INVERTER INFORMATION.
- F. PROPERLY IDENTIFY ALL CIRCUITS AT PANELS AND J-BOXES AND IN ACCORDANCE WITH PROJECT SPECIFICATIONS.
- G. PROVIDE ALL ADAPTERS, COUPLINGS AND ASSOCIATED FITTINGS REQUIRED FOR COMPLETE OPERATIONAL SYSTEM.
- H. WHEN INSTALLING NEW DEVICES IN EXISTING LOCATIONS, REUSE EXISTING CONDUIT/RACEWAY AND BACK BOXES IF IN GOOD CONDITION. EXTEND/INSTALL NEW CONDUIT/RACEWAY AS REQUIRED FOR PROPER MOUNTING OF DEVICE. CONCEAL ABOVE CEILINGS OR WITHIN WALLS WHERE POSSIBLE. REFER TO SPECIFICATION SECTION 26 05 33.
- I. COORDINATE ALL ELECTRICAL WORK WITH OTHER TRADES.
- J. TESTS OF ALL ELECTRICAL WORK SHALL BE PERFORMED IN THE PRESENCE OF THE ENGINEER OR ARCHITECT. AS EQUIPMENT IS INSTALLED AND AS SYSTEMS ARE COMPLETED. IN ADDITION AN ELECTRIC APPROVED CERTIFICATE SHALL BE ISSUED BY AN ELECTRICAL INSPECTION AGENCY.
- K. UNLESS NOTED ELSEWHERE ON THE CONTRACT DOCUMENTS, THE FOLLOWING LIST REPRESENTS THE TYPICAL MOUNTING HEIGHTS FOR THE DEVICES SHOWN:
 - 1. SWITCHES AND PANIC STATIONS.....48" (TO TOP)
 - 2. RECEPTACLES.....16"
 - 3. COMPUTER RECEPTACLES.....48" (TO TOP)
 - 4. WALL (W) TELEPHONE AND CALL SWITCHES.....48" (TO TOP)
 - 5. TELEPHONE OUTLETS (UNLABELED).....16"
 - 6. VOLUME CONTROLS.....48" (TO TOP)
 - 7. TELEVISION OUTLETS.....16"
 - 8. FIRE ALARM PULL STATIONS.....48" (TO TOP)
 - 9. FIRE ALARM AUDIO/VISUAL UNITS.....88" * (OR 6' BELOW CEILING, WHICHEVER IS LOWER)
 - 10. POWER PANELS.....72" (TO TOP)
 - 11. DISCONNECT SWITCHES.....60" (TO TOP)
 - 12. MOTOR STARTERS.....60" (TO TOP)

THE HEIGHTS INDICATED SHALL BE NOMINAL TO THE BOTTOM OF THE BOX UNLESS NOTED OTHERWISE. MAINTAIN HEIGHT CONSISTENCY BETWEEN NEW AND EXISTING DEVICES.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School


First Floor Demolition Plan - Area A

Drawn By: SAS Date: 10/28/2022 Drawing Number: EE100

Project No.: 279180-22004




1 First Floor Demolition Plan - Area B
1/8" = 1'-0"



2 First Floor Demolition Plan - Area E
1/8" = 1'-0"


- Keyed Notes:**
- 1 REMOVE LUMINAIRE(S) AND CIRCUITRY COMPLETE BACK TO SOURCE.
 - 2 REMOVE WALL OR CEILING MOUNTED EMERGENCY LIGHT. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.
 - 3 REMOVE LIGHT SWITCH(IES) CONTROLLING CORRIDOR LUMINAIRES. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT. PROVIDE BLANK COVER PLATE.
 - 4 REMOVE, CLEAN AND STORE CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. TAG CIRCUITRY FOR RE-USE.
 - 5 REMOVE ELECTRICAL DEVICES SHOWN. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX. DEVICE OR SWITCH OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.

- General Notes:**
- A. REFER TO DRAWING EE100 FOR GENERAL NOTES



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Areas B and E

Drawn By: SAS	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EE101	




2 First Floor Demolition Plan - Area D
1/8" = 1'-0"

1 First Floor Demolition Plan - Area C
1/8" = 1'-0"

- Keyed Notes:**
- 1 REMOVE LUMINAIRE(S) AND CIRCUITRY COMPLETE BACK TO SOURCE.
 - 2 REMOVE WALL OR CEILING MOUNTED EMERGENCY LIGHT. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.
 - 3 REMOVE LIGHT SWITCH(IES) CONTROLLING CORRIDOR LUMINAIRES. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT. PROVIDE BLANK COVER PLATE.
 - 4 REMOVE, CLEAN AND STORE CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. TAG CIRCUITRY FOR RE-USE.
 - 5 REMOVE ELECTRICAL DEVICES SHOWN. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX, DEVICE OR SWITCH OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.


General Notes:

A. REFER TO DRAWING EE100 FOR GENERAL NOTES



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Areas C and D

Drawn By: SAS	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EE102	




1 First Floor Demolition Plan - Area F
1/8" = 1'-0"

- Keyed Notes:**
- 1 REMOVE LUMINAIRE(S) AND CIRCUITRY COMPLETE BACK TO SOURCE.
 - 2 REMOVE WALL OR CEILING MOUNTED EMERGENCY LIGHT. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.
 - 3 REMOVE LIGHT SWITCH(IES) CONTROLLING CORRIDOR LUMINAIRES. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT. PROVIDE BLANK COVER PLATE.
 - 4 REMOVE, CLEAN AND STORE CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. TAG CIRCUITRY FOR RE-USE.
 - 5 REMOVE AND REINSTALL, MODIFY, EXTEND, TEMPORARILY SUPPORT, AND PROTECT EXISTING ELECTRICAL RACEWAYS AND CABLES TO ACCOMPLISH STRUCTURAL WORK (VIF), IN AREA SHOWN. REFER TO STRUCTURAL DRAWINGS FOR FURTHER INFORMATION.


General Notes:

A. REFER TO DRAWING EE100 FOR GENERAL NOTES



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

First Floor Demolition Plan - Area F

Drawn By: SAS	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EE103	




1 Second Floor Demolition Plan - Area B
1/8" = 1'-0"



2 Second Floor Demolition Plan - Area D
1/8" = 1'-0"


- Keyed Notes:**
- 1 REMOVE LUMINAIRE(S) AND CIRCUITRY COMPLETE BACK TO SOURCE..
 - 2 REMOVE WALL OR CEILING MOUNTED EMERGENCY LIGHT. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.
 - 3 REMOVE LIGHT SWITCH(IES) CONTROLLING CORRIDOR LUMINAIRES. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX OR DEVICE OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT. PROVIDE BLANK COVER PLATE.
 - 4 REMOVE, CLEAN AND STORE CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. TAG CIRCUITRY FOR RE-USE.

- General Notes:**
- A. REFER TO DRAWING EE100 FOR GENERAL NOTES



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:



complex world

CLEAR SOLUTIONS

Tetra Tech Engineers, Architects
& Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Second Floor Demolition Plan - Areas
B and D


Drawn By: SAS	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EE104	



1 First Floor Lighting, Power & Communications Plan - Area A
1/8" = 1'-0"

- Keyed Notes:**
- 1 CONNECT LUMINAIRES TO EXISTING CIRCUIT BREAKER PREVIOUSLY SERVING THE AREA USING (2) #12, (1) #12 G. IN 1/2" CONDUIT. LUMINAIRES TO BE CONTROLLED BY OCCUPANCY SENSORS AND DIRECT DIGITAL CONTROL SYSTEM.
 - 2 PROVIDE WALL MOUNTED MINIATURE INVERTER BASED ON MODEL VESTA MAX MODEL VST-MAX-375W-UNV-4-OK. MOUNT AT 72" AFF. COORDINATE FINAL LOCATION WITH OWNER. CONNECT EVERY OTHER EMERGENCY LUMINAIRE PER CORRIDOR TO ADJACENT INVERTER TO AVOID TOTAL OUTAGE UPON BATTERY FAILURE. REFER TO WIRING DIAGRAM ON DRAWING BES00.
 - 3 REINSTALL STORED CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. CENTER DEVICES IN CEILING GRID CLOSEST TO EXISTING LOCATION. MODIFY/EXTEND CIRCUITRY AS NECESSARY.

- General Notes:**
- A. REFER TO DRAWING EE100 FOR GENERAL NOTES.
 - B. REFER TO DRAWING EE600 FOR LUMINAIRE SCHEDULE.
 - C. SECURE ALL EXISTING UNSUPPORTED CABLES AND RACEWAYS ABOVE CEILINGS IN CORRIDORS USING J HOOKS, CABLETRAYS OR APPROVED HANGERS AND SUPPORTS.
 - D. INVERTER SYSTEM EMERGENCY OUTPUT CIRCUITS SHALL BE INSTALLED IN DEDICATED CONDUIT SYSTEMS AND NOT SHARED WITH OTHER ELECTRICAL CIRCUITS AS DESCRIBED IN NEC 700-9(b).
 - E. TEST FIRE ALARM SYSTEM BEFORE REMOVAL AND AFTER REINSTALLATION OF FIRE ALARM SYSTEM DEVICES. REPORT ANY SYSTEM DEFICIENCIES PRIOR TO REMOVAL OF ANY DEVICES.
 - F. LIGHTING CONTROL SEQUENCES:
LOBBY/VESTIBULES/CORRIDORS:
PERSON ENTERS THE AREA, LUMINAIRES TURN ON TO 100% OUTPUT AUTOMATICALLY BY OCCUPANCY SENSOR.
PERSON EXITS THE AREA, LUMINAIRES DIM TO 50% OUTPUT (MAINTAINING EGRESS LEVEL ILLUMINATION). MANUAL CONTROL BY BUILDING MANAGEMENT SYSTEM.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

First Floor Lighting, Power & Communications Plan - Area A

Drawn By: SAS/CR	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EE130	




1 First Floor Lighting, Power & Communications Plan - Area B
1/8" = 1'-0"



2 First Floor Lighting, Power & Communications Plan - Area E
1/8" = 1'-0"


- Keyed Notes:**
- 1 CONNECT LUMINAIRES TO EXISTING CIRCUIT BREAKER PREVIOUSLY SERVING THE AREA USING (2#12, 1#12 G. IN 1/2" CONDUIT. LUMINAIRES TO BE CONTROLLED BY OCCUPANCY SENSORS AND DIRECT DIGITAL CONTROL SYSTEM.
 - 2 PROVIDE WALL MOUNTED MINIATURE INVERTER BASED ON MODEL VESTA MAX MODEL VST-MAX-375W-UNV-4-OK. MOUNT AT 72" AFF. COORDINATE FINAL LOCATION WITH OWNER. CONNECT EVERY OTHER EMERGENCY LUMINAIRE PER CORRIDOR TO ADJACENT INVERTER TO AVOID TOTAL OUTAGE UPON BATTERY FAILURE. REFER TO WIRING DIAGRAM ON DRAWING BES00.
 - 3 REINSTALL STORED CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. CENTER DEVICES IN CEILING GRID CLOSEST TO EXISTING LOCATION. MODIFY/EXTEND CIRCUITRY AS NECESSARY.
 - 4 DISCONNECT POWER CIRCUITRY TO EXISTING SHP PUMP. CONNECT POWER CIRCUITRY TO VFD, MODIFY/EXTEND CIRCUITRY AS NECESSARY.

- General Notes:**
- A. REFER TO DRAWING EE100 FOR GENERAL NOTES.
 - B. REFER TO DRAWING EE600 FOR LUMINAIRE SCHEDULE.
 - C. SECURE ALL EXISTING UNSUPPORTED CABLES AND RACEWAYS ABOVE CEILINGS IN CORRIDORS USING J HOOKS, CABLE TRAYS OR APPROVED HANGERS AND SUPPORTS.
 - D. INVERTER SYSTEM EMERGENCY OUTPUT CIRCUITS SHALL BE INSTALLED IN DEDICATED CONDUIT SYSTEMS AND NOT SHARED WITH OTHER ELECTRICAL CIRCUITS AS DESCRIBED IN NEC 700-9(B).
 - E. TEST FIRE ALARM SYSTEM BEFORE REMOVAL AND AFTER REINSTALLATION OF FIRE ALARM SYSTEM DEVICES. REPORT ANY SYSTEM DEFICIENCIES PRIOR TO REMOVAL OF ANY DEVICES.
 - F. LIGHTING CONTROL SEQUENCES:
LOBBY/VESTIBULES/CORRIDORS:
PERSON ENTERS THE AREA, LUMINAIRES TURN ON TO 100% OUTPUT AUTOMATICALLY BY OCCUPANCY SENSOR.
PERSON EXITS THE AREA, LUMINAIRES DIM TO 50% OUTPUT (MAINTAINING EGRESS LEVEL ILLUMINATION). MANUAL CONTROL BY BUILDING MANAGEMENT SYSTEM.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Lighting, Power & Communications Plan - Areas B and E

Drawn By: SAS/CR	Date: 10/28/2022	Drawing Number: EE131
Project No.: 279180-22004		




2 First Floor Lighting, Power & Communications Plan - Area D
1/8" = 1'-0"



1 First Floor Lighting, Power & Communications Plan - Area C
1/8" = 1'-0"


- Keyed Notes:**
- CONNECT LUMINAIRES TO EXISTING CIRCUIT BREAKER PREVIOUSLY SERVING THE AREA USING (2#12, 1#12 G. IN 1/2" CONDUIT. LUMINAIRES TO BE CONTROLLED BY OCCUPANCY SENSORS AND DIRECT DIGITAL CONTROL SYSTEM.
 - PROVIDE WALL MOUNTED MINIATURE INVERTER BASED ON MODEL VESTA MAX MODEL VST-MAX-375W-UNV-4-OK. MOUNT AT 72" AFF. COORDINATE FINAL LOCATION WITH OWNER. CONNECT EVERY OTHER EMERGENCY LUMINAIRE PER CORRIDOR TO ADJACENT INVERTER TO AVOID TOTAL OUTAGE UPON BATTERY FAILURE. REFER TO WIRING DIAGRAM ON DRAWING BES00.
 - RE-INSTALL STORED CEILING MOUNTED DEVICES IN CEILING GRIDS THAT ARE BEING REPLACED. CENTER DEVICES IN CEILING GRID CLOSEST TO EXISTING LOCATION. MODIFY/EXTEND CIRCUITRY AS NECESSARY.
 - FEED PANEL PPD1 FROM MDP1. PROVIDE 100A3P CIRCUIT BREAKER IN AVAILABLE SPACE IN MDP1. CONNECT USING (4#2, 1#8 G. IN 1 1/4" CONDUIT. NEW BREAKER TO BE UL LISTED FOR USE IN PANEL AND MEET OR EXCEED AIC RATING OF EXISTING PANEL.

- General Notes:**
- A. REFER TO DRAWING EE100 FOR GENERAL NOTES.
B. REFER TO DRAWING EE800 FOR LUMINAIRE SCHEDULE.
C. SECURE ALL EXISTING UNSUPPORTED CABLES AND RACEWAYS ABOVE CEILINGS IN CORRIDORS USING J HOOKS, CABLETRAYS OR APPROVED HANGERS AND SUPPORTS.
D. INVERTER SYSTEM EMERGENCY OUTPUT CIRCUITS SHALL BE INSTALLED IN DEDICATED CONDUIT SYSTEMS AND NOT SHARED WITH OTHER ELECTRICAL CIRCUITS AS DESCRIBED IN NEC 700-9(B).
E. TEST FIRE ALARM SYSTEM BEFORE REMOVAL AND AFTER REINSTALLATION OF FIRE ALARM SYSTEM DEVICES. REPORT ANY SYSTEM DEFICIENCIES PRIOR TO REMOVAL OF ANY DEVICES.
F. LIGHTING CONTROL SEQUENCES:
LOBBY/VESTIBULES/CORRIDORS:
PERSON ENTERS THE AREA, LUMINAIRES TURN ON TO 100% OUTPUT AUTOMATICALLY BY OCCUPANCY SENSOR.
PERSON EXITS THE AREA, LUMINAIRES DIM TO 50% OUTPUT (MAINTAINING EGRESS LEVEL ILLUMINATION). MANUAL CONTROL BY BUILDING MANAGEMENT SYSTEM.



S.E.D. Control No. 13-02-00-01-0-004-023


Rev. No.:	Date:	Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

First Floor Lighting, Power & Communications Plan - Areas C and D

Drawn By: SAS/CR	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EE132




1 First Floor Lighting, Power & Communications Plan - Area F
1/8" = 1'-0"

- Keyed Notes:**
- CONNECT LUMINAIRES TO EXISTING CIRCUIT BREAKER PREVIOUSLY SERVING THE AREA USING (2#12, 1#12 G. IN 1/2" CONDUIT. LUMINAIRES TO BE CONTROLLED BY OCCUPANCY SENSORS AND DIRECT DIGITAL CONTROL SYSTEM.
 - PROVIDE WALL MOUNTED MINIATURE INVERTER BASED ON MODEL VESTA MAX MODEL VST-MAX-375W-UNV-40K. MOUNT AT 72" AFF. COORDINATE FINAL LOCATION WITH OWNER. CONNECT EVERY OTHER EMERGENCY LUMINAIRE PER CORRIDOR TO ADJACENT INVERTER TO AVOID TOTAL OUTAGE UPON BATTERY FAILURE. REFER TO WIRING DIAGRAM ON DRAWING BES00.
 - RE-INSTALL STORED CEILING MOUNTED DEVICES IN CEILINGS THAT ARE BEING REPLACED. CENTER DEVICES IN CEILING GRID CLOSEST TO EXISTING LOCATION. MODIFY/EXTEND CIRCUITRY AS NECESSARY.
 - PROVIDE DUCT SMOKE DETECTOR AND FAN SHUTDOWN FOR SUPPLY FAN IN RTU-1 ON ROOF. CONNECT TO EXISTING FIRE ALARM SYSTEM.
- General Notes:**
- A. REFER TO DRAWING EE100 FOR GENERAL NOTES.
B. REFER TO DRAWING EE600 FOR LUMINAIRE SCHEDULE.
C. SECURE ALL EXISTING UNSUPPORTED CABLES AND RACEWAYS ABOVE CEILINGS IN CORRIDORS USING J HOOKS, CABLETRAYS OR APPROVED HANGERS AND SUPPORTS.
D. INVERTER SYSTEM EMERGENCY OUTPUT CIRCUITS SHALL BE INSTALLED IN DEDICATED CONDUIT SYSTEMS AND NOT SHARED WITH OTHER ELECTRICAL CIRCUITS AS DESCRIBED IN NEC 700-9(B).
E. TEST FIRE ALARM SYSTEM BEFORE REMOVAL AND AFTER REINSTALLATION OF FIRE ALARM SYSTEM DEVICES. REPORT ANY SYSTEM DEFICIENCIES PRIOR TO REMOVAL OF ANY DEVICES.
F. LIGHTING CONTROL SEQUENCES:
LOBBY/VESTIBULES/CORRIDORS:
PERSON ENTERS THE AREA, LUMINAIRES TURN ON TO 100% OUTPUT AUTOMATICALLY BY OCCUPANCY SENSOR.
PERSON EXITS THE AREA, LUMINAIRES DIM TO 50% OUTPUT (MAINTAINING EGRESS LEVEL ILLUMINATION). MANUAL CONTROL BY BUILDING MANAGEMENT SYSTEM.

Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description


Beacon City School District
Beacon, New York

complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET

TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School


First Floor Lighting, Power & Communications Plan - Area F

Drawn By: SAS/CR	Date: 10/28/2022	Drawing Number: EE133
Project No.: 279180-22004		



- | | | | |
|---|-------------------------------------|---------------------|-------------------------------------|
| N | Drawn By:
SAS/CR | Date:
10/28/2022 | Drawing Number:

EE134 |
| | Project No.:
279180-22004 | | |




Keyed Notes:

- 1 PROVIDE 60A3P CIRCUIT BREAKER IN AVAILABLE SPACE IN PANEL MP4 IN ELEC/STOR F152. CONNECT USING (3) #6, (1) #10 G. IN 3/4" CONDUIT. NEW BREAKER TO BE UL LISTED FOR USE IN PANEL AND MEET OR EXCEED AIC RATING OF EXISTING PANEL.
- 2 PROVIDE FAN SHUT DOWN RELAY AND CONNECT TO EXISTING FIRE ALARM SYSTEM. WIRE RELAY INTO FAN CONTROL CIRCUIT.
- 3 REMOVE POWER CIRCUITRY FOR EXHAUST FAN COMPLETE BACK TO SOURCE. LABEL ANY UNUSED CIRCUIT BREAKERS AS "SPARE".
- 4 REFER TO DRAWING EE600 FOR PANELBOARD SCHEDULE, CIRCUIT BREAKER AND WIRING SIZES.
- 5 PROVIDE RETURN AIR DUCT SMOKE DETECTOR AND FAN SHUT DOWN RELAY AND CONNECT TO EXISTING FIRE ALARM SYSTEM. WIRE RELAY INTO FAN CONTROL CIRCUIT.


General Notes:

- A. REFER TO DRAWING EE100 FOR GENERAL NOTES



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.:	Date:	Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Roof Power Plan - Areas C, D, E and F

Drawn By: SAS	Date: 10/28/2022	Drawing Number: EE160
Project No.: 279180-22004		



Keyed Notes:

1 PROVIDE ULTRA THIN LINEAR WASHER/GRAZER TO EDGE SIDE LIGHT DISPLAY CABINET BASED ON MODEL KELVIX Z3-48W-35K-1530-CP-DS 3. CONNECT TO LIGHTING CIRCUIT PREVIOUSLY SERVING THE AREA. LOCATE TRANSFORMER IN CABINTRY OF DISPLAY CASE.

2 MOUNT 7" AND 7"EM 9'-0" AFF TO BOTTOM OF LUMINAIRE.

General Notes:

A. REFER TO DRAWING EE100 FOR GENERAL NOTES.

B. REFER TO DRAWING EE600 FOR LUMINAIRE SCHEDULE.

C. INVERTER SYSTEM EMERGENCY OUTPUT CIRCUITS SHALL BE INSTALLED IN DEDICATED CONDUIT SYSTEMS AND NOT SHARED WITH OTHER ELECTRICAL CIRCUITS AS DESCRIBED IN NEC 700-9(B).

D. LIGHTING CONTROL SEQUENCES:

CLASSROOMS:

(2) ZONE. TEACHING WALL AND GENERAL CLASSROOM EACH OPERATED WITH A (4) BUTTON LOW VOLTAGE LIGHTING CONTROL. BUTTON CAPABLE OF ON/OFF, 50% AND 100% MAY BE MANUALLY ADJUSTED BY EACH LOW VOLTAGE LIGHTING CONTROL PER ZONE. IF LUMINAIRES ARE LEFT ON AND CLASSROOM IS UNOCCUPIED LUMINAIRES WILL TURN OFF WITHIN 15 MINUTES. ONCE ROOM BECOMES OCCUPIED AGAIN LUMINAIRES WILL TURN ON TO LAST LEVEL OR LAST LEVEL SELECTED. DAYLIGHT RESPONSIVE CONTROL WILL DIM ROW OF LUMINAIRES CLOSEST TO WINDOW TO PRESET SET POINT OF ROOM TO MAINTAIN UNIFORMITY OF ILLUMINATION.

OFFICES:

PERSON ENTERS THE ROOM AND LUMINAIRES TURN ON TO 50% OUTPUT BY OCCUPANCY SENSOR. WHEN PERSON EXITS THE ROOM THE OCCUPANCY SENSOR WILL TURN OFF THE LUMINAIRES AFTER 15 MINUTES. LOW VOLTAGE LIGHTING CONTROL. BUTTON CAPABLE OF ON/OFF, 50% AND 100% MAYBE BE MANUALLY ADJUSTED BY BUTTON.


STORAGE:

PERSON ENTERS THE ROOM AND TURNS LUMINAIRES ON TO 100% OUTPUT. WHEN PERSON EXITS THE ROOM THE OCCUPANCY SENSOR WILL TURN OFF THE LUMINAIRES AFTER 15 MINUTES. LOW VOLTAGE LIGHTING CONTROL.

Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023


Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET


 **TETRA TECH**
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Enlarged Lighting Plans - Areas A and B

Drawn By: SAS/CR	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EE400




2 Enlarged First Floor Power & Communications Plan - Area B
1/4" = 1'-0"

1 Enlarged First Floor Power & Communications Plan - Area A
1/4" = 1'-0"


- Keyed Notes:**
- 1 PROVIDE DUPLEX RECEPTACLE IN LAB BENCH PEDESTAL TABLE BOX (2-GANG) SIMILAR TO LEGRAND LBP2.
 - 2 FEED PANEL PPA1 FROM MDP2 IN ELEC 111. PROVIDE 100A3P CIRCUIT BREAKER IN AVAILABLE SPACE IN MDP2. CONNECT USING (4) #2, (1) #8 G. IN 1 1/4" CONDUIT. NEW BREAKER TO BE UL LISTED FOR USE IN PANEL AND MEET OR EXCEED AIC RATING OF EXISTING PANEL.
 - 3 FEED PANEL PPB1 FROM MDP2 IN ELEC 111. PROVIDE 100A3P CIRCUIT BREAKER IN AVAILABLE SPACE IN MDP2. CONNECT USING (4) #2, (1) #8 G. IN 1 1/4" CONDUIT. NEW BREAKER TO BE UL LISTED FOR USE IN PANEL AND MEET OR EXCEED AIC RATING OF EXISTING PANEL.
 - 4 REINSTALL STORED SPECIAL OUTLET FOR KILN. CONNECT TO PANEL PPA1. SEE DRAWING EE000 FOR PANELBOARD SCHEDULE, CIRCUIT BREAKER AND WIRING SIZE.

- General Notes:**
- A. REFER TO DRAWING EE-100 FOR GENERAL NOTES.
 - B. FIRE ALARM DEVICES ARE TO BE WIRED TO EXISTING NOTIFICATION CIRCUITS.
 - C. PA SYSTEM SPEAKERS ARE TO BE COMPATIBLE AND WIRED TO EXISTING PA SYSTEM.
 - D. CLOCKS ARE TO BE COMPATIBLE WITH EXISTING CLOCK SYSTEM.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET



Beacon City School District
Beacon, New York


Reconstruction to:
Rombout Middle School

Enlarged Power & Communications
Plans - Areas A and B


Drawn By: SAS	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EE401	




Project No.:	EE500
279180-22004	




6 Fire Alarm System Wiring Diagram
NTS




7 Data Outlet
NTS




8 Daylight Responsive Controls Wiring Diagram
NTS




1 Typical Mounting Heights
NTS




4 Cord Reel Mounting Detail
NTS



2 Conduit/Backbox Installation Detail
NTS



5 Data Distribution Riser Diagram
NTS



3 Conduit/Backbox Installation Detail
NTS

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.







TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Details

Drawn By: SAS Date: 10/28/2022 Drawing Number: 279180-22004
Project No.: EE501

LUMINAIRE SCHEDULE							
TYPE	SYMBOL	DESCRIPTION	LAMPS		MANUFACTURERS (OR EQUAL)		
			WATTAGE	LUMENS	TYPE	NAME	MODEL OR SERIES
1 **		1' x 4' TROFFER (RECESSED IN GRID)	12.2	1482	LED	SIGNIFY (DAY-BRITE)	1FPZ15L835-4-DS-UNV-DIM
1 ** EM		SAME AS TYPE 1 - CONNECTED TO EMERGENCY MINIATURE INVERTER	12.2	1482	LED	SIGNIFY (DAY-BRITE)	1FPZ15L835-4-DS-UNV-DIM
2		1' x 4' TROFFER (RECESSED IN GRID)	24.6	2972	LED	SIGNIFY (DAY-BRITE)	1FPZ30L835-4-DS-UNV-DIM
2 EM		SAME AS TYPE 2 - CONNECTED TO EMERGENCY MINIATURE INVERTER	24.6	2972	LED	SIGNIFY (DAY-BRITE)	1FPZ30L835-4-DS-UNV-DIM
3		1' x 4' TROFFER (RECESSED IN GRID)	31.3	3775	LED	SIGNIFY (DAY-BRITE)	1FPZ38L835-4-DS-UNV-DIM
3 EM		SAME AS TYPE 3 - CONNECTED TO EMERGENCY MINIATURE INVERTER	31.3	3775	LED	SIGNIFY (DAY-BRITE)	1FPZ38L835-4-DS-UNV-DIM
4 **		2' x 2' TROFFER (RECESSED IN GRID)	15.7	1918	LED	SIGNIFY (DAY-BRITE)	2FPZ20L835-2-DS-UNV-DIM
4 ** EM		SAME AS TYPE 4 - CONNECTED TO EMERGENCY MINIATURE INVERTER	15.7	1918	LED	SIGNIFY (DAY-BRITE)	2FPZ20L835-2-DS-UNV-DIM
5		2' x 2' TROFFER (RECESSED IN GRID)	23.4	2911	LED	SIGNIFY (DAY-BRITE)	2FPZ30L835-2-DS-UNV-DIM
5 EM		SAME AS TYPE 5 - CONNECTED TO EMERGENCY MINIATURE INVERTER	23.4	2911	LED	SIGNIFY (DAY-BRITE)	2FPZ30L835-2-DS-UNV-DIM
6		2' x 2' TROFFER (RECESSED IN GRID)	29.8	3856	LED	SIGNIFY (DAY-BRITE)	2FPZ38L835-2-DS-UNV-DIM
6 EM		SAME AS TYPE 6 - CONNECTED TO EMERGENCY MINIATURE INVERTER	29.8	3856	LED	SIGNIFY (DAY-BRITE)	2FPZ38L835-2-DS-UNV-DIM
7*		2' x 2' TROFFER (RECESSED IN GRID)	35.7	4403	LED	SIGNIFY (DAY-BRITE)	2FPZ45L835-2-DS-UNV-DIM
7* EM		SAME AS TYPE 7 - CONNECTED TO EMERGENCY MINIATURE INVERTER	35.7	4403	LED	SIGNIFY (DAY-BRITE)	2FPZ45L835-2-DS-UNV-DIM
8		4" ROUND DOWNLIGHT	8.8	868	LED	SIGNIFY (LEDALITE)	L4R10935VB / L4RDW
8 ** EM		SAME AS TYPE 8 - CONNECTED TO EMERGENCY MINIATURE INVERTER	8.8	868	LED	SIGNIFY (LEDALITE)	L4R10935VB / L4RDW
9 **		4" SQUARE DOWNLIGHT	8.8	868	LED	SIGNIFY (LEDALITE)	L4R10935VB / L4RDW
9 ** EM		SAME AS TYPE 9 - CONNECTED TO EMERGENCY MINIATURE INVERTER	8.8	868	LED	SIGNIFY (LEDALITE)	L4R10935VB / L4RDW
10		2" RECESSED LINEAR. LENGTH VARIES, SEE PLANS FOR SPECIFIC LENGTHS.	14.5	1345	LED	FINELITE	HP-2-R-D-XFT-S-835
10 EM		SAME AS TYPE 10 - CONNECTED TO EMERGENCY MINIATURE INVERTER	14.5	1345	LED	FINELITE	HP-2-R-D-XFT-S-835
11**		15/16" T-BAR LED	39	2854	LED	JLC TECH	TBSL-MW-5-24-B2-X-W
11** EM		SAME AS TYPE 11 - CONNECTED TO EMERGENCY MINIATURE INVERTER	39	2854	LED	JLC TECH	TBSL-MW-5-24-B2-X-W
12**		2" RECESSED PERIMETER	27.6	2999	LED	PINNACLE ARCHITECTURAL LIGHTING	EV2DPM-A-835HO-4
12** EM		SAME AS TYPE 12 - CONNECTED TO EMERGENCY MINIATURE INVERTER	27.6	2999	LED	PINNACLE ARCHITECTURAL LIGHTING	EV2DPM-A-835HO-4
13**		WALL MOUNT LINEAR	33.1	3361	LED	SIGNIFY (LEDALITE)	7408LBEQN047DEW
13** EM		SAME AS TYPE 13 - CONNECTED TO EMERGENCY MINIATURE INVERTER	33.1	3361	LED	SIGNIFY (LEDALITE)	7408LBEQN047DEW
14** EM		4' SURFACE MOUNTED LINEAR - CONNECTED TO EMERGENCY MINIATURE INVERTER	18.8	1780	LED	PINNACLE ARCHITECTURAL LIGHTING	EX3-WET-N-835-4-S-U-OL2-1-0-W
20		EXIT SIGN (SINGLE FACE) WALL AND CEILING MOUNT. SEE PLANS FOR DIRECTIONAL INDICATORS	2.5		LED	SIGNIFY (CHLORIDE)	ER46L-2-W-R
** LUMINAIRE TYPE NOT USED IN THIS BUILDING * PROVIDE SUSPENSION KIT			* MANUFACTURER AND MODEL NUMBER ARE PROVIDED TO SHOW BASIS OF DESIGN ONLY.				

PANELBOARD: PPA1																					
Location: CORR A						Recessed MOUNTED				10,000				SYM. A.I.C....				ENCLOSURE TYPE Type 1			
AMP MAIN (LUGS) OR 100 A						AMP MAIN BREAKER WITH 100 A				AMP TRIP				SE LABEL							
208Y/120V VOLTS 3						PHASE 4 WIRE 60				HERTZ 100 A AMP BUS											
CKT NO.	POLES	TRIP AMPS	WIRE AWG	# OF WIRES	GRN. AWG	CONDUIT INCH	LOAD SERVED	A		B		C		LOAD SERVED	CONDUIT INCH	GRN. AWG	# OF WIRES	WIRE AWG	TRIP AMPS	POLES	CKT NO.
1	1	20 A					RCPT: 134	540 VA	900 VA					RCPT: 134					20 A	1	2
3	1	20 A					RCPT: A110			540 VA	1920 VA			UV-A108					25 A	1	4
5	1	20 A					RCPT: 134					720 VA	900 VA	RCPT: 134					20 A	1	6
7	1	20 A					LTG: A106, A110 & 134	891 VA	1080 VA					RCPT: A108					20 A	1	8
9	1	20 A					RCPT: A110			720 VA	0 VA			SPARE					20 A	1	10
11	1	25 A					UV-A110					1920 VA	0 VA	SPARE					20 A	1	12
13	1	20 A					RCPT: A110	720 VA	0 VA					SPARE					20 A	1	14
15	1	20 A					SPARE			0 VA	0 VA			SPARE					20 A	1	16
17	1	20 A					RCPT: A110					720 VA	0 VA	SPARE					20 A	1	18
19	1	20 A					SPARE	0 VA	0 VA					SPARE					20 A	1	20
21	1	20 A					SPARE			0 VA	0 VA			SPARE					20 A	1	22
23	1	20 A					SPARE					0 VA	0 VA	SPARE					20 A	1	24
25	1	20 A					SPARE							SPARE					20 A	1	26
27	1	20 A					SPARE	0 VA	3840 VA			0 VA	3840 VA						20 A	1	28
29	1	20 A					SPARE					0 VA	3840 VA	RCPT: KILN	3/4	#10	3	#8	40 A	3	29
TOTAL CONNECTED LOAD PER PHASE...								7915 VA		7020 VA		8100 VA									
								A		B		C									
# -PROVIDE BREAKER AS REQUIRED BY PANELBOARD MANUFACTURER FOR...																					
* -GFCI BREAKER ** -SHUNT TRIP BREAKER								TOTAL CONNECTED LOAD: 64 A													
ALL WIRE SIZE IS (2)#12, (1)#12 G. IN 1/2" CONDUIT, UNLESS NOTED OTHERWISE								TOTAL CONNECTED LOAD: 23.031 KVA													
SUPPLIED FROM: MDP2																					

PANELBOARD: PPB1																					
Location: PREP B121C						Recessed MOUNTED				10,000				SYM. A.I.C....				ENCLOSURE TYPE Type 1			
AMP MAIN (LUGS) OR 100 A						AMP MAIN BREAKER WITH 100 A				AMP TRIP				SE LABEL							
208Y/120V VOLTS 3 PHASE 4 WIRE 60 HERTZ 100 A AMP BUS																					
CKT NO.	POLES	TRIP AMPS	WIRE AWG	# OF WIRES	GRN. AWG	CONDUIT INCH	LOAD SERVED	A		B		C		LOAD SERVED	CONDUIT INCH	GRN. AWG	# OF WIRES	WIRE AWG	TRIP AMPS	POLES	CKT NO.
1	1	20 A					RCPT: B119	540 VA	540 VA					RCPT: B121					20 A	1	2
3	1	15 A					UV-B117			860 VA	1080 VA			RCPT: CORD REEL...					20 A	1	4
5	1	20 A					RCPT: B119					900 VA	1023 VA	LTG: B119 & B121					20 A	1	6
7	1	15 A					UV-B115	860 VA	900 VA					RCPT: B121					20 A	1	8
9	1	20 A					RCPT: B121			900 VA	900 VA			RCPT: B121					20 A	1	10
11	1	20 A					RCPT: B121B, B121C					900 VA	900 VA	RCPT: B121					20 A	1	12
13	1	20 A					RCPT: B119A, B119B	900 VA	900 VA					RCPT: B119					20 A	1	14
15	1	20 A					RCPT: B119			900 VA	1080 VA			RCPT: CORD REEL...					20 A	1	16
17	1	20 A					RCPT: B119					900 VA	1080 VA	RCPT: CORD REEL...					20 A	1	18
19	1	20 A					RCPT: CORD REEL...	1080 VA	1920 VA					UV-B119					25 A	1	20
21	1	25 A					UV-B121			1920 VA	0 VA			SPARE					20 A	1	22
23	1	25 A					UV-B124					1920 VA	0 VA	SPARE					20 A	1	24
25	1	20 A					SPARE	0 VA	0 VA					SPARE					20 A	1	26
27	1	20 A					SPARE			0 VA	0 VA			SPARE					20 A	1	28
29	1	20 A					SPARE					0 VA	0 VA	SPARE					20 A	1	30
TOTAL CONNECTED LOAD PER PHASE...								7640 VA		7640 VA		7578 VA									
								A		B		C									
# -PROVIDE BREAKER AS REQUIRED BY PANELBOARD MANUFACTURER FOR...																					
* -GFCI BREAKER ** -SHUNT TRIP BREAKER								TOTAL CONNECTED LOAD: 63 A													
ALL WIRE SIZE IS (2)#12, (1)#12 G. IN 1/2" CONDUIT, UNLESS NOTED OTHERWISE								TOTAL CONNECTED LOAD: 22.854 KVA													
SUPPLIED FROM: MDP2																					


PANELBOARD: PPD1																											
Location: ELEC 101					Surface MOUNTED					10,000 SYM. A.I.C....					ENCLOSURE TYPE Type 1												
AMP MAIN (LUGS) OR 100 A					AMP MAIN BREAKER WITH 100 A					AMP TRIP					SE LABEL												
208Y/120V VOLTS 3 PHASE 4 WIRE 60 HERTZ 100 A AMP BUS																											
CKT NO.	POLES	TRIP AMPS	WIRE AWG	# OF WIRES	GRN. AWG	CONDUIT INCH	LOAD SERVED	A		B		C		LOAD SERVED	CONDUIT INCH	GRN. AWG	# OF WIRES	WIRE AWG	TRIP AMPS	POLES	CKT NO.						
1	1	20 A					PRE-D130	0 VA	0 VA					PRE-D132					20 A	1	2						
3	1	15 A					UV-D134			860 VA	860 VA			UV-D135					15 A	1	4						
5	1	15 A					UV-D136					860 VA	860 VA	UV-D137					15 A	1	4						
7	1	15 A					UV-D130	860 VA	860 VA					UV-D132					15 A	1	6						
9	1	15 A					UV-D139			860 VA	0 VA			SPARE					20 A	1	10						
11	1	15 A					UV-D140					860 VA	0 VA	SPARE					20 A	1	12						
13	1	15 A					UV-D138	860 VA	0 VA					SPARE					20 A	1	14						
15	1	20 A					SPARE			0 VA	0 VA			SPARE					20 A	1	16						
17	1	20 A					SPARE					0 VA	0 VA	SPARE					20 A	1	18						
TOTAL CONNECTED LOAD PER PHASE...								2580 VA		2580 VA		2580 VA		# -PROVIDE BREAKER AS REQUIRED BY PANELBOARD MANUFACTURER FOR...													
*-GFCI BREAKER **-SHUNT TRIP BREAKER								A		B		C															
ALL WIRE SIZE IS (2#)12, (1#)12 G. IN 1/2" CONDUIT, UNLESS NOTED OTHERWISE								TOTAL CONNECTED LOAD: 21 A																			
								TOTAL CONNECTED LOAD: 7,740 KVA												SUPPLIED FROM: MDP1							



1 First Floor - Key Plan
1" = 20'-0"

General Notes

- A. VERIFY ALL PIPING LOCATIONS, SIZES, AND ARRANGEMENTS IN FIELD PRIOR TO BID. NOTIFY ARCHITECT IN WRITING OF ANY DISCREPANCIES.
- B. VERIFY IN FIELD INVERT AND DIRECTION OF FLOW IN EXISTING SOIL PIPE WHERE NEW SOIL PIPE IS TO BE CONNECTED TO EXISTING SOIL PIPE.
- C. LEGALLY DISPOSE OF ALL DEMOLITION DEBRIS.
- D. INCLUDE TRENCHING, CUTTING AND PATCHING OF FLOORS, WALLS AND CEILINGS, INCLUDING CEILING TILE REMOVAL AND REPLACEMENT, WHEN REQUIRED FOR PLUMBING WORK. PATCH ABANDONED OPENINGS AND DISTURBED FINISHES TO MATCH EXISTING. TAKE PRECAUTIONS TO PROTECT STRUCTURAL INTEGRITY OF FLOOR OR WALLS WHEN TRENCHING OR CUTTING.
- E. MATERIALS FOR PLUMBING INSTALLATION SHALL BE NEW, UNLESS SPECIFICALLY NOTED OTHERWISE.
- F. REFER TO DRAWING NO. EP402 FOR FIXTURE ROUGH-IN SCHEDULE.
- G. PROVIDE THROUGH PENETRATION FIRESTOPPING FOR FIRE RATED WALLS AND FLOORS. PENETRATIONS THROUGH EXISTING WALLS AND FLOORS ARE CONSIDERED TWO-HOUR PARTITIONS UNLESS SPECIFICALLY NOTED OTHERWISE. REFER TO "A" SERIES OR CODE COMPLIANCE DRAWINGS FOR LOCATION OF FIRE RATED WALLS AND FLOORS.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School


First Floor Key Plan

Drawn By: GPD/ sef	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	EP050	




- Plan Notes**
- A. REFER TO DRAWING NO. EP050 FOR GENERAL NOTES.
 - B. REMOVE PLUMBING FIXTURES INDICATED, INCLUDING ASSOCIATED PIPING, FASTENERS, SUPPORTS, ETC., BACK TO POINTS OF CONCEALMENT WITHIN OR BEHIND REMAINING WALLS, BELOW FLOORS OR ABOVE CEILINGS.
 - C. REMOVE ABANDONED ACCESSIBLE PIPING TO MAIN BRANCHES, STACKS OR RISERS AS REQUIRED TO ELIMINATE EXPOSED PIPING AND DEAD END PIPING RUNS LONGER THAN 1'-0". COORDINATE CONCEALMENT OF PIPING WITH FINAL CONSTRUCTION OF WALLS, FLOORS AND CEILINGS.

- Plumbing Notes**
- 1. REMOVE 3/4" HOT WATER, COLD WATER, 1 1/2" VENT AND 2" SANITARY IN CHASE. PREPARE 2" SANITARY BELOW FLOOR FOR FUTURE CONNECTION.
 - 2. REFER TO DETAILS 4/ EP402 AND 5/ EP402 FOR ADDITIONAL INFORMATION.



S.E.D. Control No. 13-02-00-01-0-004-023



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School



Enlarged Art Room Plans

Drawn By: GPD/ sef Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004

EP400



EP401



Plan Notes

- A. REFER TO DRAWING NO. EP050 FOR GENERAL NOTES.
- B. REMOVE PLUMBING FIXTURES INDICATED, INCLUDING ASSOCIATED PIPING, FASTENERS, SUPPORTS, ETC. BACK TO POINTS OF CONCEALMENT WITHIN OR BEHIND REMAINING WALLS, BELOW FLOORS OR ABOVE CEILINGS.
- C. REMOVE ABANDONED ACCESSIBLE PIPING TO MAIN BRANCHES, STACKS OR RISERS AS REQUIRED TO ELIMINATE EXPOSED PIPING AND DEAD END PIPING RUNS LONGER THAN 1'-0". COORDINATE CONCEALMENT OF PIPING WITH FINAL CONSTRUCTION OF WALLS, FLOORS AND CEILINGS.

Plumbing Notes

- ◇ FLOW CONTROL FITTING SUPPLIED BY GREASE INTERCEPTOR MANUFACTURER.

Grease Interceptor Schedule


DWG LABEL	LOCATION	DESIGN MAKE AND MODEL	GREASE RETENTION CAPACITY (POUNDS)	PDI RATED FLOW RATE (GPM)	INSTALLATION	INLET / OUTLET SIZE (NPS)	CENTERLINE OF INLET / OUTLET TO TOP (INCHES)	CENTERLINE OF INLET / OUTLET TO BOTTOM (INCHES)	EXTENSION HEIGHT (INCHES)	LENGTH (INCHES)	WIDTH (INCHES)	HEIGHT (INCHES)	VENT SIZE (NPS)	NOTES
GI-E-1	KITCHEN C125	JR SMITH 8150	100	50	FLOOR MOUNTED	3	10	6	N/A	49-1/2	27-3/4	16	2	1

- NOTES:
- PROVIDE EXTERNAL FLOW CONTROL FITTING SUPPLIED BY SAME MANUFACTURER AS GREASE INTERCEPTOR.

Plumbing Fixture Schedule

DWG LABEL	ROUGH-IN CONNECTION SIZE (INCHES)				BARRIER FREE	AGE GROUP	RIM HEIGHT	DESCRIPTION	NOTES
	SAN	VENT	CW	HW					
SINK "B"	1 1/2	1 1/2	1/2	1/2	YES	ADULT	-	ACCESSIBLE, LARGE, STAINLESS STEEL, COUNTER MOUNTED SINK W/ MANUAL, SINGLE CONTROL MIXING FAUCET W/ SWING SPOUT, SUPPLIES, OFFSET DRAIN FITTING AND TRAP.	
SINK "C"	1 1/2	1 1/2	1/2	1/2	NO	ADULT	-	LARGE, DEEP BOWL, STAINLESS STEEL, COUNTER MOUNTED SINK W/ MANUAL, SINGLE CONTROL MIXING FAUCET W/ SWING SPOUT, SUPPLIES, DRAIN FITTING, TRAP AND SOLIDS INTERCEPTOR.	1
SINK "D"	1 1/2	1 1/2	1/2	1/2	YES	ADULT	-	ACCESSIBLE, EPOXY RESIN SINK W/ MANUAL, MANUAL TYPE, SINGLE HOLE, WRIST-BLADE-HANDLE MIXING VALVE SCIENCE SINK FAUCET W/ SINGLE ACTION EYEWASH, SUPPLIES, PP SINK OUTLET FITTING AND CORROSION RESISTANT TRAP.	
SINK "E"	1 1/2	1 1/2	1/2	1/2	NO	ADULT	-	EPOXY RESIN SINK W/ MANUAL, MANUAL TYPE, SINGLE HOLE, TWO-CROSS-HANDLE MIXING VALVE SCIENCE SINK FAUCET, SUPPLIES, PP SINK OUTLET FITTING AND CORROSION RESISTANT TRAP.	
SINK "F"	1 1/2	1 1/2	1/2	1/2	NO	-	-	FLOOR MOUNTED, MOLDED LAUNDRY TUB WITH MANUAL TYPE, DECK MOUNT MIXING FAUCET WITH LEVER HANDLES AND SWING SPOUT, SUPPLIES, DRAIN FITTING WITH STOPPER AND TRAP AND SOLIDS INTERCEPTOR.	1

- NOTES:
- SEE SECTION 22 13 23 FOR SOLIDS INTERCEPTOR.



S.E.D. Control No. 13-02-00-01-0-004-023

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Rombout Middle School

Enlarged Kitchen Plans, Schedule and
Details

Drawn By: GPD/ sef	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004		EP402