

HVAC Spec Revised 01-02-15		Z. GUARANTEE:		REASONS FOR SAME:		CATALOG CUTS AND SUBMITTALS TO BE PROVIDED IN ELECTRONIC "PDF" FORMAT. THE ARCHITECT WILL FORWARD ALL SUBMISSIONS TO THE ENGINEER.		H. FLEXIBLE CONNECTIONS: NEOPRENE-COATED GLASS FABRIC, 3/2 OZ PER SQUARE YD WITH SEWED AND CEMENTED SEAMS, SIMILAR TO VENT FABRICS. PROVIDE WITH METAL COLLARS. ALLOW MINIMUM MOVEMENT OF 1 INCH.		10. AIR OUTLETS		CERTIFIED NEBB OR AABC TECHNICIAN.	
PROJECT NAME: SPRING VALLEY PD EXPANSION PROJECT NO.: 23025-00 DATE: 11-01-2023		1) ALL MATERIALS AND WORKMANSHIP SHALL BE GUARANTEED FOR A PERIOD OF ONE YEAR FROM DATE OF FINAL ACCEPTANCE OF THIS WORK. FINAL ACCEPTANCE SHALL BE DEFINED AS THE TIME AT WHICH THE MECHANICAL WORK IS TAKEN OVER AND ACCEPTED BY THE OWNER, AND IS UNDER CARE, CUSTODY, AND CONTROL OF THE OWNER. ENGAGE THE SERVICES OF VARIOUS MANUFACTURERS SUPPLYING THE EQUIPMENT FOR THE PROPER STARTUP AND OPERATION OF ALL SYSTEMS INSTALLED. INSTRUCT THE OWNERS PERSONNEL IN THE PROPER OPERATION AND SERVICING OF THE SYSTEM.		F. ELECTRONIC COPIES OF DRAWINGS:		B. ON COMPLETION AND ACCEPTANCE OF WORK, THIS CONTRACTOR SHALL FURNISH WRITTEN INSTRUCTIONS, EQUIPMENT MANUALS AND DEMONSTRATE TO THE OWNER THE PROPER OPERATION AND MAINTENANCE OF ALL EQUIPMENT AND APPARATUS FURNISHED UNDER THIS CONTRACT.		I. TURNING VANES: GALVANIZED STEEL, SMALL DOUBLE-THICKNESS VANES WITH 2 INCH INSIDE RADIUS.		A. GENERAL:		J. AFTER SUBMISSION OF THE FIELD VERIFIED BALANCING REPORT, THE AIR BALANCING COMPANY SHALL RETURN TO THE JOB SITE TO PERFORM TWO (2) OCCUPANT COMFORT BALANCES AS DIRECTED BY THE OWNER OR ENGINEER	
HVAC SPECIFICATIONS		A. THE "GENERAL CONDITIONS OF THE CONTRACT FOR CONSTRUCTION," AIA DOCUMENT A201, LATEST EDITION, AND THESE SPECIFICATIONS AS APPLICABLE ARE PART OF THIS CONTRACT.		1) IF THE CONTRACTOR REQUIRES (DWG) FORMAT, THE DRAWINGS WILL BE FORWARDED ONLY UPON RECEIPT OF SIGNED ACCEPTANCE OF TERMS FORM. PERMISSION FROM THE ARCHITECT MUST FIRST BE OBTAINED FOR ENGINEER TO INCLUDE THE ARCHITECTURAL BACKGROUND AS REFERENCE. THE CONTRACTOR IS TO OBTAIN THE ARCHITECT'S LATEST DRAWINGS DIRECTLY FROM THE ARCHITECT.		C. THESE INSTRUCTIONS SHALL BE TYPED ON 8-1/2 INCH X 11 IN FORMAT. THE CONTRACTOR SHALL GIVE ONE COPY OF THE INSTRUCTIONS TO THE OWNER AND ONE COPY TO THE ENGINEER.		J. FIRE DAMPERS: DYNAMIC, RATED AND LABELED ACCORDING TO UL 555 BY AN NRTL, GALVANIZED STEEL, CONSTRUCTION, CURTAIN TYPE WITH BLADES OUT OF THE AIRSTREAM (TYPE B), SPRING LOADED, EQUIPPED WITH FUSIBLE LINK, CONFORMING TO NFPA STANDARD 80A AND APPROVED BY NEW YORK CITY. SIMILAR TO POTOROFF OR RUSKIN, RATED AS REQUIRED. PROVIDE FIRE DAMPERS AS NOTED ON THE PLANS AND IN DUCTS AND OPENINGS IN SHAFTS, FLOORS, FIRE WALLS, FIRE-RESISTANCE PARTITIONS, FIRE RATED CEILING, EXIT CORRIDOR WALLS. PROVIDE ACCESS DOOR IN DUCT ADJACENT TO EACH FIRE DAMPER. SEE INSTALLATION ON DRAWING.		1) MARGIN TYPES, COLORS, FINISH AND METHODS OF ATTACHMENT FOR ALL DIFFUSERS, GRILLES AND REGISTERS SHALL BE COORDINATED WITH ARCHITECTURAL CEILING AND WALL DETAILS AND SPECIFICATIONS. FINISH SHALL MATCH COLOR SAMPLE AS APPROVED.		K. THE FINAL REPORT AFTER THE COMFORT BALANCE IS TO BE INCLUDED IN PROJECT OPERATING AND MAINTENANCE MANUAL.	
1. GENERAL		B. ALL APPLICABLE CODES, LAWS AND REGULATIONS GOVERNING OR RELATING TO ANY PORTION OF THIS WORK ARE HEREBY INCORPORATED INTO AND MADE A PART OF THESE SPECIFICATIONS, AND THEIR PROVISIONS SHALL BE CARRIED OUT BY THE CONTRACTOR WHO SHALL INFORM THE OWNER, PRIOR TO SUBMITTING A PROPOSAL, OF ANY WORK OR MATERIALS WHICH VIOLATE ANY OF THE ABOVE LAWS AND REGULATIONS. ANY WORK DONE BY THE CONTRACTOR CAUSING SUCH VIOLATION SHALL BE CORRECTED BY THE CONTRACTOR.		2) THESE FILES ARE BEING ISSUED FOR THE CONVENIENCE OF THE CONTRACTOR AND THE CONTRACTOR REMAINS RESPONSIBLE FOR ALL CONTRACT REQUIREMENTS RELATED TO THE NORMAL SHOP DRAWING PREPARATION PROCESS.		D. THE INSTRUCTIONS SHALL BE ORGANIZED IN SECTIONS, WITH ONE SECTION PER SYSTEM. THE COVER OF THE INSTRUCTION BOOKLET SHALL BEAR THE NAME, ADDRESS AND PHONE NUMBER OF THE PROJECT, ARCHITECT, ENGINEER, MECHANICAL CONTRACTOR AND SUBCONTRACTORS.		K. COMBINATION FIRE/SMOKE DAMPERS:		2) FRAME TYPE SUITABLE FOR MOUNTING IN CEILING OR WALL CONSTRUCTION AS INDICATED ON ARCHITECTURAL PLANS.		L. THE TESTING AND BALANCING AGENCY SHALL INCLUDE AS PART OF THEIR WORK AN EXTENDED WARRANTY OF 90 DAYS AFTER COMPLETION OF TEST AND BALANCE WORK. THE ENGINEER AT HIS DISCRETION DURING THE WARRANTY PERIOD MAY REQUEST A RECHECK, OR RESETTING OF ANY EQUIPMENT. THE MECHANICAL CONTRACTOR AND THE BALANCING CONTRACTOR SHALL PROVIDE THE NECESSARY TECHNICIANS TO FACILITATE THIS WORK.	
C. INVESTIGATE EACH SPACE THROUGH WITH EQUIPMENT MUST BE MOVED. WHERE NECESSARY, EQUIPMENT SHALL BE SHIPPED FROM MANUFACTURER IN SECTIONS OF SIZE SUITABLE FOR MOVING THROUGH AVAILABLE RESTRICTIVE SPACES. ASCERTAIN FROM BUILDING OWNER AT WHAT TIMES OF DAY EQUIPMENT MAY BE MOVED THROUGH ALL AREAS.		3) THIS CONTRACTOR IS RESPONSIBLE FOR THE MAINTENANCE AND OPERATION OF ALL SYSTEMS UNTIL THE FINAL ACCEPTANCE OF THE WORK.		G. SUBMISSIONS:		E. FINAL "AS-BUILT" DRAWINGS INDICATING AS INSTALLED CONDITIONS SHALL BE PROVIDED TO THE ARCHITECT AND ENGINEER AFTER COMPLETION OF THE INSTALLATION.		3) EXACT LOCATION OF ALL AIR OUTLETS AS PER ARCHITECTURAL PLANS.		4) PROVIDE MOUNTING AND BLOCKING		M. BALANCING AGENCY SHALL PERMANENTLY MARK ALL ADJUSTMENT DEVICES (VALVES, DAMPERS, ETC.) TO ENABLE THE SETTING TO BE RESTORED.	
D. DUCTWORK AND PIPING IS SHOWN DIAGRAMMATICALLY AND DOES NOT SHOW ALL OFFSETS, DROPS AND RISERS. THE CONTRACTOR SHALL ALLOW HIS PRICE FOR ROUTING OF DUCTWORK AND PIPING TO AVOID OBSTRUCTIONS. EXACT LOCATIONS ARE SUBJECT TO APPROVAL OF ARCHITECT. COORDINATION WITH THE EXISTING SERVICES, INCLUDING THOSE OF OTHER TRADES IS REQUIRED.		4) ALL AIR CONDITIONING UNIT COMPRESSORS AND REFRIGERATION COMPONENTS SHALL HAVE A 5-YEAR WARRANTY.		1) PROVIDE ALL COORDINATION DRAWINGS, DUCTWORK AND PIPING SHOP DRAWINGS IN AUTOCAD FORMAT, VERSION COMPATIBLE WITH OWNER. ALL CATALOGS AND SUBMITTALS TO BE PROVIDED IN ELECTRONIC "PDF" FORMAT. THE ARCHITECT WILL FORWARD ALL SUBMISSIONS TO THE ENGINEER.		6. SUBSTITUTIONS		5) SUITABLE FOR OPERATION AT 20% EXCESS AND 20% LESS THAN NOTED CAPACITY FOR CONSTANT VOLUME SYSTEMS AND AT 20% EXCESS AND 80% LESS THAN NOTED CAPACITY FOR VARIABLE VOLUME SYSTEMS.		6) MANUFACTURER RESPONSIBLE FOR EXAMINING APPLICATION OF EACH OUTLET AND GUARANTEE THAT EACH WILL PROVIDE REQUIRED NO LEVELS AND COMFORT SPACE CONDITIONS WITHOUT DRAFTS THROUGHOUT OPERATING RANGE.		N. AIR BALANCING:	
E. SUPPORT ALL DUCTWORK AND PIPING FROM BUILDING STRUCTURE AND/OR FRAMING IN AN APPROVED MANNER. WHERE OVERHEAD CONSTRUCTION DOES NOT PERMIT FASTENING OR SUPPORTS FOR EQUIPMENT, FURNISH ADDITIONAL FRAMING, INSERTS SHALL BE, SLOTTED TYPE AND FACTORY PAINTED. SINGLE ROD SHALL BE SIMILAR TO GRINNELL FIG. 281, MULTI-ROD SHALL BE SIMILAR TO FEE & MASON SERIES 9000 WITH END CAPS AND CLOSURE STRIPS. MAXIMUM LOADING INCLUDING PIPES, DUCTWORK CONTENTS AND COVERING SHALL NOT EXCEED 75% OF RATED INSET CAPABILITY, WHEN SUPPORTING FROM BUILDING USE BEAM CLAMPS IN APPROVED MANNER.		A.A. SPECIFICATIONS ARE OF SIMPLIFIED FORM AND INCLUDE INCOMPLETE SENTENCES, WORDS OR PHRASES SUCH AS "THE CONTRACTOR SHALL," "SHALL BE," "FURNISH," "PROVIDE," "A," "THE," AND "ALL" HAVE BEEN OMITTED FOR BREVITY.		2) IF PAPER SUBMISSIONS ARE TO BE PROVIDED THE FOLLOWING SHALL BE ADHERED TO:		A. NO SUBSTITUTE MATERIAL OR MANUFACTURER OF EQUIPMENT SHALL BE PERMITTED WITHOUT A FORMAL, WRITTEN SUBMITTAL TO THE ENGINEER WHICH INCLUDES ALL DIMENSIONAL, PERFORMANCE AND MATERIAL SPECIFICATIONS, ANY CHANGES IN LAYOUT, ELECTRICAL CHARACTERISTICS, STRUCTURAL REQUIREMENTS OR DESIGN DUE TO THE USE OF A SUBSTITUTION SHALL BE SUBMITTED TO THE ENGINEER AS PART OF THIS PROPOSAL. THE CONTRACTOR TAKES FULL RESPONSIBILITY FOR THE SUBSTITUTION AND ALL CHANGES RESULTING FROM THE SUBSTITUTION. ALL ITEMS SHALL BE SUBMITTED FOR REVIEW IN CONJUNCTION WITH THE SUBMITTAL OF THE SUBSTITUTION. ANY SUBSTITUTION MUST BE SUBMITTED WITH AN EXPLANATION WHY A SUBSTITUTION IS BEING UTILIZED. IF THE SUBSTITUTED ITEM DEVIATES FROM THE SPECIFIED ITEM, THOSE DEVIATIONS ARE TO BE IDENTIFIED ON A LINE BY LINE BASIS. IF THE SUBSTITUTION IS BEING UTILIZED FOR FINANCIAL REASONS, THE ASSOCIATED CREDIT MUST BE SIMULTANEOUSLY SUBMITTED.		7) ALL DUCT DIMENSIONS INDICATED ON PLANS ARE INSIDE CLEAR DIMENSIONS.		7) ALL REGISTERS AND DIFFUSERS SHALL BE PROVIDED WITH OPPOSED BLADE VOLUME DAMPERS. DAMPER OPERATING LEVERS SHALL BE ACCESSIBLE AT THE FACE OF AIR OUTLETS.		1) PRE-CONSTRUCTION AIR TESTING: MEASURE PRESSURE, TEMPERATURE, AND VOLUME OF AIR FROM EXISTING BASE BUILDING SYSTEM BEFORE STARTING WORK. TRAVESER MAN SUPPLY AND RETURN DUCTS BEFORE WORK TO OBTAIN TOTAL FLOW. SUBMIT REPORT TO ENGINEER IMMEDIATELY AFTER COMPLETION OF TEST.	
F. INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST SHALL NOT BE MADE WITHOUT APPROVAL.		DEF. DEFINITIONS:		H. SUBMIT SHOP DRAWINGS FOR THE FOLLOWING:		B. ALL SUBSTITUTED EQUIPMENT SHALL CONFORM TO SPACE REQUIREMENTS AND PERFORMANCE REQUIREMENTS SHOWN ON CONTRACT DOCUMENTS. CONTRACTOR SHALL REPLACE ANY EQUIPMENT THAT DOES NOT MEET THESE REQUIREMENTS AT HIS OWN EXPENSE. ANY MODIFICATIONS TO ASSOCIATED SYSTEMS OR ADDITIONAL COSTS ATTRIBUTED TO THIS SUBSTITUTION SHALL BE AT THIS CONTRACTOR'S EXPENSE.		8) ONLY FOUR (4) WAY DIFFUSERS SHALL BE PROVIDED. PROVIDE SHEETMETAL BLANK OFF AS REQUIRED FOR 1 WAY, 2 WAY OR 3 WAY DIFFUSERS.		9) PROVIDE BLANKING FOR PROPER COVERAGE AND BLOW WITHOUT PRODUCING OBJECTIONABLE NOISE OR AIR MOTION AT OCCUPIED LEVEL.		2) HVAC CONTRACTOR SHALL ENSURE THAT A FIRST SET OF AIR FILTERS ARE IN PLACE, WHENEVER FILTERS ARE RUNNING AND REPLACED WITH A NEW CLEAN SET OF FILTERS BEFORE TESTING IS COMMENCED.	
G. THIS CONTRACTOR SHALL SUBMIT TO THE ARCHITECT FOR APPROVAL A PLAN INDICATING THE SIZE (MINIMUM 18 INCH X 18 INCH) AND LOCATION OF ALL ACCESS DOORS REQUIRED FOR OPERATION AND MAINTENANCE OF ALL CONCEALED EQUIPMENT, DEVICES, VALVES, DAMPERS AND CONTROLS. CONTRACTOR SHALL ARRANGE FOR FURNISHING AND INSTALLATION OF ALL ACCESS DOORS IN FINISHED CONSTRUCTION AND INCLUDE COSTS IN THE BID.		1) "PROVIDE": TO SUPPLY, INSTALL AND CONNECT UP COMPLETE AND READY FOR SAFE AND REGULAR OPERATION THE PARTICULAR WORK REFERRED TO UNLESS SPECIFICALLY OTHERWISE NOTED.		I. DUCTWORK LAYOUT AND SHEET METAL DESIGNS.		C. CONTRACTOR SHALL SUBMIT BID BASED ON SPECIFIED ITEMS AND SHALL SUPPLY AS AN ALTERNATE PRICE ANY SUBSTITUTIONS.		9) PROVIDE BLANKING FOR PROPER COVERAGE AND BLOW WITHOUT PRODUCING OBJECTIONABLE NOISE OR AIR MOTION AT OCCUPIED LEVEL.		10) MANUFACTURERS, SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:		A. FLOW, LEAKAGE CLASS, TEMPERATURE, STATIC PRESSURE OF AIR AT ALL TRUNK DUCTS SERVING AREAS OF WORK.	
H. REMOVAL AND RELOCATION OF CERTAIN EXISTING WORK WILL BE NECESSARY FOR THE PERFORMANCE OF THE GENERAL WORK. ALL EXISTING CONDITIONS CANNOT BE COMPLETELY DETAILED ON THE DRAWINGS. THE CONTRACTOR SHALL SURVEY THE SITE AND INCLUDE ALL CHANGES IN MAKING UP THE WORK PROPOSAL.		2) "INSTALL": TO ERECT, MOUNT AND CONNECT COMPLETE WITH RELATED ACCESSORIES.		A. SHEETMETAL SHOP STANDARDS SHALL BE COMPILED DIRECTLY FROM THE "SMACNA DUCT CONSTRUCTION STANDARDS - METAL AND FLEXIBLE" MANUAL, LATEST EDITION. MODIFICATIONS FOR A SPECIFIC PROJECT, IF ANY, SHALL BE INDICATED DIRECTLY ON THE SMACNA TEMPLATES. MODIFIED SHOP STANDARDS NOT TAKEN DIRECTLY FROM THE SMACNA TEMPLATES WILL NOT BE ACCEPTED. ANY DEVIATIONS FROM SMACNA SHALL BE NOTED.		7. SERVICE AND WARRANTY (MAINTENANCE CONTRACT)		10) MANUFACTURERS, SUBJECT TO COMPLIANCE WITH REQUIREMENTS, PROVIDE PRODUCTS BY ONE OF THE FOLLOWING:		A. TITUS.		B. TEMPERATURE OF AIR LEAVING OUTLETS AT TWO (2) TYPICAL AIR OUTLETS.	
I. PLAN INSTALLATION OF NEW WORK AND CONNECTIONS TO EXISTING WORK TO ENSURE MINIMUM INTERFERENCE WITH REGULAR OPERATION OF EXISTING FACILITIES. ALL SYSTEM SHUTDOWNS AFFECTING OTHER AREAS SHALL BE COORDINATED WITH BUILDING OWNER. INSTALL ISOLATION VALVES AT POINT OF CONNECTION TO THE EXISTING PIPING. PROVIDE TEMPORARY DUCT CAPS AND/OR CONNECTIONS TO MINIMIZE SHUTDOWN TIME.		3) "FURNISH" OR "SUPPLY": TO PURCHASE, PROCURE, ACQUIRE AND DELIVER COMPLETE WITH RELATED ACCESSORIES.		2) AIR OUTLETS.		A. THIS CONTRACTOR SHALL PROVIDE AS AN ADD ALTERNATE PRICE A FULL ONE YEAR SERVICE OF ALL MECHANICAL COMPONENTS AND SYSTEMS, WITH PRICES FOR YEARS 2,3 AND 4 FOLLOWING THIS FIRST YEAR, AT THE TIME OF ACCEPTANCE OF PROJECT. THE TENANT OR OWNERS REPRESENTATIVE WILL DECIDE TO ACCEPT WHICH ALTERNATE, IF ANY, THIS IN ADDITION TO THE WARRANTY BEING PROVIDED AS PART OF THE BASE CONTRACT.		B. SQUARE DIFFUSERS: DIFFUSERS SHALL BE STEEL CONSTRUCTION PAINTED WHITE SUITABLE FOR THE TYPE OF CEILING.		B. ANEMOSTAT PRODUCTS; A MESTEK COMPANY.		C. QUANTITY OF AIR AT EACH AIR INLET AND OUTLET AFTER BALANCING.	
J. CONNECT NEW WORK TO EXISTING WORK IN NEAT AND APPROVED MANNER. RESTORE EXISTING WORK DISTURBED WHILE INSTALLING NEW WORK TO ACCEPTABLE CONDITION AS DETERMINED BY ARCHITECT.		4) "WORK": LABOR, MATERIALS, EQUIPMENT, APPARATUS, CONTROLS, ACCESSORIES AND OTHER ITEMS REQUIRED FOR PROPER AND COMPLETE INSTALLATION.		3) AIR AND WATER BALANCE REPORT.		8. ACCESS DOORS IN GENERAL CONSTRUCTION		C. REGISTERS AND GRILLES:		1) RETURN AND EXHAUST REGISTERS: STEEL CONSTRUCTION WITH VOLUME DAMPER.		D. PROVIDE FOR ALL AIR CONDITIONING UNITS, SUPPLY CFM, OUTSIDE AIR CFM, RETURN AIR CFM, MIXED AIR CFM. PROVIDE OUTSIDE AIR, MIXED AIR AND SUPPLY AIR TEMPERATURES (DRY BULB - COOLING AND HEATING, WET-BULB-COOLING) INDICATE UNIT OPERATING MODE DURING TEST.	
K. DISCONNECT, REMOVE AND/OR RELOCATE EXISTING MATERIAL, EQUIPMENT AND OTHER WORK AS NOTED OR REQUIRED FOR PROPER INSTALLATION OF NEW SYSTEM.		5) "CONCEALED": EMBEDDED IN MASONRY OR OTHER CONSTRUCTION, INSTALLED IN FURRED SPACES, WITHIN DOUBLE PARTITIONS OR HUNG CEILING, IN TRENCHES, IN CRAWL SPACES, OR IN ENCLOSURES.		4) AC UNITS AND FANS.		A. THIS CONTRACTOR SHALL SUBMIT TO THE ARCHITECT FOR APPROVAL A PLAN INDICATING THE SIZE (MINIMUM 18 INCH X 18 INCH) AND LOCATION OF ALL ACCESS DOORS REQUIRED FOR OPERATION AND MAINTENANCE OF ALL CONCEALED EQUIPMENT, DEVICES, VALVES, DAMPERS AND CONTROLS. CONTRACTOR SHALL ARRANGE FOR FURNISHING AND INSTALLATION OF ALL ACCESS DOORS IN FINISHED CONSTRUCTION AND INCLUDE COSTS IN THE BID.		1) RETURN AND EXHAUST REGISTERS: STEEL CONSTRUCTION WITH VOLUME DAMPER.		2) SUPPLY REGISTERS: STEEL CONSTRUCTION ADJUSTABLE DOUBLE DEFLECTION STEEL AIRFOIL LOUVERS, WITH VOLUME DAMPER. PROVIDE AIR EQUALIZING DEFLECTOR WHERE REGISTER COLLAR DUCT IS LESS THAN 2 FEET LONG.		E. CALIBRATE ALL NEW TERMINAL BOXES (VAV) AS REQUIRED TO MEET SPECIFIED MINIMUM/MAXIMUM CFM.	
L. THE CONTRACTOR SHALL KEEP ALL EQUIPMENT AND MATERIALS, AND ALL PARTS OF THE BUILDING, EXTERIOR SPACES AND ADJACENT STREETS, SIDEWALKS AND PAVEMENTS, FREE FROM MATERIAL, AND DEBRIS, RESULTING FROM THE EXECUTION OF THIS WORK. EXCESS MATERIALS WILL NOT BE PERMITTED TO ACCUMULATE EITHER ON THE INTERIOR OR THE EXTERIOR.		6) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		5) PIPING SHOP STANDARDS		B. EXCEPT AS OTHERWISE SHOWN OR NOTED, ALL DUCTWORK AND OTHER SHEET METAL WORK SHALL BE GALVANIZED STEEL.		2) ALL MIXED AIR PLenums, EXCEPT WHERE MOISTURE CARRYOVER FROM OUTDOOR AIR LOUVER WILL OCCUR.		3) TRANSFER GRILLES: STEEL CONSTRUCTION WITHOUT VOLUME DAMPER.		F. LISTING OF DESIGN AND ACTUAL READINGS AS WELL AS ALL MANUFACTURER'S DATA FOR EQUIPMENT.	
M. SEAL OPENINGS AROUND DUCTS AND PIPING THROUGH PARTITIONS, WALLS AND FLOORS (NOT IN SHAFTS) WITH MINERAL WOOL OR OTHER NONCOMBUSTIBLE MATERIAL.		7) "SIMILAR" OR "EQUAL": EQUAL, IN MATERIALS, WEIGHT, SIZE, DESIGN AND EFFICIENCY OF SPECIFIED PRODUCT.		6) PIPING LAYOUT, DETAIL, AT 3/8 INCH SCALE. PIPING LAYOUT WITH FITTINGS, VALVES AND EQUIPMENT. USE SINGLE LINE FOR PIPE SIZES 3 INCHES AND SMALLER, AND DOUBLE LINE FOR PIPE SIZES 4 INCHES AND GREATER. FABRICATION OF PIPE ANCHORS, HANGERS, SUPPORTS FOR MULTIPLE PIPES, ALIGNMENT GUIDES, EXPANSION JOINTS AND LOOPS, AND ATTACHMENTS OF THE SAME TO THE BUILDING STRUCTURE. DETAIL LOCATION OF ANCHORS, ALIGNMENT GUIDES, AND EXPANSION JOINTS AND LOOPS SUBMIT ALL WELDING CERTIFICATES.		C. DESCRIPTION OF DUCTWORK PRESSURE CLASS AND EQUIPMENT:		3) RETURN AIR STUB DUCTS AT MER WALLS AND SHAFT INTAKE OPENINGS FOR FULL LENGTH.		4) ALL MIXED AIR PLenums, EXCEPT WHERE MOISTURE CARRYOVER FROM OUTDOOR AIR LOUVER WILL OCCUR.		G. THE TEST FOR EQUIPMENT CONNECTED AND DRIVEN BY A VARIABLE FREQUENCY DRIVE SHALL INCLUDE NATURAL CRITICAL SPEED TESTING.	
N. PROVIDE ALL NECESSARY FLASHING AND COUNTERFLASHING TO MAINTAIN THE WATERPROOFING INTEGRITY OF THE BUILDING AS REQUIRED BY THE INSTALLATION OR REMOVAL OF PIPES, DUCTS, LOUVERS, CONDOUT, AND EQUIPMENT. PROVIDE EQUIPMENT CURBS AND DRAINAGE STEEL AS REQUIRED.		8) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		7) VIBRATION ISOLATION.		1) 2 INCH DUCT CLASS AND LESS: ALL OTHER LOW PRESSURE DUCTWORK, SEAL CLASS "C", LEAKAGE CLASS 24 (RECTANGULAR) OR CLASS "2" (ROUND).		4) ALL MIXED AIR PLenums, EXCEPT WHERE MOISTURE CARRYOVER FROM OUTDOOR AIR LOUVER WILL OCCUR.		5) ALSO, WHERE NOTED ON A DRAWING.		H. MEASUREMENTS SHALL BE TAKEN THROUGHOUT THE OPERATING RANGE OF THE EQUIPMENT STARTING FROM A COMPLETE STOP, RAMPING SLOWLY UP TO MAXIMUM SPEED AND PAUSING BRIEFLY AT ELECTRICAL AND MECHANICAL, NATURAL FREQUENCIES OF THE EQUIPMENT/VFD FROM 0 TO 60 HZ.	
O. ALL PRESENT MATERIAL, EQUIPMENT AND CONSTRUCTION DEBRIS TO BE REMOVED UNDER THIS CONTRACT SHALL BECOME THE PROPERTY OF THE CONTRACTOR WITH THE EXCEPTION OF SPECIFIC EQUIPMENT AND APPARATUS REQUESTED BY THE BUILDING REPRESENTATIVE. ARCHITECT OR AS NOTED TO BE RELOCATED ON THE DRAWINGS SHALL BE PROPERLY DISPOSED OF BY THIS CONTRACTOR.		9) "SIMILAR" OR "EQUAL": EQUAL, IN MATERIALS, WEIGHT, SIZE, DESIGN AND EFFICIENCY OF SPECIFIED PRODUCT.		8) DAMPER AND VALVE ACTUATORS.		2) ALL OUTSIDE AIR, EXHAUST, AND RELIEF DUCTWORK WITH 5 FEET OF LOUVERS SHALL BE ALUMINUM WITH SEAMS SEALED WATER TIGHT WITH ALCOA ALUMINUMATIC TYPE C SEAM SEALER OR SOLDER. PITCH DUCTWORK TOWARDS LOUVER.		5) RETURN AIR STUB DUCTS AT MER WALLS AND SHAFT INTAKE OPENINGS FOR FULL LENGTH.		6) SOUNDING IN DUCTWORK: FIBROUS GLASS, MINIMUM 3 LB DENSITY, 1 INCH THICKNESS, MAXIMUM 0.25 X FACTOR AT 75 DEG F MEAN TEMPERATURE WITH ACRYLIC COATED FINISH FACTORY APPLIED EDGE COATING AND STENCILED IN ACCORDANCE WITH NFPA 90A. FLAME SPREAD SHALL BE A MAXIMUM OF 25. LINING SHALL NOT SUPPORT MICROBIAL GROWTH AND SHALL BE TESTED IN ACCORDANCE WITH ASTM C 1071 AND ASTM G21/G22, SIMILAR TO MANVILLE PERMACOTE LINACUSTIC.		I. INSULATION - GENERAL REQUIREMENTS	
P. MATERIALS AND WORKMANSHIP, UNLESS OTHERWISE NOTED, SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.		10) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		9) AUTOMATIC CONTROL SYSTEMS AND DEVICES.		A. THIS CONTRACTOR SHALL SUBMIT TO THE ARCHITECT FOR APPROVAL A PLAN INDICATING THE SIZE (MINIMUM 18 INCH X 18 INCH) AND LOCATION OF ALL ACCESS DOORS REQUIRED FOR OPERATION AND MAINTENANCE OF ALL CONCEALED EQUIPMENT, DEVICES, VALVES, DAMPERS AND CONTROLS. CONTRACTOR SHALL ARRANGE FOR FURNISHING AND INSTALLATION OF ALL ACCESS DOORS IN FINISHED CONSTRUCTION AND INCLUDE COSTS IN THE BID.		6) SOUNDING IN DUCTWORK: FIBROUS GLASS, MINIMUM 3 LB DENSITY, 1 INCH THICKNESS, MAXIMUM 0.25 X FACTOR AT 75 DEG F MEAN TEMPERATURE WITH ACRYLIC COATED FINISH FACTORY APPLIED EDGE COATING AND STENCILED IN ACCORDANCE WITH NFPA 90A. FLAME SPREAD SHALL BE A MAXIMUM OF 25. LINING SHALL NOT SUPPORT MICROBIAL GROWTH AND SHALL BE TESTED IN ACCORDANCE WITH ASTM C 1071 AND ASTM G21/G22, SIMILAR TO MANVILLE PERMACOTE LINACUSTIC.		7) INSULATION - GENERAL REQUIREMENTS		A. ALL INSULATION MATERIALS, INCLUDING JACKETS, FACING, ADHESIVE COATINGS, AND ACCESSORIES ARE TO BE FIRE HAZARD RATED AND LISTED BY UNDERWRITERS LABORATORIES, INC. USING STENNER TUNNEL TEST METHOD FOR FIRE HAZARD CLASSIFICATION OF BUILDING MATERIALS. STANDARD UL 723 (ASTM E-84), (ASTA A25-1983), FLAME SPREAD: MAXIMUM 25. FUEL CONTRIBUTED AND SMOKE DEVELOPED: MAXIMUM 50. FLAME-PROOFING TREATMENTS SUBJECT TO DETEIORATION FROM MOISTURE OR HUMIDITY ARE NOT ACCEPTABLE.	
Q. THE WORK IN THE BUILDING SHALL BE DONE WHEN AND AS DIRECTED, AND IN A MANNER SATISFACTORY TO THE OWNER. THE WORK SHALL BE PERFORMED SO AS TO CAUSE THE LEAST POSSIBLE INCONVENIENCE AND DISTURBANCE TO THE PRESENT OCCUPANTS.		11) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		10) SEQUENCE OF OPERATIONS		B. EXCEPT AS OTHERWISE SHOWN OR NOTED, ALL DUCTWORK AND OTHER SHEET METAL WORK SHALL BE GALVANIZED STEEL.		8) SOUNDING IN DUCTWORK: FIBROUS GLASS, MINIMUM 3 LB DENSITY, 1 INCH THICKNESS, MAXIMUM 0.25 X FACTOR AT 75 DEG F MEAN TEMPERATURE WITH ACRYLIC COATED FINISH FACTORY APPLIED EDGE COATING AND STENCILED IN ACCORDANCE WITH NFPA 90A. FLAME SPREAD SHALL BE A MAXIMUM OF 25. LINING SHALL NOT SUPPORT MICROBIAL GROWTH AND SHALL BE TESTED IN ACCORDANCE WITH ASTM C 1071 AND ASTM G21/G22, SIMILAR TO MANVILLE PERMACOTE LINACUSTIC.		9) INSULATION - GENERAL REQUIREMENTS		A. ALL INSULATION MATERIALS, INCLUDING JACKETS, FACING, ADHESIVE COATINGS, AND ACCESSORIES ARE TO BE FIRE HAZARD RATED AND LISTED BY UNDERWRITERS LABORATORIES, INC. USING STENNER TUNNEL TEST METHOD FOR FIRE HAZARD CLASSIFICATION OF BUILDING MATERIALS. STANDARD UL 723 (ASTM E-84), (ASTA A25-1983), FLAME SPREAD: MAXIMUM 25. FUEL CONTRIBUTED AND SMOKE DEVELOPED: MAXIMUM 50. FLAME-PROOFING TREATMENTS SUBJECT TO DETEIORATION FROM MOISTURE OR HUMIDITY ARE NOT ACCEPTABLE.	
R. THE CONTRACTOR'S PROPOSAL FOR ALL WORK SHALL BE PRECIDIATED ON THE PERFORMANCE OF THE WORK DURING REGULAR WORKING HOURS. WHEN SO DIRECTED, HOWEVER, THE CONTRACTOR SHALL INSTALL WORK IN OVERTIME AND THE ADDITIONAL COST TO BE CHARGED THEREFORE SHALL BE ONLY THE "PREMIUM" PORTION OF THE WAGES PAID.		12) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		I. COORDINATION DRAWINGS: PLANS, DRAWN TO SCALE INDICATING COORDINATION BETWEEN THE TRADES USING INPUT FROM INSTALLERS OF THE ITEMS INVOLVED.		C. DESCRIPTION OF DUCTWORK PRESSURE CLASS AND EQUIPMENT:		9) INSULATION - GENERAL REQUIREMENTS		A. ALL INSULATION MATERIALS, INCLUDING JACKETS, FACING, ADHESIVE COATINGS, AND ACCESSORIES ARE TO BE FIRE HAZARD RATED AND LISTED BY UNDERWRITERS LABORATORIES, INC. USING STENNER TUNNEL TEST METHOD FOR FIRE HAZARD CLASSIFICATION OF BUILDING MATERIALS. STANDARD UL 723 (ASTM E-84), (ASTA A25-1983), FLAME SPREAD: MAXIMUM 25. FUEL CONTRIBUTED AND SMOKE DEVELOPED: MAXIMUM 50. FLAME-PROOFING TREATMENTS SUBJECT TO DETEIORATION FROM MOISTURE OR HUMIDITY ARE NOT ACCEPTABLE.		B. PRODUCTS SHALL NOT CONTAIN ASBESTOS, LEAD, MERCURY, OR MERCURY COMPOUNDS.	
S. UNLESS OTHERWISE SPECIFICALLY SPECIFIED, INCLUDE ALL CUTTING AND PATCHING OF EXISTING FLOORS, WALLS, PARTITIONS AND OTHER MATERIALS IN THE EXISTING BUILDING. THE CONTRACTOR SHALL RESTORE THESE AREAS TO ORIGINAL CONDITION.		13) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		J. COORDINATION DRAWINGS: PLANS, DRAWN TO SCALE INDICATING COORDINATION BETWEEN THE TRADES USING INPUT FROM INSTALLERS OF THE ITEMS INVOLVED.		1) 2 INCH DUCT CLASS AND LESS: ALL OTHER LOW PRESSURE DUCTWORK, SEAL CLASS "C", LEAKAGE CLASS 24 (RECTANGULAR) OR CLASS "2" (ROUND).		10) INSULATION - GENERAL REQUIREMENTS		A. ALL INSULATION MATERIALS, INCLUDING JACKETS, FACING, ADHESIVE COATINGS, AND ACCESSORIES ARE TO BE FIRE HAZARD RATED AND LISTED BY UNDERWRITERS LABORATORIES, INC. USING STENNER TUNNEL TEST METHOD FOR FIRE HAZARD CLASSIFICATION OF BUILDING MATERIALS. STANDARD UL 723 (ASTM E-84), (ASTA A25-1983), FLAME SPREAD: MAXIMUM 25. FUEL CONTRIBUTED AND SMOKE DEVELOPED: MAXIMUM 50. FLAME-PROOFING TREATMENTS SUBJECT TO DETEIORATION FROM MOISTURE OR HUMIDITY ARE NOT ACCEPTABLE.		C. DEFINITIONS	
T. REMOVABLE ACCESS TIE AND/OR ACCESS DOOR ARE REQUIRED IN HUNG CEILING, SHAFTS AND WALLS FOR ALL VOLUME AND FIRE DAMPERS, AUTOMATIC DAMPERS AND ALL OTHER MECHANICAL EQUIPMENT AND DEVICES. HVAC CONTRACTOR TO FURNISH ACCESS LOCATION REQUIREMENTS TO GENERAL CONTRACTOR. ACCESS TIE IDENTIFICATION: PROVIDE BUTTONS, TABS, AND MARKERS TO IDENTIFY LOCATION OF CONCEALED VALVES, DAMPERS AND EQUIPMENT.		14) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		K. COORDINATION DRAWINGS: PLANS, DRAWN TO SCALE INDICATING COORDINATION BETWEEN THE TRADES USING INPUT FROM INSTALLERS OF THE ITEMS INVOLVED.		2) ALL OUTSIDE AIR, EXHAUST, AND RELIEF DUCTWORK WITH 5 FEET OF LOUVERS SHALL BE ALUMINUM WITH SEAMS SEALED WATER TIGHT WITH ALCOA ALUMINUMATIC TYPE C SEAM SEALER OR SOLDER. PITCH DUCTWORK TOWARDS LOUVER.		11) INSULATION - GENERAL REQUIREMENTS		D. UPON COMPLETION OF THE INSTALLATION, THE CONTRACTOR SHALL REBALANCE ANY EXISTING PORTIONS OF AIR DISTRIBUTION SYSTEM AFFECTED BY THE RENOVATION AND ALSO BALANCE ALL NEW WORK.		1) EXPOSED: INDOOR DUCTS, PIPING OR EQUIPMENT LOCATED IN MECHANICAL EQUIPMENT ROOMS AND IN AREAS WHICH WILL BE VISIBLE WITHOUT REMOVING CEILING OR OPENING ACCESS PANELS.	
U. ALL EQUIPMENT SHALL BE APPROVED FOR USE IN NYC AND/OR SHALL HAVE A BSA NUMBER. THIS INFORMATION MUST BE INCLUDED IN THE SUBMITTAL PACKAGE.		15) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		L. COORDINATION DRAWINGS: PLANS, DRAWN TO SCALE INDICATING COORDINATION BETWEEN THE TRADES USING INPUT FROM INSTALLERS OF THE ITEMS INVOLVED.		3) WIRE MESH SCREEN (WMS): NO. 16 USS, 34 SQUARE MESH, IN 1 INCH WIDE GALVANIZED STEEL ENCLLOSING FRAME. FLANGED DUCT OPENING TO REUSE FRAME.		12) TESTING AND BALANCING		E. IF DISCREPANCIES EXIST IN THE REPORT THAT REQUIRE FIELD VERIFICATION, THE TESTING AND BALANCING COMPANY IN THE PRESENCE OF THE ENGINEER SHALL VISIT THE JOBSITE FOR FIELD VERIFICATION OF THE REPORT.		2) CONCEALED: INDOOR DUCTS, PIPING OR EQUIPMENT WHICH IS NOT EXPOSED.	
V. ALL MATERIAL AND EQUIPMENT TO BE NEW UNLESS OTHERWISE NOTED AND SHALL BE IN ACCORDANCE WITH BUILDING STANDARDS.		16) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		M. COORDINATION DRAWINGS: PLANS, DRAWN TO SCALE INDICATING COORDINATION BETWEEN THE TRADES USING INPUT FROM INSTALLERS OF THE ITEMS INVOLVED.		4. EXISTING DUCTWORK TO BE REUSED:		13) TESTING AND BALANCING		F. THE CONTRACTOR SHALL PROVIDE ALL LABOR, PRESSURE GAUGES, FLOW METERS, SHEAVES, AND BELTS REQUIRED TO BALANCE SYSTEMS.		3) OUTDOOR: DUCTS, PIPING OR EQUIPMENT WHICH IS EXPOSED TO THE WEATHER.	
W. SUBMISSION OF A PROPOSAL SHALL BE CONSTRUED AS EVIDENCE THAT A CAREFUL EXAMINATION OF THE PORTIONS OF THE EXISTING BUILDING, EQUIPMENT, ETC., WHICH AFFECT THIS WORK, AND THE ACCESS TO SUCH SPACES, HAS BEEN MADE AND THAT THE CONTRACTOR IS FAMILIAR WITH EXISTING CONDITIONS AND DIFFICULTIES THAT WILL AFFECT THE EXECUTION OF THE WORK. LATER CLAIMS SHALL NOT BE MADE FOR LABOR, EQUIPMENT OR MATERIALS REQUIRED BECAUSE OF DIFFICULTIES ENCOUNTERED WHICH COULD HAVE BEEN FORESEEN DURING SUCH AN EXAMINATION. THE ON-SITE INSPECTION SHALL VERIFY EXISTING DUCTWORK, PIPING (SIZES, CLEARANCES, ETC) AND CONDITIONS.		17) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		N. COORDINATION DRAWINGS: PLANS, DRAWN TO SCALE INDICATING COORDINATION BETWEEN THE TRADES USING INPUT FROM INSTALLERS OF THE ITEMS INVOLVED.		5. AS-BUILTS AND EQUIPMENT OPERATION INSTRUCTIONS		14) TESTING AND BALANCING		G. BALANCING REPORT SHALL BE PROVIDED ON NEBB OR AABC-TYPE FORMS.		1) SUPPLY/RETURN (CONCEALED): 2 INCH THICK, D-1 MATERIAL, VAPORSEAL FINISH.	
X. INSURANCE: IN ACCORDANCE WITH BUILDING REQUIREMENTS AND SHALL INCLUDE A HOLD HARMLESS CLAUSE FOR OWNER AND ENGINEER.		18) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		O. INSULATION (ISSQUARE FEET)		A. PROVIDE MANUAL, VOLUME DAMPERS TO PROPERLY PROVIDE MANUAL BALANCING VOLUME DAMPERS AS REQUIRED TO PROPERLY BALANCE THE AIR DISTRIBUTION SYSTEM. IF THE LOCATION OF BALANCING DAMPERS ARE NOT DEFINED ON THE DRAWINGS, THE FOLLOWING MINIMUM STANDARDS SHALL GOVERN:		15. DUCTWORK INSULATION		H. BALANCING AND TESTING SHALL BE PERFORMED AND SUPERVISED BY A		2) RETURN (CONCEALED IN UNCONDITIONED SPACES): 2 INCH THICK, D-1 MATERIAL, ALL LOCATIONS.	
Y. THE FINAL ACCEPTANCE WILL BE MADE AFTER THE CONTRACTOR HAS ADJUSTED HIS EQUIPMENT, BALANCED THE VARIOUS SYSTEMS, DEMONSTRATED THAT IT FULLY FULFILLS THE REQUIREMENTS OF THE DRAWINGS AND SPECIFICATIONS AND HAS FURNISHED ALL THE REQUIRED CERTIFICATES OF INSPECTION AND APPROVAL.		19) "EXPPOSED": NOT INSTALLED UNDERGROUND OR "CONCEALED" AS DEFINED ABOVE.		DESCRIPTION PIPING (FIBERGLASS) DUCTWORK (FIBERGLASS) ACOUSTIC LINING (ISSQUARE FEET)		A. LOW PRESSURE: ALL SUPPLY AIR MAIN BRANCHES FROM TR							