# SECTION 11 66 23 - GYMNASIUM EQUIPMENT

# PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Volleyball equipment.

#### 1.3 DEFINITIONS

A. FIVB: Federation Internationale de Volleyball (The International Volleyball Federation).

# 1.4 PREINSTALLATION MEETINGS

A. Preinstallation Conference: Conduct conference at Project site.

#### 1.5 SUBMITTALS, GENERAL

A. General: Submit all action submittals and informational submittals required by this Section concurrently.

#### 1.6 ACTION SUBMITTALS

- A. Product Data: For each type of product indicated. Include assembly, disassembly, and storage instructions for removable equipment.
  - 1. Volleyball Equipment:
    - a. Floor insert.
- B. Shop Drawings: For gymnasium equipment.
  - 1. Include details of field assembly for removable equipment, connections, installation, mountings, floor inserts, and operational clearances.

# 1.7 INFORMATIONAL SUBMITTALS

A. Setting Drawings: For embedded items and cutouts required in other work.

### 1.8 CLOSEOUT SUBMITTALS

A. Operation and Maintenance Data: For gymnasium equipment to include in operation and maintenance manuals.

## 1.9 FIELD CONDITIONS

A. Field Measurements: Verify position and elevation of floor inserts and layout for gymnasium equipment.

## PART 2 - PRODUCTS

## 2.1 VOLLEYBALL EQUIPMENT

- A. Source Limitations: Obtain from single source from single manufacturer.
- B. Floor Insert: Brass-plated or solid brass floor plate and steel pipe sleeve, concealed by floor plate, with capped bottom end, sized with ID to fit post standards, minimum length required, to securely anchor pipe sleeve as indicated on Drawings; with anchors designed for securing floor insert to floor substrate indicated; quantity as indicated on Drawings.
  - 1. Floor Plate: Lockable swivel access cover, designed for use with wood floors and to be flush with adjacent flooring. Provide two tool(s) for unlocking access covers.

### 2.2 MATERIALS

A. Anchors, Fasteners, Fittings, and Hardware: Gymnasium equipment manufacturer's standard corrosion-resistant or noncorrodible units; concealed; tamperproof, vandal- and theft-resistant design.

# PART 3 - EXECUTION

#### 3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, with Installer present, for compliance with requirements for court layout, alignment of mounting substrates, installation tolerances, operational clearances, and other conditions affecting performance of the Work.
  - 1. Verify critical dimensions.
  - 2. Examine supporting structure, subfloors, and footings below finished floor.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.
- C. Beginning installation constitutes Contractor's acceptance of substrates and conditions.

# 3.2 INSTALLATION, GENERAL

- A. Install gymnasium equipment after other finishing operations, including painting, have been completed unless otherwise indicated.
- B. Permanently Placed Gymnasium Equipment and Components: Install rigid, level, plumb, square, and true; anchored securely to supporting structure; positioned at locations and elevations indicated; in proper relationship to adjacent construction; and aligned with court layout.
  - 1. Floor-Insert Locations: Coordinate locations with application of game lines and markers, and core drill floor for inserts after game lines are applied.
  - 2. Floor-Insert Elevation: Coordinate installed heights of floor inserts with installation and field finishing of finish flooring and floor-plate type.

# 3.3 ADJUSTING

A. Adjust movable components of gymnasium equipment to operate safely, smoothly, easily, and quietly; free from binding, warp, distortion, nonalignment, misplacement, disruption, or malfunction, throughout entire operational range; and lubricate as recommended in writing by manufacturer.

END OF SECTION 11 66 23