



GENERAL ELECTRICAL NOTES:


1. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR SUPPLYING, INSTALLING AND CONNECTING ALL LINE AND LOW VOLTAGE CONDUIT, CONDUCTORS, SWITCHES, DISCONNECTS, JUNCTION BOXES, AND FIXTURES FOR POWER, TELECOMMUNICATIONS, AND LIGHTING SYSTEMS.
2. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR SUPPLYING, INSTALLING, AND CONNECTING ALL CONTROL CONDUIT AND CONDUCTORS FOR CONTROL SYSTEM.
3. THE ELECTRICAL CONTRACTOR SHALL SUPPLY, RIG AND MOUNT THE NEW TRANSFER SWITCH AND ASSOCIATED COMPONENTS.
4. THE ELECTRICAL CONTRACTOR SHALL PROVIDE ATS START UP AND TESTING.
5. LABEL ALL PANELS, DISCONNECTS, MOTOR STARTERS, AND CONTROLLERS. ALL LABELS ARE TO BE SELF ADHERING PLASTIC LAMINATED WITH 3/8" WHITE LETTERS ON A BLACK BACKGROUND. ALL DEVICES WILL BE IDENTIFIED BY THEIR NUMBER, VOLTAGE AND SOURCE OF POWER.
6. PROVIDE A TYPEWRITTEN CIRCUIT DIRECTORY IN ALL NEW PANEL BOXES.
7. THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR ARRANGING AND SCHEDULING ALL ELECTRICAL INSPECTIONS, PAY ALL FEES, AND SUBMIT A FINAL INSPECTION REPORT TO THE ENGINEER.
8. THE ELECTRICAL CONTRACTOR SHALL INSTALL ALL GROUNDING IN ACCORDANCE WITH NEC ARTICLE 250 AND ACCORDING TO THE REQUIREMENTS INDICATED ON THE DRAWINGS. EQUIPMENT GROUNDING CONDUCTORS SHALL BE USED. GROUNDING THROUGH RACEWAY AND CONDUITS IS NOT PERMITTED.
9. THE ELECTRICAL CONTRACTOR SHALL FURNISH AND INSTALL GROUND CONDUCTORS TO BOND THE WTP GROUNDING SYSTEM TOGETHER.
10. THE LOCATIONS AND ROUTES OF CONDUITS AND RACEWAYS SHOWN ON THESE DRAWINGS ARE SCHEMATIC. ALL CONDUITS ABOVE THE SLAB SHALL BE INSTALLED PARALLEL OR PERPENDICULAR TO THE BUILDING. CONDUITS ABOVE THE CEILING SHALL BE MOUNTED AS HIGH AS POSSIBLE. ALL BELOW GROUND CONDUITS SHALL BE INSTALLED USING THE MOST DIRECT ROUTE WITH CONSIDERATION OF PROPER COORDINATION WITH OTHER UTILITIES - UNDERGROUND OR ABOVE GROUND.
11. THE ELECTRICAL CONTRACTOR SHALL PROVIDE ALL CONDUIT AND CONDUCTORS FOR TELEPHONE AND LAN SYSTEMS. ALL CONDUCTORS SHALL BE COPPER WITH TYPE THHN/THWN OR XHHW INSULATION UNLESS OTHERWISE NOTED. ALL CONDUIT AND CONDUCTORS SHALL BE SIZED PER NEC.
12. THE ELECTRICAL CONTRACTOR SHALL PROVIDE LAMPS FOR ALL LIGHTING FIXTURES.
13. ALL DUPLEX RECEPTACLES SHALL BE MOUNTED VERTICALLY AND 18" NOMINALLY AFF TO BOTTOM OF BOX UNLESS OTHERWISE INDICATED.
14. ALL LIGHTING SHALL BE WARRANTED BY THE MANUFACTURER FOR 5 YEARS. ALL LIGHTING THAT FAIL WITHIN THE FIRST YEAR OF SUBSTANTIAL COMPLETION SHALL BE REPLACED BY THE ELECTRICAL CONTRACTOR AT NO COST TO THE OWNER.
15. FASTENING OF HANGERS TO THE ROOF WILL NOT BE PERMITTED. ANY CONTRACTOR RESPONSIBLE FOR PUNCTURING THE ROOF STRUCTURE WILL REPAIR THE ROOF AT THEIR EXPENSE.
16. ALL DISCONNECT SWITCHES AND SAFETY SWITCHES ARE TO BE HEAVY DUTY TYPE.
17. MC CABLE WILL NOT BE ACCEPTED.
18. "GREENFIELD" AND LIQUID TIGHT FLEX CONDUIT MAY BE USED IN LENGTHS NOT TO EXCEED 72".
19. THE ELECTRICAL CONTRACTOR SHALL CAULK ALL PENETRATIONS RELATED TO ELECTRICAL WORK, IN 1 & 2 RATED HR FIRE WALL WITH 3M FIRE CAULK. SEAL LARGER OPENINGS WITH WIREMOLD "FLAMESTOPPER" KIT.
20. ALL EXTERIOR EXPOSED CONDUIT SHALL BE PVC COATED GRC.
21. ALL CONDUIT IN CLASS 1 DIV 1 LOCATIONS SHALL BE PVC COATED GRC.
22. THE ELECTRICAL CONTRACTOR SHALL PROVIDE SEAL OFFS FOR ALL CONDUIT BETWEEN CLASSIFIED AND UNCLASSIFIED LOCATIONS.
23. ALL CONDUIT IN CHEMICAL ROOMS SHALL BE PVC.
24. ALL OTHER INTERIOR CONDUIT SHALL BE GRC.
25. THE ELECTRICAL CONTRACTOR SHALL FURNISH AND INSTALL ALL EQUIPMENT CONDUIT AND CONDUCTORS FOR THE HVAC EQUIPMENT. THIS SHALL INCLUDE LINE AND LOW VOLTAGE EQUIPMENT.
26. THE ELECTRICAL CONTRACTOR SHALL FURNISH AND INSTALL ALL FIBER OPTIC CABLE AND CONDUITS FOR THE FIBER RUNS.
27. THE SCADA VENDOR SHALL BE RESPONSIBLE FOR ALL FIBER OPTIC TERMINATIONS AND TESTING.
28. THE SCADA VENDOR SHALL PROVIDE ALL TERMINATIONS FOR SCADA VENDOR SUPPLIED PANELS. SCADA VENDOR SHALL PROVIDE CONTROL PANEL START UP.
29. THE ELECTRICAL CONTRACTOR SHALL FURNISH, INSTALL, AND TERMINATE ALL CONDUIT AND CONDUCTORS FOR VENDOR SUPPLIED CONTROL PANELS.



GROUND GRID EXOTHERMIC CONNECTION TO BUILDING FOUNDATION REINFORCING BAR  
SIZE AS INDICATED ON DRAWINGS



MAIN GROUND GRID CONDUCTOR BELOW GRADE (BURY 30" BELOW GRADE THROUGHOUT)  
SIZE AS INDICATED ON DRAWINGS



3/4"x 10' COPPER CLAD GROUND ROD WITH EXOTHERMIC CONNECTION TO MAIN GROUND GRID CONDUCTOR




GROUND GRID RISER CONDUCTOR THROUGH SLAB FOR CONNECTION TO COLUMN, EQUIPMENT, ETC.



EXOTHERMIC CONNECTION BETWEEN GROUND GRID CONDUCTORS



NEW PANEL



HOMERUN  
GP = GENERAL PURPOSE PANEL 'GP'  
2 = CIRCUIT No.



CONDUIT UP



CONDUIT DOWN



FLEXIBLE CONDUIT CONNECTION



SPECIAL USE RECEPTACLE  
REFER TO INFORMATION ON INDIVIDUAL DRAWINGS



RECEPTACLE  
GF = GROUND FAULT  
WP = WEATHERPROOF  
CKT = CIRCUIT



SINGLE RECEPTACLE



SWITCH  
A = SWITCHING SCHEME  
3 = 3 WAY  
4 = 4 WAY  
M = MOTOR STARTER TYPE



NEW TELEPHONE JACK



NEW ETHERNET JACK




WALL MOUNTED DOOR HOLDER

SYMBOLS



LIGHTNING ARRESTER




CIRCUIT BREAKER  
△ = DRAW-OUT  
1600 = AMP FRAME SIZE  
1200 = AMP TRIP SENSOR  
SST = SOLID STATE TRIP UNIT  
LT = LONG TIME TRIP FUNCTION  
ST = SHORT TIME TRIP FUNCTION  
IT = INSTANTANEOUS TRIP FUNCTION



CIRCUIT BREAKER  
400 = AMP FRAME SIZE  
300 = AMP TRIP RATING



DRAW-OUT TYPE POWER CIRCUIT BREAKER



DELTA-WYE TRANSFORMER  
SIZE AS INDICATED ON DRAWINGS



POTENTIAL TRANSFORMER



CURRENT TRANSFORMER



SOLID STATE SOFT STARTER



LOCAL START / LOCK STOP CONTROLLER



TRANSIENT VOLTAGE SURGE SUPPRESSION



FIRE ALARM CONTROL PANEL



RADIO TRANSCEIVER



OMNI DIRECTIONAL ANTENNA WITH MODULE



SOUNDER STROBE



60 MIN TIMER



FLOW METER CONTROL BOX TRANSMITTER



FLOW METER



ANNUNCIATOR PANEL



ADDRESSABLE MINI MODULE



NORMALLY OPEN CONTACT



NORMALLY CLOSED CONTACT



DISCONNECT SWITCH



DISCONNECT SWITCH



COMBINATION DISCONNECT SWITCH MOTOR STARTER  
GREENHECK MODEL AS INDICATED ON CONDUIT SCHEDULE



EMERGENCY STOP



MOTOR  
SIZE AS INDICATED ON DRAWINGS  
X = HORSEPOWER



KEY INTERLOCK



JUNCTION BOX



SIZE  
80E = RATING



GENERATOR  
SIZE AS INDICATED ON DRAWINGS



VARIABLE FREQUENCY DRIVE



METHANE SENSOR



OXYGEN SENSOR



H2S SENSOR



STROBE LIGHT



FIRE ALARM PULL STATION WITH KEY RESET



PHOTOELECTRIC SMOKE DETECTOR



EXPLOSION PROOF SMOKE DETECTOR



EXPLOSION PROOF FIRE PULL STATION WITH KEY RESET



EXTERIOR STROBE LIGHT WITH HORN



HEAT DETECTOR  
X = RATE OF RISE IN DEGREES




SUPPRESSION SYSTEM SUPERVISION

DATE: 9/30/2024  
DRAWN BY: EMB  
SCALE: NTS  
REVIEWED BY: RF  
PROJECT NO.:  
FILE:

DELAWARE  
ENGINEERING, D.P.C.

CIVIL AND ENVIRONMENTAL ENGINEERING

28 MADISON AVENUE EXTENSION, ALBANY, NY 12203 - 518.452.1290  
55 SOUTH MAIN ST ONEONTA, NY 13820 - 607.432.8073  
31 NORTH MAIN STREET, LIBERTY, NY 12544 - 518.452.1471 39862  
16 EAST MARKET STREET RED HOOK, NY 12571 - 518.452.1290  
548 BROADWAY, MONTICELLO, NY 12071 - 845.791.7777



REVISIONS		DESCRIPTION
NO.	DATE	

RHINEBECK WTP  
PLANT IMPROVEMENTS  
VILLAGE OF RHINEBECK  
DUTCHESS COUNTY, NEW YORK

ELECTRICAL NOTES &  
LEGEND

SHEET:  
E-001