## Wall Indication Legend

EXISTING WALLS TO REMAIN EXISTING TO BE REMOVED

## General Demolition Notes

CEASE OPERATION AND NOTIFY ARCHITECT IMMEDIATELY IF SAFETY OF STRUCTURE APPEARS TO BE ENDANGERED. TAKE PRECAUTIONS TO SUPPORT STRUCTURE UNTIL DETERMINATION IS MADE FOR CONTINUING OPERATIONS.

DEMOLITION DRAWINGS DO NOT INCLUDE MECHANICAL/ELECTRICAL DEMOLITION AND ITS AFFECTS ON DEMOLITION OF GENERAL CONSTRUCTION ITEMS. CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTION

OF ALL EXISTING ELEMENTS TO REMAIN FROM ANY

DAMAGE DURING DEMOLITION.

## **General Demolition Notes**

THE CONTRACTOR SHALL PATCH AND REPAIR ALL EXISTING ADJACENT CONSTRUCTION AS MAY BE REQUIRED AFTER DEMOLITION TO PROVIDE A COMPLETE INSTALLATION.


THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING AND LEGALLY DISPOSING OF ALL DEBRIS CAUSED BY DEMOLITION. THE CONTRACTOR SHALL NOT ALLOW ANY EXCESSIVE DEBRIS TO ACCUMULATE ON THE SITE AT ANY TIME.

CONTRACTOR TO CEASE WORK AND NOTIFY OWNER SHOULD ANY HAZARDOUS MATERIALS BE ENCOUNTERED AND PERFORM ABATEMENT/ REMEDIATION WORK ACCORDINGLY.


ALL EXIST BASEBOARD HEATERS TO REMAIN.

## **Keyed Demolition**

- REMOVE EXIST CEILING TILE OR
- REMOVE EXIST LIGHTING FIXTURES ELECTRICAL DUGS.
- . REMOVE EXIST PLUMBING FIXTURE
- REMOVE AND REPLACE EXIST PL
- 5. REMOVE ALL EXIST PLUMBING AN DEFUNCT.
- 6. REMOVE EXIST DOOR COMPLETE. REMOVE AND REPLACE EXIST DO HARDWARE COMPLETE.
- REMOVE EXIST DOOR, FRAME, ANI COMPLETE, INFILL OPENING WITH L CONSTRUCTION.
- REMOVE EXIST DOOR AND FRAME OPENING WITH LIKE MATERIALS.



Notes #	DEMOLITION NOTE SYMBOL		
R GWB COMPLETE, REG, REFER TO	10. REMOVE PORTION OF WALL AND RECONSTRUCT TO PROVIDE NEW DOOR - REFER TO SCHEDULE FOR SIZE.	<ol> <li>REMOVE EXIST BAR CABINETS COMPLETE.</li> <li>REMOVE TROPHY CASE DISPLAY COMPLETE.</li> <li>REMOVE EXIST LOCKER.</li> </ol>	28. REMOVE EXIST TREES. 29. REMOVE EXIST FLUE.
URE COMPLETE. PLUMBING FIXTURE.	11. REMOVE AND REPLACE EXIST WINDOW COMPLETE (ADD ALT).	20. REMOVE ALL EXIST EQUIPMENT AND WIRING.	30. REMOVE EXIST CONCRETE SLAB. 31. REMOVE AND REPLACE EXIST DAMAGED FASCIA
AND ELECTRICAL	12. REMOVE EXIST AC WINDOW UNIT AND REMOVE EXIST WINDOW COMPLETE, REPLACE WITH NEW WINDOW.	21. REMOVE EXIST SHELVING. 22. REMOVE AND REPLACE EXIST HANDRAILS.	IN KIND WITH NEW (5 1/4×4 AND 5 1/4×10). 32. EXIST OUTDOOR STORAGE CONTAINER TO BE
TE, DOOR, FRAME, AND	13. REMOVE EXIST WINDOW AND INFILL OPENING WITH LIKE CONSTRUCTION.	23. REMOVE AND REPLACE EXIGT STAIR FINISH ON TREADS AND RISERS.	REMOVED. 33. MECHANICAL EQUIPMENT TO BE REMOVED, REFER TO MECHANICAL DWGS FOR NEW EQUIPMENT.
AND HARDWARE	14. REMOVE EXIST WALL PARTITION COMPLETE.	24. REMOVE EXIST CLOSET. 25. REMOVE AND/OR RELOCATE EXIST ELECTRICAL	34. EXIST ROOF MEMBRANE TO REMAIN.
	COMPLETE.	26. REMOVE EXIST KITCHEN EQUIPMENT COMPLETE.	35. EXIST ASPHALT SHINGLED MANSARD ROOF TO REMAIN.
AME AND INFILL 5.	INFILL EXIST M.O. W/ LIKE MATERIALS.	27. REMOVE EXIST TILE WALL AT KITCHEN.	36. EXIST WALL MOUNTED ROOF ANTENNAE TO BE REMOVED.



- 37. EXIST VENT TO REMAIN.
- 38. REMOVE FAN OR VENT AND INFILL OPENING WITH LIKE CONSTRUCTION.
- 39, REMOVE EXISTING LOUVRE AND INFILL OPENING WITH LIKE CONSTRUCTION.
- 40, REMOVE EXIST BATHROOM STALL PARTITIONS. 41. REMOVE AND REUSE (IF POSSIBLE) EXIST DOOR
- AND FRAME, PROVIDE NEW HARDWARE. 42. REMOVE AND INFILL EXIST BOILER INTAKE AIR
- VENT. 43. UPGRADE DCV BACKFLOW TO RPZ.
- 44. REMOVE PORTION OF MANSARD ROOF TO
- 45. REMOVE EXIST SUSPENDED AHU AND ASSOCIATED

- DUCTWORK.
- 46. REMOVE EXIST OIL TANK.
- 47. REMOVE EXIST 4x4 POST.
- 48, REMOVE EXIST ROOFTOP EQUIPMENT, INFILL WITH LIKE CONSTRUCTION AND PATCH ROOFING AS REQUIRED.

ARCHITECI

Joseph G. Thompson Architect, PLLC

108 N Division Street, Ste 100

Peekskill, New York 10566

PH: (8 4 5) 5 3 2 - 8 1 5 6

EM: joe@jthompsonarch.com

- 49, TROUGH DRAIN AND OIL/ WATER SEPARATOR COVER TO BE REMOVED AND REPLACED IN KIND. 50, EXISTING WAS METER AND SUPPLY LINES TO BE
- REMOVED AS PART OF NEW SERVICE UPGRADE WORK- REFER TO PLUMBING DRAWINGS.
- 51. EXISTING PTAC UNIT TO BE REPLACED W/ NEW. ENLARGE M.O. AND PROVIDE NEW LOUVER AS REQ'D PER HYAC DRAWINGS.

