

18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																																																																																																																									
<p>ABBREVIATIONS: (SOME MAY NOT BE USED)</p> <table border="0"> <tr> <td>A</td><td>AMP</td><td>DSP</td><td>GARBAGE DISPOSAL</td><td>HH</td><td>HAND HOLE</td><td>NEC</td><td>NATIONAL ELECTRIC CODE</td></tr> <tr> <td>AC</td><td>ABOVE COUNTER</td><td>DW</td><td>DISHWASHER</td><td>HOA</td><td>HAND-OFF-AUTO SWITCH</td><td>NL</td><td>NIGHT LIGHT</td></tr> <tr> <td>ACC</td><td>AIR COOLED CONDENSING UNIT</td><td>DWG</td><td>DRAWING</td><td>HP</td><td>HORSEPOWER</td><td>NO/NC</td><td>NORMALLY OPEN/NORMALLY CLOSED</td></tr> <tr> <td>ACP</td><td>ACCESS CONTROL PANEL</td><td>EC</td><td>ELECTRICAL CONTRACTOR</td><td>HVAC</td><td>HEATING, VENTILATION AND/OR AIR CONDITIONING</td><td>CEM</td><td>ORIGINAL EQUIPMENT MANUFACTURER</td></tr> <tr> <td>AFCI</td><td>ARC FAULT CIRCUIT INTERRUPTER</td><td>ECB</td><td>ENGLOSED CIRCUIT BREAKER</td><td>IG</td><td>ISOLATED GROUND</td><td>OLS</td><td>THERMAL OVERLOAD UNITS</td></tr> <tr> <td>AFF</td><td>ABOVE FINISHED FLOOR</td><td>EM</td><td>EMERGENCY</td><td>IN</td><td>INCHES</td><td>P</td><td>POLE</td></tr> <tr> <td>AFS</td><td>ABOVE FINISHED GRADE</td><td>EMT</td><td>ELECTRICAL METALLIC TUBING</td><td>INT</td><td>INTERNAL</td><td>PC</td><td>PHOTOCELL</td></tr> <tr> <td>AHU</td><td>AIR HANDLING UNIT</td><td>ELU</td><td>EMERGENCY LIGHTING UNIT</td><td>IT</td><td>INFORMATION TECHNOLOGIES</td><td>PE</td><td>PHOTO EYE</td></tr> <tr> <td>AWG</td><td>AMERICAN WIRE GAGE</td><td>ES</td><td>ELECTRIC STRIKE</td><td>JB</td><td>JUNCTION BOX</td><td>PH</td><td>PHASE</td></tr> <tr> <td>BFG</td><td>BELOW FINISHED GRADE</td><td>EXR</td><td>EXISTING TO REMAIN</td><td>K</td><td>KILO</td><td>PV</td><td>POST INDICATING VALVE</td></tr> <tr> <td>BLDG</td><td>BUILDING</td><td>FA</td><td>FIRE ALARM</td><td>KVA</td><td>KILO-VOLT AMPERE</td><td>PDE</td><td>POWER OVER ETHERNET</td></tr> <tr> <td>BTU</td><td>BRITISH THERMAL UNITS</td><td>FA&P</td><td>FIRE ALARM ANNUNCIATOR PANEL</td><td>KW</td><td>KILOWATT</td><td>PR</td><td>PAIR</td></tr> <tr> <td>C</td><td>CONDUIT</td><td>FACP</td><td>FIRE ALARM CONTROL PANEL</td><td>LBS</td><td>POUNDS</td><td>PVC</td><td>POLYVINYL CHLORIDE</td></tr> <tr> <td>CAT</td><td>CATEGORY</td><td>FTC</td><td>FIBER OPTIC CABLE CROSS CONNECT CABINET</td><td>LV</td><td>LOW VOLTAGE</td><td>RAF</td><td>RETURN AIR FAN</td></tr> <tr> <td>CB</td><td>CIRCUIT BREAKER</td><td>FLA</td><td>FULL LOAD AMPS</td><td>MAX</td><td>MAXIMUM</td><td>RECEPT</td><td>RECEPTACLE</td></tr> <tr> <td>CFM</td><td>CUBIC FEET PER MINUTE</td><td>FLR</td><td>FLOOR</td><td>MC</td><td>METAL CLAD CABLE</td><td>RVCC</td><td>REMOTE VOICE COMMAND CENTER</td></tr> <tr> <td>CKT</td><td>CIRCUIT</td><td>FT</td><td>FEET</td><td>MCB</td><td>MAIN CIRCUIT BREAKER</td><td>REL</td><td>RELAY</td></tr> <tr> <td>COMM</td><td>COMMUNICATION</td><td>FTL</td><td>FEED-THRU LUGS</td><td>MDP</td><td>MAIN DISTRIBUTION PANEL</td><td>REM</td><td>REMOVE</td></tr> <tr> <td>CONT.</td><td>CONTINUED</td><td>FVNR</td><td>FULL VOLTAGE NON-REVERSING</td><td>MH</td><td>MOUNTING HEIGHT</td><td>REP</td><td>REPLACE</td></tr> <tr> <td>CT</td><td>CURRENT TRANSFORMER</td><td>G</td><td>GROUND</td><td>MIN</td><td>MINIMUM</td><td>RSS</td><td>GRID GALVANIZED STEEL</td></tr> <tr> <td>CU</td><td>COPPER</td><td>GC</td><td>GENERAL CONTRACTOR</td><td>MLO</td><td>MAIN LUGS ONLY</td><td>RPM</td><td>REVOLUTIONS PER MINUTE</td></tr> <tr> <td>CUH</td><td>CABINET UNIT HEATER</td><td>GFI</td><td>GROUND FAULT CIRCUIT INTERRUPTER</td><td>MM</td><td>MULTIMODE FIBER OPTIC CABLE</td><td>SAF</td><td>SUPPLY AIR FAN</td></tr> <tr> <td>CVT</td><td>CONTROL VOLTAGE TRANSFORMER</td><td>GPM</td><td>GALLONS PER MINUTE</td><td>MS</td><td>MOTOR STARTING</td><td>SCH</td><td>SCHEDULE</td></tr> <tr> <td>DDC</td><td>DIRECT DIGITAL CONTROL</td><td>H</td><td>HEIGHT</td><td>MTG</td><td>MOUNTING</td><td>SER</td><td>SERVICE ENTRANCE RATED</td></tr> <tr> <td>DLC</td><td>DESIGN LIGHTS CONSORTIUM</td><td>HC</td><td>HANDICAP ACCESSIBLE</td><td></td><td></td><td></td><td></td></tr> </table>																		A	AMP	DSP	GARBAGE DISPOSAL	HH	HAND HOLE	NEC	NATIONAL ELECTRIC CODE	AC	ABOVE COUNTER	DW	DISHWASHER	HOA	HAND-OFF-AUTO SWITCH	NL	NIGHT LIGHT	ACC	AIR COOLED CONDENSING UNIT	DWG	DRAWING	HP	HORSEPOWER	NO/NC	NORMALLY OPEN/NORMALLY CLOSED	ACP	ACCESS CONTROL PANEL	EC	ELECTRICAL CONTRACTOR	HVAC	HEATING, VENTILATION AND/OR AIR CONDITIONING	CEM	ORIGINAL EQUIPMENT MANUFACTURER	AFCI	ARC FAULT CIRCUIT INTERRUPTER	ECB	ENGLOSED CIRCUIT BREAKER	IG	ISOLATED GROUND	OLS	THERMAL OVERLOAD UNITS	AFF	ABOVE FINISHED FLOOR	EM	EMERGENCY	IN	INCHES	P	POLE	AFS	ABOVE FINISHED GRADE	EMT	ELECTRICAL METALLIC TUBING	INT	INTERNAL	PC	PHOTOCELL	AHU	AIR HANDLING UNIT	ELU	EMERGENCY LIGHTING UNIT	IT	INFORMATION TECHNOLOGIES	PE	PHOTO EYE	AWG	AMERICAN WIRE GAGE	ES	ELECTRIC STRIKE	JB	JUNCTION BOX	PH	PHASE	BFG	BELOW FINISHED GRADE	EXR	EXISTING TO REMAIN	K	KILO	PV	POST INDICATING VALVE	BLDG	BUILDING	FA	FIRE ALARM	KVA	KILO-VOLT AMPERE	PDE	POWER OVER ETHERNET	BTU	BRITISH THERMAL UNITS	FA&P	FIRE ALARM ANNUNCIATOR PANEL	KW	KILOWATT	PR	PAIR	C	CONDUIT	FACP	FIRE ALARM CONTROL PANEL	LBS	POUNDS	PVC	POLYVINYL CHLORIDE	CAT	CATEGORY	FTC	FIBER OPTIC CABLE CROSS CONNECT CABINET	LV	LOW VOLTAGE	RAF	RETURN AIR FAN	CB	CIRCUIT BREAKER	FLA	FULL LOAD AMPS	MAX	MAXIMUM	RECEPT	RECEPTACLE	CFM	CUBIC FEET PER MINUTE	FLR	FLOOR	MC	METAL CLAD CABLE	RVCC	REMOTE VOICE COMMAND CENTER	CKT	CIRCUIT	FT	FEET	MCB	MAIN CIRCUIT BREAKER	REL	RELAY	COMM	COMMUNICATION	FTL	FEED-THRU LUGS	MDP	MAIN DISTRIBUTION PANEL	REM	REMOVE	CONT.	CONTINUED	FVNR	FULL VOLTAGE NON-REVERSING	MH	MOUNTING HEIGHT	REP	REPLACE	CT	CURRENT TRANSFORMER	G	GROUND	MIN	MINIMUM	RSS	GRID GALVANIZED STEEL	CU	COPPER	GC	GENERAL CONTRACTOR	MLO	MAIN LUGS ONLY	RPM	REVOLUTIONS PER MINUTE	CUH	CABINET UNIT HEATER	GFI	GROUND FAULT CIRCUIT INTERRUPTER	MM	MULTIMODE FIBER OPTIC CABLE	SAF	SUPPLY AIR FAN	CVT	CONTROL VOLTAGE TRANSFORMER	GPM	GALLONS PER MINUTE	MS	MOTOR STARTING	SCH	SCHEDULE	DDC	DIRECT DIGITAL CONTROL	H	HEIGHT	MTG	MOUNTING	SER	SERVICE ENTRANCE RATED	DLC	DESIGN LIGHTS CONSORTIUM	HC	HANDICAP ACCESSIBLE					<p>GENERAL PROJECT NOTES:</p> <ol style="list-style-type: none"> THE EXISTING FIRE ALARM PANEL IS A HONEYWELL NOTIFIER PANEL MAINTAINED BY SAFENET SECURITY SYSTEMS. OBTAIN THE SERVICES OF THE OWNER'S FIRE ALARM VENDOR FOR PROGRAMMING, ADDITIONS, AND/OR RELOCATIONS OF EXISTING FIRE ALARM SYSTEM DEVICES.
A	AMP	DSP	GARBAGE DISPOSAL	HH	HAND HOLE	NEC	NATIONAL ELECTRIC CODE																																																																																																																																																																																																																			
AC	ABOVE COUNTER	DW	DISHWASHER	HOA	HAND-OFF-AUTO SWITCH	NL	NIGHT LIGHT																																																																																																																																																																																																																			
ACC	AIR COOLED CONDENSING UNIT	DWG	DRAWING	HP	HORSEPOWER	NO/NC	NORMALLY OPEN/NORMALLY CLOSED																																																																																																																																																																																																																			
ACP	ACCESS CONTROL PANEL	EC	ELECTRICAL CONTRACTOR	HVAC	HEATING, VENTILATION AND/OR AIR CONDITIONING	CEM	ORIGINAL EQUIPMENT MANUFACTURER																																																																																																																																																																																																																			
AFCI	ARC FAULT CIRCUIT INTERRUPTER	ECB	ENGLOSED CIRCUIT BREAKER	IG	ISOLATED GROUND	OLS	THERMAL OVERLOAD UNITS																																																																																																																																																																																																																			
AFF	ABOVE FINISHED FLOOR	EM	EMERGENCY	IN	INCHES	P	POLE																																																																																																																																																																																																																			
AFS	ABOVE FINISHED GRADE	EMT	ELECTRICAL METALLIC TUBING	INT	INTERNAL	PC	PHOTOCELL																																																																																																																																																																																																																			
AHU	AIR HANDLING UNIT	ELU	EMERGENCY LIGHTING UNIT	IT	INFORMATION TECHNOLOGIES	PE	PHOTO EYE																																																																																																																																																																																																																			
AWG	AMERICAN WIRE GAGE	ES	ELECTRIC STRIKE	JB	JUNCTION BOX	PH	PHASE																																																																																																																																																																																																																			
BFG	BELOW FINISHED GRADE	EXR	EXISTING TO REMAIN	K	KILO	PV	POST INDICATING VALVE																																																																																																																																																																																																																			
BLDG	BUILDING	FA	FIRE ALARM	KVA	KILO-VOLT AMPERE	PDE	POWER OVER ETHERNET																																																																																																																																																																																																																			
BTU	BRITISH THERMAL UNITS	FA&P	FIRE ALARM ANNUNCIATOR PANEL	KW	KILOWATT	PR	PAIR																																																																																																																																																																																																																			
C	CONDUIT	FACP	FIRE ALARM CONTROL PANEL	LBS	POUNDS	PVC	POLYVINYL CHLORIDE																																																																																																																																																																																																																			
CAT	CATEGORY	FTC	FIBER OPTIC CABLE CROSS CONNECT CABINET	LV	LOW VOLTAGE	RAF	RETURN AIR FAN																																																																																																																																																																																																																			
CB	CIRCUIT BREAKER	FLA	FULL LOAD AMPS	MAX	MAXIMUM	RECEPT	RECEPTACLE																																																																																																																																																																																																																			
CFM	CUBIC FEET PER MINUTE	FLR	FLOOR	MC	METAL CLAD CABLE	RVCC	REMOTE VOICE COMMAND CENTER																																																																																																																																																																																																																			
CKT	CIRCUIT	FT	FEET	MCB	MAIN CIRCUIT BREAKER	REL	RELAY																																																																																																																																																																																																																			
COMM	COMMUNICATION	FTL	FEED-THRU LUGS	MDP	MAIN DISTRIBUTION PANEL	REM	REMOVE																																																																																																																																																																																																																			
CONT.	CONTINUED	FVNR	FULL VOLTAGE NON-REVERSING	MH	MOUNTING HEIGHT	REP	REPLACE																																																																																																																																																																																																																			
CT	CURRENT TRANSFORMER	G	GROUND	MIN	MINIMUM	RSS	GRID GALVANIZED STEEL																																																																																																																																																																																																																			
CU	COPPER	GC	GENERAL CONTRACTOR	MLO	MAIN LUGS ONLY	RPM	REVOLUTIONS PER MINUTE																																																																																																																																																																																																																			
CUH	CABINET UNIT HEATER	GFI	GROUND FAULT CIRCUIT INTERRUPTER	MM	MULTIMODE FIBER OPTIC CABLE	SAF	SUPPLY AIR FAN																																																																																																																																																																																																																			
CVT	CONTROL VOLTAGE TRANSFORMER	GPM	GALLONS PER MINUTE	MS	MOTOR STARTING	SCH	SCHEDULE																																																																																																																																																																																																																			
DDC	DIRECT DIGITAL CONTROL	H	HEIGHT	MTG	MOUNTING	SER	SERVICE ENTRANCE RATED																																																																																																																																																																																																																			
DLC	DESIGN LIGHTS CONSORTIUM	HC	HANDICAP ACCESSIBLE																																																																																																																																																																																																																							
<p>SYMBOLS LEGEND:</p> <table border="0"> <tr> <td></td><td>SURFACE MOUNTED PANEL</td> <td></td><td>FIRE ALARM CONTROL PANEL</td> </tr> <tr> <td></td><td>RECESSED PANEL</td> <td></td><td>REMOTE ANNUNCIATOR PANEL</td> </tr> <tr> <td></td><td>JUNCTION BOX</td> <td></td><td>PULL STATION</td> </tr> <tr> <td></td><td>HOME RUN TO PANEL. 2#12, #12G, 3/4" UNLESS OTHERWISE NOTED. PROVIDE SEPARATE GROUND AND NEUTRAL FOR EACH BRANCH CIRCUIT. X-Z, Y INDICATES PANEL Z, Y-INDICATES CIRCUIT NUMBERS</td> <td></td><td>CEILING OR WALL MOUNTED LED EXIT SIGN. PROVIDE DIRECTIONAL ARROWS AS SHOWN ON DRAWINGS</td> </tr> <tr> <td></td><td>CIRCUIT CONTINUATION WITH "Y" INDICATING DEVICE OR AREA DESCRIPTION "X" INDICATES PANEL "Z, Y" INDICATES CIRCUIT NUMBERS</td> <td></td><td>CEILING OR WALL MOUNTED EMERGENCY LIGHTING UNIT</td> </tr> <tr> <td></td><td>CIRCUIT CONSISTING OF GROUND, NEUTRAL AND PHASE CONDUCTORS. ADDITIONAL SLASH MARKS INDICATE SWITCHING OR TRAVELER CONDUCTORS, AND A LONG SOLID LINE INDICATES NEUTRAL. A SEPARATE GREEN GROUND CONDUCTOR SHALL BE PLACED IN ALL NEW CIRCUITS</td> <td></td><td>CEILING OR WALL MOUNTED COMBINATION EXIT SIGN / EMERGENCY LIGHTING UNIT</td> </tr> <tr> <td></td><td>CONNECTION POINT</td> <td></td><td>WALL MOUNTED LIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>CAPPED CONDUIT</td> <td></td><td>WALL MOUNTED SCONCE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>CONDUIT TURNED DOWN</td> <td></td><td>LINEAR WALL MOUNTED. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>CONDUIT TURNED UP</td> <td></td><td>LIGHT FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>LINE TYPE SHOWING WIRING BETWEEN LOW VOLTAGE DEVICES</td> <td></td><td>BALLAST DIRECTION INDICATED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>SINGLE POLE SWITCH, 20 AMP 120/277 UNLESS NOTED OTHERWISE "PRV" INDICATES FAN CONTROL SWITCH "P" INDICATES PILOT LIGHT "MS" INDICATES "HP" RATED GENERAL USE "SM" SWITCH WITH OVERLOADS SIZED FOR EQUIPMENT AND LOCKABLE HASP "MS" INDICATES 3 POLE 600 VOLT 30 AMP 3HP RATED MANUAL MOTOR STARTER WITH LOCKABLE HASP "WP" INDICATES WEATHER PROOF "3" INDICATES THREE WAY SWITCH "4" INDICATES FOUR WAY SWITCH "K" INDICATES KEYSWITCH "LV" INDICATES LOW VOLTAGE MOMENTARY SWITCH "LVF" INDICATES LOW VOLTAGE MULTIFUNCTION DIMMING SWITCH, 6-BUTTON "VS" INDICATES VACANCY SENSOR SWITCH "VSD" INDICATES 2 POLE WALL MOUNTED VACANCY SENSOR SWITCH "D" INDICATES DIMMER SWITCH "LVD" INDICATES LOW VOLTAGE MULTIFUNCTION DIMMING SWITCH "VSD" INDICATES DIMMING VACANCY SENSOR SWITCH "SP" INDICATES SPEAKER CONTROL</td> <td></td><td>LINEAR VARIABLE LENGTH OR EXISTING FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>NEMA 1 NON-FUSED DISCONNECT UON "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES</td> <td></td><td>LINEAR PENDANT FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>NEMA 1 FUSED DISCONNECT UON "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES "ZZ" FUSE SIZE</td> <td></td><td>DIRECTIONAL UPLIGHT OR WALLWASH FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>COMBINATION MOTOR STARTER. SIZE AS INDICATED "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES "ZZ" FUSE SIZE "NF" NON-FUSED</td> <td></td><td>LINEAR STRIP FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>VARIABLE FREQUENCY DRIVE. HP AS INDICATED</td> <td></td><td>SURFACE DOWNLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>COMBINATION NON-FUSED DISCONNECT VARIABLE FREQUENCY DRIVE. HP AS INDICATED</td> <td></td><td>RECESSED DOWNLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>DUPLEX RECEPTACLE "GFI" INDICATES GROUND FAULT CIRCUIT INTERRUPTER "AFI" INDICATES ARC FAULT CIRCUIT INTERRUPTER "WP" WEATHER-PROOF "AC" INDICATES ABOVE COUNTER. VERIFY HEIGHT "SR" INDICATES SURFACE RACEWAY</td> <td></td><td>PENDANT MOUNTED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>ABOVE COUNTER GFI DUPLEX RECEPTACLE. VERIFY HEIGHT</td> <td></td><td>ROOFTOP MOUNTED FLOODLIGHT MOUNTED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>QUADPLEX RECEPTACLE</td> <td></td><td>SPOTLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE</td> </tr> <tr> <td></td><td>SIMPLEX RECEPTACLE</td> <td></td><td>ADDED TO A FIXTURE INDICATES EMERGENCY OR GENERATOR POWERED CIRCUIT "LS" INDICATES LIFE SAFETY CIRCUIT "NL" INDICATES NIGHT LIGHT</td> </tr> <tr> <td></td><td>SPECIAL RECEPTACLE. TYPE AS INDICATED</td> <td></td><td>ACCESS CONTROL PANEL</td> </tr> <tr> <td></td><td>DUPLEX RECEPTACLE WITH 2 USB CHARGING PORTS, 3.6 AMP SMART OUTPUT. LEVITON T5832 OR EQUAL</td> <td></td><td>CARD READER</td> </tr> <tr> <td></td><td>CEILING MOUNTED DUPLEX RECEPTACLE "DC" INDICATES DROP CORD</td> <td></td><td>DOOR CONTACTS</td> </tr> <tr> <td></td><td>FLUSH FLOOR MOUNTED DUPLEX RECEPTACLE</td> <td></td><td>ELECTRIC STRIKE</td> </tr> <tr> <td></td><td>TELEPHONE OUTLET MOUNTED AT 48" UON WITH 1" CONDUIT UP TO ABOVE CEILING. 1-PORT IN FACEPLATE. PROVIDE 1-CAT 6 CABLE</td> <td></td><td>DOOR OPERATOR POWER CONNECTION</td> </tr> <tr> <td></td><td>DATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 1-PORT IN FACEPLATE UON. PROVIDE 1-CAT 6 CABLE UON</td> <td></td><td>DOOR OPERATOR PUSH PAD ACTUATOR</td> </tr> <tr> <td></td><td>TELEDATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 2-PORTS IN FACEPLATE. PROVIDE 2-CAT 6 CABLES</td> <td></td><td>DOOR OPERATOR SWIPE ACTUATOR</td> </tr> <tr> <td></td><td>CEILING MOUNTED DATA OUTLET. 1-PORT IN FACEPLATE UON. PROVIDE 1-CAT 6 CABLE UON</td> <td></td><td>HANDICAP DOOR OPERATOR PUSH PAD ACTUATOR</td> </tr> <tr> <td></td><td>FLUSH FLOOR MOUNTED DATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 2-PORTS IN FACEPLATE UON. PROVIDE 2-CAT 6 CABLE UON</td> <td></td><td>SECURITY CAMERA</td> </tr> <tr> <td></td><td>CEILING MOUNTED WIFI ANTENNA. PROVIDE CABLE ABOVE CEILING. PROVIDE 1 CAT 6 CABLE WITH 10' SERVICE LOOP. FOR NON-ACCESSIBLE CEILINGS. INSTALL LOW VOLTAGE RING WALL MOUNTED AT 84" UON.</td> <td></td><td>CAMERA JUNCTION BOX</td> </tr> <tr> <td></td><td>WALL MOUNTED 4" SQUARE JUNCTION BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE</td> <td></td><td></td> </tr> <tr> <td></td><td>CEILING MOUNTED 4" SQUARE JUNCTION BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE CEILING</td> <td></td><td></td> </tr> <tr> <td></td><td>FLUSH FLOOR MOUNTED 4" SQUARE FLOOR BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE CEILING</td> <td></td><td></td> </tr> <tr> <td></td><td>CABLE TV OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 1 PORT IN FACEPLATE. PROVIDE 1 RG-6/U COAXIAL CABLE</td> <td></td><td></td> </tr> <tr> <td></td><td>WALL OR CEILING MOUNTED SPEAKER PA SYSTEM</td> <td></td><td></td> </tr> <tr> <td></td><td>WALL OR CEILING MOUNTED SOUND SYSTEM/THEATRICAL SPEAKER</td> <td></td><td></td> </tr> <tr> <td></td><td>TELEPHONE BACKBOARD. FIRE RETARDANT PLYWOOD PAINTED WITH 2 COATS GRAY FIRE RETARDANT PAINT</td> <td></td><td></td> </tr> <tr> <td></td><td>GROUNDING BAR</td> <td></td><td></td> </tr> </table>																			SURFACE MOUNTED PANEL		FIRE ALARM CONTROL PANEL		RECESSED PANEL		REMOTE ANNUNCIATOR PANEL		JUNCTION BOX		PULL STATION		HOME RUN TO PANEL. 2#12, #12G, 3/4" UNLESS OTHERWISE NOTED. PROVIDE SEPARATE GROUND AND NEUTRAL FOR EACH BRANCH CIRCUIT. X-Z, Y INDICATES PANEL Z, Y-INDICATES CIRCUIT NUMBERS		CEILING OR WALL MOUNTED LED EXIT SIGN. PROVIDE DIRECTIONAL ARROWS AS SHOWN ON DRAWINGS		CIRCUIT CONTINUATION WITH "Y" INDICATING DEVICE OR AREA DESCRIPTION "X" INDICATES PANEL "Z, Y" INDICATES CIRCUIT NUMBERS		CEILING OR WALL MOUNTED EMERGENCY LIGHTING UNIT		CIRCUIT CONSISTING OF GROUND, NEUTRAL AND PHASE CONDUCTORS. ADDITIONAL SLASH MARKS INDICATE SWITCHING OR TRAVELER CONDUCTORS, AND A LONG SOLID LINE INDICATES NEUTRAL. A SEPARATE GREEN GROUND CONDUCTOR SHALL BE PLACED IN ALL NEW CIRCUITS		CEILING OR WALL MOUNTED COMBINATION EXIT SIGN / EMERGENCY LIGHTING UNIT		CONNECTION POINT		WALL MOUNTED LIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		CAPPED CONDUIT		WALL MOUNTED SCONCE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		CONDUIT TURNED DOWN		LINEAR WALL MOUNTED. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		CONDUIT TURNED UP		LIGHT FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		LINE TYPE SHOWING WIRING BETWEEN LOW VOLTAGE DEVICES		BALLAST DIRECTION INDICATED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		SINGLE POLE SWITCH, 20 AMP 120/277 UNLESS NOTED OTHERWISE "PRV" INDICATES FAN CONTROL SWITCH "P" INDICATES PILOT LIGHT "MS" INDICATES "HP" RATED GENERAL USE "SM" SWITCH WITH OVERLOADS SIZED FOR EQUIPMENT AND LOCKABLE HASP "MS" INDICATES 3 POLE 600 VOLT 30 AMP 3HP RATED MANUAL MOTOR STARTER WITH LOCKABLE HASP "WP" INDICATES WEATHER PROOF "3" INDICATES THREE WAY SWITCH "4" INDICATES FOUR WAY SWITCH "K" INDICATES KEYSWITCH "LV" INDICATES LOW VOLTAGE MOMENTARY SWITCH "LVF" INDICATES LOW VOLTAGE MULTIFUNCTION DIMMING SWITCH, 6-BUTTON "VS" INDICATES VACANCY SENSOR SWITCH "VSD" INDICATES 2 POLE WALL MOUNTED VACANCY SENSOR SWITCH "D" INDICATES DIMMER SWITCH "LVD" INDICATES LOW VOLTAGE MULTIFUNCTION DIMMING SWITCH "VSD" INDICATES DIMMING VACANCY SENSOR SWITCH "SP" INDICATES SPEAKER CONTROL		LINEAR VARIABLE LENGTH OR EXISTING FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		NEMA 1 NON-FUSED DISCONNECT UON "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES		LINEAR PENDANT FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		NEMA 1 FUSED DISCONNECT UON "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES "ZZ" FUSE SIZE		DIRECTIONAL UPLIGHT OR WALLWASH FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		COMBINATION MOTOR STARTER. SIZE AS INDICATED "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES "ZZ" FUSE SIZE "NF" NON-FUSED		LINEAR STRIP FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		VARIABLE FREQUENCY DRIVE. HP AS INDICATED		SURFACE DOWNLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		COMBINATION NON-FUSED DISCONNECT VARIABLE FREQUENCY DRIVE. HP AS INDICATED		RECESSED DOWNLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		DUPLEX RECEPTACLE "GFI" INDICATES GROUND FAULT CIRCUIT INTERRUPTER "AFI" INDICATES ARC FAULT CIRCUIT INTERRUPTER "WP" WEATHER-PROOF "AC" INDICATES ABOVE COUNTER. VERIFY HEIGHT "SR" INDICATES SURFACE RACEWAY		PENDANT MOUNTED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		ABOVE COUNTER GFI DUPLEX RECEPTACLE. VERIFY HEIGHT		ROOFTOP MOUNTED FLOODLIGHT MOUNTED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		QUADPLEX RECEPTACLE		SPOTLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE		SIMPLEX RECEPTACLE		ADDED TO A FIXTURE INDICATES EMERGENCY OR GENERATOR POWERED CIRCUIT "LS" INDICATES LIFE SAFETY CIRCUIT "NL" INDICATES NIGHT LIGHT		SPECIAL RECEPTACLE. TYPE AS INDICATED		ACCESS CONTROL PANEL		DUPLEX RECEPTACLE WITH 2 USB CHARGING PORTS, 3.6 AMP SMART OUTPUT. LEVITON T5832 OR EQUAL		CARD READER		CEILING MOUNTED DUPLEX RECEPTACLE "DC" INDICATES DROP CORD		DOOR CONTACTS		FLUSH FLOOR MOUNTED DUPLEX RECEPTACLE		ELECTRIC STRIKE		TELEPHONE OUTLET MOUNTED AT 48" UON WITH 1" CONDUIT UP TO ABOVE CEILING. 1-PORT IN FACEPLATE. PROVIDE 1-CAT 6 CABLE		DOOR OPERATOR POWER CONNECTION		DATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 1-PORT IN FACEPLATE UON. PROVIDE 1-CAT 6 CABLE UON		DOOR OPERATOR PUSH PAD ACTUATOR		TELEDATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 2-PORTS IN FACEPLATE. PROVIDE 2-CAT 6 CABLES		DOOR OPERATOR SWIPE ACTUATOR		CEILING MOUNTED DATA OUTLET. 1-PORT IN FACEPLATE UON. PROVIDE 1-CAT 6 CABLE UON		HANDICAP DOOR OPERATOR PUSH PAD ACTUATOR		FLUSH FLOOR MOUNTED DATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 2-PORTS IN FACEPLATE UON. PROVIDE 2-CAT 6 CABLE UON		SECURITY CAMERA		CEILING MOUNTED WIFI ANTENNA. PROVIDE CABLE ABOVE CEILING. PROVIDE 1 CAT 6 CABLE WITH 10' SERVICE LOOP. FOR NON-ACCESSIBLE CEILINGS. INSTALL LOW VOLTAGE RING WALL MOUNTED AT 84" UON.		CAMERA JUNCTION BOX		WALL MOUNTED 4" SQUARE JUNCTION BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE				CEILING MOUNTED 4" SQUARE JUNCTION BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE CEILING				FLUSH FLOOR MOUNTED 4" SQUARE FLOOR BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE CEILING				CABLE TV OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 1 PORT IN FACEPLATE. PROVIDE 1 RG-6/U COAXIAL CABLE				WALL OR CEILING MOUNTED SPEAKER PA SYSTEM				WALL OR CEILING MOUNTED SOUND SYSTEM/THEATRICAL SPEAKER				TELEPHONE BACKBOARD. FIRE RETARDANT PLYWOOD PAINTED WITH 2 COATS GRAY FIRE RETARDANT PAINT				GROUNDING BAR																																															
	SURFACE MOUNTED PANEL		FIRE ALARM CONTROL PANEL																																																																																																																																																																																																																							
	RECESSED PANEL		REMOTE ANNUNCIATOR PANEL																																																																																																																																																																																																																							
	JUNCTION BOX		PULL STATION																																																																																																																																																																																																																							
	HOME RUN TO PANEL. 2#12, #12G, 3/4" UNLESS OTHERWISE NOTED. PROVIDE SEPARATE GROUND AND NEUTRAL FOR EACH BRANCH CIRCUIT. X-Z, Y INDICATES PANEL Z, Y-INDICATES CIRCUIT NUMBERS		CEILING OR WALL MOUNTED LED EXIT SIGN. PROVIDE DIRECTIONAL ARROWS AS SHOWN ON DRAWINGS																																																																																																																																																																																																																							
	CIRCUIT CONTINUATION WITH "Y" INDICATING DEVICE OR AREA DESCRIPTION "X" INDICATES PANEL "Z, Y" INDICATES CIRCUIT NUMBERS		CEILING OR WALL MOUNTED EMERGENCY LIGHTING UNIT																																																																																																																																																																																																																							
	CIRCUIT CONSISTING OF GROUND, NEUTRAL AND PHASE CONDUCTORS. ADDITIONAL SLASH MARKS INDICATE SWITCHING OR TRAVELER CONDUCTORS, AND A LONG SOLID LINE INDICATES NEUTRAL. A SEPARATE GREEN GROUND CONDUCTOR SHALL BE PLACED IN ALL NEW CIRCUITS		CEILING OR WALL MOUNTED COMBINATION EXIT SIGN / EMERGENCY LIGHTING UNIT																																																																																																																																																																																																																							
	CONNECTION POINT		WALL MOUNTED LIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	CAPPED CONDUIT		WALL MOUNTED SCONCE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	CONDUIT TURNED DOWN		LINEAR WALL MOUNTED. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	CONDUIT TURNED UP		LIGHT FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	LINE TYPE SHOWING WIRING BETWEEN LOW VOLTAGE DEVICES		BALLAST DIRECTION INDICATED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	SINGLE POLE SWITCH, 20 AMP 120/277 UNLESS NOTED OTHERWISE "PRV" INDICATES FAN CONTROL SWITCH "P" INDICATES PILOT LIGHT "MS" INDICATES "HP" RATED GENERAL USE "SM" SWITCH WITH OVERLOADS SIZED FOR EQUIPMENT AND LOCKABLE HASP "MS" INDICATES 3 POLE 600 VOLT 30 AMP 3HP RATED MANUAL MOTOR STARTER WITH LOCKABLE HASP "WP" INDICATES WEATHER PROOF "3" INDICATES THREE WAY SWITCH "4" INDICATES FOUR WAY SWITCH "K" INDICATES KEYSWITCH "LV" INDICATES LOW VOLTAGE MOMENTARY SWITCH "LVF" INDICATES LOW VOLTAGE MULTIFUNCTION DIMMING SWITCH, 6-BUTTON "VS" INDICATES VACANCY SENSOR SWITCH "VSD" INDICATES 2 POLE WALL MOUNTED VACANCY SENSOR SWITCH "D" INDICATES DIMMER SWITCH "LVD" INDICATES LOW VOLTAGE MULTIFUNCTION DIMMING SWITCH "VSD" INDICATES DIMMING VACANCY SENSOR SWITCH "SP" INDICATES SPEAKER CONTROL		LINEAR VARIABLE LENGTH OR EXISTING FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	NEMA 1 NON-FUSED DISCONNECT UON "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES		LINEAR PENDANT FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	NEMA 1 FUSED DISCONNECT UON "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES "ZZ" FUSE SIZE		DIRECTIONAL UPLIGHT OR WALLWASH FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	COMBINATION MOTOR STARTER. SIZE AS INDICATED "XX" INDICATES DISCONNECT SIZE "Y" NUMBER OF POLES "ZZ" FUSE SIZE "NF" NON-FUSED		LINEAR STRIP FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	VARIABLE FREQUENCY DRIVE. HP AS INDICATED		SURFACE DOWNLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	COMBINATION NON-FUSED DISCONNECT VARIABLE FREQUENCY DRIVE. HP AS INDICATED		RECESSED DOWNLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	DUPLEX RECEPTACLE "GFI" INDICATES GROUND FAULT CIRCUIT INTERRUPTER "AFI" INDICATES ARC FAULT CIRCUIT INTERRUPTER "WP" WEATHER-PROOF "AC" INDICATES ABOVE COUNTER. VERIFY HEIGHT "SR" INDICATES SURFACE RACEWAY		PENDANT MOUNTED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	ABOVE COUNTER GFI DUPLEX RECEPTACLE. VERIFY HEIGHT		ROOFTOP MOUNTED FLOODLIGHT MOUNTED FIXTURE. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	QUADPLEX RECEPTACLE		SPOTLIGHT. SEE LIGHT FIXTURE SCHEDULE FOR TYPE																																																																																																																																																																																																																							
	SIMPLEX RECEPTACLE		ADDED TO A FIXTURE INDICATES EMERGENCY OR GENERATOR POWERED CIRCUIT "LS" INDICATES LIFE SAFETY CIRCUIT "NL" INDICATES NIGHT LIGHT																																																																																																																																																																																																																							
	SPECIAL RECEPTACLE. TYPE AS INDICATED		ACCESS CONTROL PANEL																																																																																																																																																																																																																							
	DUPLEX RECEPTACLE WITH 2 USB CHARGING PORTS, 3.6 AMP SMART OUTPUT. LEVITON T5832 OR EQUAL		CARD READER																																																																																																																																																																																																																							
	CEILING MOUNTED DUPLEX RECEPTACLE "DC" INDICATES DROP CORD		DOOR CONTACTS																																																																																																																																																																																																																							
	FLUSH FLOOR MOUNTED DUPLEX RECEPTACLE		ELECTRIC STRIKE																																																																																																																																																																																																																							
	TELEPHONE OUTLET MOUNTED AT 48" UON WITH 1" CONDUIT UP TO ABOVE CEILING. 1-PORT IN FACEPLATE. PROVIDE 1-CAT 6 CABLE		DOOR OPERATOR POWER CONNECTION																																																																																																																																																																																																																							
	DATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 1-PORT IN FACEPLATE UON. PROVIDE 1-CAT 6 CABLE UON		DOOR OPERATOR PUSH PAD ACTUATOR																																																																																																																																																																																																																							
	TELEDATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 2-PORTS IN FACEPLATE. PROVIDE 2-CAT 6 CABLES		DOOR OPERATOR SWIPE ACTUATOR																																																																																																																																																																																																																							
	CEILING MOUNTED DATA OUTLET. 1-PORT IN FACEPLATE UON. PROVIDE 1-CAT 6 CABLE UON		HANDICAP DOOR OPERATOR PUSH PAD ACTUATOR																																																																																																																																																																																																																							
	FLUSH FLOOR MOUNTED DATA OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 2-PORTS IN FACEPLATE UON. PROVIDE 2-CAT 6 CABLE UON		SECURITY CAMERA																																																																																																																																																																																																																							
	CEILING MOUNTED WIFI ANTENNA. PROVIDE CABLE ABOVE CEILING. PROVIDE 1 CAT 6 CABLE WITH 10' SERVICE LOOP. FOR NON-ACCESSIBLE CEILINGS. INSTALL LOW VOLTAGE RING WALL MOUNTED AT 84" UON.		CAMERA JUNCTION BOX																																																																																																																																																																																																																							
	WALL MOUNTED 4" SQUARE JUNCTION BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE																																																																																																																																																																																																																									
	CEILING MOUNTED 4" SQUARE JUNCTION BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE CEILING																																																																																																																																																																																																																									
	FLUSH FLOOR MOUNTED 4" SQUARE FLOOR BOX. EXTRA DEEP FOR AV CABLE PROVIDE 2-1 1/2" CONDUITS TO ABOVE CEILING																																																																																																																																																																																																																									
	CABLE TV OUTLET WITH 1" CONDUIT UP TO ABOVE CEILING. 1 PORT IN FACEPLATE. PROVIDE 1 RG-6/U COAXIAL CABLE																																																																																																																																																																																																																									
	WALL OR CEILING MOUNTED SPEAKER PA SYSTEM																																																																																																																																																																																																																									
	WALL OR CEILING MOUNTED SOUND SYSTEM/THEATRICAL SPEAKER																																																																																																																																																																																																																									
	TELEPHONE BACKBOARD. FIRE RETARDANT PLYWOOD PAINTED WITH 2 COATS GRAY FIRE RETARDANT PAINT																																																																																																																																																																																																																									
	GROUNDING BAR																																																																																																																																																																																																																									
<p>KEY PLAN</p>																																																																																																																																																																																																																										
<p>REVISIONS</p> <table border="1"> <thead> <tr> <th>No.</th> <th>Description</th> <th>Date</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>																		No.	Description	Date																																																																																																																																																																																																						
No.	Description	Date																																																																																																																																																																																																																								
<p>ISSUED: BID SET DATE: 06/21/2024 SCALE: AS NOTED SHEET NAME: ELECTRICAL LEGEND, DETAILS, AND PROJECT NOTES SHEET NUMBER: HE-E001</p>																																																																																																																																																																																																																										

ARCHITECT

ksqdesign

NEW YORK OKLAHOMA

KSQ Design
215 W 40th Street 15th Floor
New York, NY 10018
646.627.9880
www.ksqdesign.com

Owner
Nanuet Union Free School District
101 Church Street
Nanuet, NY 10954
845.627.9880
www.nanuetusd.org

Structural Engineer
Clapper Structural Engineering
160 Partition Street
Saugerties, NY 12477
845.943.9801
www.clappersstructural.com

MEP Engineer
Sage Engineering Associates, LLP
9 Columbia Circle
Albany, NY 12203
518.453.6091
www.sagegrp.com
www.enr.com/professionals-number-search

Environmental Engineer
Quest Environmental Solutions
1376 Route 9
Wappingers Falls, NY 12590
845.298.6251
www.qualityenv.com

Construction Manager
Jacobs
One Penn Plaza
24th Floor, Suite 2400
New York, NY 10119
646.906.6550
www.jacobs.com

Highview Elementary School
24 Highview Ave
Nanuet, NY 10954
OEC Building
135 Convent Rd
Nanuet, NY 10954
Maintenance Building
103 Church St.
Nanuet, NY 10954
Miller Elementary School
50 Blauvelt Rd Unit 1
Nanuet, NY 10954
A MacArthur Barr Middle School
143 Church St
Nanuet, NY 10954

KEY PLAN

REVISIONS

No.	Description	Date

ISSUED: BID SET
DATE: 06/21/2024
SCALE: AS NOTED
SHEET NAME: ELECTRICAL LEGEND, DETAILS, AND PROJECT NOTES
SHEET NUMBER: HE-E001

PROJECT NUMBER: 0000 COPYRIGHT © 2023 KSO ARCHITECTS, PC

ISSUE FOR BID SET