## PLUMBING FIXTURE SCHEDULE

GENERAL NOTES:

PIPE SIZES SHOWN ARE FOR SUPPLY AND DRAINAGE ONLY. PROVIDE SUPPLIES WITH SCREWDRIVER STOPS, WALL ESCUTCHEON, 17-GAUAGE SEMICAST "P" TRAPS WITH CLEANOUT PLUGS, PLUMBING FIXTURE SUPPORTS AND NECESSARY FITTINGS TO MAKE FINAL CONNETION. REFER TO SPECIFICATIONS FOR EQUIVALENTS. REFER TO ARCHITECTURAL DRAWINGS FOR MOUNTING ELEVATION OF PLUMBING FIXTURES, CLEARANCE BELOW SINKS AND LAVATORIES AND OFFSET DRAIN LOCATIONS. OFFSET DRAINS SHALL BE OFFSET LEFT REAR OR OFFSET RIGHT REAR. COORDINATE MOUNTING HEIGHTS FOR CHILDREN AND ADULT FIXTURES WITH ARCHITECTURAL DRAWINGS.


TAG	TYPE	ADA	MANUFACTURER	MODEL	COLD	HOT	SAN	VENT	DESCRIPTION	REMARKS
LAV-1	LAVATORY	Yes	AMERICAN STANDARD	LUCERNE 0355.012	1/2"	1/2"	1 1/2"	1 1/2"	CONTOURED BACK AND SIDE SPLASH SHIELDS, FAUCET LEDGE, 20"X18" NOMINAL DIMENSIONS. SYMMONS   THEF #S-20-2-G-1.5-W SINGLE LEVER FAUCET WITH GRID DRAIN ASSEMBLY AND 6" HANDLE. TRUEBRO #102-EZ   LAVA	OVIDE LEONARD #170A-LF-BP RMOSTATIC MIXING-VALVE UNDER ATORY. PIPE TEMPERED HOT (110DEG F.) COLD WATER TO FAUCET.
MS-1	JANITOR SINK	No	ACORN	TSH-24	3/4"	3/4"	3"	2"	TERRAZZO-WARE ONE-PIECE PRECAST 24"X24" MOP SINK WITH 12" SHOLDERS, STAINLESS STEEL CAPS, 3" RUBBER DRAIN GASEKET. CHICAGO FAUCET #897-CP MANUAL WALL-MOUNT FAUCET WITH 8" BODY, VACUUM BREAKER SPOUT WITH PAIL HOOK AND WALL BRACE.	
MS-2	MOP SINK	No	ACORN	TRH-362406	3/4"	3/4"	3"	2"	TERRAZZO-WARE ONE-PIECE PRECAST 36"X24" MOP SINK WITH 6" SHOLDERS, STAINLESS STEEL CAPS, 3" RUBBER DRAIN GASEKET. CHICAGO FAUCET #897-CP MANUAL WALL-MOUNT FAUCET WITH 8" BODY, VACUUM BREAKER SPOUT WITH PAIL HOOK AND WALL BRACE.	
S-1	SCULLERY SINK	No	ELKAY	WNSF8230LR2	1/2"	1/2"	2"	2"		E (2) 1 1/2" INDIRECT WASTE LINES FROM K TO FLOOR SINK.
SH-1	SHOWER	Yes	N/A	N/A	1/2"	1/2"	2"	1 1/2"	SYMMONS 9603-PLR PRESSURE BALANCING MIXING VALVE WITH HAND SHOWER, 36" ADA GRAB BAR AND 60" FLEXIBLE METAL HOSE, INTEGRAL SERVICE STOPS, 2.5 GPM FLOW RESTRICTOR.	
SH-2	SHOWER	No	ACORN	SBS-36-3F	1/2"	1/2"	2"	1 1/2"	TERRAZZO-WARE ONE-PIECE PRECAST 36"X36" SHOWER BASE WITH 4" HIGH THRESHOLD, 2" RUBBER DRAIN GASKET. SYMMONS S-9601-P PRESSURE BALANCED SHOWER VALVE WITH INTEGRAL VOLUME CONTROL, SHOWER HEAD, INTEGRAL SERVICE STOPS, 2.5 GPM FLOW RESTRICTOR.	
WC-1	WATER CLOSET	Yes	SLOAN	ST-2029	1"	0"	4"	2"	ELONGATED FLOOR MOUNTED, VITREOUS CHINA, ADA TOILET. CHURCH 295CT TOILET SEAT. SLOAN ROYAL 111-1.6 MANUAL FLUSH VALVE.	

	PLUMBING DRAINAGE SPECIALTY SCHEDULE									
TAG	TYPE	MANUFACTURER	MODEL	DESCRIPTION	REMARKS					
FCO-1	FLOOR CLEANOUT	J. R. SMITH	#4032	CAST IRON CLEANOUT, WITH ROUND ADJUSTABLE NICKEL-BRONZE TOP (SQUARE TOP IN PORCELAIN TILED FLOORS) BRONZE PLUG AND VANDAL PROOF SCREWS.						
FCO-2	FLOOR CLEANOUT	J. R. SMITH	#4231M	CAST IRON CLEANOUT, WITH 6" ROUND EXTRA HEAVY DUTY DUCTILE IRON COVER, BRONZE PLUG AND VANDAL PROOF SCREWS.						
FD-1	FLOOR DRAIN	J. R. SMITH	#2005Y	CAST IRON BODY WITH FLASHING COLLAR, 6"DIA. ROUND (6' SQUARE IN PORCELAIN TILED FLOORS) NICKEL-BRONZE ADJUSTABLE STRAINER. VANDAL PROOF SCREWS. QUAD CLOSE TRAP SEAL. 2' PIPE SIZE UNLESS OTHERWISE INDICATED ON FLOOR PLANS.						
FD-2	FLOOR DRAIN	J. R. SMITH	#2131Y	CAST IRON DEEP BODY, AND FLASHING COLLAR 12" DIA. CAST IRON BAR GRATE. QUAD CLOSE TRAP SEAL. 2' PIPE SIZE UNLESS OTHERWISE INDICATED ON FLOOR PLANS.						
FS-1	FLOOR SINK	J. R. SMITH	#3004	10"DEEP 14 GAUGE TYPE 316 STAINLESS STEEL RECEPTOR BODY, 12"SQ. 1/2 GRATE, CAST TYPE 316 STAINLESS STEEL DOME BOTTOM STRAINER. 2" PIPE SIZE UNLESS OTHERWISE INDICATED ON FLOOR PLANS.						
RD-1	ROOF DRAIN	J. R. SMITH	#1015-CID-R-C	ADJUSTABLE ROOF DRAIN, CAST IRON BODY WITH COMBINED FLASHING CLAMP AND GRAVEL STOP, CAST IRON DOME, CAST IRON STANDPIPE, SUMP RECEIVER AND UNDER DECK CLAMP. DRAIN SIZE AS INDICATED ON ROOF PLAN.						
TD-1	TRENCH DRAIN	ABT, INC.	#2512AF	SEVEN (7) 39.19" (1 METER) PRECAST POLYESTER POLYMER CONCRETE PRESLOPED (0.6%) CHANNELS WITH RADIUS BOTTOM, #502 DUCTILE IRON GRATE (CLASS "C" LOADING), #510 ANCHOR FRAMES, #901 SERIES CATCH BASIN WITH FOUL AIR TRAP (ON END), #106 END PLATE AND #2224 INSTALLATION DEVICES.						
WM-1	WASHING MACHINE OUTLET BOX	OATEY	#38995	1/4 TURN BRASS HAMMER BALL VALVE, COPPER SWEAT CONNECTION, 2" DRAIN OPENING, 20GA STEEL BOX, 18GA STEEL FACEPLATE.						

	PLUMBING WATER SPECIALTY SCHEDULE										
TAG	TYPE	MANUFACTURER / ITEM DESCRIPTION	REMARKS								
WH		J.R. SMITH #5509QT-NB, NICKEL BRONZE BOX, BRONZE NICKEL PLATED NON-FREEZE QUARTER TURN WALL HYDRANT WITH INTEGRAL VACUUM BREAKER, 3/4"HOSE CONNECTION "T" HANDLE KEY.	SEE ARCHITECTURAL DOCUMENTS FOR WALL THICKNESS								
WHA	WATER HAMMER ARRESTOR	SIOUX CHIEF "HYDRA-RESTER" SEAMLESS PRESSURE CHAMBER. SPUN CLOSED COPPER TUBE PERMANENTLY SEALED AT 60 PSIG. SHALL CONFORM TO ASME/ANSI STANDARDS AND PDI CERTIFIED. INSTALL PER FACTORY RECOMMENDATION. LIFETIME WARRANTY.	PROVIDE AT QUICK CLOSING VALVES.								

				GA	S-FIRED WATER H	IEATER	RSCHE	DULE					
			GAS E	BURNER	WA	ATER SID	E			ELEC	TRICAL I	DATA	
					STORAGE		PIPE DI	AMETER					
ID	MANUFACTURER	MODEL NO.	INPUT (BTU/H)	FUEL TYPE	RECOVERY @ 100°F (GPH)	VOL (gal)	INLET	OUTLET	THERMAL EFFICIENCY	FLA	VOLT	PH	REMARKS
WH-1	A. O. SMITH	BTH-120	120,000	NG	138.0	60.0	1 1/2"	1 1/2"	95	5 A	120 V	1	KLINAKKS

			SUMP	PUMP :	SCHEDI	ULE			
			PUI	PUMP MOTOR					
ID	MANUFACTURER	MODEL NO.	FLOW (GPM)	HEAD (FT)	POWER (hp)	RPM	VOLT	PH	REMARKS



3 Lear Jet Lane, Suite 205 Latham, NY 12110 518.765.5105 • www.h2m.com

CONSULTANT

MEP: Kenneth A. Hipsky, P.E., LEED AP 243 Godfrey Road Mystic, CT 06355 (860)-310-9827

MARK	DATE	DESCRIPTION

"ALTERATION OF THIS DOCUMENT EXCEPT BY A LICENSED PROFESSIONAL IS ILLEGAL."										
DESIGNED BY:	DRAW	N BY:	CHECKED BY:		REVIEWED BY:					
KAH		ALL								
PROJECT No:		DATE:		SCALE	:					
CARM1902		3/22/	2021	4	AS SHOWN					

CARMEL FIRE DEPARTMENT INC.

ADDITION/RENOVATION



94 GLENEIDA AVE, CARMEL HAMLET NY, 10512

CONTRACT

CONTRACT G
GENERAL CONSTRUCTION

STATUS

**BID SET** 

SHEET TITLE

PLUMBING SCHEDULES

RAWING No.

P 501