SC									S	ELF	CON	ΓΑΙΝΙ	ED A	IR C	ONDI	TION	ING	UNIT	SCH	IEDUL	E (A	IR C	COOLE	D)								BASIS OF	DESIGN:AIR WI	SE
			COMPRES	SOR DATA		SUPPLY FAN DATA				EVAPORATOR COIL DATA						CONDE	ENSER [DATA			FII	TER DA	ΛTA	EL	.ECTRICA	L DATA	4							
UNIT NO.	LOCATION	AREA SERVED	NO. OF COMP.	HP (EA.)	TOTAL CFM	MIN. O.A. CFM	OUTLET VEL. (FPM)	TOTAL S.P. (IN.W.G.)	MIN. EXT. S.P. (IN.W.G.)	FAN RPM	MOTOR HP	ENT. DB (°F)	ENT. WB (°F)	LVG. DB (°F)	LVG. WB (°F)	MAX. FACE VEL. (FPM)	MIN. ROWS DEEP	OUT- DOOR DESIGN DB (°F)	No. OF FAN	MAX. COND. TEMP. (°F)	TOTAL CFM	FAN RPM	EXT. S.P. (IN.W.G.)	MOTOR HP (EACH)	TYPE	IN. THICK	FACE VEL. (FPM)	VOLT/ PH	FLA	MCA	MFS	MODEL No.	MEA No.	REMARKS
AC-R	ROOF	IR - RECOV.	1	_	2200	400	1100	4.88	2.0	3105	5	80	67	50.0	49.6	406	6	95	_	120	-	_	_	_	MERV	2	400	208-3	70.1	70.1	80	-	-	SEE NOTES
_	_	-	_	_	_	_			_	_	_	_	_	_		_			_	_	_	_	_	_	_	_	_	_	_	_	_	_	-	_

1. PROVIDE UNIT WITH ECM SUPPLY AND RETURN FAN MOTORS. RETURN FAN TO BE 1800 CFM, 1.0 ESP, 1.9 TSP, 1.5 HP, 1770 RPM

2. UNITS TO HAVE BACNET COMPATIBLE DDC CONTROLS, MIXED AIR AND SUPPLY AIR THERMOSTATS DISCHARGE AIR SP SENSOR FOR THE SUPPLY AIR FAN CONTROL, AND AIR FLOW SWITCH.

3. UNIT INLET AND DISCHARGE ARRANGEMENTS ARE TO BE COORDINATED AND CONFIRMED WITH APPROVED SHEETMETAL SHOP DRAWINGS.

4. UNIT TO HAVE MERV8 PREFILTERS, MERV 14 POST FILTERS.

5. UNIT IS TO HAVE 2-INCH INSULATION AND DOUBLE WALL CONSTRUCTION. UNIT IS TO BE MOUNTED ON A SINGLE SKID AND IS TO BE WEATHERPROOF FOR ROOF MOUNTING.

6. UNIT IS TO HAVE SINGLE POINT ELECTRICAL CONNECTION AND A 120V OUTLET FOR SERVICING.

																									{	~~~	l					
SC								SEL	F CO	NTAII	NED	AIR	COND	OITIO	NING	UNI	TT (W	ATE	R CO	OLED)				<u>}</u>		}			BASIS OF	DESIGN: V	WATER FURNACE
			COMPRES	SOR DATA			SUPF	LY FAN	DATA				EVAF	PORATOR	R COIL I	DATA			CON	DENSER	DATA		FIL	TER DA	TA }	El	ECTRIC	CAL DAT	TA			
UNIT NO.	LOCATION	AREA SERVED	NO. OF	HP (EA.)	TOTAL CFM	MIN. O.A.	OUTLET VEL.	TOTAL S.P.	MIN. EXT.	FAN RPM	MOTOR HP	ENT. DB (°F)	ENT. WB	LVG. DB	MBH SENS.	MBH TOTAL	MIN. ROWS	GPM	TEM	P °F	, א.ט.	FOULING FACTOR	TYPE	IN. THICK	FACE VEL.	, VOLT/) FLA	MCA	МОСР	MODEL No.	EER COOLING	REMARKS
			COMP.	(LA.)	CI IVI	CFM	(FPM)	(IN.W.G.)	EXT. S.P. (IN.W.G.)	IXFIVI		(°F)	(°F)	(°F)	(MBH)	(MBH)	DEEP		ENT.	LVG.	(FT.)			-	(FPM)) PH						
AC-1	CORR. CLG	RM 104 - 109	1	-	500	150	720	_	1.0	1	0.5	81	66	55.4	13.81	21.62	_	5.0	85	95.72	6.7	_	MERV8	2	180	208-1	17.5	20.9	30	VERSA-023	15.0	_
AC-2	CORR. CLG	RM 101 - 103	1	-	800	100	1150	_	1.0	-	0.5	77	64	58.3	16.14	22.78	_	5.5	85	95.29	7.6	_	MERV8	2	288	208-1	17.5	20.9	30	VERSA-023	15.0	_
AC-3	CORR CLG.	RM 113 - 116	1	-	1200	100	1450	_	1.0	_	0.5	76.7	64	5.4	28.25	34.99	_	8.5	85	95.16	9.4	_	MERV8	2	675	208-1	21.3	20.9	40	VERSA-036	15.0	_
_	-	-	_	_	_	_	_	_	_	_	_	-	_	_	-	-	_	_	_	_	_	-	-	_	- (_	} -	_	_	-	-	_
NOTES:	•				•	•	•	•			•	•			•	•	•	•	•	•	•	•				<u> </u>	\sum		•	•		

1. PROVIDE UNIT WITH ECM SUPPLY FAN MOTOR.

2. UNITS TO HAVE BACNET COMPATIBLE DDC CONTROLS, MIXED AIR AND SUPPLY AIR THERMOSTATS AND AIR FLOW SWITCH.

3. UNIT INLET AND DISCHARGE ARRANGEMENTS ARE TO BE COORDINATED AND CONFIRMED WITH APPROVED SHEETMETAL SHOP DRAWINGS.

RHC,	/HC/HRC/I	PHC_			H	EATIN	IG C	OIL S	SCHE	DULE	(HC	T WA	ATER)			MFG: GREENHECK
	EQUIPMENT OR SYSTEM SERVED		,	AIR DAT	4			FI	LUID DA	TA		СО	IL DATA	ARRA	NGEMENT	
COIL			1 1/10	D.B. TEMP. (°F)		P.D.	FLUID		TEMP	TEMP. (°F)		MIN.	NOMINAL	TOTAL	NO. OF	REMARKS
NO.		CFM	VELOC. (FPM)	ENT.	LVG.	(IN.W.G.)		GPM	ENT.	LVG.	P.D. (FT)	ROWS DEEP	SIZE (IN.) F.W. X F.L.	NO. OF COILS	COILS HI X WIDE	
HC-1	AC-R, IR RM	1060	763	55	79.7	0.10	WTR	2.9	180	160	6.8	1	12.5 X 16	1	1	_
HC-2	AC-R, REC. #3	780	624	55	94.3	0.12	WTR	3.4	180	160	8.4	1	10 X 18	1	1	_
HC-3	AC-R, REC. #1,2	360	648	55	88.6	0.15	WTR	1.3	180	160	0.3	1	5 X 16	1	1	_
HC-4	AC-1	500	600	55	90.6	0.10	WTR	2.0	180	160	3.0	1	10 X 12	1	1	_
HC-5	AC-2	800	658	55	84.6	0.14	WTR	2.6	180	160	0.2	1	12.5 X 14	1	1	_
HC-6	AC-3	1200	864	55	88.4	0.21	WTR	4.4	180	160	4.4	2	12.5 X 16	1	1	_
_	_	-	_	_	_	-	-	_	_	_	_	_	-	_	-	_

ERV-1 SCHEDULE:

1. UNIT TO BE AN ALPHA-AIR MODEL AAH100G1ASTAG.
2. UNIT TO GE 208 V-1 PH, 9.3 MCA, 15 MOCP, WITH 1 COMPRESSOR, 1 SUPPLY FAN AND 1 RETURN FAN. 9. WHIT SHALL BE 350 CFM COTSIDE AIR AT 1.0 ESP, 400 CPM RETURN AIR AT 1.0 ESP.

4. UNIT IS TO BE 7.6 MBH(S), 26.4 MBH(T) WITH AN ISMER OF 11.1

5. UNIT IS TO HAVE 2-INCH MERV 13 FILTERS ON THE OUTSIDE AIR, MERV 8 FILTERS ON THE RETURN AIR.

6. UNIT IS TO HAVE SINGLE POINT ELECTRICAL CONNECTION, NON-FUSED DISCONNECT AND SHALL HAVE DDC CONTROLS WITH BACNET CAPABILITY. 7. UNIT SHALL HAVE SEALED INTERNAL INSULATION.

SH		STE	CAM :	HUMI	DIFI	ER S	CHED	ULE	BASI	S OF DESIGN:	: NEPTRONIC
			/	AIR DATA	4	STEAM	DATA	DUCT			
UNIT LOCATION		AREA OR SYSTEM SERVED	TOTAL CFM	MOIS CONTEN LB DF	NT GR/	, ,	INLET PRESS. (PSIG)	SIZE W × H (IN.)	NO. OF MANIF.	MODEL No.	REMARKS
				ENT.	LVG.	ПП	(1316)	(1117)			
H-1	JAN. CL.	IR, RECOV.	2200	26	38	17	5	24X12	11	SKE4-N06M	SEE NOTES
_	_	_	_	_	_	_	_	_	_	_	_

1. PROVIDE UNIT WITH STEAM GENERATING MODULATING HUMIDIFIER - 208V, 3PH, 16.5 FLA. 2. UNIT TO HAVE BACNET COMPATIBLE DDC CONTROLS, DUCT MOUNTED HIGH AND LOW LIMIT HUMIDISTAT, ROOM MOUNTED HUMIDISTAT, AND AIR FLOW SWITCH.

3. PROVIDE UNIT WIT LO-HOSE 1-3/8 NF, SCH80, NF SHS80, AND SW APS ACCESSORIES.

4. PROVIDE UNIT WITH MF SAM-AE2 STEAM DISPERSION MANIFOLD. 5. UNIT TO BE INTERLOCKED WITH ROOFTOP AIR CONDITIONING UNIT AC-R.

	UPPLY FAN XHAUST FAN				F/	BASIS OF DESIGN: GREENHECK							
UNIT		AREA OR SYSTEM	FAN		TSP	FAN RPM	DRIVE		MOTOR DA	ГА	WEIGHT	MODEL	
NO.	LOCATION	SERVED	TYPE	CFM				ВНР	HP	V/PH	(LBS)	NO.	REMARKS
F-1	ROOF	MED-GAS / CLEAN STORAGE	MUSHROOM	100	0.375	999	BELT	0.04	0.167	120-1	100	GB-097	SEE NOTE

NOTES: PROVIDE UNIT WITH SPARK-PROOF CONSTRUCTION, EXPLOSION PROOF MOTOR, ROOF CURB, MANUAL MOTOR STARTER WITH OVERLOADS, INTERLOCK FAN WITH MOTORIZED DAMPERS. FAN TO RUN CONTINUOUSLY.

THIS PLAN IS APPROVED ONLY FOR WORK INDICATED ON THE APPLICATION SPECIFICATION SHEET. ALL OTHER MATTERS SHOWN ARE NOT TO BE RELIED UPON, OR TO BE CONSIDERED AS EITHER BEING APPROVED OR IN ACCORDANCE WITH APPLICABLE CODES.

GENERAL NOTES

COLUMBIA | COLUMBIA UNIVERSITY IRVING MEDICAL CENTER

Tel 212.492.1400 Fax 212.492.1472

Tel 212.563.7400

Tel 212.433.2326

155 White Plains Road Tarrytown, NY 10591

Gensler

1700 Broadway Suite 400 New York, NY 10019 **United States**

United States



21 Pennsylvania Plaza New York, NY 10001

HARMANGROUP

450 7th Avenue

New York, NY 10123 **United States**

901 Manchester Avenue Moyland, PA 19065 United States

Tel 610.565.4607

KEY NOTES

KEY PLAN

10.04.21 ISSUE FOR BID 1 10.12.21 ADDENDUM #1

Seal / Signature

INTERVENTIONAL RADIOLOGY - TARRYTOWN

Project Number 12491.000

MECHANICAL SCHEDULES

AS NOTED

© 2021 Gensler