

SECTION 095113 - ACOUSTICAL PANEL CEILINGS

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes acoustical panels and exposed suspension systems for ceilings.

1.2 COORDINATION

- A. Coordinate layout and installation of acoustical panels and suspension system with other construction that penetrates ceilings or is supported by them, including light fixtures, HVAC equipment, fire-suppression system, and partition assemblies.

1.3 ACTION SUBMITTALS

- A. Product Data: Submit product data for each type of product indicated.
- B. Shop Drawings: Submit shop drawings of reflected ceiling plans drawn accurately to large scale and coordinating penetrations and ceiling-mounted items. Show the following:
 - 1. Patterns of ceiling suspension assembly members with setting out/work points.
 - 2. Method of attaching hangers to building structure.
 - 3. Ceiling-mounted items including lighting fixtures, diffusers, grilles, speakers, sprinklers, access panels, and special moldings at walls, column penetrations, and other junctures of acoustical ceilings with adjoining construction.
- C. Samples: Submit samples for each acoustical panel, for each exposed suspension system member, for each exposed molding and trim, and for each color and texture required, prepared on Samples of size indicated below. Samples shall show the full range of color and texture variations to be expected in the final installation.
 - 1. Acoustical Panel: Set of 6-inch square Samples of each type, color, pattern, and texture.
 - 2. Exposed Suspension System Members, Moldings, and Trim: Set of 12-inch long Samples of each type, finish, and color.

1.4 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish and store at the site where directed, 2 percent of each type of acoustic panel installed in the Project, packaged in manufacturer's unopened cartons and identified as to contents.

1.5 QUALITY ASSURANCE

- A. **Installer Qualifications:** Engage an Installer, with not less than 5 years experience in the installation of materials specified, and who has completed acoustical panel ceilings similar in material, design, and extent to that indicated for this Project with a record of successful in-service performance.
- B. **Source Limitations:** Obtain each type of acoustical ceiling panel and supporting suspension system through one source from a single manufacturer.
- C. **Performance Requirements:** In areas where gypsum wallboard partitions are dependent on the ceiling suspension system for lateral support, design and install suspension system components to sustain the imposed load from the completed partition system including a minimum inward and outward pressure of 5 psf normal to the plane of the wall.
- D. **Seismic Standard:** Provide acoustical panel ceilings designed and installed to withstand the effects of Seismic Zone 4 earthquake motions according to the following:
 - 1. **CISCA's Guidelines for Systems Requiring Seismic Restraint:** Comply with CISCA's "Guidelines for Seismic Restraint of Direct-Hung Suspended Ceiling Assemblies--Seismic Zones 3 & 4."
- E. **Sample Installations:** Before installing acoustical panel ceilings, install sample installations for each type of acoustical panel ceiling installation required to demonstrate aesthetic effects and qualities of materials and execution. The sample installation shall be complete in every way and include all attachments to structure, hangers, grids, ceiling panels, moldings and column trims, light fixtures, air outlets and inlets, speakers, sprinklers heads, heat and smoke detectors. Install sample installations to comply with the following requirements, using materials indicated for the completed Work:
 - 1. **Size and Location:** Provide 250 square foot sample installations in locations as directed by Architect.
 - 2. **Demonstrate the proposed range of aesthetic effects and workmanship.**
 - 3. **Obtain Architect's approval of sample installations before starting work.**
 - 4. **Maintain sample installations during construction in an undisturbed condition as a standard for judging the completed Work.**
- F. **Approved sample installations may become part of the completed Work if undamaged at time of Substantial Completion.**
- G. **Requirements of Regulatory Agencies:** Provide acoustical ceiling components and assemblies which have been approved for installation in the City of New York. Comply with the applicable provisions of Referenced Standard RS 5-16 of the NYC Building Code.

1.6 DELIVERY, STORAGE, AND HANDLING

- A. Deliver acoustical panels, suspension system components, and accessories to Project site in original, unopened packages and store them in a fully enclosed, conditioned space where they will be protected against damage from moisture, humidity, temperature extremes, direct sunlight, surface contamination, and other causes.
- B. Before installing acoustical panels, permit them to reach room temperature and a stabilized moisture content.
- C. Handle acoustical panels carefully to avoid chipping edges or damaging units in any way.

1.7 FIELD CONDITIONS

- A. Environmental Limitations: Do not install acoustical panel ceilings until wet work (painting, drywall, interior tilework, and concrete leveling) in spaces is complete and dry, work above ceilings is complete, and ambient temperature and humidity conditions are maintained at the levels indicated for Project when occupied for its intended use.

PART 2 - PRODUCTS

2.1 METAL SUSPENSION SYSTEMS

- A. Metal Suspension System Standard: Provide manufacturer's standard direct-hung metal suspension systems of types, structural classifications, and finishes indicated that comply with applicable requirements in ASTM C 635.
- B. Clean Room Metal Suspension System: Provide manufacturer's Clean Room direct-hung metal suspension systems of types, structural classifications, and finishes indicated that comply with applicable requirements in ASTM C 635.
- C. Overhead Deck Hanger Attachment Devices: Size for five times the design load indicated in ASTM C 635, Table 1, "Direct Hung," unless otherwise indicated.
 - 1. Fastener system of type suitable for application indicated, fabricated from corrosion-resistant materials, with eyepins, clips or other accessory devices for attaching hangers of type indicated, and with capability to sustain, without failure, a load equal to 10 times that imposed by ceiling assembly.
- D. Hangers: As follows:

1. Wire Hangers, Braces, and Ties: Zinc-coated carbon-steel wire; ASTM A 641/A 641M, Class 1 zinc coating, soft temper.
 - a. Size: Select wire diameter so its stress at three times hanger design load (ASTM C 635, Table 1, "Direct Hung") will be less than yield stress of wire, but provide not less than 12 gage (0.106-inch) diameter wire.
 2. Rod Hangers: ASTM A 510, mild carbon steel.
 - a. Diameter: 1/4-inch.
 - b. Protective Coating: ASTM A 153/A 153M, hot-dip galvanized.
 3. Flat Hangers: Commercial-sheet steel, ASTM A 653/A 653M, G60, hot dip galvanized.
 - a. Size: 1 by 3/16 inch by length indicated.
- E. Carrying Channels: ASTM C 754, cold rolled steel channels, 1-1/2-inch, 475 pounds per 1000 feet.
- F. Metal Edge Moldings and Trim: Type and profile indicated or, if not indicated, manufacturer's standard moldings for edges and penetrations that fit acoustical panel edge details and suspension systems indicated; formed from sheet metal of same material, finish, and color as that used for exposed flanges of suspension system runners; provide in longest standard single piece lengths.
1. Shadow (Stepped Moldings): Stepped edge molding that forms reveal of same depth and width as that formed between edge of panel and flange at exposed suspension member. Form from sheet metal of same material and finish as that used for exposed flanges of suspension system runners.
 2. F Moldings: Provide F moldings at ceiling breaks, soffits, bulkheads, and changes in elevation other than vertical walls and columns to the extent indicated. Form from sheet metal of same material and finish as that used for exposed flanges of suspension system runners.
 3. Metal Perimeter Channel Trim: Shapes and profiles to suit conditions indicated; fabricated from extruded aluminum; finished to match exposed flanges of suspension system runners. Provide manufacturer's recommended tee-bar connection clips, and hanging clips, which lock into specially designed bosses on the channel trim and are screw attached to the web of the intersecting suspension system members. Join sections of trim together with manufacturer's standard splice plates and alignment clips.
 4. Perimeter Wing Trim: Shapes and profiles to suit conditions indicated; fabricated from and finished to match exposed panel. Provide manufacturer's recommended connect wing cantilevers, connect splines, connect hooks, connect multi-connection, and installation screws suitable for installation indicated.

- G. Clips: Provide support clips, clamps, fasteners, splines, and other attachment devices as required to align components and to connect components and transfer imposed loads of suspension system.
1. Provide partition attachment clips, and fasteners for areas where partition ceiling runners are secured to the ceiling suspension system.
 2. Provide attachment clips for runner to angle molding to avoid use of pop rivets.
 3. Provide grid converter accessories as required to change main tee direction 90 degrees from adjacent main tee.
 4. Provide light fixture clips.
 5. Provide hold down clips at entryways to reduce flutter as required.
 6. Provide miter closure clips.
 7. Seismic Struts: Manufacturer's standard compression struts designed to accommodate seismic forces.
 8. Seismic Clips: Manufacturer's standard seismic clips designed and spaced to secure acoustical panels in-place.
- H. Manufacturers and Products: Refer to drawings and schedules for extent and types of each metal suspension system required.
- I. Subject to requirements, provide scheduled suspension systems, or comparable products, acceptable to the Architect, by one of the following:
1. Armstrong World Industries, Inc.
 2. CertainTeed Corporation.
 3. Chicago Metallic Corporation.
 4. United States Gypsum Company.

2.2 ACOUSTICAL PANELS (CL##)

- A. Manufacturers and Products: Refer to drawings and schedules for extent and types of each acoustical panel required.
- B. Subject to requirements, provide scheduled acoustical panels, or comparable products, acceptable to the Architect, by one of the following:
1. Armstrong World Industries, Inc.
 2. CertainTeed Corporation.
 3. Chicago Metallic Corporation.
 4. Rockfon (Roxul Inc.).
 5. United States Gypsum Company.

- C. Acoustical Panel Standard: Provide manufacturer's standard panels according to ASTM E 1264 and designated by type, form, pattern, acoustical rating, and light reflectance unless otherwise indicated.
- D. Recycled Content: Postconsumer recycled content plus one-half of preconsumer recycled content.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates, areas, and conditions, including structural framing to which acoustical panel ceilings attach or abut, with Installer present, for compliance with requirements specified in this and other Sections that affect ceiling installation, anchorage, with requirements for installation tolerances, and other conditions affecting performance of acoustical panel ceilings.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Layout the Work to center board pattern both directions around Work points shown in each major space or room as shown on the Drawings or directed and, where possible, adjust pattern so that edge pieces will be not less than 1/2 unit in width.

3.3 INSTALLATION

- A. General: Install acoustical panel ceilings to comply with ASTM C 636 and seismic requirements indicated, per manufacturer's written instructions and CISCA's "Ceiling Systems Handbook," and as required to match the accepted sample installation.
- B. Suspend ceiling hangers as follows:
 - 1. Fasten hangers to anchors that extend into decks. Space hangers not more than 48 inches long each member supported directly from hangers; and provide hangers not more than 6 inches from ends of each member. Provide additional hangers for support of fixtures and other items including but not limited to light fixtures and diffusers, as required to prevent overloading of deck attachment, eccentric deflection or rotation of supporting runners.
 - 2. Hangers:

- a. Secure wire hangers to ceiling suspension members and to supports above with a minimum of 3 tight turns. Connect hangers directly to drilled in anchors (eye screws), or other devices that are secure, and are appropriate for substrate.
 - b. Secure flat, angle, channel, and rod hangers to structure, including intermediate framing members, by attaching to drilled in anchors, or other devices that are secure and appropriate for both the structure to which hangers are attached and the type of hanger involved.
3. Splay hangers only where required to miss obstructions; offset resulting horizontal forces by bracing, countersplaying, or other equally effective means.
 4. Install hangers plumb and free from contact with insulation or other objects within ceiling plenum that are not part of the supporting structure or of the ceiling suspension system.
 5. Where width of ducts and other construction within ceiling plenum produces hanger spacings that interfere with location of hangers at spacings required to support standard suspension system members, install supplemental suspension members and hangers in form of trapezes or equivalent devices. Size supplemental suspension members and hangers to support ceiling loads within performance limits established by referenced standards and publications.
 6. Lateral Force Bracing:
 - a. Horizontal restraints shall be provided by four No. 12 gage (2.7 mm) wires secured to the main runner within 2 inches of the cross runner intersection and splayed 90 degrees from each other at an angle not exceeding 45 degrees from the plane of the ceiling. A strut fastened to the main runner shall be extended to and fastened to the structural members supporting the roof or floor above. The strut shall be adequate to resist the vertical component induced by the bracing wires. These horizontal restraint points shall be placed not more than 12 feet on center in both directions with the first point within 6 feet from each wall. Attachment of the restraint wires to the structure above shall be adequate for the load imposed.
 - b. Lateral force bracing members shall be spaced a minimum of 6 inches from all horizontal piping or ductwork that is not provided with bracing restraints for horizontal forces. Bracing wires shall be attached to the grid and to the structure in such a manner that they can support a design load of not less than 200 pounds or the actual design load, whichever is greater, with a safety factor of 2.
- C. Install edge moldings and trim of type indicated at perimeter of acoustical ceiling area and where necessary to conceal edges of acoustical panels.
1. Typical Edge Molding Attachment: Align moldings accurately and screw attach securely to substrate with concealed fasteners at intervals not more than 16 inches on center and not more than 3 inches from ends, leveling with ceiling suspension system. Miter corners accurately and connect securely.
 - a. Do not use exposed fasteners, including pop rivets, on moldings and trim.

2. Window and Curtain Wall Frame Head Attachment: Unless otherwise indicated, align moldings accurately and secure to window and curtain wall frame heads using manufacturer's recommended double-sided foam white tape, leveling with ceiling suspension system. Miter corners accurately and adhere securely.
 - a. Do not use exposed fasteners, including pop rivets, on moldings and trim.
- D. Install suspension system runners so they are square and securely interlocked with one another. Clip runners to angle moldings do not use exposed fasteners. Finish to lines and levels shown, with maximum deflection not to exceed $1/360$ of the span between supports. Laser level accurately in all directions, leveling to a tolerance of $1/8$ -inch noncumulative. Remove and replace dented, bent, or kinked members.
- E. Install acoustical panels with undamaged edges and fit accurately into suspension system runners and edge moldings. Run grain of units in one direction as accepted on shop drawings. Scribe and cut panels at borders and penetrations to provide a neat, precise fit.
 1. For square-edged panels, install panels with edges fully hidden from view by flanges of suspension-system runners and moldings.
 2. For reveal-edged panels on suspension-system runners, install panels with bottom of reveal in firm contact with top surface of runner flanges.
 3. For reveal-edged panels on suspension system members with box-shaped flanges, install panels with reveal surfaces in firm contact with suspension system surfaces and panel faces flush with bottom face of runners.
 4. Paint cut edges of panel remaining exposed after installation; match color of exposed panel surfaces using sealer and coating recommended in writing for this purpose by acoustical panel manufacturer.

3.4 CLEANING

- A. Clean exposed surfaces of acoustical panel ceilings, including trim, edge moldings, and suspension system members. Comply with manufacturer's written instructions for cleaning and touchup of minor finish damage. Remove and replace ceiling components that cannot be successfully cleaned and repaired to permanently eliminate evidence of damage.

END OF SECTION