

DOOR AND FRAME SCHEDULE


DOOR NO.	SIZE	DOOR			FRAME			FIRE LABEL	HARDWARE GROUP	HEAD/JAMB DETAIL	REMARKS
		TYPE	MAT'L	FINISH	TYPE	MAT'L	FINISH				
01A	12'-0" x 7'-8" HFT PACKAGED UNIT	A	GLASS/ALUM.	DARK BRONZE	PER MANF.	ALUM.	DARK BRONZE	-	SUPPLIED BY DORMA	PER MANF.	G.C. TO COORDINATE FINAL DOOR AND FRAME DIMENSIONS WITH DORMA. SEE VENDOR INFORMATION ON SHEET A0.0 FOR CONTACT INFORMATION. GLAZING TO BE 1/4" TEMPERED
01B	12'-0" x 7'-8" HFT PACKAGED UNIT	A	GLASS/ALUM.	DARK BRONZE	PER MANF.	ALUM.	DARK BRONZE	-	SUPPLIED BY DORMA	PER MANF.	G.C. TO COORDINATE FINAL DOOR AND FRAME DIMENSIONS WITH DORMA. SEE VENDOR INFORMATION ON SHEET A0.0 FOR CONTACT INFORMATION. GLAZING TO BE 1/4" TEMPERED
02	3'-0" x 7'-0" x 1 3/4"	B	S.C. WOOD	PAINTED	1	H.M.	PAINTED	-	1	A&B/A5.0	SEE DOOR SCHEDULE NOTES.
03	3'-0" x 7'-0" x 1 3/4"	B	S.C. WOOD	PAINTED	1	H.M.	PAINTED	-	2	A&B/A5.0	SEE DOOR SCHEDULE NOTES.
04	3'-0" x 7'-0" x 1 3/4"	B	S.C. WOOD	PAINTED	1	H.M.	PAINTED	-	2	A&B/A5.0	SEE DOOR SCHEDULE NOTES.
05	3'-0" x 7'-0" x 1 3/4"	B	S.C. WOOD	PAINTED	1	H.M.	PAINTED	-	4	A&B/A5.0	UNDERCUT DOOR TO PROVIDE 1" CLEARANCE. LATCH SET SHALL BE "PRIVACY" TYPE.
06	3'-0" x 7'-0" x 1 3/4"	B	S.C. WOOD	PAINTED	1	H.M.	PAINTED	-	4	A&B/A5.0	UNDERCUT DOOR TO PROVIDE 1" CLEARANCE. LATCH SET SHALL BE "PRIVACY" TYPE.
07	3'-0" x 7'-0" x 1 3/4"	B	S.C. WOOD	PAINTED	1	H.M.	PAINTED	-	3	A&B/A5.0	SEE DOOR SCHEDULE NOTES.
08	8'-0" x 10'-0" x 1 1/2"	D	MTL.	GALV.	BY MANF.	MTL.	PAINTED	-	5	FA/5.0&A4.1	CHAIN OPERATED INSULATED SERVICE DOOR FURNISHED AND INSTALLED BY O.H. DOOR VENDOR AT NEW OPENING. VERIFY OPENING SIZE IN FIELD BEFORE ORDERING DOOR.
09	3'-0" x 7'-0" x 1 3/4"	C	H.M.	PAINTED	3	H.M.	PAINTED	-	6	C&D/A5.0	VERIFY OPENING SIZE IN FIELD BEFORE ORDERING DOOR. SEE DOOR SCHEDULE NOTES. INSTALL ADDRESS ON THIS DOOR.
10	3'-0" x 7'-0" x 1 3/4"	C	H.M.	PAINTED	3	H.M.	PAINTED	-	6A	C&D/A5.0	VERIFY OPENING SIZE IN FIELD BEFORE ORDERING DOOR. SEE DOOR SCHEDULE NOTES. DO NOT INSTALL ADDRESS ON THIS DOOR.

HARDWARE GROUP


GROUP #1 (MANAGER UTILITY)	GROUP #2 (CASH ROOM DOORS)	GROUP #3 (BREAK ROOM)	GROUP #4 (RESTROOMS)	GROUP #5 (OVERHEAD DOORS)	GROUP #6 (SINGLE EXIT DOORS) NOTE: (NO HARDWARE ON EXTERIOR SIDE, U.N.O.)
BUTTS: 1 - 1/2 PAIR MCKINNEY MP 79, 4 1/2" x 4 1/2", 26D.	BUTTS: 1 - 1/2 PAIR MCKINNEY MP 79, 4 1/2" x 4 1/2", 26D.	BUTTS: 1 - 1/2 PAIR MCKINNEY MP 79, 4 1/2" x 4 1/2", 26D.	BUTTS: 1 - 1/2 PAIR HAGER ECBB1100, 4 1/2" x 4 1/2" x US26D.	DOOR PANELS: 2-3/4" INSULATED STEEL INTERLOCKING FLAT SLAT CURTAIN W/ ENDLOCKS @ BOTH ENDS BY VENDOR SCHLAGE K341F1200	BUTTS: 1 - 1/2 PAIR MCKINNEY MP 79, 4 1/2" x 4 1/2", 26D.
LATCH SET: FALCON 'ENTRANCE' LEVER W101S-D-626	LATCH SET: FALCON 'STOREROOM' LEVER W581HD-D-626	LATCH SET: FALCON 'PASSAGE' LEVER W101S-D-626	LATCH SET: FALCON 'PASSAGE' LEVER W101S-D-626 (MULTI-USE RESTROOMS)		EXIT DEVICE: VON DUPRIN GUARD-X 2670-US28
LATCH GUARD: DON-JO ILP-212-SL	LATCH GUARD: DOOR #3: DON-JO ILP-212-SL DOOR #4: DON-JO OSPL-110-SL	CLOSER: FALCON SC71 RW / PA-689 (MTD. ON INSIDE)	FALCON 'PRIVACY' LEVER K301S-D-626 (SINGLE-USE RESTROOMS)	CYLINDER CORE: FALCON C649 (IHK, IHK-626 SCHLAGE 80-035-GRN 24 GA. MIN. GALVANIZED STEEL BY VENDOR HAND CHAIN BY VENDOR)	CYLINDER CORE: FALCON C207-SC-C26D
CYLINDER CORE: FALCON C649 (CKWY-7 PIN)-626	DEAD BOLT: FALCON D241H-50-231F-7 PIN-626	KICKPLATE: ROCKWOOD K1050 - 10x34 US32D	CLOSER: FALCON SC71 RW / PA-689 (MTD. ON INSIDE)		CONST. CORE: FALCON C607 CCA 7-PIN
CLOSER: FALCON SC71 RW / PA-689 (MTD. ON INSIDE)	CYLINDER CORE: (2) FALCON C649 (CKWY-7 PIN)-626	SILENCER: (3) ROCKWOOD 608-26D	FLOOR STOP: ROCKWOOD 441-US26D DOME STOP		HOUSING: FALCON C953 (CKWY 7-PIN) 626
KICKPLATE: ROCKWOOD K1050 - 10x34 US32D	CLOSER: FALCON SC71 RW / PA-689 (MTD. ON INSIDE)	FLOOR STOP: ROCKWOOD 441-US26D DOME STOP	KICKPLATE: ROCKWOOD K1050 - 10x34 US32D	LOCKING: CHAIN KEEPER (BY VENDOR) WITH PADLOCK (SUPPLIED BY HFT GC.)	CLOSER: FALCON SC71 RW / PA-689 (MTD. INSIDE)
SILENCER: (3) ROCKWOOD 608-26D	KICKPLATE: ROCKWOOD K1050 - 10x34 US32D	DOOR VIEWER: ROCKWOOD 622-26D	SILENCER: (3) ROCKWOOD 608-26D		DOOR STOP: ROCKWOOD 472-26D STOP W/ KEEPER
FLOOR STOP: ROCKWOOD 441-US26D DOME STOP	DOOR VIEWER: ROCKWOOD 622-26D	FLOOR STOP: ROCKWOOD 441-US26D DOME STOP	FLOOR STOP: ROCKWOOD 441-US26D DOME STOP	WEATHER SEALS: BY VENDOR	DOOR VIEWER: DOORSCOPE DS2000 AL.S
					DOOR BOTTOM: PEMKO 315-CN MILL 36"
					GASKETING: PEMKO 303 AV (1) 36", (2) 84"
					THRESHOLD: PEMKO 171-A MILL 36"
					DOOR PULL: ROCKWOOD 131-26D (MTD. INSIDE)
					LATCH GUARD: DON-JO NLP-110 (EXTERIOR)
					DRIP EDGE: PEMKO 346C RAIN DRIP 40" (EXTERIOR)

DOOR SCHEDULE NOTES


- RATED DOORS SHALL BE A TIGHT-FITTING SMOKE AND DRAFT CONTROL ASSEMBLY.
- ALL EXISTING NEW DOORS AND HARDWARE SHALL COMPLY WITH CURRENT ADA REGULATIONS.
- ALL INTERIOR/EXTERIOR METAL DOORS SHALL BE 20 GA. MINIMUM.
- ALL DOOR HARDWARE SHALL BE LEVER TYPE OR PANIC HARDWARE.
- EXTERIOR DOORS SHALL BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY, SPECIAL KNOWLEDGE OR EFFORT.
- OPENINGS SHALL BE A MINIMUM OF 32" WIDE WHEN DOOR IS AT RIGHT ANGLE TO CLOSED POSITION.
- BOTTOM 10" OF ALL DOORS SHALL HAVE A SMOOTH, UNINTERRUPTED SURFACE FOR OPENING BY WHEELCHAIR FOOT REST.
- MAXIMUM EFFORT TO OPERATE DOORS SHALL NOT EXCEED 5 LBS. FOR EXTERIOR DOORS, AND 3 LBS. FOR INTERIOR DOORS WITH A PUSH OR PULL EFFORT BEING APPLIED AT RIGHT ANGLES TO HINGED DOOR AND AT THE CENTER PLANE OF SLIDING OR FOLDING DOORS. COMPENSATING DEVICES OR AUTOMATIC DOOR OPERATIONS MAY BE UTILIZED TO MEET THE ABOVE STANDARDS, WHEN FIRE DOORS ARE REQUIRED. THE MAXIMUM EFFORT TO OPERATE THE DOORWAY MAY BE INCREASED NOT TO EXCEED 14 LBS. W/ CLOSURE.
- SUBMIT HARDWARE CUT SHEETS FOR ANY ALTERNATES TO HFT REPRESENTATIVE PRIOR TO ORDERING HARDWARE FOR APPROVAL.
- REPLACE ALL EXISTING HARDWARE TO COMPLY WITH HARDWARE SCHEDULE.
- PROVIDE A SIGN ABOVE ALL ENTRANCE DOOR STATING THAT "THIS DOOR IS TO REMAIN UNLOCKED DURING BUSINESS HOURS". LETTERS SHALL BE AT LEAST 1" IN HEIGHT AND SHALL BE WHITE ON A CONTRASTING BACKGROUND.
- CONTRACTOR SHALL COORDINATE KEYING OF LOCKS WITH OWNER PRIOR TO INSTALLATION.
- ALL HARDWARE LISTED TO BE SUPPLIED BY LISTED MANUFACTURER OR EQUAL.
- ALL DOOR HARDWARE TO BE BRUSHED CHROME FINISH.
- EXTERIOR DOORS & FRAMES, EXCLUDING OVERHEAD DOOR, TO BE PAINTED TO MATCH THE ADJ. FINISH ON THE EXTERIOR AND PAINTED P-8 ON THE INTERIOR. SEE FINISH SCHEDULE ON SHEET A1.3.
- INTERIOR DOORS AND FRAMES TO BE PAINTED P-8. SEE FINISH SCHEDULE ON SHEET A1.3.
- BI-PARTING DOOR THRESHOLDS TO BE PROVIDED AND INSTALLED BY DOOR VENDOR.
- PROVIDE 8" HIGH WHITE VINYL NUMBERS STATING STREET ADDRESS IN HELVETICA FONT STYLE ON TRANSMAT AT MAIN ENTRY DOOR.
- INTERIOR DOOR FRAMES SHALL BE MIN. 20GA, U.N.O. EXTERIOR DOOR FRAMES SHALL BE MIN. 16GA, WELDED FRAMES, U.N.O.




A TYP. INTERIOR DOOR JAMB DETAIL
SCALE: 3" = 1'-0"




B TYP. INTERIOR DOOR HEAD DETAIL
SCALE: 3" = 1'-0"




C TYP. EXTERIOR DOOR JAMB DETAIL
SCALE: 3" = 1'-0"



D TYP. EXTERIOR DOOR HEAD DETAIL
SCALE: 3" = 1'-0"




E TYP. INTERIOR WINDOW HEAD DETAIL
SCALE: 3" = 1'-0"




F OVERHEAD DOOR JAMB
SCALE: 3" = 1'-0"

DOOR TYPES



FRAME TYPES



ADA ARCHITECTS SERVICES, P.C.
Lakewood, Ohio 44107
17710 Detroit Avenue
Phone (216) 521-5134 Fax (216) 521-1484
www.adaarchitects.com

HARBOR FREIGHT TOOLS
314 NY ROUTE 59
NYACK, NY 10960

THESE DOCUMENTS CONTAIN INFORMATION PROPRIETARY TO ADA ARCHITECTS SERVICES, P.C.
UNAUTHORIZED USE OF THESE DOCUMENTS IS EXPRESSLY PROHIBITED UNLESS AGREED UPON IN WRITING.

REVISIONS

#	DATE	TYPE
1		
2		
3		
4		
5		
6		
7		
8		
9		

DOOR SCHEDULE & DETAILS

DATE: 9/22/21
JOB NO.: 20420

A5.0
SHEET NO.

DO NOT SCALE THESE DRAWINGS