# OSSINING UNION FREE SCHOOL DISTRICT HVAC IMPROVEMENTS

# OSSINING HIGH SCHOOL

29 SOUTH HIGHLAND AVENUE OSSINING NEW YORK 10562 SED #66-14-01-03-0-003-042

# PARK EARLY CHILDHOOD CENTER

22 EDWARD STREET
OSSINING NEW YORK 10562
SED #66-14-01-03-0-004-023

# ARCHITECT / ENGINEER


**○**PI

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 PHONE: 800-274-9000

# OWNER

OSSINING UNION FREE SCHOOL DISTRICT
400 EXECUTIVE BOULEVARD
OSSINING, NEW YORK 10562
PHONE: 914-941-7700

# LOCATION MAP LIST OF DRAWINGS



GENERAL:
T001 TITLE

TITLE SHEET

ASBESTOS ABATEMENT:

AA-000 ACM NOTES
PECC/AA100 FIRST FLOOR ACM REMOVAL PLAN

PECC/AA200 SECOND FLOOR ACM REMOVAL PLAN

PECC/AA300 ROOF ACM REMOVAL PLAN
HS/AA100 BASEMENT ACM REMOVAL PLAN

HVAC H000

HVAC LEGEND AND ABBREVIATIONS

HS-H100 BASEMENT HVAC DEMOLITION AND NEW WORK PLAN

PES-H101 FIRST FLOOR HVAC DEMOLITION PLAN

PES-H102 SECOND FLOOR HVAC DEMOLITION PLAN PES-H103 ROOF HVAC DEMOLITION PLAN

PES-H201 FIRST FLOOR HVAC NEW WORK PLAN PES-H202 SECOND FLOOR HVAC NEW WORK PLAN

PES-H203 ROOF HVAC NEW WORK PLAN

H800 HVAC DETAILS
H900 HVAC SCHEDULES

ELECTRICAL

E000 ELECTRICAL LEGEND & NOTES

HS-E100 BASEMENT ELECTRICAL DEMOLITION AND NEW WORK PLAN

PES-E101 FIRST FLOOR ELECTRICAL DEMOLITION PLAN
PES-E102 SECOND FLOOR ELECTRICAL DEMOLITION PLAN
PES-E201 FIRST FLOOR ELECTRICAL NEW WORK PLAN
PES-E202 SECOND FLOOR ELECTRICAL NEW WORK PLAN

S-E203 ROOF ELECTRICAL NEW WORK PLAN

PARK EARLY CHILDHOOD CENTER
22 EDWARD STREET, OSSINING, NY 10562

OSSINING HIGH SCHOOL
29 SOUTH HIGHLAND AVENUE, OSSINING, NY 10562



### GENERAL NOTES

THE DESIGN OF THIS PROJECT CONFORMS TO ALL APPLICABLE PROVISIONS OF NEW YORK STATE UNIFORM FIRE PREVENTION AND BUILDING CODE, THE NEW YORK STATE ENERGY CONSERVATION CODE, AND THE BUILDING STANDARDS OF THE NEW YORK STATE EDUCATION DEPARTMENT.

CPLteam.com
ARCHITECTURE • ENGINEERING • PLANNING

50 FRONT STREET, SUITE 202
NEWBURGH NEW YORK 12550

<u>OISTRICT</u> 1-03-0-004-023 1-03-0-003-042

S UNION FREE SCHOOL DIST HVAC IMPROVEMENTS LDHOOD CENTER SED #66-14-01-03

PARK EARLY CHILDHC

DATE DRAWN CHEC 8/28/2020 JM

SCALE NONE

SHEET TITLE

TITLE SHEET

PROJECT NUMBER 14428.16/17

TOO1

#### PRE-ABATEMENT WORK NOTES:

- 1. THESE DRAWINGS HAVE BEEN PREPARED BY UTILIZING THE OWNERS ORIGINAL CONSTRUCTION DOCUMENTS IN ORDER TO ILLUSTRATE THE EXISTING CONDITIONS OF THE SITE AND STRUCTURES THEREIN. THE CONTRACTOR SHALL BEE RESPONSIBLE FOR ACTUAL VERIFICATION OF ALL EXISTING CONDITIONS IN THE FIELD.
- 2. THE ASBESTOS CONTAINING MATERIALS, CONFIGURATIONS AND LOCATIONS SHOWN IN THESE DRAWINGS ARE BASED ON THE ASBESTOS CONTAINING MATERIALS TESTING REPORT. REFER TO THE ASBESTOS CONTAINING MATERIALS REPORT FOR FURTHER INFORMATION.
- 3. THE CONTRACTOR SHALL DETERMINE EXACT FINAL LOCATIONS OF PERSONAL AND WASTE DECONTAMINATION ENCLOSURES, PICK UP AREA FOR REFUSE AND ASBESTOS DEBRIS, THESE LOCATIONS SHALL BE REVIEWED AND PROPERLY APPROVED BY THE DISTRICT PRIOR TO COMMENCEMENT OF WORK. THIS CONTRACTOR SHALL ESTABLISH, LABEL AND MAINTAIN PROPER EXITS AND WAYS OF DEPARTURE WITHIN EACH WORK AREA FOR NORMAL AND EMERGENCY USE BY WORKERS DURING ALL ABATEMENT.
- 4. THE CONTRACTOR, PRIOR TO BIDDING, SHALL BE RESPONSIBLE TO BECOME COMPLETELY FAMILIAR WITH ALL ASPECTS OF THE PROJECT, INCLUDING, BUT NOT LIMITED TO, ALL DEMOLITION AND CONSTRUCTION WORK AS SHOWN IN THE COMPLETE SET OF DRAWINGS AND IN THE PROJECT MANUAL/SPECIFICATIONS, IN ORDER THAT THE FULL SCOPE OF WORK WHICH MAY ENCOUNTER ASBESTOS CONTAINING MATERIALS IS UNDERSTOOD AND ACCOUNTED FOR BY THE CONTRACTOR IN HIS PROJECT WHETHER OR NOT SHOWN IN THESE DOCUMENTS.

#### ASBESTOS REMOVAL GENERAL NOTES:

- 1. ASBESTOS ABATEMENT INDICATED ON THIS DRAWING SHALL BE PERFORMED BY A NYS DEPARTMENT OF LABOR LICENSED ASBESTOS CONTRACTOR, SHALL VERIFY ALL EXISTING CONDITIONS, DIMENSIONS AND QUANTITIES PRIOR TO BID
- 2. THE CONTRACTOR SHALL PERFORM ALL CONTRACT WORK IN ACCORDANCE WITH CONTRACT SPECIFICATIONS, NEW YORK STATE DEPARTMENT OF LABOR (NYSDOL) INDUSTRIAL CODE RULE 56, OSHA, NESHAPS, AHEA, NYSDEC AND ALL OTHER APPLICABLE CODES.
- 3. THE CONTRACTOR SHALL MAINTAIN THE SITE AS NEAT AS POSSIBLE AND ORDERLY DURING THE WORK. ALL LOOSE DEBRIS WHICH MAY BLOW OFF THE SITE SHALL BE COLLECTED AND DISPOSED OF PROPERLY BY THE CONTRACTOR ON A DAILY BASIS AS PART OF THE PROJECT.
- 4. THE CONTRACTOR SHALL PROVIDE BARRIERS AROUND THE WORK AREAS IN ORDER TO ENSURE SAFE PASSAGE BY ANY PERSON. THESE BARRIERS SHALL ALSO SERVE TO KEEP ALL UNAUTHORIZED PERSONS OUT THE PROJECT AREA FOR THE DURATION OF THE WORK.
- 5. VARIANCES: CONTRACTOR SHALL PAY FOR AND OBTAIN ANY NECESSARY SITE SPECIFIC VARIANCES.
- 6. THE CONTRACTOR SHALL MAINTAIN SECURITY IN THE BUILDING AND THE WORK AREAS AT ALL TIMES.
- 7. PROJECT STAGING, STORAGE, SCHEDULING AND ACCESS SHALL BE COORDINATED WITH AND APPROVED BY THE ARCHITECT AND OWNER PRIOR TO PROCEEDING WITH WORK.
- 8. SHOULD IT BE NECESSARY, CONTRACTOR SHALL COORDINATE SHUT DOWN AND LOCK OUT OF THE ELECTRICAL POWER WITH OWNER'S POWER WITH OWNER'S REPRESENTATIVE PRIOR TO THE COMMENCEMENT OF WORK.
- 9. ALL TEMPORARY POWER TO THE WORK AREA SHALL BE BROUGHT IN FROM OUTSIDE THE WORK AREA THROUGH A GROUND-FAULT CIRCUIT INTERRUPTER AT THE SOURCE.

10.CONTRACTOR SHALL COORDINATE HOOKUP OF WATER SERVICE FOR

- DECONTAMINATION PURPOSED WITH OWNERS REPRESENTATIVE. WATER FOR THE DECONTAMINATION UNITS IS AVAILABLE FROM THE OWNER.

  11.THE OWNER OR OWNER'S REPRESENTATIVE IS RESPONSIBLE TO CONTRACT
- FOR NYSDOL PROJECTS MONITORING/AIR SAMPLING TECHNICIAN SERVICES AS REQUIRED.

  12.CONTRACTOR TO PROVED A COPY OF MSD'S FOR ANY CHEMICAL AGENTS TO

BE USED DURING THE ASBESTOS ABATEMENT TO THE PROJECT MONITOR AD

- THE OWNER'S REPRESENTATIVE.

  13.CONTRACTOR SHALL REQUEST AND RECEIVE PROJECT MONITOR AND OWNER'S REPRESENTATIVE APPROVAL OF ALL WORK BEFORE ANY ABATEMENT IS
- 14.UNDER NO CIRCUMSTANCES SHALL CONTAMINATED WASTE WATER BE FILTERED THOUGH A SYSTEM WITH AT LEAST A 5.0 MICRON PARTICLE SIZE COLLECTION CAPABILITY.

UNDERTAKEN.

- 15.DRAWINGS ATTEMPT TO INDICATE THE GENERAL SCOPE OF EXISTING CONDITIONS AND ITEMS EFFECTED BY THE ABATEMENT WORK. CONTRACTOR SHALL EXAMINE THE WORK AREA PRIOR TO BID AND SHALL INCLUDE FIELD VARIATIONS FROM THOSE SHOWN WITH IN THE GENERAL INTENT OF THE WORK
- 16.THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL ASBESTOS CONTAINING MATERIALS CONTAINED WITHIN THE PROJECT AND ASSOCIATED WITH ALL PROJECT WORK, IN COMPLIANCE WITH ALL APPLICABLE LAWS, RULES, REGULATIONS AND ALL REQUIREMENTS OF ALL AUTHORITIES HAVING JURISDICTION.
- 17.THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL ASBESTOS CONTAINING MATERIALS CONTAINED WITHIN THE PROJECT AND ASSOCIATED WITH ALL PROJECT WORK, IN THE MOST EFFICIENT AND COST EFFECTIVE METHOD POSSIBLE, WHICH ALSO COMPLIES WITH THE REQUIREMENTS LISTED


#### POST-ABATEMENT WORK NOTES:

- PROVIDE ALL APPLICABLE CODE RULE 56 PROCEDURES, CLEAN UP, AND ADDITIONAL TESTING AS REQUIRED.
- 2. PRIOR TO ABATEMENT, ALL CONTRACTORS WILL SURVEY EXISTING CONDITIONS IN THE ABATEMENT AND GENERAL WORK AREAS. ITEMS/MATERIALS/ETC. DAMAGED, OR NON-FUNCTIONAL SHALL BE LISTED, NOTED, PHOTOGRAPHED AND REVIEWED WITH THE PROJECT INSPECTOR. ALL OTHER ITEMS/MATERIALS SHALL BE REVIEWED WITH THE PROJECT INSPECTOR. ALL OTHER ITEMS/MATERIALS SHALL BE ASSUMED TO BE IN GOD CONDITION AND GOOD WORKING ORDER. IT SHALL BE THE RESPONSIBILITY OF THE ABETMENT CONTRACTOR TO MAINTAIN ALL MATERIALS, ITEMS, EQUIPMENT, SYSTEMS, ETC. IN ITS ORIGINAL CONDITION AND RETURN TO OWNER/GC, ETC. IN SAME CONDITION AT THE END OF THIS CONTRACT.
- 3. REMOVE ALL TEMPORARY ENCLOSURES, BARRIERS, ETC. REINSTALL ITEMS/WORK PREVIOUSLY REMOVE, ALL TAPE AND ADHESIVE RESIDUALS TO BE REMOVED. TEST AND
- 4. THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO INSURE AGAINST DAMAGE TO THE EXISTING WORK TO REMAIN IN PLACE. ANY DAMAGE TO SUCH WORK SHALL BE REPAIRED OR REPLACED TO THE SATISFACTION OF THE ARCHITECT AND OWNER AT NO ADDITIONAL COST TO THE CONTRACT.
- 5. AT COMPLETION OF THE ABATEMENT WORK, A CONDITION SURVEY SHALL BE DON BY ALL CONTRACTORS AND PROJECT INSPECTOR (SEE NOTE #2). ANY VARIATION (I.E. DAMAGE BY THE CONTRACTOR), AND OTHERWISE NOT INCLUDED AS PART OF THE RECONSTRUCTION WORK, SHALL BE REPAIRED/RESTORED BY THE ABATEMENT CONTRACTOR.
- 6. THE CONTRACTOR SHALL, UPON COMPLETION OF THE REMOVAL, PROVIDE WRITTEN DOCUMENTATION (INCLUDING ALL APPROPRIATE THIRD PARTY TESTING RESULTS) THAT THE PROJECT WORK AREAS ARE COMPLETELY FREE OF ALL ASBESTOS CONTAINING MATERIALS.
- 7. THE CONTRACTOR SHALL PROVIDE RECORDS OF ALL ASBESTOS CONTAINING MATERIALS REMOVED FROM THE SITE, INCLUDING THE COMPOSITION AND VOLUMES OF DISPOSED MATERIALS AND THE FINAL DISPOSAL SITE(S).



50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614





AC IMPROVEMENTS

OOD CENTER SED #66-14-01-03-0-004-02

OOL SED #66-14-01-03-0-003-04;

 $\Box$ 

EARL IING

DATE DRAWN CHECKED
08/28/20 JP RL

SCALE AS NOTED

SHEET TITLE
ACM NOTES


NOTES


AA000

DRAWING NUMBER


- REMOVE AND DISPOSE OF PRESUMED ASBESTOS CONTAINING PIPE INSULATION AND MUDDED JOINT PACKING ABOVE NON—ASBESTSOS PLASTER CEILING.
- REMOVE AND DISPOSE OF ASBESTOS CONTAINING INSULATION SHEET FROM WOOD CABINET HEATERS.

  \*SEE SPECIFICATION SECTION #3.17 FOR DETAILS.\*











CPLteam.com
ARCHITECTURE = ENGINEERING = PLANNING

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614





ON FREE SCHOOL DISTRICT

SIMPROVEMENTS

DICENTER SED #66-14-01-03-0-004-023

DATE DRAWN CHECKED
08/28/20 JP RL


SCALE AS NOTED

SHEET TITLE
FIRST FLOOR ACM
REMOVAL PLAN

PROJECT NUMBER
14428.16

PECC
AA100

DRAWING NUMBER



CPLteam.com
ARCHITECTURE - ENGINEERING - PLANNING

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614








scale AS NOTED SECOND FLOOR ACM REMOVAL PLAN


> PROJECT NUMBER 14428.16

KEY PLAN


PECC AA200 DRAWING NUMBER





2 ROOF ACM REMVOAL PLAN - AREA B
SCALE: 1/8" = 1'-0"



CPLteam.com
ARCHITECTURE - ENGINEERING - PLANNING 50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614









DATE DRAWN CHECKED 08/28/20 JP RL SCALE AS NOTED

SHEET TITLE ROOF ACM REMOVAL PLAN


> PROJECT NUMBER AA300 DRAWING NUMBER








50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614






HVAC IMPROVEMENTS

HICHOOD CENTER SED #66-14-01-03-0-003-042

DATE DRAWN CHECKED
08/28/20 JP RL

SCALE AS NOTED

SHEET TITLE
BASEMENT ACM
REMOVAL PLAN



					HVAC SYMBOLS	LIST				
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION		SYMBOL	DESCRIPTION		T
AAD	AUTOMATIC AIR DAMPER	<u>— ф</u>	CONNECTION - TOP	(DBL)	DOUBLE WALL LINED DUCT		<u> </u>		T-1	+
ACC	AIR-COOLED CONDENSING UNIT		CONNECTION - BOTTOM	20/10	DUCT SECTION - SUPPLY		24X12 12X10	SUPPLY / RETURN /	1-1/2 TIMES BRANCH SIZE	
AD	ACCESS DOOR		DIRECTION OF FLOW	20/10	DUCT SECTION - RETURN/EXHAUST		VD VD	EXHAUST AIR	12X10	H
AFF	ABOVE FINISHED FLOOR		REDUCER	20/10 A"	DUCT SECTION - ROUND DUCT IN INCHES			TAKEOFFS	VD	H
AHU	AIR HANDLING UNIT	,		+						+
BBD	BOILER BLOW DOWN		CAP OR PLUG	AXB FO	DUCT SECTION - FLAT OVAL DUCT IN INCHES		24X12 —8'Ø	SUPPLY / RETURN /	1-1/2 TIMES BRANCH SIZE	F
BD CA	BACKDRAFT DAMPER  COMPRESSED AIR	C+	ELBOW DOWN		ACOUSTIC THERMAL LINING	<u> </u>		EXHAUST AIR	8.\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
CD	COOLING COIL CONDENSATE DRAIN	10	ELBOW UP		FLEXIBLE DUCTWORK		VD /	TAKEOFFS	VD	
CFM	CUBIC FEET PER MINUTE	IOI	TEE OUTLET - UP		ELEVIDLE CONNECTION	<u> </u>	<u></u>			
CHWR	CHILLED WATER RETURN	<del></del>	TEE OUTLET - DOWN	l <sub>FC</sub>	FLEXIBLE CONNECTION	]	14'Ø		CONICAL TEE	
CHWS	CHILLED WATER SUPPLY	——————————————————————————————————————	UNION			<u> </u>		SUPPLY AIR	<sup>4</sup>	
CR	CONDENSER WATER RETURN	——₩——	GATE VALVE	•	FIRE DAMPER		AD ,	TAKEOFFS	10°Ø	
CS	CONDENSER WATER SUPPLY	δ	BALL VALVE			<u> </u>				
CW	DOMESTIC COLD WATER		BALANCING VALVE	<b>?</b>	SMOKE DAMPER	<b>®</b>	1.490		<u> </u>	+
D (5)	DRAIN		STRAINER			<del>                                      </del>	14"Ø	SUPPLY AIR	LATERAL	
(E)	EXISTING  EXHAUST AIR	<u>γ</u>			COMBINATION FIRE AND SMOKE DAMPER		VD VD	TAKEOFFS	74 10.\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	
EA EC	ELECTRICAL CONTRACTOR		STRAINER WITH BLOW-DOWN	<b>2</b>		<b>②</b>			V□ V□	
EF	EXHAUST FAN	,			VOLUME DAMPER	<u> </u>				+
ERHC	ELECTRIC REHEAT COIL		BUTTERFLY VALVE	<b>L</b> <sub>VD</sub>		L <sub>VD</sub>	24X12 — 6X12 — 12X10		24X12	_
ETR	EXISTING TO REMAIN		BUTTERFLY CONTROL VALVE, PNEUMATIC 2-WAY		DAMPER CONTROL, PARALLEL BLADE			SUPPLY AIR	18X12 12X10	
EUH	ELECTRIC UNIT HEATER		BUTTERFLY CONTROL VALVE, ELECTRIC ACTUATOR		DAMPER CONTROL, OPPOSED BLADE		18X12 20X12	TAKEOFFS	20X12 6X12	
F&T	FLOAT AND THERMOSTATIC TRAP	—— <b>⋈</b> ——	GLOBE VALVE				20X12			
FCU	FAN-COIL UNIT		CHECK VALVE		AUTOMATIC AIR DAMPER		24X12	SUPPLY/RETURN		
FPM	FEET PER MINUTE	<u>×</u>	TRIPLE DUTY VALVE	AAD		AAD		EXHAUST AIR	24X12	
FT	FIN-TUBE	———I <sub>Ф</sub> I———	GAS COCK, PLUG VALVE			<u> </u>	VD	TAKEOFFS W/ REGISTER/GRILLE/	VD VD	
GC	GENERAL CONTRACTOR	- U/C	UNDERCUT DOOR 1"	BDD	BACK DRAFT DAMPER	BDD		DIFFUSER		
GR GS	GLYCOL RETURN GLYCOL SUPPLY		LOUVERED DOOR W/ SQ. FT. OF FREE AREA	1			<u> </u>		TTIVD	+
HC	HVAC CONTRACTOR	<u></u>	AIR VENT - MANUAL		BLAST GATE		VD	SUPPLY/RETURN		
HHWR	HEATING HOT WATER RETURN			l <sub>BG</sub>		BG	$\rightarrow$	EXHAUST AIR END OF MAIN		
HHWS	HEATING HOT WATER SUPPLY		AIR VENT - AUTOMATIC	20/10		12X10	VD	BRANCH TAKEOFFS	T. Ivo	
НР	HEAT PUMP		FLANGE		AIR DUCT (FIRST FIGURE IS DUCT WIDTH/TOP,	12X10			T 1100	+
HPC	HIGH PRESSURE CONDENSATE		CONTROL/SOLENOIND VALVE, ELECTRIC 2-WAY		SECOND FIGURE IS DUCT DEPTH)		VD	SUPPLY/RETURN	ŢĮVD	
HPS	HIGH PRESSURE STEAM		CONTROL VALVE, ELECTRIC 3-WAY	10/00		10/20 7		EXHAUST AIR		
LF	LINEAR FOOTAGE OF FIN-TUBE RADIATION	<u> </u>	CONTROL VALVE, PNEUMATIC 2-WAY	10/20 7				END OF MAIN BRANCH TAKEOFFS	IVD IVD	
LPC	LOW PRESSURE CONDENSATE		CONTROL VALVE, PNEUMATIC 3-WAY		MULTI-BLADE AIR EXTRACTOR		<u></u>			
LPG LPS	LIQUEFIED PROPANE GAS  LOW PRESSURE STEAM	<del>4</del>		No.	TURNING VANES					
МВН	1,000 BTU/HR	<u></u>	RELIEF / SAFETY VALVE		EXISTING WORK TO BE REMOVED (HATCHED)		$\sim$	LONG RADIUS 90° ELBOW	W R	
МС	MECHANICAL CONTRACTOR	<b>\</b>	PRESSURE REDUCING VALVE	P	POINT OF CONNECTION			R/W=1.5		
MPC	MEDIUM PRESSURE CONDENSATE	早∨	VACUUM BREAKER	R	POINT OF DISCONNECTION					
MPS	MEDIUM PRESSURE STEAM		FLEXIBLE PIPE CONNECTOR	<u> </u>	AIR FLOW SENSOR					$\dagger$
MRD	MONOFLO FITTING DOWN – HHWR		EXPANSION COMPENSATOR W/ GUIDES		FILTER		$\lambda$	LONG RADIUS	$\stackrel{W}{\downarrow}$	
MSD	MONOFLO FITTING DOWN – HHWS		EXPANSION JOINT					45° ELBOW R/W=1.5		
MUW	MAKE-UP WATER  NORMALLY CLOSED	X	PIPE ANCHOR		TRANSITION SQUARE TO ROUND					
NC NG	NATURAL GAS		PIPE GUIDE							_
NO	NORMALLY OPEN	тт		$\exists$	HUMIDIFIER DISPERSION TUBE		$\sim$	90° ELBOW	τ <sup>M</sup>	
NTS	NOT TO SCALE	FT C	THERMOSTATIC TRAP	RISE				WITH TURNING		
OA	OUTSIDE AIR	FT D	FLOAT & THERMOSTATIC TRAP		RISE IN DUCT			VANES	/ I   X	
PC	PLUMBING CONTRACTOR	BT	BUCKET TRAP	R						4
PD	PUMP DISCHARGE		THERMODYNAMIC TRAP	DROP	DROP IN DUCT		1971/	00 )/2222	18X8	
PHWR	PRIMARY HEATING HOT WATER RETURN		THERMOMETER	D			18X16 — 18X8	90 VERTICAL SPLIT OFF		
PHWS	PRIMARY HEATING HOT WATER SUPPLY		WELL		SQUARE CEILING DIFFUSER (4 WAY)		18X8	(PLAN VIEW)	18X16 18X8	
RA RD	RETURN AIR REFRIGERANT DISCHARGE	——Ø	PRESSURE GAUGE	<u>e</u>	ROUND CEILING DIFFUSER					
RHC	HOT WATER REHEAT COIL	Ø	STEAM PRESSURE GAUGE		SQUARE OR RECTANGULAR CEILING GRILLE	_	20X10 20X10	DUCT TURNING		T
RLL	REFRIGERANT LIQUID PIPE	\rightarrow	WITH 1/4" NEEDLE VALVE		SUPPLY REGISTER, RETURN OR EXHAUST GRILLE		20X10	UP OR DOWN	20X10	
RSL	REFRIGERANT SUCTION PIPE		DDECCURE CAME					AIR TERMINAL UNIT-DUCT	NORK	7
RTU	ROOFTOP UNIT		PRESSURE GAUGE WITH 1/4" NEEDLE VALVE	1-WAY 2-WAY 3-WAY	SUPPLY DIFFUSER, 1-WAY, 2-WAY, 3-WAY		U MAX MIN	U - UNIT TYPE  MAX = MAXIMUM CFM  MIN = MINIMUM CFM		
RV	ROOF VENT		PNEUMATIC (CONTROL) TUBING		CELLING DIEELISED			MIN = MINIMUM CFM  AIR TERMINAL UNIT-DUCT	NORK	+
SA	SUPPLY AIR	<u>.</u> ↑.	BUTTERFLY VALVE WITH PNEUMATIC	8"Ø, D-3 300 CFM	CEILING DIFFUSER WITH NECK SIZE, TYPE, & CFM		U GPM MAX	U - UNIT TYPE GPM = GALLONS PER MIN		
SHWR	SECONDARY HEATING HOT WATER RETURN	11	AND MANUAL OPERATORS				<del>-</del>	MAX = MAXIMUM GPM  FAN POWERED AIR		-
SHWS	SECONDARY HEATING HOT WATER SUPPLY  SPLIT SYSTEM INDOOR SECTION (EVAPORATOR SECTION)	XX	PIPING	10"x10", G-3 A	CEILING RETURN OR EXHAUST GRILLE WITH SIZE, TYPE, & CFM		MAX	TERMINAL UNIT U - UNIT TYPE		
SSO	SPLIT SYSTEM INDOOR SECTION (EVAPORATOR SECTION)  SPLIT SYSTEM OUTDOOR SECTION (CONDENSING UNIT)	XX	PIPING BELOW GRADE	300 CFM			U MIN FAN	MAX = PRIMARY MAX CFA		
IC 220	TEMPERATURE CONTROLS CONTRACTOR		BASE MOUNTED PUMP	10"x8", R-2 300 CFM	SUPPLY REGISTER WITH SIZE, TYPE, & CFM			FAN = FAN CFM		
UH	UNIT HEATER		IN-LINE PUMP	300 CFM	5.22, 2, & 51/11		TYPE	TYPE = VALANCE TYPE		
UV	UNIT VENTILATOR		AIR TERMINAL UNIT WITH REHEAT COIL AND SOUND	10"x8", G-2	RETURN OR EXHAUST GRILLE		COIL SIZE CLNG GPM	COIL SIZE = COIL LENGTH CLNG GPM = COOLING C	SPM .	
V	VENT		ATTENUATOR	300 CFM	WITH SIZE, TYPE, & CFM		HTNG GPM	HTNG GPM = HEATING GI	'M	
WAHP	WATER-TO-AIR HEAT PUMP		AIR TERMINAL UNIT WITH		AIR FLOW		(X)	X = DIFFUSER OR GRILL T		1
WWHP	WATER-TO-WATER HEAT PUMP		SOUND ATTENUATOR  AIR TERMINAL UNIT WITH	L1	ACOUSTIC/THERMAL DUCTWORK LINING - 1 INCH THICK		XXX	XX = AIR FLOW VALUE (C		
1			REHEAT COIL	L2	ACOUSTIC/THERMAL DUCTWORK LINING - 2 INCH THICK			•		_
		i								
			AIR TERMINAL UNIT	PL1	ACOUSTIC/THERMAL DUCTWORK PLENUM					
		W/W ENCL.	AIR TERMINAL UNIT  WALL TO WALL FIN TUBE ENCLOSURE	PL1						



50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

8/28/2020 KAB JJM scale AS NOTED

SHEET TITLE HVAC LEGEND AND ABBREVIATIONS

> PROJECT NUMBER 14428.16/17

DRAWING NUMBER

# **SYMBOLS GENERAL NOTES:**

VALVE AND DAMPER ACTUATOR TYPES (ELECTRIC OR PNEUMATIC) WHICH ARE INDICATED IN HVAC TEMPERATURE CONTROL DRAWINGS SHALL SUPERSEDE TYPE INDICATED ON ALL OTHER HVAC DRAWINGS.

## **HVAC CONTRACTOR GENERAL NOTES:**

**DESCRIPTION** 

**CURRENT TRANSDUCER** 

OPEN/CLOSED

**ENABLE/DISABLE** 

FLOW TRANSMITTER

PRESSURE TRANSMITTER

**DUCT SMOKE DETECTOR** 

SPACE TEMPERATURE SENSOR

SPACE NATURAL GAS SENSOR

SPACE SENSOR WITH GUARD

SPACE HUMIDISTAT

WATER FLOW SENSOR

PNEUMATIC ACTUATOR

ELECTRIC ACTUATOR

**COOLING COIL** 

**HEATING COIL** 

GAS FURNACE

ALARM

STATUS

RELAY

FLOW SWITCH

PRESSURE GAUGE

**ELECTRICAL INTERFACE** 

POSITION FEEDBACK

TRAVERSE AVERAGING SENSOR

SPEED FEED BACK

**END SWITCH** 

PROBE SENSOR

FREEZE STAT SENSOR

FREEZE-STAT

SPACE CARBON DIOXIDE SENSOR

SPACE CARBON MONOXIDE SENSOR

**VARIABLE SPEED / FREQUENCY DRIVE** 

DIFFERENTIAL STATIC PRESSURE SWITCH

DIGITAL INPUT (TO BUILDING MANAGEMENT SYSTEM)

DIGITAL OUTPUT (FROM BUILDING MANAGEMENT SYSTEM)

ANALOG OUTPUT (FROM BUILDING MANAGEMENT SYSTEM)

ANALOG INPUT (TO BUILDING MANAGEMENT SYSTEM)

SPACE THERMOSTAT

T

Ţ

 $\bigoplus$ 

FS

 $\stackrel{\text{DO}}{\Longrightarrow}$ 

**~** 

START/STOP

ELECTRIC/PNEUMATIC SWITCH OR RELAY

PNEUMATIC/ELECTRIC SWITCH OR RELAY

TEMPERATURE SENSOR (DUCT OR PIPE MOUNTED)

HUMIDITY SENSOR (DUCT MOUNTED)

**DIFFERENTIAL PRESSURE TRANSMITTER** 

ELECTRIC/PNEUMATIC TRANSDUCER

ELECTRIC/ELECTRONIC TRANSDUCER

- A. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY EXISTING CONDITIONS WITHIN THE BUILDING PRIOR TO COMMENCEMENT OF ALL DEMOLITION AND NEW
- B. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO REMOVE AND REPLACE EXISTING CEILINGS, UNLESS OTHERWISE NOTED ON THE ARCHITECTURAL DRAWINGS, FOR PERFORMING DEMOLITION OR NEW WORK WITHIN THE BUILDING. THE EXISTING CEILINGS SHALL BE REMOVED IN A MANNER TO AVOID DAMAGE TO THE CEILING SYSTEMS. STORAGE OF CEILING SYSTEM COMPONENTS FOR REINSTALLATION IS THE RESPONSIBILITY OF THE CONTRACTOR. THE STORAGE OF ALL MATERIAL SHALL BE IN AREAS OR LOCATIONS APPROVED BY THE OWNER. THE OWNER WILL NOT COMPENSATE FOR ANY DAMAGED OR LOST MATERIAL WHILE IN STORAGE. AFTER COMPLETION OF ALL DEMOLITION OR NEW WORK, THE CONTRACTOR SHALL REINSTALL THE CEILING SYSTEMS TO MATCH THE ORIGINAL INSTALLATION.
- C. DEMOLITION DRAWINGS SHOW MAJOR EQUIPMENT, PIPING, AND DUCTWORK REMOVALS. THE INTENT IS NOT TO IDENTIFY ALL MISCELLANEOUS PIPING, PIPING ACCESSORIES, DUCTWORK, DUCTWORK ACCESSORIES, SUPPORTS, CONTROLS, CONTROL ACCESSORIES, CONTROL WIRING, CONDUIT, AND PNEUMATIC CONTROL TUBING TO BE DISCONNECTED AND REMOVED, BUT IS THE REQUIREMENT UNDER THIS CONTRACT. NO EQUIPMENT, PIPING, OR DUCTWORK SHALL BE ABANDONED IN PLACE, UNLESS OTHERWISE NOTED ON THE DRAWINGS.
- D. ALL EQUIPMENT INDICATED TO BE TURNED OVER TO THE OWNER SHALL BE DISCONNECTED AND REMOVED FROM THE EXISTING SYSTEMS AND DELIVERED (INCLUDING LOADING AND UNLOADING) TO A STORAGE AREA WITHIN THE BUILDING AS SELECTED BY THE OWNER. IT WILL BE THE RESPONSIBILITY OF THE CONTRACTOR TO REPAIR ANY EQUIPMENT DAMAGED DURING REMOVAL AND DELIVERY. ANY DAMAGE TO EQUIPMENT PRIOR TO DISCONNECTING SHOULD BE REPORTED TO THE OWNER'S REPRESENTATIVE. IF NOT REPORTED, THE CONTRACTOR TAKES FULL RESPONSIBILITY FOR REPAIRS TO THE EQUIPMENT.
- E. BEFORE DISCONNECTING, REMOVING, OR SERVICING ANY AIR CONDITIONING EQUIPMENT OR SYSTEMS CONTAINING REFRIGERANTS, THE EQUIPMENT OR SYSTEMS SHALL BE EVACUATED OF ALL REFRIGERANT PER THE LATEST ADOPTED RULES AND REGULATIONS BY THE UNITED STATES ENVIRONMENTAL PROTECTION AGENCY (EPA). THE CONTRACTOR OR TECHNICIAN PERFORMING THE WORK SHALL BE CERTIFIED BY AN EPA APPROVED CERTIFYING AGENCY OR ORGANIZATION.
- F. ALL DUCTWORK, PIPING, AND CONDUIT PENETRATIONS THROUGH RATED WALLS OR FLOORS SHALL BE PROVIDED WITH FIRE/SMOKE STOPPINGS PER SPECIFICATION. REFER TO CODE ANALYSIS DRAWING FOR ALL RATED WALL LOCATIONS. ALL FLOORS SHALL BE CONSIDERED RATED.
- G. UNLESS SHOWN ON THE ARCHITECTURAL DRAWINGS, IT IS THE RESPONSIBILITY OF THIS CONTRACT TO PATCH AND FINISH ALL EXISTING DUCTWORK OR PIPE PENETRATIONS THROUGH FLOORS, ROOFS, INTERIOR WALLS, AND EXTERIOR WALLS AFTER DEMOLITION WORK. IN ADDITION, ALL NEW PENETRATIONS SHALL BE PROVIDED FOR INSTALLATION OF MECHANICAL SYSTEMS INCLUDING, BUT NOT LIMITED TO, EQUIPMENT, CURBING, DUCTWORK, PIPING, CONTROLS, ETC. PATCHING AND FINISHING SHALL MATCH EXISTING CONSTRUCTION INCLUDING FIRE RATINGS. PROVIDE LINTELS PER LINTEL SCHEDULE.
- H. IT IS NOT THE INTENT OF THE DRAWINGS TO SHOW ALL AIR VENTS AND DRAINS IN THE PIPING SYSTEMS. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PROVIDE AIR VENTS AT ALL SYSTEM HIGH POINTS AND AT AREAS WITHIN THE PIPING SYSTEMS THAT COULD ACCUMULATE OR TRAP AIR WHICH WOULD PREVENT PROPER VENTING OR OPERATION OF THE SYSTEMS. DRAINS SHALL BE PROVIDED AT ALL LOW POINTS WITHIN THE PIPING SYSTEM TO FACILITATE COMPLETE DRAINING OF THE SYSTEM.
- I. PROVIDE THERMAL EXPANSION COMPENSATORS AND THERMAL EXPANSION LOOPS IN PIPING SYSTEM PER INDUSTRY STANDARDS.

**GENERAL NOTES:** 

1. FIELD VERIFY ALL PIPING SIZES.

**KEY NOTES:** 

CONNECTION.

REMOVE EXISTING EXHAUST FAN, CONTROLS AND ASSOCIATED LOUVER. PREPARE OPENINGS FOR NEW LOUVER.

REMOVE EXISTING UNIT VENTILATOR, STEAM AND CONDENSATE PIPING, CONTROLS AND DUCTWORK. PREPARE FLOOR FOR PATCHING.

REMOVE EXISTING STEAM AND CONDENSATE MAINS TO POINTS INDICATED. PREPARE ALL REMAINING RISERS AND PIPES FOR NEW

CONNECT NEW 20"X6" PLENUM DUCTWORK TO EXISTING OUTDOOR AIR LOUVER. MAKE PROVISIONS FOR PROPER TRANSITION.


5 PROVIDE NEW 30"X30" LOUVER. EXPAND OPENING AND PROVIDE NEW LINTEL TO ACCOMMODATE NEW RELIEF FAN. CONNECT TO EXISTING ANDOVER BMS. INTERLOCK WITH UV OPERATIONS.

PROVIDE NEW 35"X10" LOUVER. EXPAND OPENING AND PROVIDE NEW LINTEL ACCOMMODATE NEW OUTDOOR AIR DUCTWORK CONNECTION. REMOVE OR RELOCATE CHAIN LINK FENCING AS REQUIRED TO INSTALL THE NEW LOUVER, RE-INSTALL AFTER THE WORK IS COMPLETED.


ROLL 14"Ø DUCTWORK UP INTO JOIST SPACE. COORDINATE WITH EXISTING LIGHTING AND OTHER UTILITIES. POINT SIDE MOUNTED GRILLES DOWN 45° TOWARDS THE FLOOR. ROUTE DUCT IN BAYS WITHOUT LIGHTING.

8 CONNECT NEW STEAM AND CONDENSATE MAINS TO EXISTING MAINS AND RISERS AT POINTS INDICATED. ROUTE NEW MAINS AT THE SAME ELEVATION AS THE PIPING THAT WAS REMOVED. MAINTAIN ALL REQUIRED PIPING PITCHES. COORDINATE PIPING MAINS WITH LIGHTING AND NEW EQUIPMENT. RE-INSULATE ALL PIPING PER SPECIFICATIONS.


9 CONNECT NEW UNIT CONTROLS TO EXISTING ANDOVER CONTROLS


















50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

SURVEYOR IS ALTERED, THE ALTERING PARTY SHALL AFFIX TO THE ITEM THEIR SEAL AND THE NOTATION "ALTE

AENTS #66-14-01-03-0-004-023

HVAC IMPROVEMENTS

CHILDHOOD CENTER SED #66-14-01-03

HIGH SCHOOL

SED #66-14-01-03

DATE DRAWN CHECKED 8/28/2020 KAB JJM

SCALE AS NOTED

SHEET TITLE

BASEMENT
HVAC DEMOLITION AND
NEW WORK PLAN

PROJECT NUMBER
14428.16/17

HS
H100

DRAWING NUMBER

1. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO REMOVE AND REPLACE EXISTING CEILINGS TO PERFORM ANY DEMOLITION OR NEW WORK. ANY EXISTING CEILINGS REQUIRING REMOVAL TO COMPLETE WORK SHALL BE REMOVED IN A MANNER TO AVOID DAMAGE AND BE REUSED. STORAGE OF CEILING SYSTEM COMPONENTS FOR REINSTALLATION IS THE RESPONSIBILITY OF THE CONTRACTOR. THE STORAGE OF ALL MATERIALS SHALL BE IN AREAS OR LOCATIONS APPROVED BY THE OWNER. THE OWNER WILL NOT COMPENSATE FOR ANY DAMAGED OR LOST MATERIAL WHILE IN STORAGE. AFTER COMPLETION OF ALL DEMOLITION OR NEW WORK, THE CONTRACTOR SHALL REINSTALL THE CEILING SYSTEMS TO MATCH THE ORIGINAL INSTALLATION.

#### **KEY NOTES:**

REMOVE EXISTING UNIT VENTILATOR, WALL LOUVER, SLEEVE, GRILLE, AND DUCTWORK IN ITS ENTIRETY INCLUDING ALL ASSOCIATED ACCESSORIES. PREPARE WALL OPENING FOR NEW LOUVER. EXTRACT AND RETAIN EXISTING CONTROLS FOR RE-INSTALLATION.

REMOVE EXISTING STEAM PIPING, CONDENSATE RETURN PIPING AND TRAP TO POINT BELOW FLOOR IN CRAWL SPACE.
PREPARE PIPING FOR NEW UV. INFILL EXISTING FLOOR PENETRATIONS AS REQUIRED TO MATCH EXISTING MATERIALS


ARCHITECTURE - ENGINEERING - PLANNING


50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

FIRST FLOOR HVAC DEMOLITION PLAN

14428.16/17








FIRST FLOOR HVAC DEMOLITION PLAN - AREA B
SCALE: 1/8" = 1'-0"

1. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO REMOVE AND REPLACE EXISTING CEILINGS TO PERFORM ANY DEMOLITION OR NEW WORK. ANY EXISTING CEILINGS REQUIRING REMOVAL TO COMPLETE WORK SHALL BE REMOVED IN A MANNER TO AVOID DAMAGE AND BE REUSED. STORAGE OF CEILING SYSTEM COMPONENTS FOR REINSTALLATION IS THE RESPONSIBILITY OF THE CONTRACTOR. THE STORAGE OF ALL MATERIALS SHALL BE IN AREAS OR LOCATIONS APPROVED BY THE OWNER. THE OWNER WILL NOT COMPENSATE FOR ANY DAMAGED OR LOST MATERIAL WHILE IN STORAGE. AFTER COMPLETION OF ALL DEMOLITION OR NEW WORK, THE CONTRACTOR SHALL REINSTALL THE CEILING SYSTEMS TO MATCH THE ORIGINAL INSTALLATION.


#### **KEY NOTES:**

- 1 REMOVE EXISTING UNIT VENTILATOR, WALL LOUVER, SLEEVE, GRILLE, AND DUCTWORK IN ITS ENTIRETY INCLUDING ALL ASSOCIATED ACCESSORIES. PREPARE WALL OPENING FOR NEW LOUVER. EXTRACT AND RETAIN EXISTING CONTROLS FOR RE-INSTALLATION.
- (2) REMOVE EXISTING STEAM PIPING, CONDENSATE RETURN PIPING AND TRAP TO POINT BELOW FLOOR IN FIRST FLOOR CEILING. PREPARE PIPING FOR NEW UV. INFILL EXISTING FLOOR PENETRATIONS AS REQUIRED TO MATCH EXISTING MATERIALS AND FINISHES.
- (3) EXISTING LOUVER AND INTAKE DUCTWORK DIRECTLY BELOW UNIT SHALL REMAIN FOR REUSE. REMOVE ANY OBSTRUCTIONS AND PREPARE FOR RECONNECTION TO NEW UNIT VENTILATOR.




SECOND FLOOR HVAC DEMOLITION PLAN - AREA A

SCALE: 1/8" = 1'-0"







ARCHITECTURE - ENGINEERING - PLANNING

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

DATE DRAWN CHECKED BY SCALE AS NOTED

SECOND FLOOR HVAC DEMOLITION PLAN


14428.16/17

REMOVE EXISTING GRAVITY VENT AND CURB. PREPARE FOR NEW CURB. INFILL DECKING MATERIAL AS REQUIRED. REFER TO ROOF SUPPORT DETAILS FOR ADDITIONAL REQUIREMENTS. COORDINATE WITH THE OWNER AND THE EXISTING ROOFING MANUFACTURER TO MAINTAIN THE WARRANTY ON THE ROOF. ALL ROOFING WORK SHALL BE PER THE ROOFING MANUFACTURER'S AND NRCA REQUIREMENTS AND RECOMMENDATIONS.


CPLteam.com

AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614




2 ROOF HVAC DEMOLITION PLAN - AREA B
SCALE: 1/8" = 1'-0"




DATE DRAWN CHECKED
8/28/2020 KAB JJM

SCALE AS NOTED

SHEET TITLE
ROOF HVAC
DEMOLITION PLAN





1. REBALANCE ALL GRILLES TO AIRFLOW RATES INDICATED IN BRACKETS [].

**KEY NOTES:** 

1) PROVIDE NEW UNIT VENTILATOR, LOUVER, AND LOUVER SLEEVE. UNIT VENTILATOR SHALL INCLUDE A TWO-INCH STEP DOWN TO ALLOW INSTALLATION BELOW THE EXISTING WINDOW SILL. MODIFY VERTICAL SILL TRIM AS REQUIRED TO FACILITATE UNIT INSTALLATION FLUSH WITH WALL. FIELD VERIFY THE REQUIRED STEP DOWN HEIGHT AND CABINET DEPTH PRIOR TO SUBMITTING AND ORDERING EQUIPMENT. ROUTE PIPING IN UNIT VENTILATOR PIPE PORTAL. AVOID ROUTING PIPING IN FRONT OF LOUVERS. PROVIDE HARD DUCTED SLEEVE TO NEW LOUVER AND SEAL WEATHER TIGHT. PATCH AND REPAIR ALL DISTURBED PORTIONS OF EXISTING WALLS AND FLOOR TO MATCH EXISTING MATERIALS AND FINISHES.


PROVIDE NEW FLOOR PENETRATIONS ALIGNING WITH NEW UNIT VENTILATOR END POCKET PIPE PORTAL. EXTEND AND CONNECT STEAM AND CONDENSATE RETURN PIPING FROM CRAWL SPACE TO UNIT VENTILATOR. REINSTALL EXISTING CONTROLS AND PROVIDE NEW STEAM TRAPS.


MODIFY EXISTING OUTDOOR AIR OPENING IN EXTERIOR WALL TO ACCOMMODATE NEW LOUVER. PROVIDE NEW LINTEL. SEE UV AND LINTEL SCHEDULE FOR SIZES.


(4) PROVIDE NEW OPPOSED BLADE DAMPER SIZED TO MATCH EXISTING REGISTER. INSTALL CONCEALED BEHIND EXISTING REGISTER.

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

ARCHITECTURE - ENGINEERING - PLANNING








FIRST FLOOR HVAC NEW WORK PLAN - AREA B

SCALE: 1/8" = 1'-0"



FIRST FLOOR HVAC NEW WORK PLAN

14428.16/17

207

UV-18

ROOF

VIDEO ROOM

(E)12"x36"—

EA DN.

(E)24"x26" REGISTER [1250 CFM]

UV-17

(E)36"x18" REGISTER-\

(E)24"x18"—

(E)27"x27" UP TO

(E)24"x18"—

ROOF

VENTILATOR ON ROOF

206

<u>ROOM</u> 200A

203

SECOND FLOOR HVAC NEW WORK PLAN - AREA A

SCALE: 1/8" = 1'-0"

(E)18"x18" REGISTER [625 CFM]

[1250 CFM]

⊢(E)36"x12"

┌(E)36"x12"


EA DN.

1. REBALANCE ALL GRILLES TO AIRFLOW RATES INDICATED IN BRACKETS [].


**KEY NOTES:** 

1) PROVIDE NEW UNIT VENTILATOR, LOUVER, AND LOUVER SLEEVE. UNIT VENTILATOR SHALL INCLUDE A TWO-INCH STEP DOWN TO ALLOW INSTALLATION BELOW THE EXISTING WINDOW SILL. MODIFY VERTICAL SILL TRIM AS REQUIRED TO FACILITATE UNIT INSTALLATION FLUSH WITH WALL. FIELD VERIFY THE REQUIRED STEP DOWN HEIGHT AND CABINET DEPTH PRIOR TO SUBMITTING AND ORDERING EQUIPMENT. ROUTE PIPING IN UNIT VENTILATOR PIPE PORTAL. AVOID ROUTING PIPING IN FRONT OF LOUVERS. PROVIDE HARD DUCTED SLEEVE TO NEW LOUVER AND SEAL WEATHER TIGHT. PATCH AND REPAIR ALL DISTURBED PORTIONS OF EXISTING WALLS AND FLOOR TO MATCH EXISTING MATERIALS AND FINISHES.

- (2) PROVIDE NEW FLOOR PENETRATIONS ALIGNING WITH NEW UNIT VENTILATOR END POCKET PIPE PORTAL LOCATION. EXTEND AND CONNECT STEAM AND CONDENSATE RETURN PIPING FROM CRAWL SPACE TO UNIT VENTILATOR. REINSTALL EXISTING CONTROLS AND PROVIDE NEW STEAM TRAPS.
- (3) MODIFY EXISTING OUTDOOR AIR OPENING IN EXTERIOR WALL TO ACCOMMODATE NEW LOUVER. PROVIDE NEW LINTEL. SEE UV AND LINTEL SCHEDULE FOR SIZES.
- (4) PROVIDE NEW OPPOSED BLADE DAMPER SIZED TO MATCH EXISTING REGISTER. INSTALL CONCEALED BEHIND EXISTING REGISTER.
- (5) ALIGN NEW UV OUTSIDE AIR INTAKE PLENUM DIRECTLY OVER EXISTING INTAKE OPENING IN FLOOR. OWNER SHALL FUR OUT WALL AS NECESSARY TO FACILITATE UV INSTALLATION OVER INTAKE OPENING.







ARCHITECTURE - ENGINEERING - PLANNING

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

DATE DRAWN CHECKED 8/28/2020 KAB JJM SCALE AS NOTED

SECOND FLOOR HVAC NEW WORK PLAN

14428.16/17

H202

KEY NOTES:

1 PROVIDE NEW EXHAUST FAN AND ROOF CURB WHERE INDICATED. PROVIDE ALL NECESSARY DUCTWORK MODIFICATIONS AND TRANSITIONS AS REQUIRED TO FACILITATE CONNECTION TO EXISTING LOUVER BOX. PROVIDE ROOFING WORK AS REQUIRED TO FACILITATE INSTALLATION

AND SUPPORT OF NEW EXHAUST FAN. REFER TO ROOFING SUPPORT DETAILS FOR REQUIREMENTS.

CPLteam.com

Source = Engineering = Parteration.

AND A SPECIFIC DESCRIPTION OF THE ALTERATION.

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

VEYOR IS ALTERED, THE ALTERING PARTY SHALL AFFIX TO THE ITEM THEIR SEAL AND THE NOTATION "ALTERED BY" FOLLOWED BY THEIR SIGNA"

2

IION FREE SCHOOL DISTRICT

C IMPROVEMENTS

OD CENTER SED #66-14-01-03-0-004-0

PARK EARLY CHILDHOOD OSSINING HIGH SCHOOL

DATE DRAWN CHECKED 8/28/2020 KAB JJM

SCALE AS NOTED

SHEET TITLE


ROOF HVAC


NEW WORK PLAN

PROJECT NUMBER
14428.16/17

PES


PES H203 DRAWING NUMBER






2 ROOF HVAC NEW WORK PLAN - AREA B

SCALE: 1/8" = 1'-0"





**⊘** 3/16 (TYP.)

L4x3x1/4 LLV

THE ABOVE STEEL SIZES SHALL BE USED UNLESS NOTED OTHERWISE ON THE PLANS.
USE 1 1/2" X 20 GA. METAL DECKING TO INFILL ROOF OPENINGS WHERE EXISTING

MECHANICAL CONTRACTOR AND FINAL APPROVED EQUIPMENT SUBMITTAL.

FOR SPANS GREATER THAN 5'-0" AND UP TO 7'-0" USE L5X3 1/2X5/16 LLV ANGLES.

3. CONTRACTOR TO COORDINATE EQUIPMENT AND OPENING SUPPORTS WITH

THIS DETAIL IS FOR ROOF OPENINGS ONLY. REFER TO OTHER DETAILS FOR


**ROOF OPENING SUPPORT DETAIL** 

OPENING SIZE HAS BEEN REDUCED


- L4x3x1/4 LLV x 4" LG

L4x3x1/4 LLV x 4" LG -

(IN DECK FLUTE)











- 3. L4x4x5/16 MEMBERS CAN BE REPLACED WITH L3x3x1/4 MEMBERS FOR EQUIPMENT LESS THAN 1,000 LB IN TOTAL WEIGHT (INCLUDES OPERATING WEIGHT).
- 4. FOR SPANS GREATER THAN 5'-0" AND UP TO 7'-0" USE L6x4x3/8 LLV ANGLES.











8 EXHAUST FANS WITH EC MOTORS, INTEGRAL VFD, AND BMS SPEED CONTROL





H800 NOT TO SCALE

NOTES:

1. INSTALL ROOFING PER NRCA RECOMMENDATIONS. COORDINATE WITH OWNER AND EXISTING ROOFING MANUFACTURER TO MAINTAIN WARRANTY.

2. REMOVE EXISTING ROOFING AND ROOF INSULATION DOWN TO EXISTING ROOF DECK AS NECESSARY FOR INSTALLATION OF HVAC EQUIPMENT CURB. CUT OPENING IN EXISTING ROOF DECK AND PROVIDE STRUCTURAL SUPPORT FOR MECHANICAL EQUIPMENT AND OPENING EDGE.

3. INSTALLATION OF ALL MECHANICAL EQUIPMENT, RAILS AND CURBS SHALL CONFORM TO NYS BUILDING CODE SECTION 1604.9 AND THE WIND RESTRAINT REQUIREMENTS OF THIS PROJECT.

10 PIPE PORTAL DETAIL

NOT TO SCALE

DATE DRAWN CHECKED
8/28/2020 KAB JJM

SCALE AS NOTED

SHEET TITLE

HVAC DETAILS

ARCHITECTURE • ENGINEERING • PLANNING

50 FRONT STREET, SUITE 202

NEWBURGH, NEW YORK 12550

TEL (800) 274-9000

FAX (845) 567-9614

PES H800

						FAN SC	CHEDUL	E					
MARK	LOCATION	SERVICE	TYPE	CFM	SP	DIAMETER	FAN RPM		ELECTRI	CAL DATA		TYPICAL UNIT MFG.	REMARKS:
IVIARK	LOCATION	SERVICE	ITPE	CFIVI	IN W.G.	(IN.)	PAN RPIVI	BHP / HP	VOLTS	PHASE	VFD		REWARKS
EF-1	ROOF	RELIEF	DOWNBLAST	5,000	0.50	24.5	692	2	208	3	INTEGRAL	GREENHECK - G-240-C-VGD	1,2,3,4,5
EF-2	ROOF	RELIEF	DOWNBLAST	6,250	0.70	24.5	846	2	208	3	INTEGRAL	GREENHECK - G-240-C-VGD	1,2,3,4,5
EF-3	ROOF	RELIEF	DOWNBLAST	3,225	0.50	16.625	1277	2	208	1	INTEGRAL	GREENHECK - G-163-VG	1,2,3,4,5
EF-4	ROOF	RELIEF	DOWNBLAST	5,000	0.60	24.5	722	2	208	3	INTEGRAL	GREENHECK - G-240-C-VGD	1,2,3,4,5
EF-5	ROOF	RELIEF	DOWNBLAST	5,725	0.60	24.5	778	2	208	3	INTEGRAL	GREENHECK - G-240-C-VGD	1,2,3,4,5
EF-6	ROOF	RELIEF	DOWNBLAST	2,500	0.50	14.625	1522	1	208	1	INTEGRAL	GREENHECK - G-143-VG	1,2,3,4,5
EF-7	ROOF	RELIEF	DOWNBLAST	2,500	0.40	14.625	1490	1	208	1	INTEGRAL	GREENHECK - G-143-VG	1,2,3,4,5
EF-HS-1	GYM	RELIEF	WALL MNTD	700	0.25	14	1616	.06/.25	115	1	INTEGRAL	GREENHECK - SE1-12-436-VG	1,2,4,5
REMARKS:	1. PROVIDE WITH	MANUFACTURE	R'S DISCONNECT S	WITCH.		•				•	•		
	2. PROVIDE WITH	H MANUFACTURE	ER'S EC MOTOR WIT	TH INTEGRA	AL VFD AND 0-	-10 VDC INPUT SI	IGNAL CONTROL.						

4. PROVIDE TWO 12-INCH END COMPARTMENTS. FULL 30" HEIGHT WITH 2" STEP DOWN.

5. PROVIDE WITH MANUFACTURER'S ALUMINUM BIRDSCREEN.

2. FRONT RETURN GRILLE, BACK OUTDOOR AIR CONNECTION, TOP DISCHARGE, COIL AS HIGH AS POSSIBLE.

5. EXTERIOR LOUVER SHALL BE CUSTOM COLOR AS SELECTED BY THE ARCHITECT TO MATCH THE COLOR OF THE SURROUNDING BRICK.

MARK	LOCATION	SERVICE	FREE AREA (SQ. FT.)	CFM	SP (IN. WG)	SIZE W&H (IN.)	TYPICAL UNIT MFG. & MODEL NO.	REMARKS:
L-1	GYM	INTAKE	1.95	315	0	35X10	RUSKIN ELF375DX	1
L-2	GYM	RELIEF	0.97	630	0.06	18X18	RUSKIN ELF375DX	

			1	VENTILATIO	N SCHEDULE						
NEW TAG	WORST CASE ROOM	CFM/ft^2 AT MAXIMUM	TOTAL OCCUPANCY FOR VENTILATION	TOTAL SQ. FT.	O.A. PER SQ. FT. (CFM)	O.A. PER SW. FT. (CFM)	Vbz (CFM)	Ez	OVER VENTILATION FOR LOUVER CROSSCONTAMINATION	Voz=Vot (CFM)	SPACE MAXIMUM SUPPLY (CFM)
Park ECC - First Floor											
	Park ECC - Rm 101	0.00	30	774	10	0.12	393	0.9	0%	437	
	Park ECC - Rm 102	0.00	30	749	10	0.12	390	0.9	0%	433	
	Park ECC - Rm 103	0.00	30	776	10	0.12	393	0.9	0%	437	
	Park ECC - Rm 104	0.00	30	744	10	0.12	389	0.9	0%	433	
	Park ECC - Rm 105	0.00	30	774	10	0.12	393	0.9	0%	437	
	Park ECC - Rm 106	0.00	30	969	10	0.12	416	0.9	0%	463	
	Park ECC - Rm 107	0.00	30	1120	10	0.12	434	0.9	0%	483	
	Park ECC - Rm 108	0.00	30	776	10	0.12	393	0.9	0%	437	
	Park ECC - Rm 109	0.00	30	757	10	0.12	391	0.9	0%	434	
	Park ECC - Rm 110	0.00	30	763	10	0.12	392	0.9	0%	435	
	Park ECC - Rm 112	0.00	30	1147	10	0.12	438	0.9	0%	486	
Park ECC - Second Floor											
	Park ECC - Rm 200	0.00	30	765	10	0.12	392	0.9	0%	435	
	Park ECC - Rm 201	0.00	30	744	10	0.12	389	0.9	0%	433	
	Park ECC - Rm 202	0.00	30	780	10	0.12	394	0.9	0%	437	
	Park ECC - Rm 203	0.00	30	920	10	0.12	410	0.9	0%	456	
	Park ECC - Rm 204	0.00	30	744	10	0.12	389	0.9	0%	433	
	Park ECC - Rm 205	0.00	30	774	10	0.12	393	0.9	0%	437	
	Park ECC - Rm 206	0.00	30	941	10	0.12	413	0.9	0%	459	
	Park ECC - Rm 207	0.00	30	899	10	0.12	408	0.9	0%	453	
	Park ECC - Rm 208	0.00	30	776	10	0.12	393	0.9	0%	437	
	Park ECC - Rm 209	0.00	30	757	10	0.12	391	0.9	0%	434	
	Park ECC - Rm 210	0.00	30	759	10	0.12	391	0.9	0%	435	
	Park ECC - Rm 211	0.00	30	757	10	0.12	391	0.9	0%	434	
	Park ECC - Rm 212	0.00	30	753	10	0,12	390	0.9	0%	434	

	Outdoor Air Ventilation Calculations												
EQUIPMENT TAG	SPACE	AREA O.A. RATE (CFM/ft^2)	TOTAL OCCUPANCY	TOTAL SQ.FT.	O.A. PER PERSON (CFM)	O.A. PER SQ.FT. (CFM)	Vbz (CFM)	Ez	Louver Crosscontamination	Voz=Vot (CFM)			
UV-HS-1/2	WEIGHT ROOM	0.29	24	2340	20	0.06	620	0.9	0%	689			

LC	OSE LINTE	L SCHEDULE
WALL TYPE	SPAN	LINTEL
	1'-4" to 4'-6"	L 4 x 3 1/2 x 5/16 (L.L.V.)
4" MASONRY	4'-7" to 5'-6"	L 4 x 3 1/2 x 5/16 (L.L.V.)
/ VENEER	5'-7" to 6'-6"	L 5 x 3 1/2 x 5/16 (L.L.V.)
	6'-7" to 7'-6"	L 6 x 3 1/2 x 5/16 (L.L.V.)
	1'-4" to 4'-6"	(2) - L4 x 3 1/2 x 5/16 (L.L.V.)
	4'-7" to 5'-6"	(2) - L4 x 3 1/2 x 5/16 (L.L.V.)
8" BLOCK	5'-7" to 6'-6"	(2) - L5 x 3 1/2 x 5/16 (L.L.V.)
	6'-7" to 7'-6"	(2) - L6 x 3 1/2 x 5/16 (L.L.V.)
	7'-7" to 9'-0"	WT 9 x 25
4" BRICK &	1'-4" to 4'-6"	(3) - L4 x 3 1/2 x 5/16 (L.L.V.)
8" BLOCK	4'-7" to 5'-6"	(3) - L4 x 3 1/2 x 5/16 (L.L.V.)
OR	5'-7" to 6'-6"	(3) - L5 x 3 1/2 x 5/16 (L.L.V.)
12" BLOCK	6'-7" to 7'-6"	(3) - L6 $\times$ 3 1/2 $\times$ 5/16 (L.L.V.)

- 1. PROVIDE LOOSE LINTELS OVER ALL OPENINGS IN EXTERIOR AND INTERIOR MASONRY WALLS AS SCHEDULED UNLESS OTHERWISE INDICATED ON THE DRAWINGS.
- 2. MINIMUM BEARING FOR ALL LINTELS SHALL BE 8" EACH END.
- 3. BLOCK WALLS SHALL BE GROUTED SOLID 3 COURSES BELOW BEARING POINT FOR A WIDTH OF 16" UNLESS NOTED OTHERWISE ON STRUCTURAL FRAMING PLANS.
- 4. SEE ARCH., HVAC, & PLUMBING DRAWINGS FOR SIZE AND LOCATION OF ALL WALL OPENINGS.
- 5. CONTRACTOR SHALL PROVIDE AN ADDITIONAL 50 FT. OF ANGLE 5 x 3 1/2 x 5/16 OR THE EQUIVALENT.
- 6. FOR LINTEL SPANS GRATER THAN 6'-0", BOLT ASSEMBLIES
- TOGETHER AT 1/3 POINTS.
- 7. WHERE LINTELS REQUIRE 3 ANGLES, PROVIDE A 3/16" PLATE EQUAL TO WALL WIDTH ACROSS SPAN, ATTACHED TO BOTTOM OF THE LINTEL.

CPLteam.com
ARCHITECTURE - ENGINEERING - PLANNING

50 FRONT STREET, SUITE 202
NEWBURGH, NEW YORK 12550
TEL (800) 274-9000
FAX (845) 567-9614

DATE DRAWN CHECKED
8/28/2020 KAB JJM

SCALE AS NOTED

SHEET TITLE

HVAC SCHEDULES

PES H900

#### SINGLE LINE DIAGRAM LEGEND:

EARTH GROUND CHASSIS GROUND TRANSFORMER - KVA, PRIMARY AND SECONDARY 45 KVA VOLTAGE INDICATED. CONNECTIONS, K-RATING, AND SHIELD SPECIFIED 208/120V K-13 CURRENT TRANSFORMER POTENTIAL TRANSFORMER

DISCONNECT/LOADBREAK SWITCH CIRCUIT BREAKER

CIRCUIT BREAKER DRAWOUT MOUNTED (LOW VOLTAGE)

AUTOMATIC TRANSFER SWITCH (NORMAL POSITION SHOWN) \_\_\_\_\_M\_\_\_ ENCLOSED CIRCUIT BREAKER

LIGHTNING ARRESTER FUSED DISCONNECT SWITCH

PANEL 208-120V 225A

PANELBOARD-RATINGS AS SPECIFIED IN SINGLE LINE DIAGRAM AND ON PANELBOARD SCHEDULE

#### **COMMUNICATIONS LEGEND:**

(1) CAT3 - TELEPHONE JACK & CABLE

(NONE) STANDARD MODULAR JACK FOR TELEPHONE W WALL MOUNTED TELEPHONE MODULAR JACK P PUBLIC TELEPHONE MODULAR JACK COUNTER HEIGHT MODULAR JACK

TELEPHONE FLOOR OUTLET (1) CAT3 - TELEPHONE JACK & CABLE

DATA OUTLET WITH FLUSH BOX AND FACEPLATE (1) CAT5e - DATA JACK & CABLE

COMPUTER FLOOR OUTLET (1) CAT5e - DATA JACK & CABLE

COMBINATION TELEPHONE CABLE AND DATA OUTLETS IN DOUBLE GANG FLUSH MOUNTED BOX WITH FACEPLATE

WIRELESS TRANSMITTER (PROVIDED BY OWNER) CONTRACTOR TO PROVIDE (2) CAT5e DATA JACKS & CABLING

BACK BOX FOR OWNER PROVIDED TEL/COM WIRING & DEVICES

DATA RACK

COAX CABLE (TYPE F CONNECTOR)

CEILING MOUNT LCD PROJECTOR

SPEAKER (PUBLIC ADDRESS) (NONE) CEILING MOUNTED

W WALL MOUNTED

SPEAKER (LOCAL SOUND SYSTEM)

SPEAKER HORN MICROPHONE JACK

SPEAKER JACK

**VOLUME CONTROL** 

CLOCK

DOUBLE FACE CLOCK

COMBINATION CLOCK AND SPEAKER

INTERCOM STATION

REMOTE PRE-AMPLIFIER AND PAGING MICROPHONE

CONSOLE JACK

HOUSE LIGHT CONTROL STATION

WALL BOX AS SPECIFIED

FLOOR BOX

SYMBOLS SHOWN ON THIS ELECTRICAL SYMBOLS LIST ARE FOR REFERENCE PURPOSES ONLY. ALL OF THESE SYMBOLS MAY NOT BE USED FOR THIS PROJECT.

#### FIRE/LIFE SAFETY LEGEND:

FIRE ALARM PULL STATION

FIRE ALARM HORN

FIRE ALARM BELL

FIRE ALARM HORN AND STROBE COMBINATION

FIRE ALARM HORN AND STROBE COMBINATION, WEATHER PROOF

FIRE ALARM SPEAKER

FIRE ALARM SPEAKER - CEILING MOUNTED

FIRE ALARM SPEAKER AND STROBE COMBINATION

FIRE ALARM STROBE

FIRE ALARM STROBE - CEILING MOUNTED

SMOKE DETECTOR

SMOKE DETECTOR WITH GUARD

CARBON MONOXIDE DETECTOR

NATURAL GAS SENSOR

HEAT DETECTOR

COMBINATION SMOKE/HEAT DETECTOR

HEAT DETECTOR - 190° FIXED TEMPERATURE

HEAT DETECTOR - EXPLOSION PROOF

BEAM SMOKE DETECTOR TRANSMITTER

BEAM SMOKE DETECTOR RECEIVER

DUCT DETECTOR

SA INDICATES INSTALLATION IN SUPPLY AIR RA INDICATES INSTALLATION IN RETURN AIR

REMOTE TEST STATION FOR DUCT DETECTOR

FIRE ALARM SHUT DOWN RELAY

FIRE DOOR HOLD OPEN

TAMPER SWITCH

FLOW SWITCH

FIRE SUPRESSION ANSUL SYSTEM CONNECTION

SMOKE DAMPER RELAY CONNECTION SD/FD SMOKE DAMPER AND FIRE DAMPER SD SMOKE DAMPER

CONTROL MODULE, ADDRESSABLE

AREA OF RESCUE CALL STATION

AREA OF RESCUE MASTER TELEPHONE STATION

#### **SECURITY LEGEND:**

SECURITY KEY PAD

VIDEO CAMERA

CCTV VIDEO MONITOR

PASSIVE INFRARED MOTION DETECTOR

PROXIMITY CARD READER

CALL SWITCH

DOOR CONTACT

WINDOW CONTACT

ELECTRIC STRIKE DOOR RELEASE

MAGNETIC DOOR RELEASE

#### **NURSE CALL LEGEND:**

NURSE CALL BUTTON

NURSE CALL PATIENT BED STATION

CODE CALL BUTTON

NURSE CALL STAFF ASSIST STATION

NURSE CALL STAFF STATION

NURSE CALL DUTY/STAFF STATION

NURSE CALL DUTY STATION

NURSE CALL LIGHT

NURSE CALL CODE LIGHT

NURSE CALL ZONE LIGHT

NURSE CALL MASTER STATION

NURSE CALL EMERGENCY PULL STATION

NURSE CALL INFRARED SENSOR

#### LIGHT FIXTURE LEGEND:

VS

LIGHTING FIXTURE (SEE LIGHTING FIXTURE SCHEDULE FOR LETTER DESIGNATION AND DESCRIPTION OF FIXTURES)

EMERGENCY AND/OR NIGHT LIGHTING FIXTURE

EXIT LIGHTING FIXTURE UNIVERSAL MOUNT, SINGLE/DOUBLE FACE (WHERE USED, ARROW INDICATES CHEVRON DIRECTION)

BATTERY POWERED EMERGENCY LIGHT

TRACK LIGHTING

EMERGENCY LIGHT REMOTE HEAD

POLE MOUNTED LIGHTING (QUANTITY AND ORIENTATION OF HEADS AS SHOWN)

 $\bigcirc$ S OCCUPANCY SENSOR - CEILING MOUNTED

OCCUPANCY SENSOR - WALL MOUNTED

LIGHTING CONTACTOR

PHOTOCELL

SWITCH

LV LOW VOLTAGE 1-4 BUTTON STATION

VACANCY SENSOR - CEILING MOUNTED

(CONNECT TO LIGHTING CONTROL STATION) O OCCUPANCY SENSOR SWITCH

D DIMMER (INCANDESCENT) D3 THREE WAY DIMMER (INCANDESCENT)

DF DIMMER (FLUORESCENT) V VACANCY SENSOR SWITCH

#### **PANEL LEGEND:**

EXISTING ELECTRICAL PANEL

NEW ELECTRICAL PANEL

MDP MAIN DISTRIBUTION PANEL LVP LOW VOLTAGE PANEL HVP HIGH VOLTAGE PANEL

LP LIGHTING CONTROL PANEL IG ISOLATED GROUND PANEL

MSB MAIN SWITCH BOARD MCC MOTOR CONTROL CENTER

TVSS TRANSIENT VOLTAGE SURGE SUPPRESSION

AUTOMATIC TRANSFER SWITCH

ELECTRICAL SYSTEMS PANEL

SACP SECURITY ALARM CONTROL PANEL

FACP FIRE ALARM CONTROL PANEL PA PUBLIC ADDRESS CONTROL PANEL FAAP FIRE ALARM ANNUNCIATOR PANEL

# ELECTRICAL PANELBOARD LABELING PLACARD

LINE 1 - PANELBOARD NAME: PP1 (EXAMPLE) LINE 2 - VOLTAGE AND PHASE: 480/277V-3PH-4W (EXAMPLE) LINE 3 - WHERE PANELBOARD IS FED FROM: FF MSB BREAKER #14 (EXAMPLE)

#### **GENERAL ELECTRICAL NOTES:**

1) HATCHED AREAS ///// DESIGNATE EXISTING EQUIPMENT TO BE REMOVED, UNLESS OTHERWISE NOTED.

2) ALL WORK TO BE DONE IN ACCORDANCE WITH THE 2014 EDITION OF THE NATIONAL ELECTRIC CODE (NFPA 70).

3) CONTRACTOR SHALL FIELD VERIFY ALL CONDITIONS AND COORDINATE WITH EXISTING EQUIPMENT PRIOR TO BIDDING. **BUILDING:** 

4) INSTALLATION HEIGHT TO CENTER OF EQUIPMENT ABOVE FINISHED FLOOR UNLESS OTHERWISE NOTED TO BE: RECEPTACLE = 18" SWITCH = 44"

MODULAR JACK FOR WALL MOUNTED TELEPHONE = 52" MODULAR TELEPHONE JACK = 18" AUDIO/VISUAL FIRE ALARM INDICATORS = 88" FIRE ALARM PULL STATIONS = 48" TELEVISION OUTLET = 7'-0''COMPUTER OUTLET = 18" CALL SWITCH = 44"

REMOTE TEST STATION FOR DUCT DETECTOR = 52"

5) INSTALL DATA JACKS FOR CEILING MOUNTED WIRELESS TRANSMITTERS ABOVE CEILING IN ALL AREAS WHERE THERE IS AN ACCESSIBLE CEILING. PROVIDE FLUSH MOUNTED JACKS IN ALL HARD CEILINGS.

C = ABOVE COUNTER BACKSPLASH, COORDINATE WITH ARCHITECTURAL ELEVATIONS AND MILLWORK.

6) ALL CONDUIT AND WIRING TO BE CONCEALED IN WALLS, FLOOR, OR ABOVE CEILINGS UNLESS OTHERWISE NOTED OR APPROVED BY THE ARCHITECT/ENGINEER. ALL DEVICE OUTLET BOXES SHALL BE RECESSED UNLESS OTHERWISE NOTED OR APPROVED BY THE ARCHITECT/ENGINEER. WHERE APPROVED OR NOTED, SURFACE METAL RACEWAY AND DEVICE BOXES SHALL BE USED IN-LIEU OF CONDUIT AND CONCEALED BOXES AT NO EXTRA COST TO THE OWNER.

7) ALL CONDUIT ROUTES SHOWN ARE APPROXIMATE ONLY. CONTRACTOR SHALL FIELD VERIFY FINAL ROUTE.

8) CONDUIT RUNS SHOWN ARE SCHEMATICAL AND DO NOT INDICATE THE NECESSARY FITTINGS AND JUNCTION BOXES THAT ARE INCLUDED IN THE SCOPE OF THE WORK.

## GROUNDING:

9) ALL METAL RACEWAYS, INCLUDING CONDUIT, WIRE TROUGHS, WIREMOLD, ETC., SHALL BE GROUNDED. ALL CONNECTIONS IN METAL RACEWAYS SHALL BE COMPLETED IN SUCH A MANNER AS TO MAINTAIN A CONTINUOUS PATH TO GROUND THROUGHOUT THE ENTIRE LENGTH OF THE RACEWAY.

#### WIRING:


10) UNLESS NOTED OTHERWISE ON THE DRAWINGS OR ON THE EQUIPMENT WIRING SCHEDULE, EACH BRANCH CIRCUIT SHALL BE THREE (3) #12 AWG THHN/THWN (1 HOT, 1 NEUTRAL & 1 EQUIPMENT GROUND) IN 3/4" EMT CONDUIT. PROTECT EACH CIRCUIT WITH A 20 AMPERE, 1-POLE OVERCURRENT DEVICE UNLESS OTHERWISE NOTED. PROVIDE #10 AWG FOR 120V BRANCH CIRCUITS LONGER THAN 100 FEET. COMBINED NEUTRALS ARE NOT PERMITTED.




50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550

TEL (800) 274-9000

FAX (845) 567-9614





DATE DRAWN CHECKED [8/28/2020| MAY | JBT SCALE AS NOTED ELECTRICAL LEGEND & NOTES

> PROJECT NUMBER 14428.16/17

DRAWING NUMBER



50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

ARCHITECTURE - ENGINEERING - PLANNING

-023

C IMPROVEMENTS

DD CENTER SED #66-14-01-03-0-004-02

OL SED #66-14-01-03-0-003-04

PARK EARLY CHILDH
OSSINING HIGH SCH


DATE DRAWN CHECKED 8/28/2020 MAY JBT SCALE AS NOTED

SHEET TITLE


BASEMENT ELECTRICAL
DEMOLITION AND
NEW WORK PLAN

PROJECT NUMBER
14428.16/17

HS E100 DRAWING NUMBER











112





1 FIRST FLOOR ELECTRICAL DEMOLITION PLAN - AREA A
E101 SCALE: 1/8" = 1'-0"

101

DATE DRAWN CHECKED SHOWN SCALE AS NOTED FIRST FLOOR ELECTRICAL DEMOLITION PLAN

> 14428.16/17 PES E101

KEY NOTES:

1) DISCONNECT EXISTING CONDUIT AND WIRE FEEDING UNIT VENTILATOR AND PULL BACK TO AN AREA OUTSIDE OF DEMOLITION. TAG FOR RE-USE.

EXISTING CONDUIT/WIRING/WIREMOLD TO BE RELOCATED TO AREA OUTSIDE OF NEW UNIT VENTILATOR FOOT PRINT. REWORK/EXTEND ALL CONDUIT/WIRING/WIREMOLD AS NECESSARY TO ACCOMMODATE

ARCHITECTURE - ENGINEERING - PLANNING


50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

DATE DRAWN CHECKED SH NOTED SECOND FLOOR ELECTRICAL DEMOLITION

PROJECT NUMBER 14428.16/17

PES E102

KEY PLAN





50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

DATE DRAWN CHECKED SHOWN SCALE AS NOTED FIRST FLOOR ELECTRICAL NEW WORK PLAN

14428.16/17

PES E201






STAGE

GYMNASIUM

2 FIRST FLOOR ELECTRICAL NEW WORK PLAN - AREA B
E201 SCALE: 1/8" = 1'-0"



CPLteam.com
ARCHITECTURE = ENGINEERING = PLANNING

KEY NOTES:

50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

AC IMPROVEMENTS

SOD CENTER SED #66-14-01-03-0-004-02

DATE DRAWN CHECKED BY 28/28/2020 MAY JBT

SCALE AS NOTED

SHEET TITLE


SECOND FLOOR
ELECTRICAL NEW WORK

PROJECT NUMBER
14428.16/17

PES
E202

KEY PLAN

1 PROVIDE NEW CIRCUIT BREAKERS IN PANELS NOTED ON ELECTRICAL EQUIPMENT WIRING SCHEDULE. CIRCUIT BREAKERS TO BE UL LISTED AND LABELED AND MATCH AIC RATING OF PANEL.



50 FRONT STREET, SUITE 202 NEWBURGH, NEW YORK 12550 TEL (800) 274-9000 FAX (845) 567-9614

<u>TRICT</u> 3-0-004-023 3-0-003-042

ING UNION FREE SCHOOL DISTR HVAC IMPROVEMENTS CHILDHOOD CENTER SED #66-14-01-03-

DATE DRAWN CHECKED 8/28/2020 MAY JBT


SCALE AS NOTED

SHEET TITLE

ROOF ELECTRICAL
NEW WORK PLAN

PROJECT NUMBER 14428.16/17

PES E203 DRAWING NUMBER



$\widehat{1}$	NOOF ELECTRICAL NEW WORK PLAN - AREA A
E20:	SCALE: 1/8" = 1'-0"

	ELECTRICAL EQUIPMENT WIRING SCHEDULE														
ITEM NUMBER	EQUIPMENT	ROOM NUMBER	HP/ FLA	VOLTS	PHASE	AMPS	BREAKER SIZE/ FUSE SIZE	WIRE/CONDUIT SIZE	PANEL/CCT	REMARKS					
1	EF-1	ROOF	2	208	3	7.8A	20A/3P	(3) #8, (1) #10G IN 1"C	1S-15,17,19	1,2					
2	EF-2	ROOF	2	208	3	7.8A	20A/3P	(3) #10, (1) #12G IN 3/4"C	2S-18,20,22	1,2					
3	EF-3	ROOF	2	208	3	7.8A	20A/3P	(3) #10, (1) #12G IN 3/4"C	2S-25,27,29	1,2					
4	EF-4	ROOF	2	208	3	7.8A	20A/3P	(3) #10, (1) #12G IN 3/4"C	2N-29,31,33	1,2					
5	EF-5	ROOF	2	208	3	7.8A	20A/3P	(3) #10, (1) #12G IN 3/4"C	2N-30,32,34	1,2					
6	EF-6	ROOF	1	208	1	8A	20A/2P	(2) #10, (1) #12G IN 3/4"C	2N-35,37	1,2					
7	EF-7	ROOF	1	208	1	8A	20A/2P	(2) #10, (1) #12G IN 3/4"C	2N-39,41	1,2					

# REMARKS:

- ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR THE MOUNTING, AND LINE/LOAD SIDE CONNECTIONS OF DISCONNECT AND/OR STARTER DEVICE ASSOCIATED WITH UNIT. MEANS OF
  DISCONNECT AND/OR STARTER ASSOCIATED WITH UNIT PROVIDED BY MECHANICAL CONTRACTOR. ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR ALL FINAL CONNECTIONS TO EQUIPMENT.
- 2. PROVIDE FIRE ALARM FAN SHUT DOWN AT EACH UNIT INDICATED.

