

ELEVATION DETAIL
TYPICAL EXTERIOR RAILING

II
A202 SCALE: 3/4" = 1'-0"

SECTION DETAIL
TYPICAL EXTERIOR RAILING

FACE OF C.M.U.

4'-0"

3 3/4"

MAX. COORDINATE WITH SPLIT FACE C.M.U. INSTALLED

ELEV

T.O. RETAINING WALL

10
A202

8

A202

EXTERIOR RAILING ELEVATION

SCALE: 1/4" = 1'-0"

1/A202

2x8 WOOD STUDS, 1/2" O.C.

SPRAY FOAM INSULATION

BATT INSULATION

SEE A100x FOR WALL TYPES AND LOCATIONS

EXTERIOR SHEATHING

SEE A200x ELEVATIONS FOR VENER TYPE.

WT AT 4'-0" O.C. WELDED TO STEEL BEAM.

1" STRUCTURAL THERMAL INSULATION BLOCK.

SLOTTED RELIEF ANGLE 1/2" BOLTS AT EA. WT. SEE "S" DINGS.

CONTINUOUS FLASHING.

STEEL BEAM. SEE "S" DINGS.

2x WOOD STUD, 1/2" O.C. FILL CAVITY WITH SPRAY FOAM INSULATION.

3" RIGID INSULATION

FLASH BOND BRICK VENER

12" CMU. SEE A100x FOR WALL TYPES.

MASONRY TIES

RELIEF ANGLE DETAIL

SCALE: 1-1/2" = 1'-0"

3'-0"

1'-8"

8"

4
A202

5 3/4"

3"

1 1/2"

GRANITE #/
HONED
FINISH (TYP)

1'-8" DIA. LIMESTONE WITH THERMAL FINISH

SANDBLASTED PATTERN BY G.C.
G.C. IS RESPONSIBLE FOR
COORDINATING THE PATTERN TO
BE INSCRIBED IN LIMESTONE WITH
THE CUNTER.

EST.
1946

5

A202

SITE SIGN
MEDALLION ELEVATION

SCALE: 1" = 1'-0"

4 SECTION: SIGN DETAIL

A202 SCALE: 3/4" = 1'-0"

1'-10"

4" PRECAST COPING

2"

EQ.

2"

NOTE: THE ALUMINUM ACROLYLIC SIGN IS BY THE OWNER.

4" PRECAST COPING

2"

1'-4"

LEGS BY SIGN MANUFACTURER (TYP)

ELECTRICAL COAST TO RUN INTO SIGN LEG

2'-4"

SCALE: 1/4" = 1'-0"

NOTE: THE ALUMINUM & ACRYLIC SIGN IS BY THE OWNER.

8'-0" 8'-0" 4'-0"

4'-0" PRECAST COPIING

LEGS BY SIGN MANUFACTURER (TYP) 4'-0" PRECAST COPIING

2 A202

PITMAN VALLEY FIRE DEPARTMENT

THIS SIGN CAN SHOW 3 ROWS 5.5" CHARACTERS

2'-0" 2'-0" 7'-4" 4'-0"

5 A202

MASONRY TYPE IS SEE ELEVATION FOR MASONRY LEGEND

ELECTRICAL CONDUIT TO RUN INTO SIGN LEG

SEE SIGN SHOP DRAWING FOR SPACING

11'-4" MIN. 4'-0"

3 A202

4 A202

1 SITE SIGN FRONT ELEVATION

A202 SCALE: 1/4" = 1'-0"