

SECTION 102800 – TOILET, BATH, AND LAUNDRY ACCESSORIES

PART 1 - GENERAL

1.01 SECTION INCLUDES

- A. Furnish and install all toilet accessories.

1.02 RELATED SECTIONS

- A. Section 061000: Rough Carpentry: Wood blocking.
- B. Section 102113.13: Metal Toilet Compartments

1.03 SUBMITTALS

- A General: Submit in accordance with Section 013300.
- B See Section 013310 for Submittal Schedule.

1.04 QUALITY ASSURANCE

- A. Materials, devices, equipment and apparatus of a patented or of a special nature of manufacture shall be prepared applied, or installed in strict accordance with the manufacturer's directions.
- B. Work of this Section shall be executed in strict accordance with Drawings, approved Shop Drawings and approved samples.
- C. Insofar as possible, fitting, construction and fabrication of the Work shall be executed at shops, ready for delivery and erection at buildings.
- D. Provide all holes, connections, and fastenings for and to work of other trades abutting, adjoining or intersecting Work of this Section.

PART 2 - PRODUCTS

2.01 MATERIALS

- A. Grab bars: 18-gauge heavy-duty tested to withstand pressures of 500 pounds. Bars shall be Type 304 stainless steel, 1-1/4" diameter, .064" minimum wall thickness with 3/16" thick flanges. Bar shall pass through flanges and be brazed thereto. Bars shall be peened grips with polished ends.
- B. Toilet Paper Holder: Double 5-1/4 inch diameter roll capacity; Type 304 stainless steel with keyed door, surface mounted.
- C. Liquid Soap Dispenser: Refer to drawings
- D. Diaper-Changing Station: Koala Corporation, Horizontal design; molded polyethylene; beige color.

- E. Napkin and Tampon Vendor: 18 gauge door; Type 304 satin finish stainless steel, welded construction; double coin operation.
- F. Surface Mounted Napkin Disposal: Type 304 stainless steel.
- G. Mop Holder: Shelf 18 gauge stainless steel with satin finish 8 inches deep. Mop holder shall have 3 rubber mop holders and 4 hooks.

2.02 FABRICATION

- A. General: Materials shall be free from defects impairing strength, durability or appearance.
- B. Sections and shapes shall be rolled, formed, drawn or extruded as required for respective functions.
- C. Moulded work shall have sharply defined profile and shall be clean and straight. Plain work shall be leveled, straight and surfaces true and smooth. Edges, angles, and corners shall be square, clean and sharp, unless otherwise detailed.
- D. Fastenings, exposed metal fastenings, and accessories, unless Underwriters' prohibit for safety, shall be of same materials, texture, color and finish as the base metal to which applied.
- E. Molds, trim, frames and other metalwork shall be proper dimensions to receive masonry block and tile, plaster, ceramic tile, etc.

PART 3 - EXECUTION

3.01 INSTALLATION

- A. All items specified under this Section shall be installed in strict accordance with manufacturer's recommendations and details on Plan.
- B. Grab bars shall be screwed to solid blocking in stud partitions.
- C. Toilet Accessories:
 - 1. See drawings for manufacturer, quantity and location.

END OF SECTION 102800