# COMcheck Software Version 4.1.5.5 Mechanical Compliance Certificate

## **Project Information**

Energy Code: Project Title: Location: Climate Zone: Project Type: 2018 IECC Regeneron Tarrytown (Westchester), New York 4a New Construction

Construction Site: 777 Old Saw Mill River Road Tarrytown, NY 10591 Owner/Agent: Ted Jesson Regeneron 777 Old Saw Mill River Road Tarrytown, NY 10591 (914) 374-9486 Designer/Contractor: Brian Cleary Cosentini Associates 498 7th Avenue 15th Floor New York, NY 212-615-3845

## Additional Efficiency Package(s)

Credits: 1.0 Required 1.0 Proposed Dedicated Outdoor Air System, 1.0 credit

#### **Mechanical Systems List**

1

## Quantity System Type & Description

- 899-DOAS-R-01 (Single Zone): Single Package Heat Pump Heating Mode: Capacity = 164 kBtu/h, Proposed Efficiency = 3.64 COP, Required Efficiency = 3.20 COP Cooling Mode: Capacity = 171 kBtu/h, Proposed Efficiency = 11.00 EER, Required Efficiency: 10.60 EER + 11.6 IEER Fan System: None
- 1 899-DOAS-R-02 (Single Zone): Single Package Heat Pump Heating Mode: Capacity = 166 kBtu/h, Proposed Efficiency = 3.64 COP, Required Efficiency = 3.20 COP Cooling Mode: Capacity = 176 kBtu/h, Proposed Efficiency = 11.00 EER, Required Efficiency: 10.60 EER + 11.6 IEER Fan System: None
- 1 899-CU-R-01 (Single Zone): VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 81 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 100 kBtu/h, No minimum efficiency requirement applies Fan System: None

1 899-AC-1-01A (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 16 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

1 899-AC-1-01B (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 16 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

1 899-AC-1-01C (Single Zone):

#### Quantity System Type & Description

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 21 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

1 899-AC-1-01D (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 21 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

- 899-AC-1-01E (Single Zone):
   Cooling: 1 each VRF Zone Fan Unit, Capacity = 9 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None
- 899-AC-1-01F (Single Zone):
   Cooling: 1 each VRF Zone Fan Unit, Capacity = 13 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None
- 899-AC-1-01G (Single Zone):
   Cooling: 1 each VRF Zone Fan Unit, Capacity = 11 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None
- 899-CU-R-02 (Single Zone): VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 81 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 100 kBtu/h, No minimum efficiency requirement applies Fan System: None
- 899-AC-1-02A (Single Zone):
   Cooling: 1 each VRF Zone Fan Unit, Capacity = 16 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None
- 899-AC-1-02B (Single Zone):
   Cooling: 1 each VRF Zone Fan Unit, Capacity = 16 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None
- 1 899-AC-1-02C (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 21 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

1 899-AC-1-02D (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 21 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

1 899-AC-1-02E (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 11 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

1 899-AC-1-02F (Single Zone):

Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

 899-AC-1-02G (Single Zone):
 Cooling: 1 each - VRF Zone Fan Unit, Capacity = 9 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None

Quantity	System Type & Description
1	899-CU-R-03 (Single Zone): VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 81 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 100 kBtu/h, No minimum efficiency requirement applies Fan System: None
1	<ul> <li>899-AC-1-03A (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 41 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-03B (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 21 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-03C (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-03D (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 21 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-03E (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 11 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	899-CU-R-04 (Single Zone): VRF Condensing Unit, Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 81 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 110 kBtu/h, No minimum efficiency requirement applies Fan System: None
1	<ul> <li>899-AC-1-04A (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 16 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-04B (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 26 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-04C (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 26 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-04D (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>
1	<ul> <li>899-AC-1-04E (Single Zone):</li> <li>Cooling: 1 each - VRF Zone Fan Unit, Capacity = 25 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies</li> <li>Fan System: None</li> </ul>

Fan System: None

#### Quantity System Type & Description

1 899-AC-1-04F (Single Zone): Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 899-AC-1-04G (Single Zone): 1 Cooling: 1 each - VRF Zone Fan Unit, Capacity = 11 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 899-CU-R-05 (Single Zone): 1 VRF Condensing Unit. Air Cooled w/ Heat Recovery Heat Pump Heating Mode: Capacity = 76 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 80 kBtu/h, No minimum efficiency requirement applies Fan System: None 1 899-AC-1-05A (Single Zone): Cooling: 1 each - VRF Zone Fan Unit, Capacity = 26 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 899-AC-1-05B (Single Zone): 1 Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 1 899-AC-1-05C (Single Zone): Cooling: 1 each - VRF Zone Fan Unit, Capacity = 26 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 1 899-AC-1-05D (Single Zone): Cooling: 1 each - VRF Zone Fan Unit, Capacity = 5 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 899-AC-1-05E (Single Zone): 1 Cooling: 1 each - VRF Zone Fan Unit, Capacity = 11 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 899-AC-1-05F (Single Zone): 1 Cooling: 1 each - VRF Zone Fan Unit, Capacity = 11 kBtu/h, No Economizer, Economizer exception: Heat Recovery System No minimum efficiency requirement applies Fan System: None 899-CU-R-06 (Single Zone): 1 VRF Condensing Unit, Air Cooled Heat Pump Heating Mode: Capacity = 16 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 34 kBtu/h, No minimum efficiency requirement applies Fan System: None 899-AC-1-06 (Single Zone): 1 Cooling: 1 each - VRF Zone Fan Unit, Capacity = 34 kBtu/h, No Economizer, Economizer exception: High Efficiency Equipment No minimum efficiency requirement applies Fan System: None 899-CU-R-07 (Single Zone): 1 VRF Condensing Unit, Air Cooled Heat Pump Heating Mode: Capacity = 27 kBtu/h, No minimum efficiency requirement applies Cooling Mode: Capacity = 24 kBtu/h,

#### Quantity System Type & Description

No minimum efficiency requirement applies Fan System: None

- 899-AC-1-07 (Single Zone):
   Cooling: 1 each VRF Zone Fan Unit, Capacity = 24 kBtu/h, No Economizer, Economizer exception: High Efficiency Equipment No minimum efficiency requirement applies Fan System: None
  - 899-EH-1-01 (Single Zone): Heating: 1 each - Unit Heater, Electric, Capacity = 17 kBtu/h No minimum efficiency requirement applies Fan System: None
- 899-EH-1-02 (Single Zone):
   Heating: 1 each Unit Heater, Electric, Capacity = 17 kBtu/h No minimum efficiency requirement applies
   Fan System: None
- 899-DWH-1-01:
   Electric Storage Water Heater, Capacity: 120 gallons w/ Circulation Pump Proposed Efficiency: 0.98 SL, %/h (if > 12 kW), Required Efficiency: 0.53 SL, %/h (if > 12 kW)
- 1 899-DWH-1-02:
  - Electric Storage Water Heater, Capacity: 200 gallons w/ Circulation Pump Proposed Efficiency: 0.98 SL, %/h (if > 12 kW), Required Efficiency: 0.44 SL, %/h (if > 12 kW)

#### **Mechanical Compliance Statement**

*Compliance Statement:* The proposed mechanical design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed mechanical systems have been designed to meet the 2018 IECC requirements in COM*check* Version 4.1.5.5 and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Name - Title

1

Signature

Date

## COMcheck Software Version 4.1.5.5 Inspection Checklist

Energy Code: 2018 IECC

## Requirements: 100.0% were addressed directly in the COMcheck software

Text in the "Comments/Assumptions" column is provided by the user in the COMcheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Plan Review	Complies?	Comments/Assumptions
C103.2 [PR2] <sup>1</sup>	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the mechanical systems and equipment and document where exceptions to the standard are claimed. Load calculations per acceptable engineering standards and handbooks.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C103.2 [PR3] <sup>1</sup>	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the service water heating systems and equipment and document where exceptions to the standard are claimed. Hot water system sized per manufacturer's sizing guide.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C406 [PR9] <sup>1</sup>	Plans, specifications, and/or calculations provide all information with which compliance can be determined for the additional energy efficiency package options.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 M

2 Medium Impact (Tier 2)

Section # & Req.ID	Footing / Foundation Inspection	Complies?	Comments/Assumptions
,	Snow/ice melting system and freeze protection systems have sensors and controls configured to limit service for pavement temperature and outdoor temperature. future connection to controls.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.

Additional Comments/Assumptions:

 1
 High Impact (Tier 1)
 2
 Medium Impact (Tier 2)
 3
 Low Impact (Tier 3)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.5, C404.5.1, C404.5.2 [PL6] <sup>3</sup>	Heated water supply piping conforms to pipe length and volume requirements. Refer to section details.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.1, C404.6.2 [PL3] <sup>1</sup>	Automatic time switches installed to automatically switch off the recirculating hot-water system or heat trace.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.1, C404.6.2 [PL3] <sup>1</sup>	Automatic time switches installed to automatically switch off the recirculating hot-water system or heat trace.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.6.3 [PL7] <sup>3</sup>	Pumps that circulate water between a heater and storage tank have controls that limit operation from startup to <= 5 minutes after end of heating cycle.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Plumbing Rough-In Inspection	Complies?	Comments/Assumptions
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C404.7 [PL8] <sup>3</sup>	Demand recirculation water systems have controls that start the pump upon receiving a signal from the action of a user of a fixture or appliance and limits the temperature of the water entering the cold-water piping to 104°F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1High Impact (Tier 1)2

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C402.2.6 [ME41] <sup>3</sup>	$13^{3}$ Thermally ineffective panel surfaces of sensible heating panels have	$\Box$ Does Not	Exception: Requirement does not apply.
		□Not Observable □Not Applicable	
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
[ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
[ME61] <sup>2</sup>	accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C403.11.3 [ME61] <sup>2</sup>	HVAC piping insulation insulated in accordance with Table C403.11.3. Insulation exposed to weather is protected from damage and is provided with shielding from solar radiation.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	Complies Does Not Not Observable Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	Complies Does Not Not Observable Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.

 1
 High Impact (Tier 1)
 2
 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	fan system motor nameplate hp or fan system bhn	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>		□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	fan system motor nameplate hp or fan system bhn	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>		□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.
C403.8.1 [ME65] <sup>3</sup>	fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.

1 High Impact (Tier 1) 2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME65] <sup>3</sup>	HVAC fan systems at design conditions do not exceed allowable fan system motor nameplate hp or fan system bhp.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met. See the Mechanical Systems list for values.	
[ME117] <sup>2</sup>		□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.	
[ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.	
1High Impact (Tier 1)2Medium Impact (Tier 2)3Low Impact (Tier 3)				

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.8.3 [ME117] <sup>2</sup>		Complies	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at the design point of operation $<=$ 15%	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
		□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
		□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at	Complies	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
1	the design point of operation $\leq 15\%$ of maximum total efficiency of the	□Not Observable □Not Applicable	

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.8.3 [ME117] <sup>2</sup>		Complies	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at the design point of operation $<=$ 15%	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
		□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
		□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at	Complies	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
1	the design point of operation $\leq 15\%$ of maximum total efficiency of the	□Not Observable □Not Applicable	

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.8.3 [ME117] <sup>2</sup>		Complies	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at the design point of operation $<=$ 15%	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
		□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
		□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) $>=$ 67. The total efficiency of the fan at	□Complies □Does Not	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
	the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Not Observable □Not Applicable	
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at	Complies	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
1	the design point of operation $\leq 15\%$ of maximum total efficiency of the	□Not Observable □Not Applicable	

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation <= 15% of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.8.3 [ME117] <sup>2</sup>	Fans have efficiency grade (FEG) >= 67. The total efficiency of the fan at the design point of operation $\leq 15\%$ of maximum total efficiency of the fan.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Fans integral to equipment listed under Section C403.2.3.
C403.12.1 [ME71] <sup>2</sup>	Systems that heat outside the building envelope are radiant heat systems controlled by an occupancy sensing device or timer switch.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C403.2.3 [ME55] <sup>2</sup>	HVAC equipment efficiency verified.	□Complies □Does Not □Not Observable □Not Applicable	<i>See the Mechanical Systems list for values.</i>
C403.2.2 [ME59] <sup>1</sup>	Natural or mechanical ventilation is provided in accordance with International Mechanical Code Chapter 4. Mechanical ventilation has capability to reduce outdoor air supply to minimum per IMC Chapter 4.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.7.1 [ME59] <sup>1</sup>	Demand control ventilation provided for spaces >500 ft2 and >25 people/1000 ft2 occupant density and served by systems with air side economizer, auto modulating outside air damper control, or design airflow >3,000 cfm.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Systems with energy recovery.
C403.7.2 [ME115] <sup>3</sup>	Enclosed parking garage ventilation has automatic contaminant detection and capacity to stage or modulate fans to 50% or less of design capacity.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

2 Medium Impact (Tier 2)

Section #	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
& Req.ID			
C403.7.6 [ME141] <sup>3</sup>	HVAC systems serving guestrooms in Group R-1 buildings with > 50 guestrooms: Each guestroom is provided with controls that automatically manage temperature setpoint and ventilation (see sections C403.7.6.1 and C403.7.6.2).	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C403.7.4 [ME57] <sup>1</sup>	Exhaust air energy recovery on systems meeting Table C403.7.4(1) and C403.7.4(2).	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Where the largest exhaust source is less than 75% of the design outdoor airflow.
C403.7.5 [ME116] <sup>3</sup>	Kitchen exhaust systems comply with replacement air and conditioned supply air limitations, and satisfy hood rating requirements and maximum exhaust rate criteria.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
,	HVAC ducts and plenums insulated in accordance with C403.11.1 and constructed in accordance with C403.11.2, verification may need to occur during Foundation Inspection.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Not Observable	Exception: Requirement does not apply.

1 High Impact (Tier 1) 2 Medium I

2 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Not Observable □Not Applicable	Exception: Requirement does not apply.
3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Not Observable	Exception: Requirement does not apply.

 1
 High Impact (Tier 1)
 2
 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Not Observable	Exception: Requirement does not apply.

 1
 High Impact (Tier 1)
 2
 Medium Impact (Tier 2)

Section # & Req.ID	Mechanical Rough-In Inspection	Complies?	Comments/Assumptions
C403.4.3. 3.2 [ME121] <sup>3</sup>	Closed-circuit cooling tower within heat pump loop have either automatic bypass valve or lower leakage positive closure dampers. Open-circuit tower within heat pump loop have automatic valve to bypass all heat pump water flow around the tower. Open- or closed-circuit cooling towers used in conjunction with a separate heat exchanger have heat loss by shutting down the circulation pump on the cooling tower loop. Open- or closed circuit cooling towers have a separate heat exchanger to isolate the cooling tower from the heat pump loop, and heat loss is controlled by shutting down the circulation pump on the cooling tower loop.	□Not Observable	Exception: Requirement does not apply.
C403.4.1. 4 [ME63] <sup>2</sup>	Heating for vestibules and air curtains with integral heating include automatic controls that shut off the heating system when outdoor air temperatures > 45F. Vestibule heating and cooling systems controlled by a thermostat in the vestibule with heating setpoint <= 60F and cooling setpoint >= 80F.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.2. 1 [ME53] <sup>3</sup>	have means for air balancing.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.5, C403.5.1, C403.5.2 [ME123] <sup>3</sup>		□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2

2 Medium Impact (Tier 2)

Section # & Req.ID	Rough-In Electrical Inspection	Complies?	Comments/Assumptions
C405.6 [EL26] <sup>2</sup>	Low-voltage dry-type distribution electric transformers meet the minimum efficiency requirements of Table C405.6.	□Complies □Does Not □Not Observable	Requirement will be met.
C405.7 [EL27] <sup>2</sup>	Electric motors meet the minimum efficiency requirements of Tables C405.7(1) through C405.7(4). Efficiency verified through certification under an approved certification program or the equipment efficiency ratings shall be provided by motor manufacturer (where certification programs do not exist).	□Not Applicable □Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C405.8.2, C405.8.2. 1 [EL28] <sup>2</sup>	Escalators and moving walks comply with ASME A17.1/CSA B44 and have automatic controls configured to reduce speed to the minimum permitted speed in accordance with ASME A17.1/CSA B44 or applicable local code when not conveying passengers.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C405.9 [EL29] <sup>2</sup>	Total voltage drop across the combination of feeders and branch circuits $\leq 5\%$ .	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1 High Impact (Tier 1) 2 Mediu

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C303.3, C408.2.5. 3 [FI8] <sup>3</sup>	Furnished O&M manuals for HVAC systems within 90 days of system acceptance.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.2 [FI27] <sup>3</sup>	HVAC systems and equipment capacity does not exceed calculated loads.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	Heating and cooling to each zone is controlled by a thermostat control. Minimum one humidity control device per installed humidification/dehumidification system.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1 [FI47] <sup>3</sup>	5 5	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	□Complies □Does Not □Not Observable □Not Applicable	<b>Exception:</b> Requirement does not apply.
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	□Complies □Does Not □Not Observable □Not Applicable	Exception: Requirement does not apply.

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
		□Complies □Does Not	<b>Exception:</b> Requirement does not apply.
	from coming on when not needed.	□Not Observable □Not Applicable	
C403.2.4. 1.1 [FI42] <sup>3</sup>	1 supplemental electric resistance heat [42] <sup>3</sup> from coming on when not needed.	Complies Does Not	Exception: Requirement does not apply.
		□Not Observable □Not Applicable	
C403.2.4. 1.1 [FI42] <sup>3</sup>	supplemental electric resistance heat	Complies Does Not	Exception: Requirement does not apply.
		Not Observable	
C403.2.4. 1.1 [FI42] <sup>3</sup>	.4. Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	Complies Does Not	<b>Exception:</b> Requirement does not apply.
6402.2.4		Not Observable	
C403.2.4. 1.1 [FI42] <sup>3</sup>	Heat pump controls prevent supplemental electric resistance heat from coming on when not needed.	Complies Does Not	Exception: Requirement does not apply.
		Not Observable	
C403.4.1. 2 [FI38] <sup>3</sup>	Thermostatic controls have a 5 °F deadband.	Complies Does Not	Requirement will be met.
	<del>.</del>	Not Observable	
C403.2.4. 1.3 [FI20] <sup>3</sup>	Temperature controls have setpoint overlap restrictions.	Complies Does Not	Requirement will be met.
	E 1 1 1 1 1 1	Not Observable	
C403.2.4. 2 [FI39] <sup>3</sup>	Each zone equipped with setback controls using automatic time clock or programmable control system.	Complies Does Not	Requirement will be met.
6402.2.4		Not Observable	
2.1,	Automatic Controls: Setback to 55°F (heat) and 85°F (cool); 7-day clock, 2- hour occupant override, 10-hour	Complies Does Not	Requirement will be met.
2.2 [FI40] <sup>3</sup>	backup	□Not Observable □Not Applicable	
C404.3 [FI11] <sup>3</sup>	Heat traps installed on supply and discharge piping of non-circulating systems.	□Complies □Does Not	Exception: Requirement does not apply.
		□Not Observable □Not Applicable	
C404.3 [FI11] <sup>3</sup>	Heat traps installed on supply and discharge piping of non-circulating systems.	Complies Does Not	Exception: Requirement does not apply.
	-	□Not Observable □Not Applicable	
C404.4 [FI25] <sup>2</sup>	All piping insulated in accordance with section details and Table C403.11.3.	Does Not	Requirement will be met.
		□Not Observable □Not Applicable	

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
C404.4 [FI25] <sup>2</sup>	All piping insulated in accordance with section details and Table C403.11.3.	Does Not	Requirement will be met.
C404.6.1 [FI12] <sup>3</sup>	Controls are installed that limit the operation of a recirculation pump installed to maintain temperature of a storage tank. System return pipe is a dedicated return pipe or a cold water supply pipe.	<ul> <li>Not Applicable</li> <li>Complies</li> <li>Does Not</li> <li>Not Observable</li> <li>Not Applicable</li> </ul>	Requirement will be met.
C404.6.1 [FI12] <sup>3</sup>	Controls are installed that limit the operation of a recirculation pump installed to maintain temperature of a storage tank. System return pipe is a dedicated return pipe or a cold water supply pipe.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C406.6 [FI52] <sup>1</sup>	Dedicate outdoor air system efficiency package: Buildings with hydronic and/or multiple-zone HVAC systems are equipped with an independent ventilation system designed to provide >= 100-percent outdoor air to each individual occupied space, as specified by the IMC. The ventilation system is capable of total energy recovery and includes HVAC system controls that manage temperature resets >= 25 percent of delta design supply-air / room-air temp. Reference section C406.6 for qualifying systems/equipment.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.1.1 [FI57] <sup>1</sup>	Building operations and maintenance documents will be provided to the owner. Documents will cover manufacturers' information, specifications, programming procedures and means of illustrating to owner how building, equipment and systems are intended to be installed, maintained, and operated.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.1 [FI28] <sup>1</sup>	Commissioning plan developed by registered design professional or approved agency.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.3. 1 [FI31] <sup>1</sup>	HVAC equipment has been tested to ensure proper operation.	Complies Does Not Not Observable Not Applicable	Requirement will be met.
C408.2.3. 2 [FI10] <sup>1</sup>	HVAC control systems have been tested to ensure proper operation, calibration and adjustment of controls.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
C408.2.4 [FI29] <sup>1</sup>	Preliminary commissioning report completed and certified by registered design professional or approved agency.	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

2 Medium Impact (Tier 2)

Section # & Req.ID	Final Inspection	Complies?	Comments/Assumptions
1	Furnished HVAC as-built drawings submitted within 90 days of system acceptance.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	
C408.2.5. 3 [FI43] <sup>1</sup>	An air and/or hydronic system balancing report is provided for HVAC systems.	□Complies □Does Not	Requirement will be met.
		Not Observable	
C408.2.5. 4 [FI30] <sup>1</sup>	Final commissioning report due to building owner within 90 days of receipt of certificate of occupancy.	□Complies □Does Not	Requirement will be met.
		□Not Observable □Not Applicable	

Additional Comments/Assumptions:

 1
 High Impact (Tier 1)
 2
 Medium Impact (Tier 2)
 3
 Low Impact (Tier 3)