

## SECTION 260923 - LIGHTING CONTROL DEVICES

### PART 1 - GENERAL

#### 1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

#### 1.2 SUMMARY

- A. Section Includes:
  - 1. Indoor occupancy and vacancy sensors.
  - 2. Switchbox-mounted vacancy sensors.
  - 3. Wired wall dimmers and switches with wireless communication inputs.

#### 1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings:
  - 1. Show installation details for the following:
    - a. Occupancy sensors.
    - b. Vacancy sensors.
    - c. Wired wall switches.
  - 2. Interconnection diagrams showing field-installed wiring.
  - 3. Include diagrams for power, signal, and control wiring.

#### 1.4 INFORMATIONAL SUBMITTALS

- A. Coordination Drawings: Reflected ceiling plan(s) and elevations, drawn to scale, on which the following items are shown and coordinated with each other, using input from installers of the items involved:
  - 1. Suspended ceiling components.
  - 2. Structural members to which equipment will be attached.
  - 3. Items penetrating finished ceiling, including the following:
    - a. Luminaires.

- b. Air outlets and inlets.
  - c. Speakers.
  - d. Sprinklers.
  - e. Access panels.
  - f. Control modules.
- B. Field quality-control reports.
- C. Sample Warranty: For manufacturer's warranties.

#### 1.5 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For each type of lighting control device to include in operation and maintenance manuals.

#### 1.6 WARRANTY

- A. Manufacturer's Warranty: Manufacturer and Installer agree to repair or replace lighting control devices that fail(s) in materials or workmanship within specified warranty period.
- 1. Failures include, but are not limited to, the following:
    - a. Faulty operation of lighting control software.
    - b. Faulty operation of lighting control devices.
  - 2. Warranty Period: Two years from date of Substantial Completion.

### PART 2 - PRODUCTS

#### 2.1 INDOOR OCCUPANCY AND VACANCY SENSORS

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
- 1. Hubbell Controls
  - 2. Lutron
  - 3. Leviton
- B. General Requirements for Sensors:
- 1. Wall or Ceiling-mounted, solid-state indoor occupancy and vacancy sensors.
  - 2. Passive infrared or Ultrasonic or Dual technology.
  - 3. Separate power pack.
  - 4. Hardwired or wireless connection to switch.

5. Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
  6. Electrical contractor shall ensure that lighting fixtures are compatible with lighting controls. Coordinate with all manufacturer requirements.
  7. Operation:
    - a. Occupancy Sensor: Unless otherwise indicated, turn lights on when coverage area is occupied, and turn them off when unoccupied; with a time delay for turning lights off, adjustable over a minimum range of 1 to 20 minutes.
    - b. Vacancy Sensor: Unless otherwise indicated, lights are manually turned on and sensor turns lights off when the room is unoccupied; with a time delay for turning lights off, adjustable over a minimum range of 1 to 20 minutes.
    - c. Combination Sensor: Unless otherwise indicated, sensor shall be programmed to turn lights on when coverage area is occupied and turn them off when unoccupied, or to turn off lights that have been manually turned on; with a time delay for turning lights off, adjustable over a minimum range of 1 to 20 minutes.
  8. Sensor Output: Contacts rated to operate the connected relay, complying with UL 773A. Sensor is powered from the power pack.
  9. Power: Line voltage or Battery with 10 year operational life without needing to replace batteries.
  10. Power Pack: Dry contacts rated for 20-A LED load at 120- and 277-V ac, and for 1 HP at 120-V ac. Sensor has 24-V dc, 150-mA, Class 2 power source, as defined by NFPA 70.
  11. Mounting:
    - a. Sensor: Suitable for mounting in any position on a standard outlet box.
    - b. Relay: Externally mounted through a 1/2-inch (13-mm) knockout in a standard electrical enclosure.
    - c. Time-Delay and Sensitivity Adjustments: Recessed and concealed behind hinged door.
  12. Indicator: Digital display, to show when motion is detected during testing and normal operation of sensor.
  13. Bypass Switch: Override the "on" function in case of sensor failure.
  14. Automatic Light-Level Sensor: Adjustable from 2 to 200 fc (21.5 to 2152 lux); turn lights off when selected lighting level is present.
- C. PIR Type: Ceiling mounted; detect occupants in coverage area by their heat and movement.
1. Detector Sensitivity: Detect occurrences of 6-inch- (150-mm-) minimum movement of any portion of a human body that presents a target of not less than 36 sq. in. (232 sq. cm).
  2. Detection Coverage (Room, Ceiling Mounted): Detect occupancy anywhere in a circular area of 1000 sq. ft. (93 sq. m) when mounted on a 96-inch- (2440-mm-) high ceiling.
  3. Detection Coverage (Corridor, Ceiling Mounted): Detect occupancy within 90 feet (27.4 m) when mounted on a 10-foot- (3-m-) high ceiling.

## 2.2 SWITCHBOX-MOUNTED OCCUPANCY/VACANCY SENSORS

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. Hubbell Controls
  2. Lutron
  3. Leviton
- B. General Requirements for Sensors: Automatic-wall-switch occupancy sensor with manual on-off switch, suitable for mounting in a single gang switchbox.
1. Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
  2. Occupancy Sensor Operation: Unless otherwise indicated, turn lights on when coverage area is occupied, and turn lights off when unoccupied; with a time delay for turning lights off, adjustable over a minimum range of 1 to 20 minutes.
  3. Operating Ambient Conditions: Dry interior conditions, 32 to 120 deg F (0 to 49 deg C).
  4. Switch Rating: Not less than 800-VA ballast or LED load at 120 V, 1200-VA ballast or LED load at 277 V, and 800-W incandescent.
- C. Wall-Switch Sensor :
1. Standard Range: 180-degree field of view, field adjustable from 180 to 40 degrees; with a minimum coverage area of 2100 sq. ft (196 sq. m).
  2. Sensing Technology: Dual technology - PIR and ultrasonic.
  3. Switch Type: SP, field-selectable automatic "on," or manual "on," automatic "off."
  4. Capable of controlling load in three-way application.
  5. Voltage: Match the circuit voltage.
  6. Ambient-Light Override: Concealed, field-adjustable, light-level sensor from 10 to 150 fc (108 to 1600 lux). The switch prevents the lights from turning on when the light level is higher than the set point of the sensor.
  7. Concealed, field-adjustable, "off" time-delay selector at up to 30 minutes.
  8. Adaptive Technology: Self-adjusting circuitry detects and memorizes usage patterns of the space and helps eliminate false "off" switching.
  9. Color: As selected by Architect.
  10. Faceplate: Color matched to switch.

## 2.3 WIRED WALL DIMMERS AND SWITCHES WITH WIRELESS COMMUNICATION INPUTS

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
1. Hubbell controls
  2. Lutron

3. Leviton

B. General Requirements:

1. Operates at the rated capacity across the full ambient temperature range including modified capacities for ganged configurations which require removal of fins.
2. Provide radio frequency interference suppression.
3. Surge Tolerance: Designed and tested to withstand surges of 6,000 V, 200 amps according to IEEE C62.41.2 without impairment to performance.
4. Dimmers: Provide full range, continuously variable control of light intensity.
5. Dimmers for Electronic Low Voltage (ELV) Transformers:
  - a. Provide circuitry designed to control the input of electronic (solid-state) low voltage (ELV) transformers. Do not use dimmers that utilize standard phase control.
  - b. Provide resettable overload protection that provides automatic shut-off when dimmer capacity is exceeded. Do not use protection methods that are non-resettable or require device to be removed from outlet box.
  - c. Designed to withstand a short, per UL 1472, between load hot and either neutral or ground without damage to dimmer.
6. Dimmers for Magnetic Low Voltage (MLV) Transformers:
  - a. Provide circuitry designed to control and provide a symmetrical AC waveform to input of magnetic low voltage transformers per UL 1472.
  - b. Magnetic low voltage transformers to operate below rated current or temperature.
7. Electronic Switches:
  - a. Listed as complying with UL 20, UL 508, and UL 1472.

C. Preset Smart Wall Dimmers and Switches with Wireless Communication Inputs

1. Communicates via radio frequency with up to ten compatible occupancy/vacancy sensors, ten wireless control stations, and one daylight sensor.
2. Dimmer Control: Multi-function tap switch with small, raised rocker for dimmer adjustment.
  - a. Rocker raises/lowers light level, with new level becoming the current preset level.
  - b. Switch single tap raises lights to preset level or fades lights to off.
  - c. Switch double tap raises light to full on level.
  - d. Switch tap and hold slowly fades lights to off over period of 10 seconds.
  - e. LEDs adjacent to tap switch indicate light level when dimmer is on, and function as locator light when dimmer is off.
3. Switch Control:
  - a. Switch programming to control L1 light fixtures in the bathrooms in a zone independent from the other fixtures present.
  - b. L1 fixtures are to be dimmed 50% when unoccupied.
  - c. Other fixtures are to turn off when unoccupied.
4. Dimmer High End Trim:
  - a. Incandescent Dimmers: Minimum of 92 percent of line voltage.
  - b. Dimmers for Electronic Low Voltage (ELV) Transformers: Minimum of 95 percent of line voltage.

- c. Dimmers for Magnetic Low Voltage Transformers: Minimum of 92 percent of line voltage.

## 2.4 CONDUCTORS AND CABLES

- A. Power Wiring to Supply Side of Remote-Control Power Sources: Not smaller than No. 12 AWG. Comply with requirements in other section for "Low-Voltage Electrical Power Conductors and Cables."
- B. Classes 2 and 3 Control Cable: Multi-conductor cable with stranded-copper conductors not smaller than No. 18 AWG. Comply with requirements in other section for "Low-Voltage Electrical Power Conductors and Cables."
- C. Class 1 Control Cable: Multi-conductor cable with stranded-copper conductors not smaller than No. 14 AWG. Comply with requirements in other section for "Low-Voltage Electrical Power Conductors and Cables."

## PART 3 - EXECUTION

### 3.1 EXAMINATION

- A. Examine lighting control devices before installation. Reject lighting control devices that are wet, moisture damaged, or mold damaged.
- B. Examine walls and ceilings for suitable conditions where lighting control devices will be installed.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 SENSOR INSTALLATION

- A. Comply with NECA 1.
- B. Coordinate layout and installation of ceiling-mounted devices with other construction that penetrates ceilings or is supported by them, including light fixtures, HVAC equipment, smoke detectors, fire-suppression systems, and partition assemblies.
- C. Install and aim sensors in locations to achieve not less than 90-percent coverage of areas indicated. Do not exceed coverage limits specified in manufacturer's written instructions.

### 3.3 CONTACTOR INSTALLATION

- A. Comply with NECA 1.

### 3.4 WIRING INSTALLATION

- A. Comply with NECA 1.
- B. Wiring Method: Comply with other section for "Low-Voltage Electrical Power Conductors and Cables." Minimum conduit size is 1/2 inch (13 mm).
- C. Wiring within Enclosures: Comply with NECA 1. Separate power-limited and non-power-limited conductors according to conductor manufacturer's written instructions.
- D. Size conductors according to lighting control device manufacturer's written instructions unless otherwise indicated.
- E. Splices, Taps, and Terminations: Make connections only on numbered terminal strips in junction, pull, and outlet boxes; terminal cabinets; and equipment enclosures.

### 3.5 IDENTIFICATION

- A. Identify components and power and control wiring according to other section for "Identification for Electrical Systems."
  - 1. Identify controlled circuits in lighting contactors.
  - 2. Identify circuits or luminaires controlled by photoelectric and occupancy sensors at each sensor.
- B. Label time switches and contactors with a unique designation.

### 3.6 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to evaluate lighting control devices and perform tests and inspections.
- B. Perform the following tests and inspections:
  - 1. Operational Test: After installing time switches and sensors, and after electrical circuitry has been energized, start units to confirm proper unit operation.
  - 2. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.
- C. Lighting control devices will be considered defective if they do not pass tests and inspections.
- D. Prepare test and inspection reports.

3.7 ADJUSTING

- A. Occupancy Adjustments: When requested within 12 months from date of Substantial Completion, provide on-site assistance in adjusting lighting control devices to suit actual occupied conditions. Provide up to two visits to Project during other-than-normal occupancy hours for this purpose.
1. For occupancy and motion sensors, verify operation at outer limits of detector range. Set time delay to suit Owner's operations.
  2. For daylighting controls, adjust set points and deadband controls to suit Owner's operations.
  3. Align high-bay occupancy sensors using manufacturer's laser aiming tool.

END OF SECTION 260923