

Structural Loads:

A. FLOOR LIVE LOADS PER BCNYS 1607

OCCUPANCY OR USE	UNIFORM	CONCENTRATED
READING ROOMS	60 PSF	1000 LBS
CLASSROOMS	40 PSF	1000 LBS
LOBBIES	100 PSF	
OFFICES	50 PSF	2000 LBS
TOILET ROOMS	60 PSF	
PARTITIONS	15 PSF PER 1607.5	

REDUCTION IN LIVE LOADS HAS BEEN APPLIED WHERE PERMITTED PER 1607.11

B. ROOF LIVE LOADS PER BCNYS 1607.13

MINIMUM ROOF LIVE LOAD	
	20 PSF

C. RAIN LOADS PER BCNYS 1611

RAIN INTENSITY, I	
	2.75 IN/HR
RAIN LOAD, R	
	18 PSF

RAIN SURCHARGE LOAD HAS BEEN APPLIED TO AREAS WHERE PONDING OCCURS IN ACCORDANCE WITH BCNYS 1611.1

D. SNOW LOADS PER BCNYS 1608

GROUND SNOW, P _g (FIGURE 1608.2)	
	30 PSF
FLAT ROOF SNOW LOAD, P _f (ASCE 7)	
	23.1 PSF
SNOW EXPOSURE FACTOR, C _e	
	1.0
THERMAL FACTOR, C _t	
	1.0
SLOPE FACTOR, C _s	
	1.0
SNOW LOAD IMPORTANCE FACTOR, I _s	
	1.1

ADDITIONAL SNOW LOADS HAVE BEEN APPLIED TO AREAS WHERE DRIFTING OCCURS IN ACCORDANCE WITH BCNYS 1608.

E. WIND LOAD DESIGN CRITERIA PER BCNYS 1609

BASIC DESIGN WIND SPEED (3 SECOND GUST), V	
	121 MPH
ALLOWABLE STRESS DESIGN WIND SPEED, V _{ASD}	
	93.7MPH
RISK CATEGORY	
	I
EXPOSURE CATEGORY	
	B
INTERNAL PRESSURE COEFFICIENT, GCP	
	+/- 0.18

F. SEISMIC DESIGN CRITERIA PER BCNYS 1613

RISK CATEGORY	
	III
SEISMIC IMPORTANCE FACTOR, I _s	
	1.25
MAPPED SPECTRAL RESPONSE ACCELERATION AT SHORT PERIODS, S _s	
	23.3 %g
AT 1 SECOND PERIODS, S ₁	
	5.7 %g
DESIGN SPECTRAL RESPONSE ACCELERATION AT SHORT PERIODS, S _{0s}	
	24.8 %g
AT 1 SECOND PERIODS, S ₀₁	
	9.1 %g
SEISMIC DESIGN CATEGORY	
	B

Code Compliance Review

PROJECT LOCATION:
29 EDUCATION DRIVE, BEACON, NEW YORK 12508
BOUNDED BY EDUCATION DRIVE TO THE NORTH, SARGENT AVE TO THE WEST, KNEVELS AVE TO THE SOUTH, AND TIORONDA AVE TO THE EAST.

PROJECT DESCRIPTION:
THIS PROJECT INCLUDES RENOVATION OF APPROXIMATELY 3,081 SF OF SPACE ON THE BASEMENT, FIRST AND SECOND FLOOR OF STAIR RAILING MODIFICATIONS, MECHANICAL VENTILATION AND RELOCATION OF LIBRARY/MEDIA CENTER SPACE.

WORK GENERALLY CONSISTS OF THE FOLLOWING:
ALTERATIONS - LEVEL 1
• MODIFY RAILING TO MEET ADA REQUIREMENTS
• REPLACE GREASE INTERCEPTOR IN KITCHEN
ALTERATIONS - LEVEL 2
• ADD MECHANICAL VENTILATION TO GYM OFFICE AND NURSES OFFICE
• RELOCATE LIBRARY/MEDIA CENTER TO MAIN FLOOR

APPLICABLE CODES AND STANDARDS:
BASED ON THE 2020 NEW YORK STATE UNIFORM FIRE PREVENTION AND BUILDING CODE INCLUDING APPLICABLE 2018 ICC CODES AND 2020 BUILDING CODES OF NYS, AND ICC A117.1-2017 STANDARD FOR ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES.
REFER TO PROJECT MANUAL FOR REQUIREMENTS STATED IN "NYCRR 155 REGULATIONS OF THE COMMISSIONER OF EDUCATION".

BUILDING DATA:
BUILDING: SARGENT ELEMENTARY SCHOOL
29 EDUCATION DRIVE
BEACON, NY 12508
DESCRIPTION: THREE STORY MASONRY AND REINFORCED CONCRETE BUILDING.
YEAR BUILT: 1958
ADDITIONS: 1975, 1986 AND 1998
BUILDING AREA: BASEMENT 20,726 SQFT
1ST FLOOR 29,024 SQFT
2ND FLOOR 9,615 SQFT
TOTAL GROSS AREA= 59,365 SQFT

CODE DATA SUMMARY:
USE GROUP: E ; EDUCATION
CONSTRUCTION TYPE -
EXISTING: IIB
FIRE SAFETY: AN AUTOMATIC SPRINKLER SYSTEM IS NOT PROVIDED.
WORK AREA:
CORRIDOR DOORS: ALL CORRIDOR DOORS SCHEDULED TO BE REPLACED SHALL HAVE MINIMUM FIRE DOOR ASSEMBLY RATING OF 20 MINUTES IN ACCORDANCE WITH SECTION 716.5

PATH OF CODE COMPLIANCE:
2018 IBC CODES AND 2020 EXISTING BUILDING CODE OF NYS
301.1.2 WORK AREA COMPLIANCE METHOD
CHAPTER 5 - CLASSIFICATION OF WORK
503 ALTERATION - LEVEL 1 (CHAPTER 7)
504 ALTERATION - LEVEL 2 (CHAPTER 8)
EXIT TRAVEL DISTANCE (PER TABLE 1017.2):
FOR EXIT TRAVEL DISTANCE - SEE CG351.
NEW CONSTRUCTION WILL COMPLY WITH REQUIREMENTS OF 2018 ICC CODES AND 2020 BUILDING CODES OF NYS
CORRIDOR ENCLOSURES (PER TABLE 1020.1):
FOR CORRIDOR FIRE RESISTANCE - SEE ENLARGED PLANS, PARTITION TYPES AND DOOR SCHEDULE.
ALL CROSS CORRIDOR PARTITIONS ARE SMOKE PARTITIONS AND EXTEND FROM FINISH FLOOR TO DECK ABOVE.
ASSEMBLY AREAS (PER TABLE 1004.1.2):
[LIST NEW ASSEMBLY AREAS AND MAXIMUM OCCUPANCY DESIGNATIONS]

General Code Notes


- A. REFER TO CODE COMPLIANCE DRAWINGS FOR ADDITIONAL CODE COMPLIANCE INFORMATION.
- B. COORDINATE WITH FLOOR PLANS, WALL SECTIONS AND PARTITION TYPES FOR RATED WALL TYPES AND LOCATIONS. IMMEDIATELY NOTIFY ARCHITECT OF ANY WALL RATING DISCREPANCIES BETWEEN CG351 DRAWINGS AND FLOOR PLANS.
- C. ALL WALLS, INCLUDING AT CORRIDORS, SHALL EXTEND COMPLETELY TO THE UNDERSIDE OF DECKING, SUPPORTING STRUCTURE OR ROOF ABOVE, TYPICAL UNLESS NOTED OTHERWISE.
- D. AT AREAS OF PROJECT WORK, COMPLETELY SEAL ALL PENETRATIONS REQUIRED TO COMPLY WITH FIRE RESISTANCE RATINGS IDENTIFIED ON THE CG351 DRAWINGS, REGARDLESS IF WALL IS NEW OR EXISTING, TYPICAL UNLESS NOTED OTHERWISE.
- E. PROVIDE APPLIED FIREPROOFING TO ALL BEAMS, JOISTS AND STRUCTURAL STEEL ELEMENTS AT ALL FIRE BARRIERS, FIRE PARTITIONS, AND OTHER RATED WALLS WHERE INDICATED ON DRAWINGS, AND THAT ARE NOT COMPLETELY PROTECTED WITHIN THE RATED CONSTRUCTION. PROTECTION OF SUCH ELEMENTS SHALL MATCH THE RATING OF THE WALL THAT THE ELEMENTS ARE CONTAINED WITHIN.
- F. ALL CMU CONSTRUCTION SHALL MEET FIRE RESISTANCE REQUIREMENTS INDICATED. PROVIDED BLOCK TYPE AS REQUIRED TO COMPLY WITH UL DESIGN NUMBERS AND WALL RATINGS INDICATED, REGARDLESS IF NOTED AS SUCH ON PLAN DETAILS.

Legend

- 1-HOUR FIRE PARTITION
- - - - - COMMON EGRESS PATH
- XX NUMBER OF OCCUPANTS IN EACH SPACE, UNO
- ⊕ EXISTING FIRE EXTINGUISHER LOCATION
- RW RESCUE WINDOW
- ALTERATION LEVEL 1 WORK AREA
- ALTERATION LEVEL 2 WORK AREA


General Notes

- A. DO NOT SCALE DRAWINGS TO OBTAIN DIMENSIONS.
- B. TAKE FIELD MEASUREMENTS TO FIT THE WORK PROPERLY. VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS IN THE FIELD.
- C. REFER INCONSISTENCIES TO ARCHITECT PRIOR TO COMMENCING THE WORK IN AFFECTED AREA.
- D. ITEMS ARE SHOWN DIAGRAMMATICALLY ON DRAWINGS. VERIFY SPACE REQUIREMENTS AND DIMENSIONS TO FIT THE WORK PROPERLY.
- E. NOTES SHOWN ON ONE DRAWING APPLY TO ALL SIMILAR DRAWINGS.
- F. DO NOT DISTURB CONSTRUCTION SUSPECTED OF CONTAINING HAZARDOUS MATERIAL. IF ENCOUNTERED, IMMEDIATELY NOTIFY ARCHITECT, CONSTRUCTION MANAGER AND OWNER.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET


TT TETRA TECH ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York


Reconstruction to:
Sargent Elementary School

Code Compliance Review and Vintage Plan


Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.:	CG350	
279180-22004		




1 Vintage Key Plan
1/16" = 1'-0"



3 Second Floor Key Plan
1/16" = 1'-0"




1 First Floor Key Plan
1/16" = 1'-0"



2 Basement Key Plan
1/16" = 1'-0"

- General Code Notes**
- A. REFER TO CODE COMPLIANCE DRAWINGS FOR ADDITIONAL CODE COMPLIANCE INFORMATION.
 - B. COORDINATE WITH FLOOR PLANS, WALL SECTIONS AND PARTITION TYPES FOR RATED WALL TYPES AND LOCATIONS. IMMEDIATELY NOTIFY ARCHITECT OF ANY WALL RATING DISCREPANCIES BETWEEN CG351 DRAWINGS AND FLOOR PLANS.
 - C. ALL WALLS, INCLUDING AT CORRIDORS, SHALL EXTEND COMPLETELY TO THE UNDERSIDE OF DECKING, SUPPORTING STRUCTURE OR ROOF ABOVE, TYPICAL UNLESS NOTED OTHERWISE.
 - D. AT AREAS OF PROJECT WORK, COMPLETELY SEAL ALL PENETRATIONS REQUIRED TO COMPLY WITH FIRE RESISTANCE RATINGS IDENTIFIED ON THE CG351 DRAWINGS, REGARDLESS IF WALL IS NEW OR EXISTING, TYPICAL UNLESS NOTED OTHERWISE.
 - E. PROVIDE APPLIED FIREPROOFING TO ALL BEAMS, JOISTS AND STRUCTURAL STEEL ELEMENTS AT ALL FIRE BARRIERS, FIRE PARTITIONS, AND OTHER RATED WALLS WHERE INDICATED ON DRAWINGS, AND THAT ARE NOT COMPLETELY PROTECTED WITHIN THE RATED CONSTRUCTION. PROTECTION OF SUCH ELEMENTS SHALL MATCH THE RATING OF THE WALL THAT THE ELEMENTS ARE CONTAINED WITHIN.
 - F. ALL CMU CONSTRUCTION SHALL MEET FIRE RESISTANCE REQUIREMENTS INDICATED. PROVIDED BLOCK TYPE AS REQUIRED TO COMPLY WITH UL DESIGN NUMBERS AND WALL RATINGS INDICATED, REGARDLESS IF NOTED AS SUCH ON PLAN DETAILS.

- Legend**
- 1-HOUR FIRE PARTITION
 - - - COMMON EGRESS PATH
 - XX NUMBER OF OCCUPANTS IN EACH SPACE, UNO
 - ⊕ EXISTING FIRE EXTINGUISHER LOCATION
 - RW RESCUE WINDOW
 - ▨ ALTERATION LEVEL 1 WORK AREA
 - ▩ ALTERATION LEVEL 2 WORK AREA



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

Code Compliance Basement, First and Second Floor Key Plans

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.:	CG351	



BID SET

Demolition Key Notes

- (1A) WITHIN THIS SPACE, REMOVE ALL CONSTRUCTION IN ITS ENTIRETY. STRUCTURE TO REMAIN, TYPICAL UNO. REMOVE CEILING AND ALL FINISH MATERIALS ON FLOOR AND WALL OR OTHER ITEMS ATTACHED TO FACE OF WALLS SCHEDULED TO REMAIN, TYPICAL UNO.
 - (1H) PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PROVIDE LINTEL PER LINTEL SCHEDULE. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
 - (1N) REMOVE STUDENT ARTWORK TILE. PROTECT AND DELIVER TO OWNER STORAGE LOCATION FOR THEIR REUSE.
 - (8B) REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (9A) SALVAGE TILES FROM EXISTING WALL SURFACE AND TURN OVER TO OWNER.
 - (9C) REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS):**
- A. CARPET
 - B. CERAMIC FLOOR TILE
 - C. CONCRETE (NATURAL OR SEALED OR STAINED OR PAINTED)
 - D. LINOLEUM, SHEET OR TILE
 - E. PORCELAIN TILE
 - F. POURED EPOXY
 - G. RUBBER FLOORING
 - H. TERRAZZO
 - I. VAT/VCT
 - J. VINYL SHEET
 - K. WOOD FLOORING
- (10A) REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TACK BOARDS AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (10C) REMOVE SIGNAGE.

General Demolition Notes

- A. - - - - - REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
 1. DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 2. DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE A LEADER POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 3. DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE SPACE IDENTIFIED BY THAT LEADER.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNERS AGENT(S) IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS
 Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET



Beacon City School District
 Beacon, New York

Reconstruction to:
 Sargent Elementary School

Basement Demolition Plan - Area A

Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.:	CA100	
279180-22004		



1 Basement Demolition Plan - Area A
 1/8" = 1'-0"

Demolition Key Notes

- (1A) WITHIN THIS SPACE, REMOVE ALL CONSTRUCTION IN ITS ENTIRETY. STRUCTURE TO REMAIN, TYPICAL UNO. REMOVE CEILING AND ALL FINISH MATERIALS ON FLOOR AND WALL OR OTHER ITEMS ATTACHED TO FACE OF WALLS SCHEDULED TO REMAIN, TYPICAL UNO.
 - (1H) PROVIDE NEW OR ENLARGE EXISTING OPENING IN WALL TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. PROVIDE LINTEL PER LINTEL. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES. COORDINATE WITH SCHEDULED WORK ON MECHANICAL DRAWINGS.
 - (1N) REMOVE STUDENT ARTWORK TILE. PROTECT AND DELIVER TO OWNER STORAGE LOCATION FOR THEIR REUSE.
 - (8B) REMOVE DOOR AND FRAME COMPLETELY. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (9A) SALVAGE TILES FROM EXISTING WALL SURFACE AND TURN OVER TO OWNER.
 - (9C) REMOVE FLOOR FINISH, MASTIC AND WALL BASE TO EXTENT REQUIRED TO PERFORM SCHEDULED WORK. AT ALL AREAS OF FLOOR REMOVAL, LEVEL SLAB WITH ADJACENT SLABS AT LOCATIONS SCHEDULED TO RECEIVE FLOOR FINISH. INCLUDE CONCRETE FLOOR PATCHING AND LEVELING MATERIALS TO MAKE SURFACE LEVEL. PREPARE FOR FINISH. PATCH AREAS OF WALLS TO REMAIN THAT WERE DAMAGED BY REMOVAL OF WALL BASE.
- SUFFIX KEY (FLOOR FINISH IDENTIFICATIONS):**
- A. CARPET
 - B. CERAMIC FLOOR TILE
 - C. CONCRETE (NATURAL OR SEALED OR STAINED OR PAINTED)
 - D. LINOLEUM, SHEET OR TILE
 - E. PORCELAIN TILE
 - F. POURED EPOXY
 - G. RUBBER FLOORING
 - H. TERRAZZO
 - I. VAT/VCT
 - J. VINYL, SHEET
 - K. WOOD FLOORING
- (10A) REMOVE TEACHING SURFACES INCLUDING MARKER BOARDS, TACK BOARDS AND CHALK BOARDS. PATCH EXPOSED SURFACES TO MATCH ADJACENT FINISHES / SURFACES.
 - (10C) REMOVE SIGNAGE.

General Demolition Notes

- A. - - - - - REMOVE ITEMS INDICATED BY DASHED LINE.
- B. KEYED DEMOLITION TAGS REFER TO SPECIFIC LOCATIONS AS FOLLOWS:
 1. DEMOLITION TAGS LOCATED WITHIN THE MIDDLE OF A SPACE REFER TO DEMOLITION OF ALL ITEMS OF THAT SAME TYPE WITHIN THAT ENTIRE SPACE.
 2. DEMOLITION TAGS PLACED IMMEDIATELY ON OR ADJACENT TO A DASHED LINE INDICATING ITEM REMOVAL OR THAT HAVE A LEADER POINTING TO SPECIFIC ITEM(S) REFER TO DEMOLITION OF THAT SPECIFIC ITEM ONLY OF THAT TYPE WITHIN THAT SPACE.
 3. DEMOLITION TAGS IN SERIES REFER TO DEMOLITION OF ALL THOSE ITEMS EITHER WITHIN THAT ENTIRE SPACE OR TO THE SPACE IDENTIFIED BY THAT LEADER.
- C. WHEN AN ITEM IS INDICATED TO BE DEMOLISHED REMOVE ALL ASSOCIATED COMPONENTS AS PART OF THAT WORK.
- D. ALL ARTWORK NOT PERMANENTLY AFFIXED TO EXISTING CONSTRUCTION SHALL BE REMOVED AND STORED BY OWNER PRIOR TO BEGINNING DEMOLITION WORK. CONTACT OWNER'S AGENT(S) IF ANY ARTWORK IS ENCOUNTERED PRIOR TO START OF DEMOLITION WORK.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

First Floor Demolition Plan - Area A


Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.:	CA101	
279180-22004		

1 First Floor Demolition Plan - Area A
1/8" = 1'-0"



1 Basement Plan - Area A
1/8" = 1'-0"

- ### General Plan Notes
- A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
 - B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL, TYPICAL UNLESS NOTED OTHERWISE.
 - 1. ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.
 - C. INFILL AREAS OF RECESSED FLOOR MAT AND/OR FINISH REMOVALS WITH REPAIR MATERIAL, PROVIDE SUBSTRATE LEVEL AS REQUIRED SO SCHEDULED FINISHED FLOOR WILL MATCH THAT OF EXISTING ADJACENT AREAS.
 - D. PROVIDE BRACING WITHIN CHASES AS FOLLOWS:
 - 1. MASONRY WALLS: FULL-HEIGHT 4" CMU BRACES AT MAXIMUM SPACING OF 11'-0" OC.
 - 2. GYPSUM BOARD/TILE BACKING PANELS ON METAL FRAMING: FULL-HEIGHT 6" METAL STUD BRACES AT MAXIMUM SPACING OF 11'-0" OC.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

Basement Plan - Area A


Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.:	279180-22004	
		CA130



1 First Floor Plan - Area A
1/8" = 1'-0"

- ### General Plan Notes
- A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
 - B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL, TYPICAL UNLESS NOTED OTHERWISE.
 - 1. ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.
 - C. INFILL AREAS OF RECESSED FLOOR MAT AND/OR FINISH REMOVALS WITH REPAIR MATERIAL, PROVIDE SUBSTRATE LEVEL AS REQUIRED SO SCHEDULED FINISHED FLOOR WILL MATCH THAT OF EXISTING ADJACENT AREAS.
 - D. PROVIDE BRACING WITHIN CHASES AS FOLLOWS:
 - 1. MASONRY WALLS: FULL-HEIGHT 4" CMU BRACES AT MAXIMUM SPACING OF 11'-0" OC.
 - 2. GYPSUM BOARD/TILE BACKING PANELS ON METAL FRAMING: FULL-HEIGHT 6" METAL STUD BRACES AT MAXIMUM SPACING OF 11'-0" OC.

- ### Keyed Plan Notes
- 1. DISPLAY CASE, REFER TO DETAIL @CA750.
 - 2. PROVIDE EXTERIOR WALL INFILL AT EXISTING OPENING. MATCH ADJACENT CONSTRUCTION MATERIALS AND THICKNESS, V.I.F.
 - 3. INSTALL LOUVER FURNISHED BY OTHERS AT NEW OPENING. COORDINATE WITH MECHANICAL DRAWINGS.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

First Floor Plan - Area A


Drawn By: GK	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	CA131	



1 Second Floor Plan
1/8" = 1'-0"

General Plan Notes

- A. WHERE EXISTING CONSTRUCTION IS DAMAGED OR DISTURBED, PATCH AS REQUIRED TO RESTORE SURFACES TO THEIR ORIGINAL CONDITION.
- B. PARTITION TYPE TAGS APPLY TO ENTIRE LENGTH OF WALL INDICATED BY THAT TAG, REGARDLESS OF OPENINGS WITHIN THAT WALL, TYPICAL UNLESS NOTED OTHERWISE.
 - 1. ALL INTERIOR WALLS SHALL BE WALL/PARTITION TYPE P12.3, TYPICAL UNLESS NOTED OTHERWISE.
- C. INFILL AREAS OF RECESSED FLOOR MAT AND/OR FINISH REMOVALS WITH REPAIR MATERIAL, PROVIDE SUBSTRATE LEVEL AS REQUIRED SO SCHEDULED FINISHED FLOOR WILL MATCH THAT OF EXISTING ADJACENT AREAS.
- D. PROVIDE BRACING WITHIN CHASES AS FOLLOWS:
 - 1. MASONRY WALLS: FULL-HEIGHT 4" CMU BRACES AT MAXIMUM SPACING OF 11'-0" OC.
 - 2. GYPSUM BOARD/TILE BACKING PANELS ON METAL FRAMING: FULL-HEIGHT 6" METAL STUD BRACES AT MAXIMUM SPACING OF 11'-0" OC.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York


Reconstruction to:
Sargent Elementary School

Second Floor Plan


Drawn By: TLG	Date: 10/28/2022	Drawing Number:
Project No.:		CA132
279180-22004		




6 Interior Elevation
1/4" = 1'-0"




1 First Floor Reflected Ceiling Plan Area A
1/8" = 1'-0"




5 Ceiling Detail
3" = 1'-0"



4 Soffit Detail
1" = 1'-0"



3 Soffit Detail
1" = 1'-0"



2 Ceiling Detail
3" = 1'-0"

General Finish Notes

- ALL FINISH PRODUCTS ARE TO BE INSTALLED IN ACCORDANCE WITH CONTRACT SPECIFICATION AND MANUFACTURERS INSTRUCTIONS. REFER TO SPECIFICATIONS AND FINISH DETAILS FOR ADDITIONAL INFORMATION ON INSTALLATION OF SPECIFIED MATERIALS.
- ALL PAINTS FOR INTERIOR AND EXTERIOR ARE TO BE APPLIED IN ACCORDANCE WITH SPECIFICATION SECTION 09 91 00 AND 09 96 00.
 - ALL EXPOSED STRUCTURES, INCLUDING BUT NOT LIMITED TO PIPING AND FIREPROOFING, CONDUIT, AND ALL ASSOCIATED EQUIPMENT ARE TO BE PAINTED.
 - APPLY PAINT TO BOTH NEW AND EXISTING ITEMS IN ALL AREAS INDICATED WITH A FINISH BOX AND/OR NOTES - THESE ITEMS ARE INCLUDING BUT ARE NOT LIMITED TO:
 - FFC'S, LADDERS, BEAMS, DOORFRAMES - BOTH SIDES
 - GLAZING FRAMES IN DOORWALLS - BOTH SIDES
 - ALL EXPOSED STAIR PARTS INCLUDING RAILINGS, HAND AND GUARD RAILS, STRINGERS AND UNDERSIDES OF STAIRS, ALL ITEMS ARE TO BE ACCENT COLORS.
 - PATTERNS FOR FLOORS ARE AS SHOWN. SUBMIT SHOP DRAWINGS SHOWING DETAILED LAYOUTS OF EACH AREA INCLUDING EDGES AND TRANSITIONS, ALL LAYOUTS ARE TO BE CENTERED IN EACH ROOM UNO - TYP ALL DRAWINGS. ABOVE REQUIREMENTS ARE TO INCLUDE BUT NOT LIMITED TO:
 - CARPET
 - VCT
 - LVT
 - RUBBER
 - FIELD AND ACCENT PAINT ARE ISSUED DURING THE CONSTRUCTION PHASE. CONTRACTOR IS TO ASSUME ALL FIELD AND ACCENT COLORS ARE DIFFERENT ROOM TO ROOM, AS WELL AS WITHIN EACH ROOM. REQUIREMENTS ARE TO INCLUDE BUT ARE NOT LIMITED TO:
 - WALL FIELD COLOR
 - WALL ACCENT COLOR
 - CEILING CLOUDS, ACCENT COLOR
 - SOFFITS, ACCENT COLOR
 - DOOR AND WINDOW FRAMES, ACCENT COLOR
 - EXPOSED COLUMNS, ACCENT COLOR
 - GUARDRAILS, ACCENT COLOR
 - HANDRAILS, ACCENT COLOR
 - EXPOSED DECKS, ACCENT COLOR
 - EXPOSED JOISTS, ACCENT COLOR
 - EXPOSED DUCTWORK, ACCENT COLOR
 - PROVIDE PAINT AT ALL NEW SOFFITS. REFER TO REFLECTIVE CEILING PLANS FOR ADDITIONAL LOCATIONS.
 - ALL EXPOSED BRICK, GROUND FACE BLOCK IS TO REMAIN UNPAINTED, UNO.
 - CONFIRM WITH OWNER AND ARCHITECT PRIOR TO PAINTING OVER MURALS ON EXISTING SURFACES.
 - PROVIDE PAINT AND RUBBER BASE AT ALL NEW CHASES. REFER TO NEW WORK PLANS FOR ADDITIONAL LOCATIONS.
 - CARPET IS TO RUN WALL TO WALL, UNDER ALL FURNITURE, MOVEABLE EQUIPMENT AND LIBRARY SHELVING UNITS, INCLUDING ALL UNITS AT THE PERIMETER WALLS.
 - FOR ALL RENOVATED AREAS REQUIRING FINISH WORK REMOVE, PROTECT AND REINSTALL MOVABLE EQUIPMENT INCLUDING BUT NOT LIMITED TO: BOARD UNITS, LOCKERS, GYM EQUIPMENT, SHADES/BLINDS, BOOKCASES ETC. REINSTALL IN ORIGINAL LOCATION, OR AS NOTED ON DRAWINGS. COORDINATE WITH OWNER. REFER TO SPEC SECTION 01 23 00 ALTERATION PROJECT PROCEDURES FOR MORE INFORMATION.
 - PROVIDE ALL FINISHES AS INDICATED BY ROOM FINISH BOX AND/OR AS NOTED ON DRAWINGS.

General Ceiling Notes

- LIGHTING AND OTHER CEILING-MOUNTED FIXTURES ARE SHOWN FOR DRAWING CLARITY. COORDINATE ALL CEILING WORK PRIOR TO INSTALLATION OF CEILING GRID.
- CENTER CEILING-MOUNTED ITEMS (LIGHTS, GRILLES, DETECTORS, SPRINKLER HEAD, ETC) WITHIN THE CEILING PANELS AND GRIDS UNLESS THE PANELS ARE SCORED. CENTER ITEMS WITHIN THE PATTERN OF SCORED PANELS.
- PATCH CEILING SYSTEMS TO REMAIN THAT HAVE BEEN DISTURBED BY SCHEDULED WORK TO MATCH ADJACENT CONSTRUCTION PRIOR TO PAINTING.
- X 18'-0" DESIGNATES BOTTOM OF CEILING ABOVE FINISHED FLOOR AT THAT POINT UNO. DESIGNATION "ME" INDICATES MATCH EXISTING CEILING HEIGHT.
- AT ALL LOCATIONS OF GYPSUM CEILINGS - PROVIDE 24" X 24" CONCEALED FLANGE ACCESS DOOR REGARDLESS OF LOCATION OR REQUIREMENT FOR ACCESS TO EQUIPMENT.

Ceiling Types


- (A2) X'X" ACOUSTIC PANEL CEILING
- (A3) X'X" ACOUSTIC PANEL CEILING
- (M) X'X" ACOUSTIC PANEL CEILING
- (B) X'X" PAINTED 1/2" GYPSUM CEILING ON SUPPORT MATERIALS (GRID SUSPENSION SYSTEM, TYP UNO)

Ceiling Tile Legend

- (Hatched Box) TIDE FELT PANEL (A4)

General Notes

- DO NOT SCALE DRAWINGS TO OBTAIN DIMENSIONS.
- TAKE FIELD MEASUREMENTS TO FIT THE WORK PROPERLY. VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS IN THE FIELD.
- REFER INCONSISTENCIES TO ARCHITECT PRIOR TO COMMENCING THE WORK IN AFFECTED AREA.
- ITEMS ARE SHOWN DIAGRAMMATICALLY ON DRAWINGS. VERIFY SPACE REQUIREMENTS AND DIMENSIONS TO FIT THE WORK PROPERLY.
- NOTES SHOWN ON ONE DRAWING APPLY TO ALL SIMILAR DRAWINGS.
- DO NOT DISTURB CONSTRUCTION SUSPECTED OF CONTAINING HAZARDOUS MATERIAL. IF ENCOUNTERED, IMMEDIATELY NOTIFY ARCHITECT, CONSTRUCTION MANAGER AND OWNER.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description

complex world CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET

TETRA TECH ARCHITECTS & ENGINEERS


Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School


First Floor Reflected Ceiling Plan - Area A

Drawn By: GK	Date: 10/28/2022	Drawing Number: CA161
Project No.:	279180-22004	


3 Work Room 6A
1/4" = 1'-0"




2 Work Room 6A
1/4" = 1'-0"




6 Library Media Center 6
1/4" = 1'-0"



5 Library Media Center 6
1/4" = 1'-0"



9 Library Media Center 6
1/4" = 1'-0"




7 Display Case Window
1/4" = 1'-0"

8 Corridor Elevation
1/4" = 1'-0"


LIBRARY SHELVING SCHEDULE			
A	WORDEN	SHELVING - STARTER	36"W X 42" H X 14" D
B	WORDEN	SHELVING - ADDER	36"W X 42" H X 14" D
C	WORDEN	SHELVING - DOUBLE UNITS	36"W X 42" H X 24" D
D	WORDEN	SHELVING - BIG BOOK	16"W X 17" H X 18" D

REFER TO DRAWING CA900 FOR LIBRARY SHELVING NOTES.
REFER TO DRAWING CA900 FOR SHELVING TOP DETAIL.
ALL UNITS ARE TO BE MODIFIED PER SHELVING SCHEDULE.
PROVIDE FULL FINISHED FILLER PANELS AT ALL TOP/SIDE/CORNERS AS REQUIRED, PROVIDED BY LIBRARY SHELVING SUPPLIER, INCLUDING BETWEEN BASE UNITS AT WINDOW SEAT AREAS, TYP.



10 Terrazzo Base at New Opening
1 1/2" = 1'-0"

1 Enlarged 1st Floor Library Plan
1/4" = 1'-0"



4 Enlarged 1st Floor Library Plan Finish Plan
1/4" = 1'-0"



Room Finish Key	
C1	CARPET - TYPE 1
C3	CARPET ACCENT PLANKS
HPC	HIGH PERFORMANCE COATING
LVT	LUXURY VINYL TILE
N	NO WORK REQUIRED
P	PAINT SURFACE(S) INCLUDING SOFFITS
QT	QUARRY TILE
RF1	RUBBER FLOORING - TYPE 1
RS	RUBBER STAIR TREAD AND RISERS
RB	RUBBER BASE
RFB	RECESSED FLOOR MAT
T1	TERRAZZO - TYPE 1 - POURED EPOXY
TB	TERRAZZO BASE - PRECAST
VCT1	VINYL COMPOSITION TILE - TYPE 1
*	SEE REFLECTED CEILING PLAN
+	INDICATED CHANGE IN FLOOR FINISH

NOTE: ALL FINISHES LISTED MAY NOT BE REQUIRED FOR THIS PROJECT


FINISHES SHOWN IN ROOM FINISH BOX ARE FOR ALL WALLS AND ENTIRE FLOOR AND CEILING. REFER TO EACH ROOM FOR MORE INFORMATION.		
RM#	CLG*	WALL
	FLR	BASE

Window Treatment Key	
—	INDICATES AREAS OF WINDOW TREATMENT

Window Treatment Notes

THIS DRAWING IS FOR LOCATION OF WINDOW TREATMENTS ONLY. SPECIFICATIONS SECTION AND ARCH. DRAWINGS FOR SIZES AND ADDITIONAL PRODUCT INFORMATION.
SHADE SIZES SHALL BE COORDINATED WITH WINDOWS, INCLUDING ALL RESCUE WINDOW REQUIREMENTS.


REFER TO DRAWING CA400 FOR CASEWORK NOTES
REFER TO DRAWING CA400 FOR GENERAL FINISH NOTES



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School


Enlarged Plans / Interior Elevations

Drawn By: MHH/GK	Date: 10/28/2022	Drawing Number: CA400
Project No.:	279180-22004	


BID SET




11 Typical Stair Base Section
1 1/2" = 1'-0"




12 Typical Stair Head Section
1 1/2" = 1'-0"




13 Guardrail Section Detail
1" = 1'-0"




7 South Stair Section
1/8" = 1'-0"




8 North Stair Section
1/8" = 1'-0"




9 Railing Termination Detail
1 1/2" = 1'-0"




10 Wall Mounted Rail Support Detail
6" = 1'-0"




4 North Stair Enlarged Basement Plan
1/4" = 1'-0"




5 North Stair Enlarged First Floor Plan
1/4" = 1'-0"




6 North Stair Enlarged Second Floor Plan
1/4" = 1'-0"




1 South Stair Enlarged Basement Plan
1/4" = 1'-0"



2 South Stair Enlarged First Floor Plan
1/4" = 1'-0"



3 South Stair Enlarged Second Floor Plan
1/4" = 1'-0"



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET



Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School


Enlarged Stair Plans, Sections, and Details

Drawn By: GK Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004 CA401


ROOM NUMBER	DOOR NUMBER	DOOR							FRAME							REMARKS		
		TYPE	MATERIAL	WIDTH	HEIGHT	RATING	GLAZING	TYPE	MATERIAL	WIDTH	HEIGHT	RATING	GLAZING	HEAD	JAMB		SILL	HDW SET
1st FLOOR																		
6	1	N3	WD	3'-0"	7'-2"	20 MIN	FP	F2	HM	3'-4"	7'-4"	20 MIN	-	H-13	J-13	-	01	NOTE 1
6	2	N3	WD	3'-0"	7'-2"	20 MIN	FP	F2	HM	3'-4"	7'-4"	20 MIN	-	H-13	J-13	-	01	NOTE 1
6	3	N3	WD	3'-0"	7'-2"	20 MIN	FP	F2	HM	3'-4"	7'-4"	20 MIN	-	H-2	J-2	-	02	NOTE 1
6	4	-	-	0"	0"	20 MIN	-	F22	HM	1'-6"	1'-6"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 6'-0" AFF
6	5	-	-	0"	0"	20 MIN	-	F22	HM	1'-0"	3'-0"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 3'-0" AFF
6	6	-	-	0"	0"	20 MIN	-	F22	HM	2'-0"	2'-0"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 6'-0" AFF
6	7	-	-	0"	0"	20 MIN	-	F22	HM	1'-0"	2'-0"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 4'-0" AFF
6	8	-	-	0"	0"	20 MIN	-	F22	HM	1'-0"	3'-0"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 3'-0" AFF
6	9	-	-	0"	0"	20 MIN	-	F22	HM	2'-0"	2'-0"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 4'-0" AFF
6	10	-	-	0"	0"	20 MIN	-	F22	HM	1'-0"	2'-0"	45 MIN	FPC	J-14 SIM	J-14	-		NOTE 1, SILL HEIGHT 5'-0" AFF
6A	1	F	WD	3'-0"	7'-2"	-	-	F2	HM	3'-4"	7'-4"	-	-	H-13	J-13	-	03	PROVIDE LOUVER 10" HIGH X 20" WIDE

GENERAL NOTES:
VERIFY ALL DIMENSIONS IN THE FIELD


SPECIFIC NOTES:
- NOT APPLICABLE
1. COORDINATE WITH CURVED WALL RADIUS, SEE PLAN




DOOR TYPES




FRAME TYPES




6 Sill Detail
1/4" = 1'-0"




4 Storefront S1
1/4" = 1'-0"




7 Head Detail
1/2" = 1'-0"




H-2




H-13



J-2




J-13




J-14


5 Typical Hollow Metal Frame Details
1 1/2" = 1'-0"



1 Metal Stud Partition Type P12 and P13
1 1/2" = 1'-0"



2 Metal Stud Partition Type P16
1 1/2" = 1'-0"




3 Typical Top of Wall Assembly (Rated)
3" = 1'-0"

General Door Notes

- A. HARDWARE ON DOORS FROM SPACES OF PUPIL OCCUPANCY SHALL BE A TYPE WHICH WILL ALWAYS PERMIT THE DOOR TO BE OPENED FROM THE INSIDE WITHOUT DIRECT MANIPULATION OF ANY TYPE LOCKING DEVICE.
- B. METAL VISION PANEL TRIM SHALL BE PAINTED SAME COLOR AS DOOR FRAMES.
- C. APPLY CONTINUOUS JOINT SEALANT TO ALL JOINTS BETWEEN FRAMES AND WALLS, TYP ALL.
- D. PAINT ALL HM DOORS AND FRAMES.
- E. PROVIDE LINTELS AT ALL DOOR AND WINDOW OPENINGS IN ACCORDANCE WITH LINTEL SCHEDULE ON STRUCTURAL DWGS.
- F. NOTE THAT DUE TO REQUIREMENTS IN THE BCMS, SOME FIRE RESISTANCE RATINGS MAY DIFFER BETWEEN DOORS (AND ITS GLASS, IF ANY) AND THAT DOORS FRAME ESPECIALLY IF THAT FRAME HAS GLASS (SIDELITES, TRANSOMS, ETC).
- G. VERIFY SIZES OF ALL EXISTING OPENINGS IN SCHEDULE PRIOR TO FIRST SUBMISSION OF SHOP DRAWINGS. NOTIFY ARCHITECT IF ANY ARE LESS THAN CODE MINIMUM HEIGHT OF 6'-8". ASSUME FOR BIDDING ALL EXISTING OPENINGS ARE AS NOTED IN THE SCHEDULE (VF, TYP).
- H. MATERIAL DESIGNATION KEY:
FRP FIBERGLASS REINFORCED PLASTIC
HM HOLLOW METAL
WD WOOD
AL ALUMINUM
STL STEEL
EXG EXISTING
- J. ADDITIONAL DOOR SCHEDULE DESIGNATIONS:
- EXISTING TO REMAIN
- NOT APPLICABLE
- NOT APPLICABLE OR TO BE COORDINATED WITH STOREFRONT TYPE.

General Window Notes

- A. REFER TO WINDOW TREATMENTS AS SHOWN ON DRAWINGS.
- B. GLAZING SYSTEMS FRAME TYPE KEY:
HM HOLLOW METAL
S ALUMINUM STOREFRONT



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York


Reconstruction to:
Sargent Elementary School

Door Schedule, Door and Window Types, and Details


Drawn By: GK Date: 10/28/2022 Drawing Number:
Project No.: 279180-22004 CA600




10 Window Seat - Plan
1/4" = 1'-0"




6 Typical Sill to Jamb (less than 4')
3/4" = 1'-0"




1 Typical Wall Bridging
3/4" = 1'-0"




11 Elevation- Window Seat
1/4" = 1'-0"




7 Typical Track Splice
3/4" = 1'-0"




2 Typ Non-load Bearing Head (greater than 4')
3/4" = 1'-0"



12 Bench Section
1/4" = 1'-0"



3 Typ Non-load Bearing Head (less than 4')
3/4" = 1'-0"



8 Display Case Detail
3/4" = 1'-0"

1. FOR 4" THICK WALLS

MASONRY OPENING UP TO 6'-4"	LINTEL ANGLE
	MT 6X5.9

2. FOR 6" THICK WALLS

MASONRY OPENING (L)	LINTEL ANGLE
5'-0"	2- L2 1/2X2 1/2X5/16
6'-0"	2- L3X2 1/2X5/16 LLV
7'-0"	2- L3 1/2X2 1/2X5/16 LLV
8'-0"	2- L3 1/2X2 1/2X5/16 LLV


3. FOR 8", 12", AND 16" THICK WALLS: FOR EACH 4" THICKNESS OF WALL

MASONRY OPENING (L)	LINTEL ANGLE
5'-0"	L3 1/2X3 1/2X5/16
6'-0"	L4X3 1/2X 5/16 LLV
7'-0"	L5X3 1/2X5/16 LLV
8'-0"	L5X3 1/2X5/16 LLV
9'-0"	L6X3 1/2X5/16 LLV
10'-0"	L6X3 1/2X5/16 LLV


LINTEL NOTES

- ALL OPENINGS 1'-0" AND OVER REQUIRE LINTELS.
- STEEL TO BE A36.
- THIS SCHEDULE IS TYPICAL FOR ALL MASONRY OPENINGS IN NON-LOAD BEARING WALLS UNLESS OTHERWISE NOTED.
- ALL LINTELS TO HAVE MINIMUM 8" BEARING BOTH ENDS.
- BACK TO BACK ANGLES ARE TO BE STITCH WELDED TOGETHER BEFORE PLACEMENT.
- ALL LINTELS ARE TO HAVE BOTH ENDS BEAR ON SOLID MASONRY OR SOLIDLY GROUTED HOLLOW MASONRY.
- WHERE MINIMUM 8" BEARING LENGTH CANNOT BE PROVIDED DUE TO COLUMN INTERFERENCE, PROVIDE CONNECTION OF LINTEL TO COLUMN.
- THIS LINTEL SCHEDULE IS APPLICABLE FOR USE IN EXISTING BUILDING, SHORE EXISTING STRUCTURE AND WALL AS REOD FOR INSTALLATION OF NEW MAS AND LINTEL. SEE ARCHITECTURAL AND MECHANICAL DRAWINGS FOR SIZE AND LOCATION OF OPENINGS.


9 Lintel Schedule
12" = 1'-0"



4 Typ Wall Bridging at Pipe Chase
3/4" = 1'-0"



5 Typical Sill to Jamb (greater than 4')
3/4" = 1'-0"



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET

TETRA TECH ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

Miscellaneous Details

Drawn By: GKM/MHH/TLG	Date: 10/28/2022	Drawing Number:
Project No.:	279180-22004	CA750

General Wood Casework Notes

- FOR ALL CONTRACTOR RESPONSIBILITIES REFER TO SPECIFICATION SECTION 01 10 00/01 12 00.
- A. THE CASEWORK SHOWN ON THE DRAWINGS IS BASED ON WOOD METAL WOOD CASEWORK. REFER TO THE PROJECT MANUAL, SECTION 12 32 13 FOR DETAILED SPECIFICATIONS.
- B. ALL STANDARD CASEWORK DIMENSIONS TO BE MODIFIED TO CORRESPOND WITH THE DIMENSIONS NOTED ON THE DRAWINGS. FIELD VERIFY ALL DIMENSIONS PRIOR TO FABRICATION OF CABINETS.
- C. MODEL NUMBERS LISTED ON DRAWINGS APPLY TO ELEVATIONS SHOWN. PROVIDE OPPOSITE HAND MODELS WHERE SHOWN.
- D. PROVIDE FULL DEPTH SHELVES AT BASE, WALL AND TALL CABINETS, UNLESS NOTED OTHERWISE.
- E. BASE AND TALL CABINETS ARE 24 INCHES DEEP. U.N.O. WALL CABINETS ARE 14 INCHES DEEP. UNO BASE CABINET DEPTH DOES NOT INCLUDE 1" COUNTERTOP OVERHANG, TYP.
- F. PROVIDE FINISHED ENDS, BACK EXTENSIONS, SCRIBES AND FINISHED FILLER PANELS ON ALL CABINETS. FILLER PANELS ARE NOT TO EXCEED 3" WIDE, UNLESS NOTED OTHERWISE. PROVIDE TOP AND BOTTOM FILLER PANELS AT ALL BASE & WALL UNITS. SUBMIT SHOP DRAWINGS SHOWING DETAILS OF THESE CONDITIONS.
- G. ALL COUNTERTOPS TO SOLID SURFACE UNLESS NOTED OTHERWISE. BACKSPASHES TO BE 4" HIGH, TYP.
- H. RADIUS COUNTERTOPS AT EDGE OF SOLID SURFACE COUNTERTOPS ENDS MEETING TALL SHELVING UNITS WITH A DEPTH LESS THAN COUNTERTOP DEPTH. RADIUS TO BE 1-1/2" UNLESS NOTED OTHERWISE. REFER TO DETAIL.
- I. PROVIDE CUTS AT ALL CONDITIONS THAT INTERFERE WITH COUNTERTOPS/CABINETS. SCRIBE TO FIT.
- J. PROVIDE SHOP DRAWINGS SHOWING LOCATIONS AND DETAILS FOR ALL GRILLES, LOUVERS, REMOVABLE PANELS, VALVE LOCATIONS ECT. ASSOCIATED WITH CASEWORK COORDINATE WITH ALL REQUIRED CONTRACTORS.
- K. PROVIDE CABINETS WITH FINISHED SIDES, INCLUDING BUT NOT LIMITED TO, LOCATIONS OF ADJACENT CABINETS OR EQUIPMENT WITH A DEPTH LESS THAN CABINET OR EQUIPMENT.
- L. PROVIDE ALL STANDARD FEATURES OF CASEWORK UNITS AS INDICATED BY MODEL NUMBER OR AS SHOWN ON PLANS, DETAILS AND ELEVATIONS. INCLUDED BUT NOT LIMITED TO: OUTLETS, SWITCHES, LIGHTS ETC.
- M. PROVIDE BLOCKING AT NEW AND EXISTING GYPSUM BOARD WALLS PER MANUFACTURER RECOMMENDATIONS FOR SUPPORT OF WALL TALL MOUNTED UNITS. REFER TO SPECIFICATION SECTION 06 10 00 FOR WOOD BLOCKING RESPONSIBILITIES.
- N. PROVIDE LOCKS AT ALL CASEWORK DOORS/DRAWERS AND FILE UNITS TYP.
- O. PROVIDE AS NOTED ON DRAWINGS AND DETAILS. 2" GROMMETS AT OPEN BASE COUNTERS 30"/36" OC. WIRE MANAGEMENT, KEY BOARD TRAYS AND CABLE TRAYS.
- P. PROVIDE ALL CUTOUTS AS SHOWN ON CASEWORK PLANS AND ELEVATIONS OR AS REQUIRED. CUTOUTS ARE TO INCLUDE BUT NOT LIMITED TO: ALL ELEC BOXES, OUTLETS, AND ASSOCIATED WIRING AND FINAL HOOK-UP.
- Q. REFER TO BOTH 1/8" AND 1/4" PLANS FOR LAYOUTS.

NON-GLARE SURFACE:

*TYPICAL FOR ENTIRE SIGN


TACTILE CHARACTERS:

- *5/8" MINIMUM CAP LETTER HEIGHT
- *1" MINIMUM NUMBER HEIGHT
- *RAISED 1/32" MINIMUM FULL GAPS
- *SAN SERIF TYPE STYLE
- *CHARACTERS MUST CONTRAST WITH BACKGROUND

GRADE 2 BRAILLE




TYPE 5 - Typical Permanent Room Plaque



10 Wall Covering Trim Detail
12" = 1'-0"

General Finish Notes


- ALL FINISH PRODUCTS ARE TO BE INSTALLED IN ACCORDANCE WITH CONTRACT SPECIFICATION AND MANUFACTURER'S INSTRUCTIONS. REFER TO SPECIFICATIONS AND FINISH DETAILS FOR ADDITIONAL INFORMATION ON INSTALLATION OF SPECIFIED MATERIALS.
- A. ALL PAINTS FOR INTERIOR AND EXTERIOR ARE TO BE APPLIED IN ACCORDANCE WITH SPECIFICATION SECTION 09 91 00 AND 09 96 00.
- B. ALL EXPOSED STRUCTURES, INCLUDING BUT NOT LIMITED TO PIPING AND FIREPROOFING, CONDUIT, AND ALL ASSOCIATED EQUIPMENT ARE TO BE PAINTED.
- C. APPLY PAINT TO BOTH NEW AND EXISTING ITEMS IN ALL AREAS INDICATED WITH A FINISH BOX AND/OR NOTES - THESE ITEMS ARE INCLUDING BUT ARE NOT LIMITED TO:
 - F.C.'S, LADDERS, BEAMS, DOOR/FRAMES - BOTH SIDES
 - GLAZING FRAMES IN DOOR/WALLS - BOTH SIDES. ALL EXPOSED STAIR PARTS INCLUDING RAILINGS, HAND AND GUARD RAILS, STRINGERS AND UNDERSIDES OF STAIRS. ALL ITEMS ARE TO BE ACCENT COLORS.
- D. PATTERNS FOR FLOORS ARE AS SHOWN. SUBMIT SHOP DRAWINGS SHOWING DETAILED LAYOUTS OF EACH AREA INCLUDING EDGES AND TRANSITIONS. ALL LAYOUTS ARE TO BE CENTERED IN EACH ROOM UNO - TYP ALL DRAWINGS. ABOVE REQUIREMENTS ARE TO INCLUDE BUT NOT LIMITED TO:
 - TERRAZZO AND BASE
 - CARPET
 - VCT
 - LVT
 - RUBBER
- E. FIELD AND ACCENT PAINT ARE ISSUED DURING THE CONSTRUCTION PHASE. CONTRACTOR IS TO ASSUME ALL FIELD AND ACCENT COLORS ARE DIFFERENT ROOM TO ROOM, AS WELL AS WITHIN EACH ROOM. REQUIREMENTS ARE TO INCLUDE BUT ARE NOT LIMITED TO:
 - WALL, FIELD COLOR
 - WALL, ACCENT COLOR
 - CEILING CLOUDS, ACCENT COLOR
 - SOFFITS, ACCENT COLOR
 - DOOR AND WINDOW FRAMES, ACCENT COLOR
 - EXPOSED COLUMNS, ACCENT COLOR
 - GUARDRAILS, ACCENT COLOR
 - HANDRAILS, ACCENT COLOR
 - EXPOSED DECKS, ACCENT COLOR
 - EXPOSED JOISTS, ACCENT COLOR
 - EXPOSED DUCTWORK, ACCENT COLOR
- F. PROVIDE PAINT AT ALL NEW SOFFITS. REFER TO REFLECTIVE CEILING PLANS FOR ADDITIONAL LOCATIONS.
- G. ALL EXPOSED BRICK, GROUND FACE BLOCK IS TO REMAIN UNPAINTED, UNO.
- H. CONFIRM WITH OWNER AND ARCHITECT PRIOR TO PAINTING OVER MURALS ON EXISTING SURFACES.
- I. PROVIDE PAINT AND RUBBER BASE AT ALL NEW CHASES. REFER TO NEW WORK PLANS FOR ADDITIONAL LOCATIONS.
- J. CARPET IS TO RUN WALL TO WALL, UNDER ALL FURNITURE, MOVABLE EQUIPMENT AND LIBRARY SHELVING UNITS, INCLUDING ALL UNITS AT THE PERIMETER WALLS.
- K. FOR ALL RENOVATED AREAS REQUIRING FINISH WORK REMOVE, PROTECT AND REINSTALL MOVABLE EQUIPMENT INCLUDING BUT NOT LIMITED TO: BOARD UNITS, LOCKERS GYM EQUIPMENT, SHADES/BLINDS, BOOKCASES ETC. REINSTALL IN ORIGINAL LOCATION, OR AS NOTED ON DRAWINGS. COORDINATE WITH OWNER. REFER TO SPEC SECTION 01 23 00 ALTERATION PROJECT PROCEDURES FOR MORE INFORMATION.
- L. PROVIDE ALL FINISHES AS INDICATED BY ROOM FINISH BOX AND/OR AS NOTED ON DRAWINGS.




11 Wall Covering Trim Detail - Top
12" = 1'-0"

General Library Notes


- A. THE LIBRARY EQUIPMENT SHOWN ARE BASED ON WORDEN REFER TO THE PROJECT MANUAL, SECTION 12 56 51 FOR DETAILED SPECIFICATIONS. CHAIRS ARE BASED ON COMMUNITY SEATING - SEE SPEC AND SCHEDULE.
- B. ALL SHELVING UNITS, BOTH SINGLE AND DOUBLE ARE TO BE PROVIDED WITH WOOD END PANELS.
- C. ALL LIBRARY SHELVING IS TO BE PROVIDED WITH CANOPY TOPS AS LISTED BELOW:
 - ALL 30", 42" HIGH SHELVING UNITS ARE TO BE PROVIDED WITH A CONTINUOUS SOLID SURFACE TOP
 - ALL SINGLE FACED SHELVING UNITS ARE TO BE FURNISHED AND INSTALLED WITH BACKS AS PER SPECIFICATIONS. SECURE ALL SINGLE FACED SHELVING TO WALLS.
- D. PROVIDE SOLID HARDBOARD BACKS FOR ALL SHELVING UNITS UNLESS OTHERWISE NOTED. PROVIDE FINISHED BACK PANELS FOR DOUBLE FACE SHELVING UNITS UNO.
- E. PROVIDE FINISHED FILLER PANELS BOTH VERTICAL AND HORIZONTAL ALL FILLER SIZE ARE TO BE VERIFIED IN FIELD.
- F. ALL SHELVING UNITS ARE TO BE FIELD VERIFIED PRIOR TO FABRICATION, MODIFY UNITS AS REQUIRED. SEE DETAILS.
- G. PROVIDE SHOP DRAWINGS SHOWING LAYOUTS OF ALL SHELVING, DETAILS AND CHASES.
- H. REFER TO SPEC SECTION 01 23 00 FOR ADDITIONAL INFORMATION REGARDING CASEWORK ALTERNATES.




6 Solid Surface Countertop Edge Detail
3" = 1'-0"



7 ADA Sink Base - Double Sink
3/4" = 1'-0"




8 Threshold Detail
6" = 1'-0"




9 Threshold Detail
6" = 1'-0"


1 Base Outlet Detail
3" = 1'-0"




2 Corner Filler @ Library Casework
3/4" = 1'-0"





3 Corner Filler @ Library Casework
3/4" = 1'-0"



4 Continuous Canopy Top
3/4" = 1'-0"



5 Library Desk Section
3/4" = 1'-0"



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.

TETRA TECH ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York


Reconstruction to:
Sargent Elementary School

Details


Drawn By: MHH	Date: 10/28/2022	Drawing Number:
Project No.:	279180-22004	

CA900


BID SET




4 Gym Office E13 Partial Plan
1/4" = 1'-0"




5 Gym Office E13 Ductwork Connection
1/4" = 1'-0"



1 First Floor Demolition Plan - Library/Media Center
1/8" = 1'-0"




2 First Floor Plan - Library/Media Center
1/8" = 1'-0"



3 Basement Plan - Partial Area A
1/8" = 1'-0"

General Notes


A. REFER TO CM050 FOR GENERAL NOTES.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.: Date: Description:



complex world CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

Partial Plans

Drawn By: JPF1/pgm	Date: 10/28/2022	Drawing Number:
Project No.: 279180-22004	CM100	

BID SET

REMOTE CONDENSING UNIT (RCU) SCHEDULE																		
DWG LABEL	LOCATION	SERVES	MODEL NO.	REFRIG.	SUCTION (°F)	LIQUID (°F)	SUCTION SIZE	LIQUID SIZE	NOMINAL CAPACITY	COOLING CAPACITY	COMPRESSOR QTY & TYPE	FAN CONDENSER QTY & DRIVE TYPE	EER	MCA	MOP	VPH	NET WEIGHT (LBS)	NOTES
RCU-C-1	MECH YARD	EXISTING UV	4TR4030	R-410A	45.0	110	3/8"	3/4"	2.5 TONS	30000 Btu/h	1 SCROLL	1 DIRECT	12.2	17.0	25	208/2ø	160	1-9
RCU-C-2	MECH YARD	EXISTING UV	4TR4030	R-410A	45.0	110	3/8"	3/4"	2.5 TONS	30000 Btu/h	1 SCROLL	1 DIRECT	12.2	17.0	25	208/2ø	160	1-9


NOTES:
 1. DESIGN BASIS: TRANE
 2. PROVIDE MOTOR STARTER AND NEMA 3R DISCONNECT.
 3. PROVIDE DEFROST CONTROLS.
 4. PROVIDE LOW AMBIENT OPERATION BELOW 60°F.
 5. PROVIDE INTERNAL THERMAL PROTECTION.
 6. PROVIDE BRAZED TUBING REFRIGERANT LINE SETS AND COUPLINGS.
 7. FIELD CHARGE REFRIGERANT FOR SUPPLY LINE, CONDENSER AND COILS.
 8. VERIFY LINE SIZES WITH MANUFACTURER.
 9. PROVIDE 4" CONCRETE PAD.

FAN COIL UNIT (FCU) SCHEDULE																			
EQUIP NO.	LOCATION	MODEL NO.	SA CFM	MIN. OA	NO. ROW	EAT (°F)	LAT (°F)	CAP. (MBH)	GPM	WPD (FT HD)	ESP	SUPPLY FAN (IN. WG.)	RPM	MOTOR SIZE (HP)	V/PH	FLA	MCA	MOP	NOTES
FCU-C-E13	GYM OFFICE E13	FCB8040	190	20	2	60.1	116.6	9.2	0.5	1.2	0.00	740	0.01	120W/1ø	2.2	2.8	15	1-7	

NOTES:
 1. DESIGN BASIS: TRANE
 2. CEILING CABINET UNIT
 3. PROVIDE 1" MERV13 FILTER.
 4. HOT WATER COIL CONDITIONS: EWT=180°F, LWT=120°F
 5. PROVIDE NEMA 1 DISCONNECT SWITCH.
 6. VERIFY PIPE AND ELECTRICAL LEFT/RIGHT HAND CONNECTIONS PRIOR TO ORDERING.
 7. PROVIDE RETURN AIR BOTTOM INLET, FRONT GRILLE OUTLET AND BACK FRESH AIR DUCT COLLAR.


SARGENT BUILDING/EQUIPMENT VENTILATION CALCULATIONS													
EQUIPMENT NUMBER	ROOM NUMBER	ROOM NAME	OCCUPANCY CLASSIFICATION	Az - AREA (SF)	MINIMUM VENTILATION RATES								
					Pz - ZONE OCCU. #/1000 FT	ZONE OCCU.	Rp (CFM/Person)	RpP	Ra (CFM/SF)	RaA	Vbz (CFM)	EZ	Voz (CFM)
EXG UVø	ø	LIBRARY/MEDIA CENTER	Media center	1821	25	46	10	480	0.12	219	679	0.9	780
EXG UVø	øA	WORK ROOM	Office Space	98	5	1	5	5	0.08	8	11	0.9	20
FCU-C-E13	E13	GYM OFFICE	Office Space	146	5	1	5	4	0.08	9	12	0.8	20

NOTES:
 Rp = PEOPLE OUTDOOR AIR RATE, Ra = AREA OUTDOOR AIR RATE, Vbz = BREATHING ZONE OUTDOOR AIRFLOW,
 Ez = AIR DISTRIBUTION CONFIGURATION, Voz = ZONE OUTDOOR AIRFLOW




- UNIT VENTILATOR - HOT WATER (VALVE CONTROL) AND DX COOLING - SEQUENCE OF OPERATIONS:
- OCCUPIED MODE:**
 - SUPPLY FAN AND ASSOCIATED EXHAUST FAN SHALL RUN CONTINUOUSLY.
 - THE OUTSIDE AIR DAMPER SHALL OPEN TO THE POSITION REQUIRED TO MAINTAIN THE MINIMUM OUTSIDE AIR QUANTITY INDICATED. OUTSIDE AIR DAMPER SHALL NEVER BE POSITIONED BELOW THIS MINIMUM POSITION EXCEPT IN CASE OF ALARM.
 - WHEN THE SPACE TEMPERATURE IS AT OR BELOW THE HEATING SETPOINT, THE 2-WAY CONTROL VALVE SHALL MODULATE TO MAINTAIN SPACE HEATING SETPOINT SUBJECT TO DISCHARGE HIGH LIMIT OF 110 DEG. F (ADJUSTABLE) AND DISCHARGE LOW LIMIT OF 70 DEG. F (ADJUSTABLE).
 - WHEN THE SPACE TEMPERATURE RISES 3 DEG. F (ADJUSTABLE) ABOVE THE SPACE HEATING SETPOINT, AND THE OUTSIDE AIR TEMPERATURE IS LOWER THAN THE SPACE TEMPERATURE, THE OUTSIDE AIR DAMPER SHALL MODULATE OPEN AND THE ASSOCIATED RELIEF HOOD DAMPER SHALL OPEN TO MAINTAIN THE OCCUPIED SETPOINT. THIS SHALL BE DONE SUBJECT TO DISCHARGE LOW LIMIT OF 55 DEG. F (ADJUSTABLE), AND WITH THE HEATING VALVE FULLY CLOSED.
 - WHEN THE SPACE TEMPERATURE IS 3 DEG. F (ADJUSTABLE) ABOVE THE COOLING SETPOINT, AND THE OUTSIDE AIR CANNOT COOL THE SPACE, THE RESPECTIVE CONDENSING UNIT SHALL BE CYCLED TO MAINTAIN SPACE TEMPERATURE WITH THE HEATING VALVE FULLY CLOSED. USE 5 DEG. F (ADJUSTABLE) DEADBAND BETWEEN HEATING AND COOLING SETPOINTS.
 - UNOCCUPIED MODE:**
 - SUPPLY FAN AND ASSOCIATED EXHAUST FAN SHALL BE OFF.
 - THE OUTSIDE AIR DAMPER AND ASSOCIATED RELIEF HOOD DAMPER SHALL BE FULLY CLOSED.
 - WHERE SPACE HAS FINNED TUBE RADIATION, RADIATION SHALL PROVIDE FIRST STAGE UNOCCUPIED HEATING.
 - ON DROP IN SPACE TEMPERATURE BELOW THE UNOCCUPIED SETPOINT, CYCLE THE FAN ON AND COIL CONTROL VALVE FULL OPEN AS REQUIRED TO MAINTAIN REDUCED SPACE TEMPERATURE. USE 5 DEG. F (ADJUSTABLE) DEADBAND TO MINIMIZE SHORT CYCLING.
 - A TIMED LOCAL OVERRIDE CONTROL SHALL ALLOW AN OCCUPANT TO OVERRIDE THE SCHEDULE AND PLACE THE UNIT INTO OCCUPIED MODE FOR 1 HOUR (ADJUSTABLE). AT EXPIRATION OF THIS TIME, CONTROL OF THE UNIT SHALL AUTOMATICALLY RETURN TO THE SCHEDULE.
 - WARM-UP MODE:**
 - THE UNIT SHALL START PER AN OPTIMUM START PROGRAM.
 - THE OUTSIDE AIR DAMPER AND ASSOCIATED RELIEF HOOD DAMPER SHALL BE FULLY CLOSED, AND THE ASSOCIATED EXHAUST FAN SHALL BE OFF.
 - THE SUPPLY FAN SHALL RUN AND THE CONTROL VALVE SHALL MODULATE TO MAINTAIN OCCUPIED SETPOINT.
 - PURGE VENTILATION MODE:**
 - PROVIDE GLOBAL INITIATION OF PURGE VENTILATION MODE AT THE OPERATOR'S WORKSTATION SUCH THAT ONE INITIATION STARTS OR STOPS PURGE VENTILATION MODE FOR ALL EQUIPMENT SO PROGRAMMED. PROVIDE FOR GLOBAL ADJUSTMENT OF THE BELOW DESCRIBED SCHEDULING AND PERCENTAGE VENTILATION CHANGES, AND ALSO FOR LOCAL ADJUSTMENT AWAY FROM GLOBAL SETPOINTS. IF GLOBAL SETPOINTS ARE SUBSEQUENTLY RE-ADJUSTED, PROVIDE WARNING WITH A LIST OF UNITS WITH LOCAL OVERRIDES, BUT DO NOT RE-ADJUST LOCAL OVER-RIDE SETPOINTS GLOBALLY.
 - PROVIDE A PURGE VENTILATION MODE WITH INCREASED VENTILATION AS POSSIBLE WITHIN THE LIMITS OF THE EQUIPMENT. OPERATE WITH ALL THREE MODES DESCRIBED ABOVE WITH THE FOLLOWING MODIFICATIONS TO THE OCCUPIED PERIOD.
 - START OCCUPIED VENTILATION MODE 1 HOUR (ADJ.) EARLIER AND END IT 4 HOURS (ADJ.) LATER.
 - INCREASE VENTILATION AS POSSIBLE BY 100% (ADJ.) WHERE 0% INCREASE IS THE MINIMUM VENTILATION DESCRIBED ABOVE AND 100% IS 100% OUTSIDE AIR WITH NO RETURN AIR.
 - MAINTAIN OCCUPIED SPACE TEMPERATURE AND INCREASED VENTILATION AS POSSIBLE WITHIN HEATING CAPACITY CONSTRAINTS OF LOCAL AND PLANT HEATING CAPACITY. IF SPACE TEMPERATURE DROPS MORE THAN 2 DEG. F (ADJ.) BELOW SPACE HEATING SETPOINT WITH THE HEATING VALVE 100% OPEN, MODULATE VENTILATION RATE BACK TO MINIMUM SPECIFIED VENTILATION RATE DESCRIBED ABOVE WITH HEATING VALVE AT 100% OPEN.
 - SAFETIES:**
 - A SEPARATE LOW LIMIT FREEZE STAT WITH AUTOMATIC RESET SHALL BE INSTALLED WITH SENSING ELEMENT SERPENTINED ACROSS THE FACE OF THE COIL. WHENEVER COIL FREEZE-UP CONDITIONS ARISE (36 DEG. F ADJUSTABLE) THE SUPPLY FAN SHALL STOP, THE OUTSIDE AIR DAMPER SHALL CLOSE 100%, AND CONTROL VALVE SHALL OPEN 100%. AN ALARM SHALL ALSO BE ACTIVATED.
 - UPON FAILURE OF THE FAN, AS SENSED BY THE CURRENT SENSING STATUS SWITCH, ACTIVATE AN ALARM.

4 UV - Hot Water - Valve Control and DX Cooling




- FAN COIL UNIT - HOT WATER - VALVE CONTROL - SEQUENCE OF OPERATIONS:
- OCCUPIED MODE:**
 - SUPPLY FAN AND ASSOCIATED EXHAUST FAN SHALL RUN CONTINUOUSLY.
 - THE OUTSIDE AIR DAMPER SHALL OPEN TO THE POSITION REQUIRED TO MAINTAIN THE MINIMUM OUTSIDE AIR QUANTITY AS INDICATED.
 - WHEN THE SPACE TEMPERATURE IS AT OR BELOW THE HEATING SETPOINT, THE 2-WAY CONTROL VALVE SHALL MODULATE TO MAINTAIN SPACE HEATING SETPOINT SUBJECT TO DISCHARGE HIGH LIMIT OF 110 DEG. F (ADJUSTABLE) AND DISCHARGE LOW LIMIT OF 70 DEG. F (ADJUSTABLE).
 - WHEN THE SPACE TEMPERATURE RISES 3 DEG. F (ADJUSTABLE) ABOVE THE SPACE HEATING SETPOINT, AND THE OUTSIDE AIR TEMPERATURE IS LOWER THAN THE SPACE TEMPERATURE, THE OUTSIDE AIR DAMPER SHALL MODULATE OPEN AND THE ASSOCIATED RELIEF HOOD DAMPER SHALL OPEN TO MAINTAIN THE OCCUPIED SETPOINT. THIS SHALL BE DONE SUBJECT TO DISCHARGE LOW LIMIT OF 55 DEG. F (ADJUSTABLE), AND WITH THE HEATING VALVE FULLY CLOSED.
 - UNOCCUPIED MODE:**
 - THE SUPPLY FAN AND ASSOCIATED EXHAUST FAN SHALL BE OFF.
 - THE OUTSIDE AIR DAMPER AND THE ASSOCIATED RELIEF HOOD DAMPER SHALL BE FULLY CLOSED.
 - WHERE SPACE HAS FINNED TUBE RADIATION, RADIATION SHALL PROVIDE FIRST STAGE UNOCCUPIED HEATING.
 - ON DROP IN SPACE TEMPERATURE BELOW THE UNOCCUPIED SETPOINT, CYCLE THE FAN AND COIL CONTROL VALVE FULL OPEN AS REQUIRED TO MAINTAIN REDUCED SPACE TEMPERATURE. USE 5 DEG. F (ADJUSTABLE) DEADBAND TO MINIMIZE SHORT CYCLING.
 - A TIMED LOCAL OVERRIDE CONTROL SHALL ALLOW AN OCCUPANT TO OVERRIDE THE SCHEDULE AND PLACE THE UNIT INTO OCCUPIED MODE FOR 1 HOUR (ADJUSTABLE). AT EXPIRATION OF THIS TIME, CONTROL OF THE UNIT SHALL AUTOMATICALLY RETURN TO THE SCHEDULE.
 - WARM-UP MODE:**
 - THE UNIT SHALL START PER AN OPTIMUM START PROGRAM.
 - THE OUTSIDE AIR DAMPER AND THE ASSOCIATED RELIEF HOOD DAMPER SHALL BE FULLY CLOSED AND THE ASSOCIATED EXHAUST FAN SHALL BE OFF.
 - THE SUPPLY FAN SHALL RUN AND THE CONTROL VALVE SHALL MODULATE TO MAINTAIN OCCUPIED SETPOINT.
 - PURGE VENTILATION MODE:**
 - PROVIDE GLOBAL INITIATION OF PURGE VENTILATION MODE AT THE OPERATOR'S WORKSTATION SUCH THAT ONE INITIATION STARTS OR STOPS PURGE VENTILATION MODE FOR ALL EQUIPMENT SO PROGRAMMED. PROVIDE FOR GLOBAL ADJUSTMENT OF THE BELOW DESCRIBED SCHEDULING AND PERCENTAGE VENTILATION CHANGES, AND ALSO FOR LOCAL ADJUSTMENT AWAY FROM GLOBAL SETPOINTS. IF GLOBAL SETPOINTS ARE SUBSEQUENTLY RE-ADJUSTED, PROVIDE WARNING WITH A LIST OF UNITS WITH LOCAL OVERRIDES, BUT DO NOT RE-ADJUST LOCAL OVER-RIDE SETPOINTS GLOBALLY.
 - PROVIDE A PURGE VENTILATION MODE WITH INCREASED VENTILATION AS POSSIBLE WITHIN THE LIMITS OF THE EQUIPMENT. OPERATE WITH ALL THREE MODES DESCRIBED ABOVE WITH THE FOLLOWING MODIFICATIONS TO THE OCCUPIED PERIOD.
 - START OCCUPIED VENTILATION MODE 1 HOUR (ADJ.) EARLIER AND END IT 4 HOURS (ADJ.) LATER.
 - INCREASE VENTILATION AS POSSIBLE BY 100% (ADJ.) WHERE 0% INCREASE IS THE MINIMUM VENTILATION DESCRIBED ABOVE AND 100% IS 100% OUTSIDE AIR WITH NO RETURN AIR.
 - MAINTAIN OCCUPIED SPACE TEMPERATURE AND INCREASED VENTILATION AS POSSIBLE WITHIN HEATING CAPACITY CONSTRAINTS OF LOCAL AND PLANT HEATING CAPACITY. IF SPACE TEMPERATURE DROPS MORE THAN 2 DEG. F (ADJ.) BELOW SPACE HEATING SETPOINT WITH THE HEATING VALVE 100% OPEN, MODULATE VENTILATION RATE BACK TO MINIMUM SPECIFIED VENTILATION RATE DESCRIBED ABOVE WITH HEATING VALVE AT 100% OPEN.
 - SAFETIES:**
 - A SEPARATE LOW LIMIT FREEZE STAT WITH AUTOMATIC RESET SHALL BE INSTALLED WITH SENSING ELEMENT SERPENTINED ACROSS THE FACE OF THE COIL. WHENEVER COIL FREEZE-UP CONDITIONS ARISE (36 DEG. F ADJUSTABLE) THE SUPPLY FAN SHALL STOP, THE OUTSIDE AIR DAMPER SHALL CLOSE 100%, AND THE CONTROL VALVE SHALL OPEN 100%. AN ALARM SHALL ALSO BE ACTIVATED.
 - UPON FAILURE OF THE FAN, AS SENSED BY THE CURRENT SENSING STATUS SWITCH, ACTIVATE AN ALARM.


5 FCU - Hot Water - Valve Control - With Outside Air



1 Pipe Insulation



2 FCU/UV Hot Water Piping Schematic



3 Floor Mounted UV OA Intake Detail

TEMPERATURE CONTROLS SYMBOLS LIST	
AI	ANALOG IN
AO	ANALOG OUT
COM	COMMUNICATIONS PORT
CS	AIRBORNE CONTAMINANT SENSOR
DI	DIGITAL IN
DM	DAMPER MOTOR
DO	DIGITAL OUT
EMCS	ENERGY MANAGEMENT CONTROL SYSTEM
F	FLOW (WATER/AIR)
FM	FLOW METER
FS	AIR FLOW SENSOR
FZ	FREEZE STAT
H	HUMIDITY SENSOR
HL	HIGH LIMIT
KWH	KILOWATT HOUR METER
LL	LOW LIMIT
M/S	MANUAL SWITCH STOP / START
P	PRESSURE SENSOR
DP	DIFFERENTIAL PRESSURE
PS	POSITION SENSOR
S/S	STOP / START
SD	SMOKE DETECTOR
ST	STATUS
START	STARTER
T	ADJUSTABLE THERMOSTAT
TS	TEMPERATURE SENSOR
VFD	VARIABLE FREQUENCY DRIVE
WS	WATER SENSOR
%	PERCENT
ES	END SWITCH
BS	BOILER SWITCH

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.: Date: Description:



complex world | CLEAR SOLUTIONS
 Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
 Beacon, New York

Reconstruction to:
 Sargent Elementary School


Details, Schedules and Controls

Drawn By: JPF/1pgm Date: 10/28/2022 Drawing Number:
 Project No.: 279180-22004 CM500


BID SET



1 Basement - Key Plan
1/16" = 1'-0"



2 First Floor - Key Plan
1/16" = 1'-0"




3 Second Floor - Key Plan
1/16" = 1'-0"

Demolition General Notes

- A. ALL ELECTRICAL DEVICES INTERFERING WITH DEMOLITION WORK SHALL BE DISCONNECTED AND REMOVED, UNLESS OTHERWISE NOTED. EXISTING CIRCUIT WIRING SHALL BE REMOVED BACK TO SOURCE AND PANEL DIRECTORIES MODIFIED ACCORDINGLY.
- B. ANY DEVICE INTERFERING WITH DEMOLITION WORK NOT SHOWN ON THESE DRAWINGS SHALL NOT BE REMOVED WITHOUT WRITTEN AUTHORIZATION FROM THE OWNER'S REPRESENTATIVE OR THE ENGINEER.
- C. ALL ELECTRICAL DEMOLITION WORK SHALL BE PROPERLY COORDINATED WITH ALL OTHER TRADES.
- D. EC IS SOLELY RESPONSIBLE FOR THE SAFE HANDLING AND DISPOSAL OF ALL REMOVED LUMINAIRES AND BALLASTS THAT MAY CONTAIN PCBs (POLYCHLORINATED BIPHENYLS), IN ACCORDANCE WITH ALL APPLICABLE EPA, OSHA, FEDERAL, STATE, AND LOCAL CODES AND LAWS.
- E. EC IS SOLELY RESPONSIBLE FOR THE SAFE HANDLING AND DISPOSAL OF ALL REMOVED FLUORESCENT LIGHT TUBES THAT MAY CONTAIN MERCURY, IN ACCORDANCE WITH ALL APPLICABLE EPA, OSHA, FEDERAL, STATE, AND LOCAL CODES AND LAWS.
- F. AT ALL CORRIDORS WHERE NEW CEILINGS ARE BEING INSTALLED, DISCONNECT AND REMOVE DEVICES AS INDICATED, TAG EXISTING WIRING FOR REUSE.

General Notes

- A. COORDINATE ALL ELECTRICAL WORK AND POWER OUTAGES WITH OWNER AND OTHER TRADES PRIOR TO THE START OF CONSTRUCTION. NO POWER OUTAGES SHALL OCCUR WITHOUT OWNER'S PRIOR KNOWLEDGE AND CONSENT.
 - B. REFER TO DRAWING G100 FOR STANDARD SYMBOLS AND ABBREVIATIONS.
 - C. CIRCUIT WIRING FOR ALL LIGHTING CIRCUITS SHALL BE IN 1/2" EMT CONDUIT (MIN) OR TYPE MC CABLE CONCEALED ABOVE CEILINGS AND IN WALLS (REFER TO SPECIFICATION SECTION 26 05 33 FOR LOCATIONS WHERE MC CABLE IS ACCEPTABLE). ALL CIRCUIT CONDUCTORS SHALL BE #12AWG COPPER (MIN) 90°C THHN THERMOPLASTIC INSULATION.
 - D. CIRCUIT EXIT AND EMERGENCY LUMINAIRES TO UNSWITCHED HOT LEG OF LIGHTING CIRCUIT OF THE AREA BEING SERVED BY OR ADJACENT TO THE LUMINAIRE. REFER TO PLANS AND DETAILS FOR MINATURE INVERTER INFORMATION.
 - E. PROPERLY IDENTIFY ALL CIRCUITS AT PANELS AND J-BOXES AND IN ACCORDANCE WITH PROJECT SPECIFICATIONS.
 - F. PROVIDE ALL ADAPTERS, COUPLINGS AND ASSOCIATED FITTINGS REQUIRED FOR COMPLETE OPERATIONAL SYSTEM.
 - G. WHEN INSTALLING NEW DEVICES IN EXISTING LOCATIONS, REUSE EXISTING CONDUIT/RACEWAY AND BACK BOXES IF IN GOOD CONDITION. EXTEND/INSTALL NEW CONDUIT/RACEWAY AS REQUIRED FOR PROPER MOUNTING OF DEVICE. CONCEAL ABOVE CEILINGS OR WITHIN WALLS WHERE POSSIBLE. REFER TO SPECIFICATION SECTION 26 05 33.
 - H. COORDINATE ALL ELECTRICAL WORK WITH OTHER TRADES.
 - I. TESTS OF ALL ELECTRICAL WORK SHALL BE PERFORMED IN THE PRESENCE OF THE ENGINEER OR ARCHITECT, AS EQUIPMENT IS INSTALLED AND AS SYSTEMS ARE COMPLETED. IN ADDITION AN ELECTRIC APPROVED CERTIFICATE SHALL BE ISSUED BY AN ELECTRICAL INSPECTION AGENCY.
 - J. UNLESS NOTED ELSEWHERE ON THE CONTRACT DOCUMENTS, THE FOLLOWING LIST REPRESENTS THE TYPICAL MOUNTING HEIGHTS FOR THE DEVICES SHOWN:
 - 1. SWITCHES AND PANIC STATIONS.....48" (TO TOP)
 - 2. RECEPTACLES.....16"
 - 3. COMPUTER RECEPTACLES.....48" (TO TOP)
 - 4. WALL (W) TELEPHONE AND CALL SWITCHES.....48" (TO TOP)
 - 5. TELEPHONE OUTLETS (UNLABELED).....16"
 - 6. VOLUME CONTROLS.....48" (TO TOP)
 - 7. TELEVISION OUTLETS.....16"
 - 8. FIRE ALARM PULL STATIONS.....48" (TO TOP)
 - 9. FIRE ALARM AUDIOVISUAL UNITS.....88"
* (OR IF BELOW CEILING, WHICHEVER IS LOWER)
 - 10. POWER PANELS.....72" (TO TOP)
 - 11. DISCONNECT SWITCHES.....60" (TO TOP)
 - 12. MOTOR STARTERS.....60" (TO TOP)
- THE HEIGHTS INDICATED SHALL BE NORMAL TO THE BOTTOM OF THE BOX UNLESS NOTED OTHERWISE. MAINTAIN HEIGHT CONSISTENCY BETWEEN NEW AND EXISTING DEVICES.



Key Plan
N.T.S.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York
Reconstruction to:
Sargent Elementary School


Key Plans

Drawn By: SAS	Date: 10/28/2022	Drawing Number: CE050
Project No.: 279180-22004		


BID SET




1 Partial First Floor Demolition Plan - Area A
1/8" = 1'-0"




2 Partial First Floor Lighting Plan - Area A
1/8" = 1'-0"



5 Partial Basement Power & Communications Plan - Area A
1/8" = 1'-0"



4 Partial Basement Power & Communications Plan - Area A
1/8" = 1'-0"




3 Partial First Floor Power & Communications Plan - Area A
1/8" = 1'-0"

Keyed Notes:

- 1 REMOVE LUMINAIRE(S). TAG CIRCUITRY FOR RE-USE.
- 2 REMOVE ELECTRICAL DEVICES SHOWN. REMOVE EXISTING CIRCUITRY BACK TO NEAREST JUNCTION BOX, DEVICE OR SWITCH OUTSIDE OF DEMOLITION AREA. MODIFY EXISTING SYSTEM CIRCUITRY TO ALLOW FOR PROPER OPERATION OF REMAINING DEVICES ON CIRCUIT.
- 3 DISCONNECT POWER CIRCUITRY SERVING HVAC EQUIPMENT. TAG CIRCUITRY FOR RE-USE.
- 4 PROTECT AND SECURE EXISTING DATA CABLES AND CONDUITS.
- 5 RE-CONNECT POWER CIRCUITRY TO RELOCATED HVAC EQUIPMENT. MODIFY/EXTEND CIRCUITRY AS NECESSARY.
- 6 CIRCUIT TO SPARE 20A1P BREAKER IN PANEL SARGENT - H. CONNECT USING (2) #12, (1) #12 G. IN 1/2" CONDUIT. AMEND PANEL DIRECTORY ACCORDINGLY.
- 7 PROVIDE 30A2P CIRCUIT BREAKER IN AVAILABLE SPACE IN PANEL SARGENT - H. CONNECT USING (2) #12, (1) #12 G. IN 3/4" CONDUIT. NEW BREAKER TO BE UL LISTED FOR USE IN PANEL AND MEET OR EXCEED AIC RATING OF EXISTING PANEL. AMEND PANEL DIRECTORY ACCORDINGLY.
- 8 CIRCUIT TO SPARE 20A1P BREAKER IN PANEL SARGENT - B. CONNECT USING (2) #12, (1) #12 G. IN 1/2" CONDUIT. AMEND PANEL DIRECTORY ACCORDINGLY.
- 9 PROVIDE RECEPTACLE IN TOE KICK OF CASEWORK. REFER TO DETAIL 1 ON SHEET CA900 FOR MORE INFORMATION.
- 10 CONNECT LUMINAIRES TO EXISTING CIRCUITRY PREVIOUSLY SERVING THE AREA.
- 11 PROVIDE WALL MOUNTED MINIATURE INVERTER BASED ON MODEL VESTA MAX MODEL VST-MAX-375W-UNV-4CK. MOUNT AT 72" AFF. COORDINATE FINAL LOCATION WITH OWNER. REFER TO WIRING DIAGRAM ON DRAWING CE500.
- 12 CONNECT LUMINAIRES TO EXISTING CIRCUITRY SERVING THE CORRIDOR LUMINAIRES. CONNECT LUMINAIRES TO EXISTING LIGHTING CONTROLS IN THE CORRIDOR.

General Notes:

- A. REFER TO DRAWING CE100 FOR GENERAL NOTES.
- B. REFER TO DRAWING CE500 FOR LUMINAIRE SCHEDULE.
- C. SECURE ALL EXISTING UNSUPPORTED CABLES ABOVE CEILINGS USING J HOOKS OR CABLETRAYS.
- D. FIRE ALARM DEVICES ARE TO BE WIRED TO EXISTING NOTIFICATION CIRCUITS.
- E. INVERTER SYSTEM EMERGENCY OUTPUT CIRCUITS SHALL BE INSTALLED IN DEDICATED CONDUIT SYSTEMS AND NOT SHARED WITH OTHER ELECTRICAL CIRCUITS AS DESCRIBED IN NEC 700-9(B).
- F. SPEAKERS ARE TO BE COMPATIBLE AND WIRED TO EXISTING PA SYSTEM.
- G. CLOCKS ARE TO BE COMPATIBLE WITH EXISTING CLOCK SYSTEM.
- H. LIGHTING CONTROL SEQUENCE:
LIBRARY:
MULTI-ZONES PER OWNER. OPERATED WITH PROGRAMMABLE TOUCH SCREEN CONTROL.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description



complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET




Beacon City School District
Beacon, New York

Reconstruction of:
Sargent Elementary School

Partial Plans

Drawn By: SAS/CR	Date: 10/28/2022	Drawing Number:
Project No.:	CE100	
279180-22004		




- INSTALLATION NOTES:**
- LOCATE CABLE BUNDLES A MINIMUM OF 6" ABOVE REMOVABLE CEILING TO MAINTAIN CLEARANCE (ALONG WALLS WHERE POSSIBLE). LOCATE IN AREAS THAT ARE ACCESSIBLE.
 - USE 2 OR MORE CABLE HANGERS AT ALL TURNS TO MAINTAIN MANUFACTURER'S BEND RADIUS REQUIREMENTS.
 - THIS SUPPORT SYSTEM TO BE USED WHEREVER CABLE TRAY IS NOT INDICATED ON PLANS.


1 Typical Installation with Cable Hangers
NTS

TYPE	SYMBOL	DESCRIPTION	LAMPS		MANUFACTURERS (OR EQUAL)	
			WATTAGE	LUMENS	TYPE	NAME
1 **	[Symbol]	1' x 4' TROFFER (RECESSED IN GRID)	12.2	1482	LED	SIGNIFY (DAY-BRITE) 1FPZ15L835-4-DS-UNV-DIM
1 .. EM	[Symbol]	SAME AS TYPE 1 - CONNECTED TO EMERGENCY MINIATURE INVERTER	12.2	1482	LED	SIGNIFY (DAY-BRITE) 1FPZ15L835-4-DS-UNV-DIM
2 **	[Symbol]	1' x 4' TROFFER (RECESSED IN GRID)	24.6	2972	LED	SIGNIFY (DAY-BRITE) 1FPZ30L835-4-DS-UNV-DIM
2 .. EM	[Symbol]	SAME AS TYPE 2 - CONNECTED TO EMERGENCY MINIATURE INVERTER	24.6	2972	LED	SIGNIFY (DAY-BRITE) 1FPZ30L835-4-DS-UNV-DIM
3 **	[Symbol]	1' x 4' TROFFER (RECESSED IN GRID)	31.3	3775	LED	SIGNIFY (DAY-BRITE) 1FPZ38L835-4-DS-UNV-DIM
3 .. EM	[Symbol]	SAME AS TYPE 3 - CONNECTED TO EMERGENCY MINIATURE INVERTER	31.3	3775	LED	SIGNIFY (DAY-BRITE) 1FPZ38L835-4-DS-UNV-DIM
4 **	[Symbol]	2' x 2' TROFFER (RECESSED IN GRID)	15.7	1918	LED	SIGNIFY (DAY-BRITE) 2FPZ20L835-2-DS-UNV-DIM
4 .. EM	[Symbol]	SAME AS TYPE 4 - CONNECTED TO EMERGENCY MINIATURE INVERTER	15.7	1918	LED	SIGNIFY (DAY-BRITE) 2FPZ20L835-2-DS-UNV-DIM
5 **	[Symbol]	2' x 2' TROFFER (RECESSED IN GRID)	23.4	2911	LED	SIGNIFY (DAY-BRITE) 2FPZ30L835-2-DS-UNV-DIM
5 .. EM	[Symbol]	SAME AS TYPE 5 - CONNECTED TO EMERGENCY MINIATURE INVERTER	23.4	2911	LED	SIGNIFY (DAY-BRITE) 2FPZ30L835-2-DS-UNV-DIM
6	[Symbol]	2' x 2' TROFFER (RECESSED IN GRID)	29.8	3856	LED	SIGNIFY (DAY-BRITE) 2FPZ38L835-2-DS-UNV-DIM
6 EM	[Symbol]	SAME AS TYPE 6 - CONNECTED TO EMERGENCY MINIATURE INVERTER	29.8	3856	LED	SIGNIFY (DAY-BRITE) 2FPZ38L835-2-DS-UNV-DIM
7 **	[Symbol]	2' x 2' TROFFER (RECESSED IN GRID)	35.7	4403	LED	SIGNIFY (DAY-BRITE) 2FPZ45L835-2-DS-UNV-DIM
7 .. EM	[Symbol]	SAME AS TYPE 7 - CONNECTED TO EMERGENCY MINIATURE INVERTER	35.7	4403	LED	SIGNIFY (DAY-BRITE) 2FPZ45L835-2-DS-UNV-DIM
8 **	[Symbol]	4" ROUND DOWNLIGHT	8.8	868	LED	SIGNIFY (LEDALITE) L4R10935VB / L4RDW
8 .. EM	[Symbol]	SAME AS TYPE 8 - CONNECTED TO EMERGENCY MINIATURE INVERTER	8.8	868	LED	SIGNIFY (LEDALITE) L4R10935VB / L4RDW
9	[Symbol]	4" SQUARE DOWNLIGHT	8.8	868	LED	SIGNIFY (LEDALITE) L4R10935VB / L4RDW
9 EM	[Symbol]	SAME AS TYPE 9 - CONNECTED TO EMERGENCY MINIATURE INVERTER	8.8	868	LED	SIGNIFY (LEDALITE) L4R10935VB / L4RDW
10	[Symbol]	2" RECESSED LINEAR. LENGTH VARIES. SEE PLANS FOR SPECIFIC LENGTHS.	14.5	1345	LED	FINELITE HP-2-R-D-XFT-S-835
10 EM	[Symbol]	SAME AS TYPE 10 - CONNECTED TO EMERGENCY MINIATURE INVERTER	14.5	1345	LED	FINELITE HP-2-R-D-XFT-S-835
11	[Symbol]	15 1/8" T-BAR LED	39	2854	LED	JLC TECH TBSL-MW-5-24-B2-X-W
11 EM	[Symbol]	SAME AS TYPE 11 - CONNECTED TO EMERGENCY MINIATURE INVERTER	39	2854	LED	JLC TECH TBSL-MW-5-24-B2-X-W
12	[Symbol]	2" RECESSED PERIMETER	27.6	2999	LED	PINNACLE ARCHITECTURAL LIGHTING EV2DPM-A-835HO-4
12 EM	[Symbol]	SAME AS TYPE 12 - CONNECTED TO EMERGENCY MINIATURE INVERTER	27.6	2999	LED	PINNACLE ARCHITECTURAL LIGHTING EV2DPM-A-835HO-4
13 **	[Symbol]	WALL MOUNT LINEAR	33.1	3361	LED	SIGNIFY (LEDALITE) 7408LBEQN047DEW
13 .. EM	[Symbol]	SAME AS TYPE 13 - CONNECTED TO EMERGENCY MINIATURE INVERTER	33.1	3361	LED	SIGNIFY (LEDALITE) 7408LBEQN047DEW
14 .. EM	[Symbol]	4" SURFACE MOUNTED LINEAR - CONNECTED TO EMERGENCY MINIATURE INVERTER	18.8	1780	LED	PINNACLE ARCHITECTURAL LIGHTING EX3-WET-N-835-4-S-U-OL2-1-0-W
20	[Symbol]	EXIT SIGN (SINGLE FACE) WALL AND CEILING MOUNT. SEE PLANS FOR DIRECTIONAL INDICATORS	2.5		LED	SIGNIFY (CHLORIDE) ER46L-2-W-R

2 Luminaire Schedule
NTS



3 Emergency Miniature Inverter Wiring Diagram
1/4" = 1'-0"



4 Typical Troffer Mounting Detail
NTS

5 Ceiling Mounting Device Detail
NTS

- DETAIL NOTES:**
- IN AREAS RECEIVING NEW CEILING ALL CEILING MOUNTED ITEMS (DETECTORS, SPEAKERS, ETC) ARE TO BE CENTERED WITHIN THE PATTERN OF THE CEILING PANEL. A 2'x4' PANEL SCORED TO A 2'x2' PATTERN SHALL HAVE ITEMS CENTERED IN THE 2'x2' PORTION.
 - PROVIDE ADDITIONAL SUPPORT FOR EXIT SIGNS, WHERE REQUIRED.

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.: Date: Description:

complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET

TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York


Reconstruction to:
Sargent Elementary School

Details

- PROVIDE VOLUME CONTROL IN ALL OFFICES
- PROVIDE WIRING AS REQUIRED BY SYSTEM MANUFACTURER INSTALL IN RACEWAY IN WALL SECTIONS TO EXISTING PA SYSTEM
- PROVIDE WIRING AS REQUIRED BY SYSTEM MANUFACTURER INSTALL IN RACEWAY IN WALL SECTIONS TO EXISTING MASTER CLOCK SYSTEM


6 Clock and Speaker System Wiring Diagram

12" = 1'-0"




NOTES:

- PAIN T ALL SURFACE RACEWAY AND BOXES TO MATCH EXISTING SURFACES. (WHERE APPLICABLE).
- PROVIDE RELAYS WHERE TWO OR MORE CIRCUITS FEED LIGHTING IN SAME ROOM.
- ADJUST SENSITIVITY OF EACH OCCUPANCY SENSOR TO DETECT HUMAN MOVEMENT BUT NOT HVAC EQUIPMENT.
- ADJUST TIME DELAY FOR OPTIMUM PERFORMANCE. APPLY MASKING SEGMENTS TO DETECTION HEAD WHERE REQUIRED.
- POWER PACK AND THE LOAD SWITCHED BY THE POWER PACK MUST BE FED FROM THE SAME PHASE.
- REFER TO LIGHTING PLANS FOR LIGHTING SEQUENCES




1 Typical Mounting Heights

NTS



4 Data Outlet

NTS




2 Conduit/Backbox Installation Detail

NTS

7 Daylight Responsive Controls Wiring Diagram

NTS



FIRE ALARM SEQUENCE OF OPERATION

- UPON ACTIVATION TROUBLE CONDITION THE FIRE ALARM PANEL SHALL GO INTO "TROUBLE" MODE INDICATING WHICH ZONE IS IN TROUBLE BY A LIGHT IN THE REMOTE ANNUNCIATOR AND AT THE FIRE ALARM PANEL.


- NOTES:
- FIRE ALARM RISER IS INTENDED TO BE SCHEMATIC ONLY. ALL DEVICES INDICATED ON PLANS AND DETAILS ARE TO BE INSTALLED AND CONNECTED FOR PROPER OPERATION OF SYSTEM.
 - WIRE NEW DEVICES INTO EXISTING WIRING OR PROVIDE A NEW CIRCUIT AS DIRECTED BY FIRE ALARM SYSTEM REPRESENTATIVE.

8 Fire Alarm System Wiring Diagram

NTS


5 Data Distribution Riser Diagram

NTS



5 Data Distribution Riser Diagram

NTS



3 Conduit/Backbox Installation Detail

NTS

- NOTES:
- PROVIDE LARGER BOXES AND CONDUIT SIZES WHEN REQUIRED TO ACCOMMODATE DEVICES AND WIRING
 - COORDINATE QUANTITY OF DEVICES AND TYPE OF DEVICE REQUIRED WITH FLOOR PLANS
 - COORDINATE CONDUIT LOCATIONS WITH OTHER TRADES AND OWNER PRIOR TO INSTALLATION

S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.: Date: Description:



complex world CLEAR SOLUTIONS
Tetra Tech Engineers, Architects & Landscape Architects, P.C.




Beacon City School District
Beacon, New York

Reconstruction to:
Sargent Elementary School

Details

Drawn By: SAS Date: 10/28/2022 Drawing Number: 279180-22004
CE501

BID SET




1 Basement Floor Plan - Area A
1/8" = 1'-0"


Grease Interceptor Schedule

DWG LABEL	LOCATION	DESIGN MAKE AND MODEL	GREASE RETENTION CAPACITY (POUNDS)	PDI RATED FLOW RATE (GPM)	INSTALLATION	INLET / OUTLET SIZE (NPS)	CENTERLINE OF INLET / OUTLET TO BOTTOM (INCHES)	CENTERLINE OF INLET / OUTLET TO TOP (INCHES)	EXTENSION HEIGHT (INCHES)	LENGTH (INCHES)	WIDTH (INCHES)	HEIGHT (INCHES)	VENT SIZE (NPS)	NOTES
GI-C-1	KITCHEN E03	JR SMITH 8050	100	50	BURIED	3	17-1/2	6-3/4	FIELD VERIFY	35-1/2	20-3/4	24-1/4	2	1, 2

NOTES:
 1. PROVIDE EXTERNAL FLOW CONTROL FITTING SUPPLIED BY SAME MANUFACTURER AS GREASE INTERCEPTOR.
 2. SET UNIT COVER/EXTENSION FLUSH WITH FINISHED FLOOR.




3 Grease Interceptor Detail
NTS



4 Trenching Below Existing Slab Detail
NTS


5 Typical Chemical Anchors
NTS



2 Kitchen E03 Plan
1/4" = 1'-0"

- General Notes**
- VERIFY ALL PIPING LOCATIONS, SIZES, AND ARRANGEMENTS IN FIELD PRIOR TO BID. NOTIFY ARCHITECT IN WRITING OF ANY DISCREPANCIES.
 - VERIFY IN FIELD INVERT AND DIRECTION OF FLOW IN EXISTING SOIL PIPE WHERE NEW SOIL PIPE IS TO BE CONNECTED TO EXISTING SOIL PIPE.
 - LEGALLY DISPOSE OF ALL DEMOLITION DEBRIS.
 - INCLUDE TRENCHING, CUTTING AND PATCHING OF FLOORS, WALLS AND CEILINGS, INCLUDING CEILING TILE REMOVAL AND REPLACEMENT, WHEN REQUIRED FOR PLUMBING WORK. PATCH ABANDONED OPENINGS AND DISTURBED FINISHES TO MATCH EXISTING. TAKE PRECAUTIONS TO PROTECT STRUCTURAL INTEGRITY OF FLOOR OR WALLS WHEN TRENCHING OR CUTTING.
 - MATERIALS FOR PLUMBING INSTALLATION SHALL BE NEW, UNLESS SPECIFICALLY NOTED OTHERWISE.
 - REPLACE PLUMBING EQUIPMENT INDICATED. MODIFY AND EXTEND EXISTING PIPING AS REQUIRED TO MEET FIXTURE MFR'S ROUGH-IN RECOMMENDATIONS AND TO MAKE CONNECTIONS. CONCEAL PIPING WITHIN OR BEHIND WALLS, BELOW FLOORS OR ABOVE CEILINGS. PATCH DISTURBED FINISHES TO MATCH EXISTING UNLESS SPECIFICALLY NOTED OTHERWISE.

- Plumbing Notes**
- REMOVE 3 BAY SINK AND STORE FOR REINSTALLATION AFTER GREASE INTERCEPTOR IS REPLACED. CLEAN TABLE BEFORE REINSTALLATION.
 - FLOW CONTROL FITTING SUPPLIED BY GREASE INTERCEPTOR MANUFACTURER.
 - REFER TO DETAILS 4/CP130 AND 5/CP130 FOR ADDITIONAL INFORMATION.



S.E.D. Control No. 13-02-00-01-0-008-020

Rev. No.	Date	Description

complex world | CLEAR SOLUTIONS

Tetra Tech Engineers, Architects & Landscape Architects, P.C.

BID SET


TETRA TECH
ARCHITECTS & ENGINEERS

Beacon City School District
Beacon, New York


Reconstruction to:
Sargent Elementary School

Basement Floor Plan - Area A, Details and Schedule


Drawn By: GPD / sef	Date: 10/28/2022	Drawing Number: CP130
Project No.:	279180-22004	



1 First Floor Plan - Area A
1/8" = 1'-0"



2 Partial First Floor - Area A Demolition Plan
1/4" = 1'-0"




3 Condensate Connection Detail
NTS


Plumbing Fixture Schedule								NOTES
DWG LABEL	ROUGH-IN CONNECTION SIZE (INCHES)				BARRIER FREE	AGE GROUP	RIM HEIGHT	
	SAN	VENT	CW	HW				
SINK "A"	1 1/2	1 1/2	1/2	1/2	YES	ADULT	-	ACCESSIBLE, STAINLESS STEEL, COUNTER MOUNTED SINK W/ MANUAL, SINGLE CONTROL MIXING FAUCET W/ SWING SPOUT, SUPPLIES, OFFSET DRAIN FITTING AND TRAP.

NOTES:
 1. SIZES INDICATED ARE MINIMUM. LARGER SIZES SPECIFICALLY INDICATED ON DRAWINGS SUPERCEDE MINIMUM SIZES INDICATED IN THIS SCHEDULE.
 2. TERMINATION STYLE AND SIZE FOR FIXTURE CONNECTIONS SHALL BE AS INDICATED BY FIXTURE MANUFACTURER.
 3. DRAIN AND TRAP CONCEALED BEHIND ADA CASEWORK PANEL. REFER TO DETAILS ON "A" SERIES DRAWINGS.

- Plan Notes**
- A. REFER TO DRAWING NO. CP130 FOR GENERAL NOTES.
 - B. REMOVE PLUMBING FIXTURES INDICATED, INCLUDING ASSOCIATED PIPING, FASTENERS, SUPPORTS, ETC., BACK TO POINTS OF CONCEALMENT WITHIN OR BEHIND REMAINING WALLS, BELOW FLOORS OR ABOVE CEILINGS.
 - C. REMOVE ABANDONED ACCESSIBLE PIPING TO MAIN BRANCHES, STACKS OR RISERS AS REQUIRED TO ELIMINATE EXPOSED PIPING AND DEAD END PIPING RUNS LONGER THAN 1'-0". COORDINATE CONCEALMENT OF PIPING WITH FINAL CONSTRUCTION OF WALLS, FLOORS AND CEILINGS.



S.E.D. Control No. 13-02-00-01-0-008-020



complex world CLEAR SOLUTIONS
 Tetra Tech Engineers, Architects & Landscape Architects, P.C.



Beacon City School District
 Beacon, New York

Reconstruction to:
 Sargent Elementary School

First Floor Plan - Area A and Schedule

Drawn By: GPD / sef Date: 10/28/2022 Drawing Number:
 Project No.: 279180-22004 CP131

BID SET