





1. ALL DEMOLITION WORK SHALL BE IN COMPLIANCE WITH ALL FEDERAL, STATE, AND CITY OF WHITE PLAINS APPLICABLE BUILDING AND LIFE AND SAFETY REGULATIONS.
2. VERIFY IN FIELD EXACT LOCATIONS OF EXISTING HOT WATER AND COLD WATER SUPPLY PIPING, SANITARY, WASTE & VENT PIPING.
3. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL CONSTRUCTION DEBRIS AND UNWANTED MATERIAL OFF SITE IN ACCORDANCE WITH CONTRACT SPECIFICATIONS.
4. THE CONTRACTOR SHALL TAKE CARE NOT TO DAMAGE ADJOINING SURFACES OF THE SIDE THE CONTRACT AREA OR SCOPE OF WORK. THE CONTRACTOR SHALL BE RESPONSIBLE TO RESTORE TO EXISTING CONDITIONS SURFACE DAMAGED DURING CONSTRUCTION INCLUDING PATCHING AND PAINTING AS REQUIRED AND DEEMED NECESSARY BY THE ARCHITECT.
5. CONTRACTORS SITE ACCESS SHALL BE AS CALLED OUT ON THE ARCHITECTURAL SHEETS. THE CONTRACTOR SHALL ADEQUATELY PROTECT THE WALLS, FLOOR, AND FINISHES FROM DAMAGE DURING THE PROJECT DURATION. THE CONTRACTOR SHALL BE RESPONSIBLE TO PATCH AND RESTORE ALL SURFACES THAT ARE DAMAGED TO THE SATISFACTION OF THE ARCHITECT.
6. THE CONTRACTOR SHALL TAKE CARE AS TO ADEQUATELY PROTECT ALL ADJOINING ROOMS, CLOSETS, CORRIDORS, CRITICAL BARRIERS (DUCTS, VENTS, ETC.), AND OTHER SPACES FROM DUST AND DEBRIS DURING THE DEMOLITION AND INSTALLATION OF THE FLOORING AND PAINTING. THE CONTRACTOR SHALL BE RESPONSIBLE TO WIPE DOWN AND CLEAN ALL AFFECTED ROOMS UPON COMPLETION OF THE PROJECT.
7. ALL EQUIPMENT SHALL BE EXISTING TO REMAIN UNLESS OTHER WISE NOTED AND THUS BE PROTECTED THROUGH THE PROJECT DURATION. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT OF ANY DEFECTIVE OR NON-WORKING EQUIPMENT PRIOR TO WORK STARTING AND FOLLOWING INSTALLATION OF NEW FINISHES, SHALL VERIFY THAT ALL OF THE ITEMS ARE IN PROPER WORKING ORDER UPON COMPLETION.

2. EXISTING FLOOR SINK BODY TO REMAIN. REPLACE STRAINER AND RAISE/LOWER TO MATCH NEW FINISHED FLOOR HEIGHT.



1. VERIFY IN FIELD EXISTING LOCATIONS OF HOT WATER AND COLD WATER SUPPLY PIPING, SANITARY, WASTE & VENT PIPING. REROUTE AND MODIFY EXISTING PLUMBING PIPING AS REQUIRED FOR CONNECTIONS TO NEW AND EXISTING PLUMBING FIXTURES.
2. INSULATE ALL NEW WATER PIPING AND RE-INSULATE ALL EXISTING WATER PIPING WHERE INSULATION IS DAMAGED.
3. ALL 3" & 4" SANITARY PIPING TO BE SLOPED A MINIMUM OF 1/8"/FT. ALL 1-1/2" & 2" SANITARY PIPING TO BE SLOPED A MINIMUM OF 1/4"/FT.
4. CHASE WALL WILL NEED TO BE OPENED TO ALLOW ACCESS TO EXISTING PIPING AND THEN REPAIRED. REFER TO ARCHITECTURAL DRAWINGS FOR MORE DETAIL.

1. PROVIDE INDIRECT 1-1/2" DRAIN FROM DRAIN VALVES ON SERVING LINE HOT FOOD TABLE AND SERVING LINE 2-TIER CERAMIC GLASS SHELF TABLE TO EXISTING FLOOR SINK. MAINTAIN MINIMUM 3" AIR GAP BETWEEN INDIRECT DRAIN AND FLOOR SINK.
2. CONNECT NEW 3/4" HOT WATER PIPING TO NEW UNDERCOUNTER DISHWASHER FROM EXISTING 3 COMPARTMENT SINK 3/4" HOT WATER SUPPLY. 1-1/2" DRAIN FROM DISHWASHER TO EXISTING FLOOR SINK WITH 3" AIR GAP. MODIFY PIPING AS REQUIRED.
3. CONNECT NEW 1/2" CW TO NEW POT FILLER FROM EXISTING CW.



The diagram shows a floor plan of a building with several rooms. One room is highlighted in black. Above the plan, there is a legend with two circles. The first circle is divided horizontally, with '1' in the top half and 'P 100' in the bottom half. The second circle is also divided horizontally, with '2' in the top half and 'P 100' in the bottom half. An arrow points from the first circle to the highlighted room.