14

12

11

17

7/3/2025 11:58:03 AM

12. PRIOR TO PLACING CONCRETE, ALL REINFORCEMENT SHALL BE FREE OF LOOSE FLAKY RUST, MUD, OIL OR OTHER COATING THAT WILL DESTROY, REDUCE OR HAMPER FULL BOND CAPACITY.

13. THE PLACEMENT OF DOWELS, ANCHOR RODS, OR ANY OTHER EMBEDMENTS INTO WET CONCRETE "WET STICKING" SHALL NOT BE PERMITTED.

14. CONTROL AND EXPANSION JOINTS SHALL BE PROVIDED TO MINIMIZE CRACKING AS PER ARCHITECTURAL AS WELL AS STRUCTURAL REQUIREMENTS AND IN ACCORDANCE WITH STANDARD PRACTICES ACCEPTED IN THE INDUSTRY

15. THE FOLLOWING CRITERIA SHALL BE MET WITH REGARDS TO PLACEMENT OF CONDUITS, PIPES, ETC. IN CONCRETE SLABS.

THICKNESS. CLEAR DISTANCE BETWEEN TWO ADJACENT CONDUITS SHALL BE A MINIMUM OF 3 DIAMETERS OF LARGER OF THE TWO CONDUITS

B. VERTICAL SLEEVES, PIPES, ETC. THROUGH SLAB EITHER CLUSTERED OR INDIVIDUAL, SHALL NOT INTERRUPT MORE THAN 1/8 OF THE WIDTH OF COLUMN STRIP

C. NO REINFORCEMENT BARS SHALL BE CUT, BENT, SHIFTED OR OTHERWISE ALTERED AS CONDUITS, PIPES, ETC. AS COMPARED TO WHAT IS SHOWN ON THESE DRAWINGS.

D. ANY DEVIATIONS FROM ABOVE REQUIREMENTS SHALL BE SHOWN ON THE SHOP DRAWINGS AND SUBMITTED FOR APPROVAL BY THIS OFFICE.

A. ALL CONDUITS SHALL BE CENTERED AT MID-DEPTH OF SLAB. CONDUIT DIAMETER SHALL NOT EXCEED 1/3 OF SLAB

1. MASONRY WALL CONSTRUCTION SHOWN ON STRUCTURAL DRAWINGS SHALL CONFORM TO THE FOLLOWING

A. UNITS SHALL BE 16" LONG (NOMINAL) MEDIUM WEIGHT AGGREGATE CONCRETE HOLLOW UNITS WITH A MAXIMUM OVEN DRY DENSITY OF 125 PCF. UNITS SHALL CONFORM TO THE REQUIREMENTS OF ASTM C90. NET SOLID UNIT AREA SHALL NOT EXCEED THE FOLLOWING PERCENTAGES OF THE GROSS UNIT AREA:

8" CMU- 55% 10" CMU- 50%

12" CMU- 45%

MINIMUM UNIT COMPRESSIVE STRENGTHS TO BE USED ARE AS FOLLOWS:

ALL FLOORS - 3,750 PSI f'm = 2,500 PSI

B. MORTAR SHALL BE TYPE S OR TYPE M, IN CONFORMANCE WITH ASTM C270. C. GROUT SHALL CONFORM TO ASTM 476 AND SHALL HAVE A MINIMUM 28-DAY COMPRESSIVE STRENGTH EQUAL TO THE

MASONRY ASSEMBLY STRENGTHS (F'm) INDICATED IN NOTE 1A. D. USE SPECIAL UNITS AS REQUIRED TO ALLOW PROPER INSTALLATION OF BOTH VERTICAL AND HORIZONTAL REINFORCEMENT, AND ACCESSORIES TO ACCOMMODATE ARCHITECTURAL AND STRUCTURAL DESIGN. THESE MAY INCLUDE

2. GROUT SOLID ALL CELLS CONTAINING VERTICAL REINFORCEMENT BARS.

3. ALL VERTICAL REINFORCEMENT BARS SHALL BE CENTERED IN THE CELL IN BOTH DIRECTIONS.

BUT NOT BE LIMITED TO BOND BEAM, LINTEL, TROUGH, CORNER AND OTHER SPECIAL UNITS.

4. THE MINIMUM HORIZONTAL REINFORCING FOR ALL MASONRY WALLS SHALL CONSIST OF TWO WIRE-9 GAGE RODS @ 16"O.C. SEE MASONRY SHEAR WALL SCHEDULES ON 5-400 SERIES DRAWINGS FOR MASONRY SHEAR WALL REINFORCING.

5. THE FOLLOWING SHALL BE PROVIDED IN PARAPET WALLS:

A. ALL CELLS AND ALL JOINTS IN SOLID, CAVITY OR MASONRY BONDED HOLLOW WALL CONSTRUCTION SHALL BE FILLED SOLID WITH GROUT AND MORTAR.

B. HORIZONTAL WIRE REINFORGEMENT SHALL BE PROVIDED AT VERTICAL INTERVALS NOT GREATER THAN 12". C. HORIZONTAL REINFORCEMENT SHALL EXTEND AROUND THE CORNER FOR AT LEAST 4 FT. IN BOTH DIRECTIONS AND SPLICES SHALL BE LAPPED AT LEAST 6".

D. NONREINFORCED PARAPET WALLS SHALL BE NOT LESS THAN 8" IN THICKNESS AND THEIR HEIGHT SHALL NOT EXCEED THREE TIMES THEIR THICKNESS.

6. HORIZONTAL REINFORCEMENT SHALL BE CONTINUOUS THROUGH CORNERS, INTERSECTION, AND PILASTERS IN BRICK AND C.M.U.

7. BONDING OF MASONRY UNITS SHALL BE CONTINUED THROUGH CORNERS, INTERSECTIONS, AND PILASTERS IN BRICK AND C.M.U.

8. VERTICAL REINFORCEMENT CONSISTING OF 1#4 MINIMUM SHALL BE PROVIDED AT BOTH SIDES OF ALL OPENINGS FULL HEIGHT OF

9. IN ADDITION TO REINFORCEMENT SHOWN ON PLAN, DETAILS, AND S-400 SERIES, PROVIDE MINIMUM 1#4 VERTICAL REINFORCEMENT FROM FLOOR TO FLOOR AT

A. EACH CORNER OF WALL

B. ALL ENDS OF WALLS. C. NEXT TO EXPANSION JOINTS

10. 1#4 CONTINUOUS REINFORCEMENT SHALL BE PLACED AT TOP AND BOTTOM OF ALL WALL OPENINGS AND SHALL EXTEND 24" MINIMUM OR 40 BAR DIAMETERS PAST EACH SIDE OF THE OPENINGS.

11. HORIZONTAL REINFORCEMENT SHALL BE PLACED CONTINUOUSLY AT THE TOP OF ALL C.M.U. WALLS AT EACH FLOOR. ROOF AND PARAPET WALL, 1#5 HORIZ AT 10" CMU; 2#5 HORIZ AT 12" CMU.

12. ALL GROUTING SHALL FOLLOW THE REQUIREMENTS OF ACI-530.1 ARTICLE 3.5. FOR "LOW LIFT" GROUTING, WALLS SHALL BE LAID UP AND GROUTED AT MAXIMUM INTERVAL HEIGHTS OF 5'-O". PLACE REINFORCEMENT BARS AND EXTEND THEM A SPLICE LENGTH ABOVE LIFT. LEVEL OF GROUT TO BE KEPT 1 1/2" FROM TOP OF MASONRY FORMING A GROUT KEY. "HIGH LIFT" GROUTING SHALL FOLLOW ALL REQUIREMENTS STATED IN ACI-530.1 ARTICLE 3.5D. CLEANOUT HOLES FOR INSPECTION ARE REQUIRED AT THE BASE OF THE WALL FOR ALL POURS OVER 5'-O". ALL GROUT SHALL BE CONSOLIDATED IN ACCORDANCE WITH ARTICLE 3.5E.

13. OPENINGS FOR ROUND DUCTS, PIPING AND ELECTRICAL CONDUIT BETWEEN 4 AND 12 INCHES IN DIAMETER SHALL BE SLEEVED WITH SCHEDULE 40 STEEL PIPE. NO OPENING SHALL BE IN PLACED REINFORCED GROUTED CELLS.

14. GROUT SOLID TOP TWO COURSES OF C.M.U DIRECTLY UNDER BEARING POINTS

15. HORIZONTAL AND VERTICAL CONTROL AND EXPANSION JOINTS IN FACE BRICK SHALL BE LOCATED AS PER ARCHITECTURAL DRAWINGS.

16. EXPOSED STEEL, STEEL LINTELS OR STEEL WITHIN 4" OF WEATHERING FACE OF MASONRY SHALL BE GALVANIZED.

17. ALL LINTELS SHALL BEAR 8" AT EACH JAMB. FULL CONTACT BETWEEN LINTEL AND SUPPORTING MASONRY SHALL BE PROVIDED.

STRUCTURAL STEEL NOTES:

CRITICAL BOLTS.

1. STRUCTURAL STEEL SHALL CONFORM TO THE FOLLOWING: A. WIDE FLANGE AND TEE SHAPES - ASTM A992 GRADE 50 B. CHANNELS, S SHAPES, ANGLES, PLATES AND BARS - ASTM A36

C. STEEL PIPE - ASTM A53 GRADE B D. ROUND, SQUARE & RECTANGULAR HSS SHAPES - ASTM A500 GRADE B

2. SHOP CONNECTIONS SHALL BE WELDED OR BOLTED. FIELD CONNECTIONS SHALL BE BOLTED UNLESS SPECIFICALLY SHOWN OTHERWISE ON STRUCTURAL DRAWINGS.

3. ALL BOLTING SHALL CONFORM TO THE RESEARCH COUNCIL ON STRUCTURAL CONNECTIONS "SPECIFICATION FOR STRUCTURAL JOINTS USING ASTM A325 OR A490 BOLTS", LATEST EDITION.

4. BOLTED CONNECTIONS SHALL UTILIZE ASTM A325 OR A490 BOLTS. ALL BOLTS SHALL BE 3/4 INCH DIAMETER MINIMUM. BOLTED SIMPLE SHEAR CONNECTIONS SHALL UTILIZE HIGH STRENGTH BOLTS IN BEARING TYPE CONNECTIONS AND SHALL BE INSTALLED "SNUG TIGHT". BOLTED MOMENT CONNECTIONS, SPLICE CONNECTIONS AND BRACING CONNECTIONS SHALL BE PRETENSIONED JOINTS WITH FULLY PRETENSIONED HIGH-STRENGTH BOLTS IN BEARING. CONNECTIONS WITH OVERSIZE HOLES OR SLOTTED HOLES IN WHICH THE LOAD IS NOT APPLIED NORMAL TO THE LONG DIMENSION OF THE SLOT REQUIRE SLIP

5. ALL WELDING ELECTRODES SHALL BE LOW HYDROGEN, AS REQUIRED BY AMS "STRUCTURAL WELDING CODE" AND "CODE FOR ARC AND GAS WELDING IN BUILDING CONSTRUCTION" TO SATISFY BASE-TO-FILLER METAL COMBINATION CRITERIA. ALL FILLER METAL SHALL HAVE A MINIMUM CVN TOUGHNESS OF 20 FT. LBS. AT MINUS 20 DEGREES F.

6. ALL WELDING SHALL BE DONE BY QUALIFIED WELDERS AND SHALL CONFORM TO THE AMS "CODE FOR ARC AND GAS MELDING IN BUILDING CONSTRUCTION", LATEST EDITION. MELDER CERTIFICATES SHALL BE SUBMITTED TO GACE BEFORE COMMENCEMENT OF WORK.

7. MINIMUM SIZE OF FILLET WELDS SHALL BE 1/4" MIN. FOR FIELD WELDS AND AS REQUIRED PER AISC SPECIFICATION RELATIVE TO BASE METAL THICKNESS FOR SHOP WELDS.

8. ALL DETAILING, FABRICATION AND ERECTION SHALL CONFORM TO AISC "LOAD AND RESISTANCE FACTOR DESIGN SPECIFICATION FOR STRUCTURAL STEEL BUILDINGS" AND AISC "CODE OF STANDARD PRACTICE", LATEST EDITIONS.

9. CONNECTIONS OF ALL BEAMS AND GIRDERS SHALL BE DESIGNED FOR REACTIONS INDICATED ON STRUCTURAL DRAWINGS. ALL OTHER CONNECTIONS SHALL BE DESIGNED FOR THE FULL CAPACITY OF THE MEMBERS

10. KNIFE CONNECTIONS SHALL NOT BE PERMITTED UNLESS SPECIFICALLY REQUESTED BY A CONTRACTOR AND APPROVED BY STRUCTURAL ENGINEER PRIOR TO SHOP DRAWING APPROVAL. CONTRACTOR'S BIDS SHALL BE SUBMITTED BASED ON THE KNIFE CONNECTIONS NOT ALLOWED. SPECIFIC KNIFE CONNECTION DETAILS SHALL BE SUBMITTED FOR APPROVAL AT THE TIME WHEN TYPICAL DETAILS AND ERECTION PLANS ARE SUBMITTED. THE DETAILS SHALL BE ACCOMPANIED BY CALCULATIONS SIGNED AND SEALED BY PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE PROJECT IS TO BE BUILT CALCULATIONS SHALL DEMONSTRATE THAT THE WELDS ARE NOT OVERSTRESSED DUE TO SECONDARY STRESSES DUE TO BOLT TIGHTENING, PRYING ACTION, ETC.

11. INSPECTION AND TESTING OF WELDS AND BOLTS SHALL BE AS FOLLOWS:

A. A TESTING AGENCY ACCEPTABLE TO THE ENGINEER OF RECORD SHALL BE EMPLOYED BY THE OWNER TO PERFORM ALL SHOP AND FIELD INSPECTIONS AND TESTING OUTLINED BELOW.

B. ALL WORK SHALL BE SCHEDULED BY THE CONTRACTOR TO ALLOW THE BELOW SHOP AND FIELD TESTING TO BE C. ALL WELDS SHALL BE VISUALLY INSPECTED. FIFTEEN (15) PERCENT OF RANDOMLY SELECTED FILLET. PLUG AND SLOT

WELDS SHALL BE MEASURED. D. FIFTEEN (15) PERCENT OF RANDOMLY SELECTED FILLET WELDS IN BEAM AND GIRDER SHEAR CONNECTION PLATES, ANGLES. ETC. SHALL BE CHECKED BY MAGNETIC PARTICLE METHOD. ONLY THE FINAL PASS SHALL BE CHECKED. E. ULTRASONICALLY TEST 100 PERCENT OF ALL FULL AND PARTIAL PENETRATION WELDS. WELD PREPARATION OF 100

PERCENT OF WELDS SHALL BE INSPECTED F. ALL BOLTS SHALL BE VISUALLY INSPECTED.

G. ALL SLIP CRITICAL BOLTS SHALL BE CHECKED FOR PROPER TENSIONING USING THE "DIRECT TENSION INDICATOR" METHOD. MEASURE WITH FEELER GAGES AT LEAST 15% OF BOLTS IN EACH CONNECTION. BUT NOT LESS THAN TWO BOLTS PER CONNECTION.

H. A MINIMUM OF 15 PERCENT OF BOLTS, BUT NOT LESS THAN TWO BOLTS IN EACH BEARING TYPE CONNECTION SHALL BE CHECKED FOR PROPER TENSIONING USING THE CALIBRATED TORQUE WRENCH METHOD. I. IN CASE MULTIPLE DEFECTS HAVE BEEN DETECTED, THE ABOVE EXTENT OF INSPECTION SHALL BE INCREASED AT

DISCRETION OF STRUCTURAL ENGINEER OF RECORD.

12. SUBMITTALS

A. SEE "SUBMITTALS NOTES" SECTION FOR GENERAL REQUIREMENTS

B. THE CONTRACTOR SHALL SUBMIT TO THE ARCHITECT, FOR REVIEW, ENGINEERED SHOP AND ERECTION DRAWINGS SHOWING SHOP FABRICATION DETAILS FOR EACH PIECE OF STEEL, FIELD ASSEMBLY DETAILS AND ERECTION DIAGRAMS

C. PIECE DETAIL SHALL NOT BE SUBMITTED PRIOR TO APPROVAL OF ERECTION DRAWINGS AND RELATED CONNECTION DETAILS, DIAGRAMS, SCHEDULES, ETC.

D. IN ADDITION TO BASIC INFORMATION GIVEN ON STRUCTURAL DRAWINGS, ERECTION DRAWINGS SHALL INCLUDE THE ERECTION MARK, LOCATION, SIZE AND GRADE OF EACH INDIVIDUAL PIECE OF STEEL, REINFORCING OF BEAM PENETRATIONS, THE ELEVATION OF TOP OF BEAM, THE ELEVATION OF WORK POINT AT BOTH ENDS OF SLOPED BEAMS AND CAMBER FOR EACH PIECE.

E. ROLLED SHAPES, TUBES, PLATES AND OTHER COMPONENTS SHALL BE INDENTIFIED BY USING THE STANDARD DESIGNATIONS USED IN AISC DETAILING FOR STEEL CONSTRUCTION. THE STRUCTURAL DRAWINGS MAY BE USED FOR THI PURPOSE TO THE EXTENT DESIRED BY THE CONTRACTOR

F. EACH FIELD CONNECTION SHALL BE SHOWN COMPLETE WITH DATA AND DETAILS NECESSARY FOR ASSEMBLING THE STEEL G. THE FOLLOWING INFORMATION SHALL BE CLEARLY INDICATED ON ALL SHOP DRAWINGS: THE GRADE, SIZE AND NUMBER OF BOLTS, THE TYPE, NUMBER, POSITION, DESIGNATION AND ORIENTATION OF EACH WASHER, THE BOLT TENSION INDICATING SYSTEM AND THE SIZE OF EACH HOLE. WHETHER SLOTTED OR ROUND, CONNECTION DETAILS SHALL BE

H. DETAILS SHALL BE PREPARED IN ACCORDANCE WITH AND TO ACCOMMODATE CONTRACTOR'S FIELD MEASUREMENTS OF SUPPORTING AND ADJOINING CONSTRUCTION.

. WELDS AND NONDESTRUCTIVE TESTS SHALL BE INDICATED BY USING THE SYMBOLS CONFORMING TO AMS A2.4, STANDARD SYMBOLS FOR WELDING, BRAZING AND NONDESTRUCTIVE EXAMINATION. WHERE NECESSARY FOR CLARITY, JOINT DESIGNATION, WELDING PROCESS OR OTHER DATA SHALL BE INDICATED IN THE TAIL OF THE WELDING SYMBOL J. REVIEW OF SHOP DRAWINGS SHALL INCLUDE THE FOLLOWING:

PROPORTIONED TO ENSURE ADEQUATE WRENCH CLEARANCE FOR CORRECT BOLT TENSIONING PROCEDURES

MEMBER SIZE, GRADE, SPACING AND ELEVATION.

STRUCTURAL INTEGRITY OF CONNECTIONS.

PENETRATIONS, INCLUDING SIZE AND LOCATION. K. WHERE DIRECTED, SUBMIT CERTIFIED COPIES OF MILL TEST REPORTS FOR ALL STEEL FURNISHED. COMPLY WITH ALL APPLICABLE PARTS OF ASTM SPECIFICATIONS. BEYOND ORDERING INFORMATION NORMALLY PROVIDED BY CONTRACTOR. THE MILL SHALL BE INSTRUCTED TO COLOR-CODE IN ACCORDANCE WITH ASTM A6 AND TO MARK WITH HEAT NUMBER, SIZE AND TYPE AND GRADE OF STEEL

L. MILL TEST REPORTS SHALL STATE CLEARLY THE GOVERNING ASTM SPECIFICATION AND SHALL BE CERTIFIED AND

NOTARIZED BY CONTRACTOR AS CONFORMING IN ALL RESPECTS TO THAT SPECIFICATION. M. MATERIAL PROVIDED IN ACCORDANCE WITH THE ABOVE REQUIREMENTS MAY BE USED IN THE WORK WITHOUT FURTHER LOCAL TEST. IN THE CASE OF CONTROVERSY, CONTRACTOR SHALL PERFORM TENSION, BEND AND SUCH OTHER TESTS AS ARE REQUIRED TO DEMONSTRATE COMPLIANCE WITH THE REQUIREMENTS OF THE CONTRACT DOCUMENTS.

N. WHERE DIRECTED, SUBMIT MANUFACTURER'S CERTIFICATION OF BOLTS, NUTS, WASHERS, DTI'S, ETC. FOR EACH GRADE OF EACH TYPE AND OF EACH SIZE OF FASTENER COMPONENT AND WELDING FILLER MATERIAL O. FURNISH TEMPLATES AND LAYOUT DRAWINGS FOR EXACT LOCATIONS OF ITEMS TO BE EMBEDDED IN CONCRETE, WITH

SETTING INSTRUCTIONS REQUIRED FOR INSTALLATION OF EMBEDDED ITEMS. P. SUBMIT FOR ACCEPTANCE THE NAMES OF THE FOLLOWING PRODUCTS AND/OR PRODUCERS ALONG WITH CERTIFICATION

THAT THE PRODUCTS CONFORM IN ALL RESPECTS TO THE REQUIREMENTS OF THE CONTRACT DOCUMENTS: PLATES AND SHAPES

BOLTS, NUTS AND WASHERS SHOP AND FIELD PAINT COATING OF MILLED SURFACE **WELDING MATERIALS** STUD SHEAR CONNECTORS SHIELDING GAS

Q. SPECIAL ATTENTION SHALL BE DIRECTED TO THE POSSIBLE NEED FOR INSTALLATION OF GUY CABLES, BRACING OR SHORING TO PREVENT DEFORMATION OF EXISTING OR NEW STRUCTURE DUE TO STRESSES CAUSED BY ERECTION ACTIVITIES AND EQUIPMENT, BY CONSTRUCTION LOADINGS AND BY OTHER FORCES

R. TEMPORARY MEMBERS AND CONNECTIONS WHICH MAY BE REQUIRED FOR TEMPORARY CONSTRUCTION, ERECTION AND SIMILAR WORK SHALL BE DEPICTED AND IDENTIFIED. HOWEVER, THEY SHALL NOT BE SUBJECT TO ENGINEER'S REVIEW. S. TEMPORARY, SHIPPING, HANDLING, ERECTION OR SIMILAR LOADS SHALL NOT BE CONSIDERED IN THE ENGINEER'S

REVIEW OF SHOP DRAWINGS. T. ALL STEEL THAT IS NOT PROPERLY IDENTIFIED OR WHOSE SOURCE IS SUBJECT TO QUESTION SHALL BE REJECTED AND

RETURNED WITHOUT REVIEW. U. UPON COMPLETION OF WORK SUBMIT AN AFFIDAVIT ATTESTING THAT ALL MATERIALS AND PRODUCTS PROVIDED FOR THE WORK CONFORM TO THE APPLICABLE SPECIFICATIONS, STANDARDS, YIELD POINTS, GRADE, ETC. REQUIRED BY CONTRACT DOCUMENTS

13. ALL CONNECTIONS SHALL BE DESIGNED AND DETAILED BY A PROFESSIONAL ENGINEER, REGISTERED IN THE STATE OF NEW YORK, HIRED BY THE CONTRACTOR. IF REQUESTED BY THE ENGINEER OF RECORD, CALCULATIONS SHALL BE SUBMITTED FOR THE ENGINEER OF RECORD'S REFERENCE. ALL REFERENCE CALCULATIONS SHALL BE SIGNED AND SEALED BY THE CONTRACTOR'S ENGINEER.

14. DETAILING SHALL BE PERFORMED USING APPROPRIATE ENGINEERING DESIGN PRINCIPLES AND ACCEPTED INDUSTRY STANDARDS, IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. DETAILER SHALL BE AWARE THAT THE DETAILS AND SECTIONS SHOWN ON THE STRUCTURAL DRAWINGS ARE CONCEPTUAL ONLY AND DO NOT INDICATE THE NUMBER OF BOLTS WELD SIZES, AND OTHER INFORMATION REQUIRED TO BE SHOWN ON THE SHOP DRAWINGS, UNLESS SPECIFICALLY NOTED.

15. ALL STAIR AND OTHER MISCELLANEOUS STEEL STRUCTURES SHALL BE DESIGNED AND DETAILED BY AN ENGINEER EMPLOYED BY THE CONTRACTOR. DRAWINGS SHALL BEAR THE SEAL AND SIGNATURE OF A PROFESSIONAL ENGINEER REGISTERED IN THE STATE OF NEW YORK AND SHALL BE SUBMITTED FOR REVIEW BY STRUCTURAL ENGINEER OF RECORD. CALCULATIONS SHALL BE SUBMITTED FOR REFERENCE.

16. EXISTING STRUCTURAL STEEL SHALL BE REMOVED ONLY WITH ARCHITECT'S (OR HIS REPRESENTATIVE) APPROVAL. NO FIELD CUTTING OF STRUCTURAL STEEL MEMBERS FOR THE WORK OF OTHER TRADES OR FOR ANY OTHER REASON SHALL BE PERMITTED UNLESS APPROVED BY THE ARCHITECT OR BY THE ARCHITECT'S REPRESENTATIVE.

17. NO STRUCTURAL STEEL TO RECEIVE FIREPROOFING SHALL BE PAINTED. ALL STEEL SHALL BE CLEANED IN THE FIELD OF ALL RUST, LOOSE MILL SCALE AND OTHER FOREIGN MATERIALS PRIOR TO THE APPLICATION OF FIREPROOFING.

18. ALL STEEL EXPOSED TO WEATHER SHALL BE HOT-DIPPED GALVANIZED. THIS INCLUDES ALL STEEL LINTELS. RELIEVING ANGLES, HANGERS, ETC. DAMAGED / CUT / WELDED GALVANIZATION SHALL BE TOUCHED UP / REPAIRED IN ACCORDANCE WITH ASTM A780 'STANDARD PRACTICE FOR REPAIR OF DAMAGED AND UNCOATED AREAS OF HOT-DIP GALVANIZED COATINGS'.

19. ALL BEAMS SHALL BE FABRICATED AND ERECTED WITH NATURAL CAMBER UP.

20. SHEAR STUDS SHALL BE HEADED SHEAR CONNECTORS AS MANUFACTURED AND INSTALLED BY NELSON STUD WELDING. SHEAR STUD INSTALLATION SHALL BE INSPECTED BY AN APPROVED TESTING AGENCY IN OWNER'S DIRECT EMPLOY. THREE (3) BEND TESTS SHALL BE PERFORMED AT THE BEGINNING OF CONSTRUCTION. AFTERWARDS, 20 PERCENT (MINIMUM) OF SHEAR STUDS SHALL BE INSPECTED BY "RING TEST" AND MEASURED. ALL STUD WELDING SHALL BE INSPECTED VISUALLY.

215 W 40th St - 15th flr New York, NY 10018

ARCHITECT

Owner **ROCKLAND BOCES** 65 Parrott Rd. West Nyack, NY, 10994

845-627-4700 office

www.rocklandboces.org

646.435.0660 office

www.ksq.design

Civil & MEP Engineer FELLENZER ENGINEERING LLP 22 Mulberry Street. Suite 2A Middletown, NY 10940 845-343-1481 office

> www.fellp.com Structural Engineer

GACE CONSULTING ENGINEERS 148 Madison Avenue, Fourth Floor New York, NY 10016 212-545-7878 office

www.gace.net Food Service Consultant: ELITE | STUDIO E

1856 New Hwy #1 Famingdale, NY, 11735 631-429-9400 office

www.elitestudioe.com **Construction Manager**

ARRIS CONTRACTING COMPANY, in 189 Smith Street Poughkeepsie, NY 12601 845-473-3600 office www.arriscontracting.com

> It is a violation of Title VIII, Article 147 of NYS Education Law for any person, unless acting under the direction of a licensed architect, to alter any item on this document in any way. Any licensee who alters this document is required by law to affix his or her seal and the notation "altered by" followed by his or her signature and a specific description of the alterations made.



ROCKLAND BOCES P-TECH C-TEC **BUILDING**

SED #: 50-90-00-00-0-044-001

West Nyack, NY 10994

65 Parrot Rd.

KEY PLAN	
REVISIONS	
No Description Date	-

ISSUED: BID SET ISSUANCE **DATE:** 06/30/2025

SCALE: 12" = 1'-0" SHEET NAME: **GENERAL NOTES 1**

SHEET NUMBER:

BID

- . ANCHOR CAPACITY SHALL BE BASED ON THE TECHNICAL DATA PUBLISHED BY THE ANCHOR MANUFACTURER OR OTHER METHOD AS APPROVED BY THE STRUCTURAL ENGINEER OF RECORD ("ENGINEER")
- 2. SUBSTITUTION REQUESTS FOR ALTERNATE PRODUCTS SHALL BE APPROVED IN WRITING BY THE ENGINEER PRIOR TO USE. CONTRACTOR SHALL PROVIDE CALCULATIONS DEMONSTRATING THAT THE SUBSTITUTED PRODUCT IS CAPABLE OF ACHIEVING THE PERFORMANCE VALUES OF THE SPECIFIED PRODUCT. SUBSTITUTIONS SHALL BE EVALUATED BY THEIR HAVING AN INTERNATIONAL CODE COUNCIL EVALUATION SERVICE REPORT (ICC ESR) SHOWING COMPLIANCE WITH THE RELEVANT BUILDING CODE FOR SEISMIC USES, LOAD RESISTANCE, INSTALLATION CATEGORY, AND AVAILABILITY OF COMPREHENSIVE INSTALLATION INSTRUCTIONS. ADHESIVE ANCHOR EVALUATION SHALL CONSIDER EFFECTS OF CREEP, IN-SERVICE TEMPERATURE AND
- 3. ANCHORS SHALL BE INSTALLED PER THE MANUFACTURER INSTRUCTIONS INCLUDED IN THE ANCHOR PACKAGING.
- 4. OVERHEAD ADHESIVE ANCHORS MUST BE INSTALLED USING THE HILTI PROFI SYSTEM OR OTHER MANUFACTURER'S EQUAL OR BETTER SYSTEM, IF APPROVED BY THE ENGINEER IN ADVANCE.
- 5. THE CONTRACTOR SHALL ARRANGE ANCHOR MANUFACTURER'S REPRESENTATIVE TO PROVIDE ONSITE INSTALLATION TRAINING FOR ALL OF THEIR ANCHORING PRODUCTS SPECIFIED. THE ENGINEER MUST RECEIVE DOCUMENTED CONFIRMATION THAT ALL OF THE CONTRACTOR'S PERSONNEL WHO INSTALL ANCHORS ARE TRAINED PRIOR TO THE COMMENCEMENT OF THEIR INSTALLATION.
- 6. ANCHOR CAPACITY IS DEPENDENT UPON SPACING BETWEEN ADJACENT ANCHORS AND PROXIMITY OF ANCHORS TO THE EDGE OF CONCRETE. ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH SPACING AND EDGE DISTANCES INDICATED ON THE
- I. REINFORCING BARS OR OTHER ELEMENTS EMBEDDED IN THE EXISTING CONCRETE STRUCTURE MAY CONFLICT WITH SPECIFIC ANCHOR LOCATIONS. UNLESS NOTED ON THE DRAWINGS THAT THE BARS, ETC. CAN BE CUT, THE CONTRACTOR SHALL REVIEW THE EXISTING STRUCTURAL DRAWINGS AND SHALL UNDERTAKE TO LOCATE THE POSITION OF THE EMBEDDED BARS, ETC. BY GROUND PENETRATING RADAR (GPR), X-RAY, CHIPPING OR OTHER MEANS.
- 8. CONTINUOUS OR PERIODIC SPECIAL INSPECTIONS FOR POST INSTALLED ANCHORS SHALL BE PERFORMED IN ACCORDANCE WITH SECTION 4.4 OF THE INDIVIDUAL INTERNATIONAL CODE COUNCIL- EVALUATION SERVICE (ICC- ES) REPORT FOR THE INDIVIDUAL ANCHOR. THE CONTRACTOR SHALL GIVE THE SPECIAL INSPECTOR SUFFICIENT ADVANCE NOTICE TO ALLOW ENOUGH TIME FOR PROPER INSPECTION OF HOLE PREPARATION, ANCHOR INSTALLATION, TIGHTENING, ETC. ANCHORS INSTALLED WITHOUT INSPECTION AT ALL THESE PHASES SHALL BE REJECTED AND WILL HAVE TO BE REPLACED AT CONTRACTOR'S EXPENSE.

. CLEAN STEEL IN ACCORDANCE WITH SSPC-SP6 COMMERCIAL BLAST CLEANING AND COAT WITH TNEMEC OMNITHANE 530 PRIME TO 2 - 3 MILS DRY FILM THICKNESS (DFT), OR APPROVED EQUAL, WITHIN 4 HOURS OF CLEANING. AFTER ERECTION AND TOUCH UP APPLY A FULL COAT OF TNEMEC N69F HI-BUILD EPOXOLINE II TO 3 - 5 MILS DFT FOR TEMPERATURES DURING APPLICATION / CURING BELOW 50 DEG. F DOWN TO 35 DEG. F, AND TNEMEC SERIES 135 CHEMBUILD TO 5 - 6 MILS DFT FOR TEMPERATURES DURING APPLICATION / CURING ABOVE 50 DEGREE F.

- . STEEL JOISTS AND BRIDGING SHALL CONFORM TO THE REQUIREMENTS OF THE SPECIFICATIONS OF THE STEEL JOIST
- 2. ADDITIONAL JOIST SHALL BE PROVIDED UNDER PARALLEL PARTITIONS WHEN THE PARTITION LENGTH EXCEEDS ONE-HALF THE JOIST SPAN AND AROUND ALL FLOOR AND ROOF OPENINGS WHICH INTERRUPT ONE OR MORE SPANNING MEMBERS.
- 3. STEEL JOISTS SHALL BE WELDED TO STRUCTURAL SUPPORTS
- 4. UNIFORM AND LEVEL JOIST BEARING SHALL BE PROVIDED AT BEARING WALLS BY MEANS OF SHIMS AND/OR NON-SHRINK
- . METAL DECK SHALL CONFORM TO AISI "SPECIFICATION FOR THE DESIGN OF LIGHT GAUGE COLD FORMED STEEL STRUCTURAL MEMBERS" AND TO THE STEEL DECK INSTITUTE SPECIFICATIONS AND RECOMMENDATIONS.
- 2. ALL METAL DECK SHALL BE COMPOSITE TYPE. STEEL SHALL CONFORM TO ASTM A653, GRADE 40. ALL MATERIAL SHALL BE
- 3. THE CONTRACTOR SHALL SUBMIT FOR ARCHITECT'S APPROVAL SHOP DRAWINGS INDICATING LOCATION, GAUGE AND SIZE OF EACH PIECE OF METAL DECK. THE DRAWINGS SHALL SHOW DETAILS OF WELDING TO STRUCTURAL STEEL AND SIDE LAP CONNECTION DETAILS. DETAILS RELATED TO SUPPORT OF THE DECK ON WALLS, BEAMS, ETC. SHALL BE INCLUDED.
- 4. METAL DECK SHALL BE PUDDLE WELDED TO THE STRUCTURAL STEEL SUPPORTS AT 12 INCHES ON CENTER (MAXIMUM). SIDE LAPS OR ADJOINING PANELS SHALL BE PUNCHED TOGETHER OR WELDED EVERY 24 INCHES ON CENTER (MAXIMUM).
- 5. ALL PUDDLE WELDS SHALL BE 3/4 INCH DIAMETER. ALL METAL DECK SHALL BE WELDED TO STRUCTURAL STEEL BY QUALIFIED WELDERS, USING PRE QUALIFIED PROCEDURES. THE ERECTOR SHALL ESTABLISH A WELDING PROCEDURE FOR PUDDLE WELDING PRIOR TO THE START OF ERECTION OF THE STEEL DECK. EACH WELDER SHALL BE QUALIFIED USING THIS PROCEDURE AS MONITORED BY THE QUALIFIED TESTING LABORATORY, IN OWNER'S DIRECT EMPLOY.
- 6. PROVIDE CONTINUOUS SHEET METAL CLOSURES AT ALL SLAB EDGES. PROVIDE SHEET METAL CLOSURES AT COLUMNS, CANT STRIPS, SUMP PANS, ROOF DRAINS, PIPE PENETRATIONS, ETC. CLOSURE THICKNESS SHALL BE 18 GAUGE (MINIMUM). THE APPROPRIATE GAGE SHALL BE DESIGNED BY A STRUCTURAL ENGINEER IN METAL DECK CONTRACTOR'S EMPLOY. THE GAGE SHALL BE SHOWN ON THE SHOP DRAWINGS SUBMITTED FOR ARCHITECT'S APPROVAL.
- 7. PROVIDE SUPPLEMENTAL FRAMING AT OPENINGS, MOMENT CONNECTIONS ETC. AS REQUIRED FOR SUPPORT OF THE METAL
- 8. METAL DECK SHALL BE CAPABLE OF SUPPORTING THE WET CONCRETE AND OTHER CONSTRUCTION LOADS WITHOUT SHORING.
- 9. ALL WELDS CONNECTING METAL DECK TO SUPPORTING STEEL SHALL BE VISUALLY INSPECTED BY A QUALIFIED TESTING

. THE FOLLOWING SPECIAL INSPECTION ITEMS RELATED TO STRUCTURAL WORK SHOWN ON GACE DRAWINGS ARE REQUIRED BY

B. COLD-FORMED STEEL DECK (1705.2.2) C. OPEN-WEB STEEL JOISTS (1705.2.3) D. CONCRETE CONSTRUCTION (1705.3)

G. FABRICATED ITEMS (1705.10 IN ACCORDANCE WITH 1704.2.5) THE CONTRACTOR IS OBLIGATED TO NOTIFY THE INSPECTOR AT LEAST 72 HOURS BEFORE INSTALLATION OF SUCH ITEMS SO THAT

PROPER INSPECTION CAN BE MADE. IN NO CASE SHALL SUCH ITEMS BE INSTALLED OR CONSTRUCTED WITHOUT COMPLETE APPROVAL OF THE INSPECTOR. UNAPPROVED INSTALLATION IS SUBJECT TO REMOVAL AND REPLACEMENT AT THE CONTRACTOR'S SOLE EXPENSE.

ALL SPECIAL INSPECTIONS SHALL BE PERFORMED BASED ON APPROVED SHOP DRAWINGS. INSPECTIONS PERFORMED BASED ON UNAPPROYED DRAWINGS SHALL BE CONSIDERED INVALID AND SHALL BE REJECTED.

BIDDER'S WARRANTY:

BY THE ACT OF SUBMITTING A BID FOR THE PROPOSED CONTRACT. THE BIDDER WARRANTS THAT:

12

- 1. THE BIDDER AND ALL SUBCONTRACTORS HE INTENDS TO USE HAVE CAREFULLY AND THOROUGHLY REVIEWED THE DRAWINGS SPECIFICATIONS AND OTHER CONSTRUCTION CONTRACT DOCUMENTS AND HAVE FOUND THEM COMPLETE AND FREE FROM AMBIGUITIES AND SUFFICIENT FOR THE CONTRACTOR TO BID. FABRICATE, AND INSTALL THE WORK ON TIME, FURTHER THAT,
- 2. THE BIDDER AND ALL WORKMEN, EMPLOYEES AND SUBCONTRACTORS HE INTENDS TO USE ARE SKILLED AND EXPERIENCED IN THE TYPE OF CONSTRUCTION REPRESENTED BY THE CONSTRUCTION CONTRACT DOCUMENTS BID UPON; FURTHER THAT,
- 3. NEITHER THE BIDDER NOR ANY OF HIS EMPLOYEES, AGENTS INTENDED SUPPLIERS OR SUBCONTRACTORS HAVE RELIED UPON ANY VERBAL REPRESENTATIONS, ALLEGEDLY AUTHORIZED OR UNAUTHORIZED FROM THE OWNER, HIS EMPLOYEES OR AGENTS INCLUDING ARCHITECTS, ENGINEERS OR CONSULTANTS, IN ASSEMBLING THE BID FIGURE; AND FURTHER THAT, THE BID FIGURE IS BASED SOLELY UPON THE CONSTRUCTION CONTRACT DOCUMENTS AND PROPERLY ISSUED WRITTEN ADDENDA AND NOT UPON ANY OTHER WRITTEN REPRESENTATION.
- 4. THE BIDDER ALSO MARRANTS THAT HE HAS CAREFULLY EXAMINED THE SITE OF THE WORK AND THAT FROM HIS OWN INVESTIGATIONS HE HAS SATISFIED HIMSELF AS TO THE NATURE AND LOCATION OF THE WORK AND THE CHARACTER, QUALITY, QUANTITIES OF MATERIALS AND DIFFICULTIES TO BE ENCOUNTERED, THE KIND AND EXTENT OF EQUIPMENT AND OTHER FACILITIES NEEDED FOR THE PERFORMANCE OF THE WORK, THE GENERAL AND LOCAL CONDITIONS, AND OTHER ITEMS WHICH MAY, IN ANY WAY, AFFECT THE WORK OR ITS PERFORMANCE.

SHORING NOTES

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE TO PROVIDE TEMPORARY SUPPORT AND ADEQUATE PROTECTION FOR THE STABILITY AND INTEGRITY OF THE STRUCTURE (OR PORTIONS THEREOF) DURING THE ENTIRE CONSTRUCTION PERIOD AND TO MAINTAIN IT AT LEVELS ACCEPTABLE WITHIN THE CONSTRUCTION INDUSTRY BY THE USE OF ALL MEANS AVAILABLE, INCLUDING BUT NOT LIMITED TO TEMPORARY BRACING AND SHORING (SHORING SYSTEM). IN NO CASE SHALL THE STRUCTURE BE ALLOWED TO BECOME UNSTABLE AND/OR UNSAFE, AS DEFINED BY LOCAL GOVERNMENTAL AGENCIES.
- 2. THE SHORING SYSTEM SHALL BE DESIGNED TO SUPPORT ALL APPLICABLE LOADS THAT MAY BE IMPOSED ON THE STRUCTURE DURING CONSTRUCTION IN ACCORDANCE WITH INDUSTRY STANDARDS AND GENERALLY ACCEPTED ENGINEERING PRINCIPLES.
- 3. THE SHORING SYSTEM, INCLUDING ALL DETAILS AND SEQUENCING, SHALL BE DESIGNED AND DETAILED BY A SPECIALTY STRUCTURAL ENGINEER (SSE) LICENSED AND REGISTERED IN THE STATE OF NEW YORK. THE SSE SHALL SIGN AND SEAL ITS DRAWINGS ILLUSTRATING THE SHORING SYSTEM AND SEQUENCING, WHICH MAY NEED TO BE FILED AND APPROVED BY ALL APPLICABLE GOVERNMENTAL AUTHORITIES.
- 4. REFERENCES TO SHORING IN THE STRUCTURAL DRAWINGS BY GACE ARE SOLELY FOR THE PURPOSE OF COORDINATION WITH GACE'S DESIGN. THE SHORING ENGINEER SHALL SUBMIT SHORING AND BRACING DRAWINGS TO THE ARCHITECT FOR REVIEW OF EFFECT ON THE PERMANENT STRUCTURAL ELEMENTS THAT ARE DESIGNED BY THIS OFFICE. GACE IS NOT RESPONSIBLE FOR THE DESIGN, DETAILING, REVIEW, INSPECTION, OR APPROVAL OF THE SHORING DESIGN OR PROPOSED SEQUENCING.
- 5. THE SHORING SYSTEM SHALL BE INSPECTED BY THE SSE WHO PREPARED THE DRAWINGS/SPECIFICATIONS AND SEQUENCING OR A THIRD-PARTY SPECIAL INSPECTOR. THE SSE OR SPECIAL INSPECTOR SHALL CERTIFY IN A WRITTEN STATEMENT THAT THE MORK WAS PERFORMED IN ACCORDANCE WITH THE SIGNED AND SEALED DRAWINGS/SPECIFICATIONS.

SUBMITTAL NOTES:

- 1. THE CONTRACTOR SHALL BE RESPONSIBLE FOR IDENTIFYING, PREPARING AND DELIVERING ALL SHOP DRAWINGS AND OTHER SUBMITTALS ("SUBMITTALS") REQUIRED BY THE CONTRACT DOCUMENTS IN A TIMELY MANNER. ALL MATERIAL SHALL BE DELIVERED GRADUALLY SO AS TO AVOID SUBMISSION OF LARGE NUMBER OF SUBMITTALS NOT ALLOWING THE ENGINEER TIMELY REVIEW.
- 2. THE STRUCTURAL ENGINEER OF RECORD ("EOR") SHALL REVIEW SUBMITTALS PERTINENT TO STRUCTURAL DESIGN (SHOP DRAWINGS AND OTHER PERTINENT DOCUMENTS SUCH AS MATERIAL, PRODUCT, ASSEMBLY INFORMATION, ETC.) SUBMITTED BY THE CONTRACTOR. THE ENGINEER SHALL COMMENT ON THE SUBMITTALS AND APPROVE OR DISAPPROVE WITH COMMENTS, AS APPROPRIATE, FOR GENERAL CONFORMANCE WITH THE INFORMATION GIVEN AND THE DESIGN CONCEPT EXPRESSED IN THE CONTRACT DOCUMENTS. REVIEW OF SUCH SUBMITTALS SHALL NOT BE FOR THE PURPOSE OF DETERMINING THE ACCURACY AND COMPLETENESS OF OTHER INFORMATION SUCH AS DIMENSIONS, QUANTITIES, INSTALLATION OR PERFORMANCE OF EQUIPMENT OR SYSTEMS. ETC. WHICH SHALL BE THE CONTRACTOR'S RESPONSIBILITY. ENGINEER'S REVIEW SHALL NOT IN ANY WAY RELIEVE THE CONTRACTOR OF HIS/HER RESPONSIBILITY TO ACCURATELY AND COMPLETELY INTERPRET THE CONTRACT DOCUMENTS.
- 3. IF REQUIRED BY SPECIFICATIONS, SHOP DRAWINGS AND OTHER DOCUMENTS SHALL BEAR THE SEAL AND SIGNATURE OF A PROFESSIONAL ENGINEER LICENSED IN THE STATE WHERE THE PROJECT IS TO BE CONSTRUCTED.
- 4. BEFORE SUBMITTING A SHOP DRAWING OR ANY OTHER DOCUMENT TO THE ENGINEER. THE CONTRACTOR SHALL REVIEW AND APPROVE EACH SUCH SUBMITTAL FOR CONFORMANCE WITH THE CONTRACT DOCUMENTS. EVERY COPY OF EACH SUBMITTAL SHALL BEAR THE CONTRACTOR'S REVIEW STAMP SHOWING THAT THEY HAVE BEEN REVIEWED AND APPROVED. THE ENGINEER SHALL RETURN WITHOUT REVIEW MATERIAL WHICH HAS NOT BEEN APPROVED BY THE CONTRACTOR.
- 5. THE CONTRACTOR SHALL BE SOLELY RESPONSIBLE FOR THE MEANS, METHODS, TECHNIQUES, SEQUENCES AND OPERATIONS OF CONSTRUCTION, SAFETY PRECAUTIONS AND PROGRAMS INCIDENTAL THERETO, INCLUDING REFLECTION OF EXISTING FIELD CONDITIONS. APPROVAL OF ANY SUBMITTAL BY THE ENGINEER SHALL NOT BE CONSTRUED AS ACCEPTANCE OF ANY OF THE FOREMENTIONED ASPECTS OF CONTRACTOR'S WORK.
- 6. THE ENGINEER SHALL ASSUME THAT NO SUBMITTED SHOP DRAWING OR OTHER DOCUMENT COMPRISES A VARIATION FROM THE CONTRACT UNLESS THE CONTRACTOR ADVISES THE ENGINEER OTHERWISE IN WRITING. THE CONTRACTOR SHALL NOT PROCEED WITH ANY WORK RELATED TO SUCH VARIATION BEFORE RECEIPT OF ENGINEER'S WRITTEN ACCEPTANCE.
- 7. IN CASE RESUBMISSION OF SHOP DRAWINGS, CALCULATIONS AND OTHER WRITTEN SUBMITTALS INCLUDING ADDITIONS, DELETIONS OR CORRECTIONS THE CONTRACTOR SHALL CIRCLE OR OTHERWISE IDENTIFY ALL CHANGES FROM THE PRIOR ISSUE. ALL MATERIAL SUBMITTED WITHOUT EACH CHANGE CLEARLY IDENTIFIED SHALL BE RETURNED WITHOUT REVIEW FOR RESUBMISSION.
- 8. THE RETURNED SHOP DRAWINGS AND OTHER SUBMITTALS SHALL BE STAMPED BY THE ENGINEER. THE STAMP SHALL DENOTE REVIEW STATUS WHICH MAY OR MAY NOT REQUIRE FURTHER RESUBMISSION AS PER THE FOLLOWING:

ATUS:	RESUBMISSION:
NO EXCEPTION TAKEN	NOT REQUIRED
EXCEPTIONS NOTED	NOT REQUIRED
EXCEPTIONS NOTED, REVISE & RESUBMIT	REQUIRED
REJECTED	REQUIRED

- 9. CORRECTIONS OR COMMENTS MADE ON THE SHOP DRAWINGS AND OTHER REVIEWED DOCUMENTS SHALL NOT RELIEVE THE CONTRACTOR FROM STRICT COMPLIANCE WITH THE REQUIREMENTS OF THE PLANS AND SPECIFICATIONS OR FROM HIS RESPONSIBILITY FOR ERRORS AND OMMISSIONS ON SUCH DRAWINGS AND/OR OTHER DOCUMENTS. DRAWINGS AND DOCUMENTS RETURNED WITH 'NO EXCEPTION TAKEN' OF A PARTICULAR ITEM SHALL NOT BE INTERPRETED AS 'NO EXCEPTION TAKEN' OF AN ASSEMBLY OF WHICH THE ITEM IS A COMPONENT.
- 10. THE CONTRACTOR SHALL PERFORM NO PORTION OF THE WORK REQUIRING SUBMISSION AND REVIEW OF SHOP DRAWINGS OR OTHER MATERIAL UNTIL THE RESPECTIVE SUBMITTAL HAS BEEN APPROVED BY THE ENGINEER. SUCH WORK SHALL BE PERFORMED IN ACCORDANCE ONLY WITH THE SUBMITTALS MARKED "NO EXCEPTION TAKEN" OR "EXCEPTIONS NOTED". THE CONTRACTOR SHALL BE RESPONSIBLE FOR AND BEAR ALL THE COSTS WHICH MAY RESULT FROM ORDERING OF ANY MATERIAL OR FROM PROCEEDING WITH ANY PART OF THE WORK PRIOR TO THE RECEIPT OF APPROVED RESPECTIVE SUBMITTALS.

ARCHITECT

KSQ Architects PC dba KSQ Design 215 W 40th St - 15th flr New York, NY 10018 646.435.0660 office www.ksq.design

Owner **ROCKLAND BOCES** 65 Parrott Rd West Nyack, NY, 10994 845-627-4700 office www.rocklandboces.org

Civil & MEP Engineer FELLENZER ENGINEERING LLP 22 Mulberry Street. Suite 2A Middletown, NY 10940 845-343-1481 office www.fellp.com

Structural Engineer GACE CONSULTING ENGINEERS 148 Madison Avenue, Fourth Floor

> New York, NY 10016 212-545-7878 office

www.gace.net Food Service Consultant: ELITE | STUDIO E 1856 New Hwy #1 Famingdale, NY, 11735

631-429-9400 office www.elitestudioe.com **Construction Manager**

Poughkeepsie, NY 12601

www.arriscontracting.com

189 Smith Street

845-473-3600 office

ARRIS CONTRACTING COMPANY, inc.

It is a violation of Title VIII, Article 147 of NYS Education Law for any person, unless acting under the direction of a licensed architect, to alter any item on this document in any way. Any licensee who alters this document is required by law to affix his or her seal and the notation "altered by" followed by his or her signature and a specific description of the alterations made.



ROCKLAND BOCES P-TECH C-TEC BUILDING

SED #: 50-90-00-00-0-044-001

65 Parrot Rd. West Nyack, NY 10994

	KEY P	LAN		
	REVIS	IONS		
	No.		Description	Date

ISSUED: BID SET ISSUANCE **DATE:** 06/30/2025

SCALE: 12" = 1'-0" SHEET NAME: **GENERAL NOTES 2**

SHEET NUMBER

ABBREVIATIONS KSI = KIP(S) PER SQUARE INCH = AT ADJ. = ADJACENT = LIVE LOAD ADD'L. = LONG LEG HORIZONTAL = ALTERNATE = LONG LEG YERTICAL ARCH. = COMPRESSION DEVELOPMENT В, ВОТ. = BOTTOM LENGTH = BRACED FRAME = HOOKED BAR TENSION B.P. DEVELOPMENT LENGTH = BASE PLATE, = TENSION DEVELOPMENT BEARING PLATE B.H. = BULKHEAD LENGTH BLDG. = COMPRESSION SPLICE LENGTH BM. = LONG SLOTTED BRDG. = TENSION SPLICE LENGTH = POUND(S) BSMT. = LONG = LIGHT = MOMENT CONNECTION = METAL DECK = CONSTRUCTION JOINT = MAXIMUM CONTROL JOINT = MECHANICAL = MEZZANINE CANT MFR. = MANUFACTURER COL. = COLUMN = MINIMUM CONC. = MISCELLANEOUS = CONCRETE CONN. = MOMENT = NOT IN CONTRACT CONT. N.F. = NEAR FACE Φ, DIA. = NON-SHRINK = DIAMETER = NOT TO SCALE = DEAD LOAD DET. = DETAIL = NUMBER DIAG. = NORTH - SOUTH = DIAGONAL DIM. = ON CENTER DMG(S). = OUTSIDE FACE DML(S). = OPENING E.E. = EACH END = PRECAST, PILE CAP = EACH FACE P_{L} , PL. = PLATE= POUND(S) PER FOOT = POUND(S) PER SQUARE FOOT E.S. = POUND(S) PER SQUARE INCH = EACH SIDE E.M. = RADIUS = EACH MAY = REFERENCE EA. = EACH = REINFORCEMENT = ELEVATION REQ'D = REQUIRED REV. = REVISION, REVISED = SQUARE FOOT S.L.H. = SHORT LEG HORIZONTAL EMBED. EQ. S.L.V. = SHORT LEG YERTICAL = EQUAL EXIST. = EXISTING S.O.G. = SLAB ON GRADE EXP. = EXPANSION = SECTION EXT. = EXTERIOR = SLAB, SLOPE E-M = SPLICE LENGTH IN MASONRY = EAST - WEST = FAR FACE SPEC(S). = SPECIFICATION(S) = FOUNDATION = SQUARE FIN. = SHORT SLOTTED FL./ FLR. = FLOOR = STANDARD = F00T STL. = STEEL STRUCT = STRUCTURAL = FOOTING = F00T - KIF = TOP T.O.S. = TOP OF SLAB = GAUGE GALV. TEMP. = TEMPORARY = GALVANIZED = THICKNESS, THICK GEN. = GENERAL HORIZ. = HORIZONTAL = TYPICAL = UNLESS OTHERWISE NOTED VERT. = VERTICAL = INCH = INTERIOR W.P. = WATERPROOFING, WORK = JOINT W.W.F. = WELDED WIRE FABRIC = 1000 LBS K, KIP = WIDE FLANGE KSF = KIP(S) PER SQUARE FOOT MD. = MOOD MT. = MEIGHT

17

BUILDING DESIGN INFORMATION SUMMARY 2020 BUILDING CODE OF NEW YORK STATE

12

NO.	TOPIC	CODE SECTION
1.	SNOW LOADING	GROUND SNOW LOAD, Pg = 30 psf
	CRITERIA	FLAT-ROOF SNOW LOAD, P; = 22 psf
		SNOW EXPOSURE FACTOR, C = 0.9
		SNOW IMPORTANCE FACTOR, I ,= 1.1
		THERMAL EXPOSURE FACTOR, C = 1.0
2.	SEISMIC LOADING	RISK CATEGORY = III
	CRITERIA	SEISMIC IMPORTANCE FACTOR, le = 1.25
		5s = 0.297
		SITE CLASS = C
		SHORT PERIOD DESIGN SPECTRAL RESPONSE, SDS = 0.257 g
		ONE SECOND DESIGN SPECTRAL RESPONSE, SDI = 0.062 g
		SEISMIC DESIGN CATEGORY = B
		BASIC SEISMIC FORCE RESISTING SYSTEM = NOT SPECIFICALLY DETAILED FOR SEISMIC RESISTANCE
		DESIGN SEISMIC BASE SHEAR, V = 333 kips
		SEISMIC RESPONSE COEFFICIENT, Cs = 0.0657
		RESPONSE MODIFICATION FACTOR, R = 3
		ANALYSIS METHOD USED = EQUIVALENT LATERAL FORCE PROCECURE
3.	MIND LOADING	ULTIMATE DESIGN WIND SPEED (3 SECOND GUST), Vult = 123 mph
	CRITERIA	NOMINAL DESIGN WIND SPEED, Vasd = 95 mph
		RISK CATEGORY = III
		WIND EXPOSURE CATEGORY = B
		DESIGN WIND BASE SHEAR - E-W, V = 58 kips N-S, V = 150 kips
		INTERNAL PRESSURE COEFFICIENT GCpi = +/- 0.18
		COMPONENTS & CLADDING DESIGN WIND PRESSURE (PER Vasd): ZONE 4 = + 18 psf / -20 psf ZONE 5 = + 18 psf / -24 psf
4.	HYDROSTATIC &	DESIGN GROUND WATER ELEVATION = N/A

NOTES:

. DESIGN LOADS COMPLY WITH BC1604.

2. REFER TO ARCHITECTURAL DRAWINGS FOR EXTERIOR WALL. DESIGN OF NON-LOAD BEARING EXTERIOR WALLS AND ANCHORAGES TO COMPLY WITH LOADS SHOWN ABOVE, AND WITH BC705 AND BC CHAPTER 14.

100 YEAR DESIGN FLOOD ELEVATION = N/A

MASONRY DEVELOPMENT

AND SPLICE LENGTH

f'm = 2,500 PSI

DEVELOPMENT TENSION SPLICE

LENGTH (Em) LENGTH (Sm) IN

EPOXY-COATED BAR LENGTHS SHALL BE INCREASED BY 50 PERCENT.

AS REQUIRED, AT LEAST 125% OF THE SPECIFIED YIELD STRENGTH OF THE BAR

10

12

12

34

47

MECHANICAL SPLICES SHALL HAVE THE BARS CONNECTED TO DEVELOP IN TENSION OR COMPRESSION,

WIRE SIZE DIAMETER

M2.1

M2.8

#5

0.148

0.162

0.189

0.375

0.5

0.625

0.75

0.875

STEEL YIELD STRENGTH Fy = 60,000 PSI

LAP SPLICE LENGTHS FOR CONCRETE 'Ls' (in.)

	4000 psi		5000 psi				
SIZE	fy (ksi)	TENS	BION	COMP.	TENSION		COMP.
		TYP.	TOP	COMIT.	TYP.	TOP	COMP.
#3	60	18	24	12	17	22	12
#4	60	25	32	15	22	29	15
#5	60	31	40	19	28	36	19
#6	60	37	49	23	34	44	23
#7	60	54	70	27	49	63	27
#8	90	62	80	30	56	72	30
# 9	60	70	91	34	63	81	34
#10	60	79	102	39	71	92	39
#11	60	87	114	43	78	102	43

HOOKED BAR TENSION DEVELOPMENT LENGTHS FOR CONCRETE 'Ldh' (in.)

SIZE	fy (ksi)	4000 psi	5000 psi
#3	60	8	7
#4	60	10	9
#5	60	12	11
#6	60	15	13
#7	60	17	15
#8	60	19	17
#9	60	22	20
#10	60	25	22
#11	60	27	24

NOTES:

- 1. THESE DEVELOPMENT AND SPLICE LENGTHS ARE COMPUTED FOR UNCOATED BARS IN ELEMENTS OF NORMAL WEIGHT CONCRETE WITH A MINIMUM CLEAR COVER OF 1 BAR DIAMETER AND A MINIMUM CLEAR SPACING OF 1 BAR DIAMETER IN BEAMS AND COLUMNS, AND 2X THE BAR DIAMETER IN OTHER
- 2. THESE DEVELOPMENT AND SPLICE LENGTHS SHALL BE MULTIPLIED BY ALL OF THE APPLICABLE FACTORS THAT FOLLOW:

EPOXY-COATED REINFORCING (FOR TYP. REINF.)	x1.50
EPOXY-COATED REINFORCING (FOR TOP REINF.)	
REINFORCING PLACED IN LIGHTWEIGHT CONCRETE	
#7 BARS AND LARGER WITH CLEAR COVER	
LESS THAN 1 BAR DIAMETER	x1.50

3. 'Ld' CAN BE USED AS ACI CLASS A SPLICE. 'LS' CAN BE USED AS ACI CLASS B SPLICE.

LENGTH OF SMALLER BAR.

- 4. USE TOP CONDITION FOR ANY HORIZONTAL BARS WITH MORE THAN 12 INCHES OF FRESH CONCRETE BELOW.
- 5. WHEN BARS OF DIFFERENT SIZE ARE SPLICED, SPLICE LENGTH SHALL BE THE LARGER OF THE DEVELOPMENT LENGTH OF LARGER BAR AND LAP SPLICE

5000 psi 4000 psi **TENSION TENSION** TYP. TOP TYP. TOP 15 8 | 13 | 17 19 25 10 | 17 | 23 12 22 29 24 29 38 15 | 26 | 34 42 54 43 70 48

79 | 24

#11 60 67 87 27 60 78


60

54


STRAIGHT BAR

DEVELOPMENT LENGTHS

FOR CONCRETE 'Ld' (in.




TYPICAL TIE HOOK (HAIR PIN)



4 BAR DIA. #8 OR SMALLER

TYPICAL STANDARD HOOK

NOTE: FOR DEVELOPMENT LENGTH Ldh SEE SCHEDULE



SNOW DRIFT LOADING PLAN AT 2ND FLOOR

NOTES:


SNOW LOADS ON THE REMAINDER OF THE ROOF.



3/64" = 1'-0"

1. ALL VALUES SHOWN IN POUNDS PER SQUARE FOOT (PSF).

2. SNOW DRIFT LOADS ARE SHOWN WITH 22 PSF UNIFORM



1. LIVE LOADS HAVE BEEN REDUCED FOR THE INDICATED OCCUPANCIES IN ACCORDANCE WITH SECTION

2. *DENOTES ROOF LIVE LOAD, EQUAL TO FLAT ROOF SNOW LOAD. SEE SNOW DRIFT LOADING PLAN ON

3. **DENOTES ROOF UNIFORM LOADS. SEE PLAN FOR EQUIPMENT LOADS IN ADDITION TO UNIFORM

1607.11 OF THE BUILDING CODE.

THIS SHEET FOR SNOW DRIFT LOADING INFO. AT LOCALIZED AREAS.

1. ALL VALUES SHOWN IN POUNDS PER SQUARE FOOT (PSF).

2. SNOW DRIFT LOADS ARE SHOWN WITH 22 PSF UNIFORM SNOW LOADS ON THE REMAINDER OF THE ROOF.

SHEET NUMBER: S-003

ISSUED: BID SET ISSUANCE

DATE: 06/30/2025

SCALE: As indicated

DESIGN CRITERIA

SHEET NAME:

ARCHITECT

KSQ Architects PC dba KSQ Design

215 W 40th St - 15th flr

New York, NY 10018

646.435.0660 office

ROCKLAND BOCES

845-627-4700 office

West Nyack, NY, 10994

www.rocklandboces.org

Civil & MEP Engineer

Middletown, NY 10940

845-343-1481 office

Structural Engineer

New York, NY 10016

Food Service Consultant:

212-545-7878 office

ELITE | STUDIO E

1856 New Hwy #1

631-429-9400 office www.elitestudioe.com

Famingdale, NY, 11735

Construction Manager:

Poughkeepsie, NY 12601

www.arriscontracting.com

189 Smith Street

845-473-3600 office

ARRIS CONTRACTING COMPANY, inc.

It is a violation of Title VIII, Article 147 of NYS

Education Law for any person, unless acting

under the direction of a licensed architect, to

alter any item on this document in any way

Any licensee who alters this document is required by law to affix his or her seal and the

notation "altered by" followed by his or her

signature and a specific description of the

ROCKLAND BOCES

ROCKLAND BOCES

P-TECH C-TEC

BUILDING

SED #: 50-90-00-00-0-044-001

West Nyack, NY 10994

65 Parrot Rd,

REVISIONS

alterations made.

www.gace.net

www.fellp.com

FELLENZER ENGINEERING LLP 22 Mulberry Street. Suite 2A


GACE CONSULTING ENGINEERS 148 Madison Avenue, Fourth Floor


65 Parrott Rd,

www.ksq.design


Owner


7/3/2025 11:58:24 AM






7/3/2025 11:58:44 AM







12

, REMOVE BACKING BARS,

- SHOP WELDED COVER PL.

- PLATES & BOLTS TO DEVELOP

BENDING MOMENT IN BEAM


MIN. THICKNESS = 5/16"

SHEAR PLATE


BACKGOUGE AND REINFORCE W/

FILLET OR USE DOUBLE BEYEL


TYPICAL BEAM TO COLUMN MEB SHEAR CONNECTION



TYPICAL BEAM TO GIRDER CONNECTION




TYPICAL END CONNECTION TO SPANDREL BEAMS OR STAIR HANGERS



SUPPORT BEAM SAME DEPTH SUPPORT BEAM DEEPER

> TYPICAL CANTILEVER BEAM CONNECTION

NOTE: SEE TYPICAL BEAM TO GIRDER CONNECTION FOR BALANCE OF INFORMATION.




TYPICAL BEAM TO COLUMN WEB MOMENT CONNECTION 3/4" = 1'-0" NOTES:

1. DESIGN SHEAR CONNECTION FOR ECCENTRICITY "e".

COLUMN WEB PARALLEL


TO GIRDER

2. IF THERE IS ALSO A MOMENT CONNECTION TO FLANGE OF COLUMN, WELDS OF MOMENT CONNECTING PLATE TO COLUMN ARE TO BE PROPORTIONED TO TAKE FORCES FROM BOTH DIRECTIONS SIMULTANEOUSLY.




TYPICAL STEEL COLUMN SPLICE NOTE: BEARING DIMENSION 'G' SHALL BE EQUAL OR GREATER THAN 'F'

ROOF EQPT., —




COLUMN MEB PARALLEL COLUMN WEB PERPENDICULAR TO GIRDER TO GIRDER TYPICAL COLUMN TRANSFER 3/4" = 1'-0" NOTE: DESIGN CONNECTION FOR ECCENTRICITY "e"




COLUMN WEB PERPENDICULAR TO GIRDER

BEAM ON TOP OF COLUMN 3/4" = 1'-0"



TYPICAL STEEL BEAM SUPPORTING SHAFT WALL WITH NO METAL DECK 1" = 1'-0"



TYPICAL EQUIPMENT DUNNAGE 3/4" = 1'-0"

NOTE: ALL EXPOSED STEEL FRAMING SHALL BE HOT-DIP GALVANIZED.

REVISIONS

ARCHITECT

KSQ Architects PC dba KSQ Design 215 W 40th St - 15th flr

New York, NY 10018 646.435.0660 office www.ksq.design

ROCKLAND BOCES

845-627-4700 office

West Nyack, NY, 10994

www.rocklandboces.org

Civil & MEP Engineer

Middletown, NY 10940 845-343-1481 office www.fellp.com

Structural Engineer

New York, NY 10016

Food Service Consultant:

212-545-7878 office

ELITE | STUDIO E

1856 New Hwy #1

631-429-9400 office www.elitestudioe.com

Famingdale, NY, 11735

Construction Manager:

189 Smith Street Poughkeepsie, NY 12601

845-473-3600 office

www.arriscontracting.com

ARRIS CONTRACTING COMPANY, inc.

It is a violation of Title VIII, Article 147 of NYS Education Law for any person, unless acting

under the direction of a licensed architect, to alter any item on this document in any way

Any licensee who alters this document is required by law to affix his or her seal and the notation "altered by" followed by his or her

signature and a specific description of the

ROCKLAND BOCES

ROCKLAND BOCES

alterations made.

www.gace.net

FELLENZER ENGINEERING LLP

GACE CONSULTING ENGINEERS 148 Madison Avenue, Fourth Floor

22 Mulberry Street. Suite 2A

65 Parrott Rd,

Owner

DATE: 06/30/2025


S-007


PROJECT NUMBER: C4040.00 COPYRIGHT © 2024 KSQ ARCHITECTS, PC

P-TECH C-TEC **BUILDING** SED #: 50-90-00-00-0-044-001 65 Parrot Rd, West Nyack, NY 10994 **ISSUED**: BID SET ISSUANCE **SCALE:** As indicated SHEET NAME: TYPICAL DETAILS 4 SHEET NUMBER:

7/3/2025 11:59:02 AM


FLANGES





AT PRECAST LINTEL

- 2. SEE SHELF ANGLE DETAIL FOR CONNECTION OF INTERIOR DECK TO CMU WALL.



TYPICAL NON-LOAD-BEARING CMU WALL ON SLAB ON GRADE 3/4" = 1'-0"

WALL REINF. TO RUN ----

THROUGH UNINTERRUPTED.

SPLICE AS REQ'D.

CUT BLOCK AROUND SLAB/

CONC. TOPPING

WHERE APPLICABLE,

METAL DECK!

CONT. BOND

HORIZ. REINF.

BEAM WITH 2#5

3B: DECK BUILT

INTEGRALLY WITH WALL

WALL DOWELS TO MATCH

WALL REINF. ABOVE.

CONT. 3/8" X 4" PLATE

WITH 3/4" DIAM. STUDS

4" LONG @ 24" O.C.

DECK AS REQUIRED FOR

INSTALLATION

EXIST. CMU WALL

BUILT PRIOR TO

TEMPORARILY

DECK IS FULLY

L5x5x3/8

3/4" = 1'-0"

3A : WALL BUILT FIRST

AND DECK SUPPORTED ON ANGLE

2. WELD DECK TO ANGLE/PLATE PER TYPICAL METAL DECK NOTES ON 5-002.

SEE ARCH. DWGS.

STRUCTURAL CMU

(SEE PLANS FOR SIZE)

= 560 PSI), SEE ARCH.

SUPPORT OF METAL DECK ON CMU BEARING WALL

1. METAL DECK SHALL BEAR ON ANGLE/PLATE 3" MINIMUM (END-BEARING AND SIDE LAP CONDITIONS).

3. DETAIL 3A IS TYPICAL BASIS OF DESIGN, AS SHOWN ON PLAN. SEE PLAN FOR DETAIL 3B LOCATIONS.

STD. HORIZ. JOINT REINF. IN EVERY

ARMATHERM 500-150 THERMAL BREAK

- #4 @ 4'-0" O.C. CONT. IN GROUTED CELLS

U.O.N. ON PLAN AND WALL SCHED.

NON-STRUCTURAL ROOF

ROOF DECK, SEE DETAIL

3 ON THIS SHEET FOR

CONNECTION TO WALL

FINISHES (SEE ARCH. DWGS.)

BLOCK (MIN. COMPRESSIVE STRENGTH

BED JT. @ PARAPET WALL

DECK INSTALLATION

BRACE WALL UNTIL

NOTE: REFER TO ARCHITECTURAL DRAWINGS FOR NON-LOAD BEARING WALL LOCATIONS.

ARCHITECT

KSQ Architects PC dba KSQ Design 215 W 40th St - 15th flr New York, NY 10018 646.435.0660 office

> www.ksq.design Owner **ROCKLAND BOCES**

65 Parrott Rd. West Nyack, NY, 10994 845-627-4700 office www.rocklandboces.org Civil & MEP Engineer

- WHERE NO CONC. ON DECK

GROUT ABOVE AND BELOW

FLUTES MITHIN MALL MIDTH

FELLENZER ENGINEERING LLP 22 Mulberry Street. Suite 2A Middletown, NY 10940 845-343-1481 office www.fellp.com

Structural Engineer GACE CONSULTING ENGINEERS 148 Madison Avenue, Fourth Floor New York, NY 10016

212-545-7878 office www.gace.net Food Service Consultant:

ELITE | STUDIO E 1856 New Hwy #1 Famingdale, NY, 11735 631-429-9400 office www.elitestudioe.com

Construction Manager: ARRIS CONTRACTING COMPANY, inc. 189 Smith Street Poughkeepsie, NY 12601

www.arriscontracting.com

845-473-3600 office

STRUCT. C.M.U. WALL

SEE PLANS FOR SIZE

MECH. COUPLER

- STEEL BEAM

(SEE PLAN)

TYPICAL MASONRY WALL

CONNECTION TO STEEL BEAM


It is a violation of Title VIII, Article 147 of NYS Education Law for any person, unless acting under the direction of a licensed architect, to alter any item on this document in any way Any licensee who alters this document is required by law to affix his or her seal and the notation "altered by" followed by his or her signature and a specific description of the alterations made.



ROCKLAND BOCES P-TECH C-TEC **BUILDING**

SED #: 50-90-00-00-0-044-001

65 Parrot Rd, West Nyack, NY 10994



ISSUED: BID SET ISSUANCE **DATE:** 06/30/2025 **SCALE:** As indicated SHEET NAME:

TYPICAL DETAILS 5 SHEET NUMBER:

S-008

PROJECT NUMBER: C4040.00 COPYRIGHT © 2024 KSQ ARCHITECTS, PC

7/3/2025 11:59:11 AM

12

TO CMU WALL CONNECTION 1/2" = 1'-0"

17

W/MFR REQ'S MALL REINF. TO RUN -- STL. OPEN-WEB THROUGH UNINTERRUPTED SPLICE AS REQ'D. SHIFT TO AVOID JOIST SEAT SEAT CONN., COORD. W/ MFR

REQ'S. MIN. 6" BEARING U.O.N. TYPICAL OPEN WEB BAR JOIST

14

THREADED COUPLER TO MATCH WALL JAMB REINF.

TYPICAL CMU WALL JAMB REINFORCEMENT PLACEMENT AT BEAM BEARING LOCATIONS

MALL ELEVATIONS

11


ON 5-401 AND 5-402


1/2" = 1'-0" NOTE: DETAIL APPLIES AT BEAMS PERPENDICULAR AND/OR PARALLEL TO WALL.

TYPICAL RELIEVING ANGLE

1 1/2" = 1'-0"

1. ANCHORS SHALL BE PLACED A MINIMUM OF 6" FROM EACH END OF PRECAST LINTEL. AND SHALL NOT BE PLACED MORE THAN 4" FROM EACH END OF RELIEVING ANGLE.







It is a violation of Title VIII, Article 147 of NYS Education Law for any person, unless acting under the direction of a licensed architect, to alter any item on this document in any way required by law to affix his or her seal and the notation "altered by" followed by his or her




ROCKLAND BOCES




7/3/2025 11:59:39 AM









CONCRETE GRADE BEAM SCHEDULE							
BEAM NO.	REINFORCEMENT SIZE CL SUPPORTS		STIRRUPS		REMARKS/ NOTES		
	WIDTH X DEPTH)		TYPE	SPACING FROM EACH END			
GB-01	30x24	4#7	2 LEGS	#3 @ 10" O.C.	2#7 SKIN REINF. EA SIDE		
GB-02	30x24	4#7	2 LEGS	#3 @ 7" <i>O.C.</i>	2#7 SKIN REINF. EA SIDE		
GB-03	18×18	3#6 3#6	2 LEGS	#3 @ 10" O.C.	1#6 SKIN REINF. EA SIDE		

A/4

A/5

A/6

A/7

17

FLOOR

FLOOR

LOOSE LINTEL SCHEDULE FOR MASONRY WALLS					
WALL THICKNESS UNDER 4'-0" OPNG. 4'-0" TO 8'-0" OPNG.					
4"	L1 (1L 4x3 1/2x5/16")	L2 (1L 4x3 1/2x3/8")			
6"	L3 (* 1L 5x3 1/2x5/16")	L4 (1L 5x5x3/8")			
8"	L6 (2Ls 4x3x5/16")	L7 (2Ls 4x3x3/8")			
10"	2L5 4x4x3/8"	2Ls 4x4x5/8"			
12"	2Ls 5x5x3/8"	2Ls 5x5x5/8"			
NOTEG					

<u>NOTES:</u>

1. * PLACE LONG LEG HORIZONTAL.

B/2

- 2. ADD ANGLES AS REQUIRED FOR MASONRY BACK-UP WALL.
- 3. LOOSE LINTEL SCHEDULE TO BE USED ONLY WHERE NOT OTHER INDICATED.

C/2

C/3

4. FOR MASONRY OPENING GREATER THAN 6' FIRE PROOF LINTEL OR PROVIDE INTERMEDIATE SUPPORTS.

BOND BEAM SCHEDULE						
ONRY	REINFORCING	STANDARD	a h			

ASONRY PENING	REINFORCING AS	MASONRY BLOCK (bxh) As	
P TO 4'	1#4	8x8, d = 4 3/4"	
P TO 6'	1#5	8x8, d = 4 3/4"	
P TO 8'	1#5	8x16, d = 12 3/8"	
	-		

NOTES:

STRENGTH.

C/4

I. MINIMUM BEARING LENGTH SHALL BE 8".

- 2. THIS SCHEDULE IS VALID FOR 8" MASONRY WALL. FOR 12" WALL, USE 12" WIDE BLOCK AND DOUBLE THE REINFORCING.
- 3. BOND BEAMS ARE NOT DESIGNED TO TAKE ANY FLOOR LOAD. 4. BOND BEAM SHALL BE SHORED BEFORE IT REACHES FULL

COLUMN

FLOOR

5. BLOCK DIMENSIONS ABOVE ARE NOMINAL.


C/5


PRECAST CONCRETE LINTEL SCHEDULE AT BEARING WALLS

TYPE	DESCRIPTION	SIZE (IN.) BXD	TOP REINF.	BOTTOM REINF.	STIRRUP
LC-1	MAX. CLEAR SPAN 6'-6" (10" WALL)	10x12	2#6	2#6	#3@4 1/2
LC-2	MAX. CLEAR SPAN 6'-8" (12" WALL)	12x12	2#6	2#6	#3@4 1/2
LC-3	MAX. CLEAR SPAN 8'-4"	12x16	3#6	3#6	#3@6"

NOTES:

- 1. PRECAST LINTEL CONCRETE SHALL BE 6,000 psi MIN.
- 2. PROVIDE 180 DEGREE HOOK AT EACH END OF #6 BARS AND SMALLER.
- 3. PROVIDE MINIMUM 8" BEARING AT EACH END OF LINTEL.





ROOF																			ROOF
2ND	5'-O" VARIES	31 NO X	17 12 64 22 64 22	17 12 65 22 K	17 12 63 22 63 22	18 12 64 22 64 22	18 12 67 21 8 7 8 7 8 7	18 12 8 4 67 22 8 7	23 12 84 71 22 V	10 4 54 32 9	35 N 16 N 10 N	6 4 14 0 14 10	28 01 M	12 9 4556464318	36 OF M	21 15 64 30 64 30	90 N 84 N 96 N 16	21 15 64 29	2ND
1ST	<u>~</u>													Kan Kan					15T
PIER (P) OR BUTTRESS (B)	,	(B) 16"x16" 4#6	(B) 16"X16" 4#6	(B) 1-2-1-6-1-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4-4	(B) 16"x16" 4#6	(B) 1-01×1-01 4+4	(B) "01×"01 4#4	(B) "01X"01 0#4	(B) "\delta'\delta' \delta'\delta' \delta'\delta'	(B) "21×"°1 0#4	(B) 16"×16" 4#4	(B) -6"×"6" +##	(B) "\delta'\delta'\delta' 4#4	(B) 16"×16" 4#4		(a) (b) (a) (b) (c) (d) (d) (e) (e) (e) (e) (f) (f) (f) (f) (f) (f) (f) (f) (f) (f			PIER (P) OR BUTTRESS (B)
BASEPLATE (T x M x H)		3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	1/2"×12"×12"	3/4"x12"x12"	1/2"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	BASEPLATE (T x M x H)
FLOOR	FLOOR HEIGHT	A/2	A/3	A/4	A/5	A/6	A/7	A/9	A/10	A/11	A1.7/11	B/1	B/2	C/1	C/2	C/3	C/4	C/5	FLOOR
	COLUMN SCHEDULE (20F3)																		
COLUMN	FLOOR	C/6	C/8	C/9	C/10	C/11	D/2	D/3	D/4	D/5	D/6	D/8	D/9	D/10	D/11	E/1	F/1.7	F/2	F/3.3

COLUMN SCHEDULE (10F3)


A/11

A/10

12

11

COLUMN SCHEDULE (20F3)																						
COLUMN	FLOOR HEIGHT	C/6	C/8	C/9	C/10	C/11	D/2	D/3	D/4	D/5	D/6	D/8	D/9	D/10	D/11	E/1	F/1.7	F/2	F/3.3	F/4	F/5.2	COLUMN FLOOR
ROOF																						ROOF
2ND	VARIES	18 8 8	25 16 8 7 8 7	12 P + XC	16 83 16	12 21	4 4 13	21 15 64 XC	16 b + XC	22 15 8 8 7 8	18 X 27	25 15 8 8 7 8 7 8	12 84 12	24 16 87 87 87 87 87 87 87 87 87 87 87 87 87	20 15 84 XC	6 4 8 XC	×64	9 8 8	17 12 7/1×9×	24 × C	17 12 7/1×9×	2ND
15T	-0 -0	79 22 35	69 N 30	54 Q 25 X	76 30	52 21 N	70 SIN	64 30	67 SH 30 M	65 29 X	19 01 34 M	69 21 32	55 ON 29	68 OH 34 M	48 2L 31	26 9	M10	76 36	84 40 9999H	83 40 M	83 99 39 SE	15T
PIER (P) OR BUTTRESS (B)		(7) "91X" ⁰ 1 "9#4	(P) 1-21-21-21-21-21-21-21-21-21-21-21-21-21				(7) "01X"01 "044						(P) 16"X16" 4#6			(B) 16"×16" 4#6	(B) "01X"-01 4#6	(P) 16"x"6" 4#6			(P) "01X"-01 "0+4	PIER (P) OR BUTTRESS (B)
BASEPLATE (T x M x H)		3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	1/2"x12"x12"	3/4"x12"x12"	3/4"x12"x12"	1 1/4"x12"x12"	3/4"x12"x12"	1 1/4"x12"x12"	BASEPLATE (T x M x H)
FLOOR	FLOOR HEIGHT	C/6	C/8	C/9	C/10	C/11	D/2	D/3	D/4	D/5	D/6	D/8	D/9	D/10	D/11	E/1	F/1.7	F/2	F/3.3	F/4	F/5.2	FLOOR



NOTES: 1. COLUMN SCHEDULE KEY: CUMULATIVE SERVICE — DEAD LOAD IN KIPS COL. SIZE CUMULATIVE SERVICE -LIVE LOAD IN KIPS

INDICATES COLUMN IS PART OF A LATERAL MOMENT FRAME. SEE MOMENT FRAME ELEVATIONS ON 5-401 THROUGH S-403 FOR LATERAL COLUMN LOADS.

ISSUED: BID SET ISSUANCE **DATE:** 06/30/2025 **SCALE:** As indicated

> SCHEDULES SHEET NUMBER:

SHEET NAME:

REVISIONS

S-301

7/3/2025 12:00:14 PM

PROJECT NUMBER: C4040.00 COPYRIGHT © 2024 KSQ ARCHITECTS, PC

189 Smith Street Poughkeepsie, NY 12601 845-473-3600 office www.arriscontracting.com It is a violation of Title VIII, Article 147 of NYS Education Law for any person, unless acting under the direction of a licensed architect, to

ARCHITECT

KSQ Architects PC dba KSQ Design 215 W 40th St - 15th flr

New York, NY 10018 646.435.0660 office www.ksq.design

ROCKLAND BOCES 65 Parrott Rd,

West Nyack, NY, 10994 845-627-4700 office www.rocklandboces.org

Civil & MEP Engineer

845-343-1481 office

Structural Engineer

New York, NY 10016 212-545-7878 office

Food Service Consultant:

ELITE | STUDIO E 1856 New Hwy #1 Famingdale, NY, 11735 631-429-9400 office www.elitestudioe.com

Construction Manager:

ARRIS CONTRACTING COMPANY, inc.

www.fellp.com

www.gace.net

FELLENZER ENGINEERING LLP 22 Mulberry Street. Suite 2A Middletown, NY 10940

GACE CONSULTING ENGINEERS 148 Madison Avenue, Fourth Floor

Owner

ROCKLAND BOCES P-TECH C-TEC

alter any item on this document in any way. Any licensee who alters this document is

alterations made.

required by law to affix his or her seal and the notation "altered by" followed by his or her signature and a specific description of the

ROCKLAND BOCES

SED #: 50-90-00-00-0-044-001

BUILDING

65 Parrot Rd, West Nyack, NY 10994

