











LIGHT FIXTURE SCHEDULE	
SYMBOL	DESCRIPTION
	24"x24" FIXTURE
	24"x48" FIXTURE
	DECORATIVE WALL SCONCE - INTERIOR
	DECORATIVE WALL SCONCE - EXTERIOR
	SURFACE MOUNTED FIXTURE - EXTERIOR
	12"x48" SURFACE MOUNTED CEILING FIXTURE
	LINEAR CLOSET FIXTURE
	EXISTING WALL MOUNTED FLOOD LIGHT
	BATHROOM LINEAR SURFACE FIXTURE
	SERVICE LIGHT - EXTERIOR

NOTE:
REFER TO ELECTRICAL DRAWINGS FOR FIXTURE SPECIFICATIONS AND WIRING

GRID & CEILING TILE SPECIFICATION
ARMSTRONG - FINE FIGURED ANGLED TEGULAR 24"x24"x5/8", FIGUARD HUMIGUARD WITH BIOBLOCK. PROVIDE 3/8" EXPOSED TEE GRID SYSTEM. ALL TILE OUTS TO BE TEGULAR.

- RCP GENERAL NOTES:
- ALL FIXTURES AND EQUIPMENT SUSPENDED FROM CEILING STRUCTURE SHALL BE IN CONFORMANCE WITH INSTALLATION METHODS UNDER ASTM C-836 AND 2015 IMC.
 - ALL JOINTS AT NEW DUCTWORK TO BE SEALED WITH APPROVED SEALANT AS PER 2021 IBC (INTL. ENERGY CODE) SEE MECH. DUGS.
 - LIGHTS AT SUSPENDED CEILING: LIGHT FIXTURES WEIGHING LESS THAN 56 LBS. SHALL HAVE TWO (2) GAGE WIRES ATTACHED AT OPPOSING CORNERS OF THE FIXTURE TO THE STRUCTURE ABOVE.
 - THE STARTING POINT OF CEILING TILE IS THE CENTER OF ROOM. CENTER CEILING TILE TO THE CENTER OF THE ROOM (UNLESS NOTED OTHERWISE)
 - SEE INTERIOR AND EXTERIOR ELEVATIONS FOR HEIGHTS OF WALL MOUNTED LIGHTING.
 - ALL CENTERLINES INDICATED ARE TO CENTER OF ROOM.



545.5 WESTCHESTER AVENUE
RYE BROOK, NY 10573
914-937-5596

EPF-HP #230997 / 23PR10281

RENOVATION OF THE RYE TOWN PARK BATH HOUSE RYE, NEW YORK, 10580

DATE	ISSUE TO	PR	TO
04.07.2025	SHPO REVIEW		
06.05.2025	SHPO REVIEW		
06.26.2025	ISSUE FOR PERMIT		
07.07.2025	ISSUE FOR BID		

NO	DATE	REVISIONS	BY

REFLECTED CEILING PLAN	
PROJECT NO.:	22105
SCALE:	1/4" = 1'-0"
DRAWN BY:	JP
CHECKED BY:	GG
DATE:	12/13/21