

COMCHECK Software Version COMCHECKWeb

Interior Lighting Compliance Certificate

Project Information

Energy Code: 2020 New York Energy Conservation Construction Code
Project Title: 10 and 20 Dunnington Drive
Project Type: Addition

Construction Site: 2020 New York Energy Conservation Construction Code
Owner/Agent: 10 and 20 Dunnington Drive
Suffern, New York 10901
Designer/Contractor:

Allowed Interior Lighting Power

A Area Category	B Floor Area (f2)	C Allowed Watts /f2	D Allowed Watts
1-Mezzanine 1 (Office)	4746	0.79	3749
2-Mezzanine 2 (Office)	5408	0.79	4272
3-Administration (Office)	10963	0.79	8661
4-ASRS Addition (Warehouse)	102307	0.48	49107
Total Allowed Watts =			65790

Proposed Interior Lighting Power

Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixture	D Fixture Watt.	E (C X D)
1-Mezzanine 1 (Office)				
LED: LF2: Other:	1	27	20	540
LED: B4: Other:	1	10	20	200
2-Mezzanine 2 (Office)				
LED: LF2: Other:	1	25	20	500
LED: B4: Other:	1	7	20	140
LED: LF3: Other:	1	11	11	124
3-Administration (Office)				
LED: LF2: Other:	1	76	20	1520
LED: LF3: Other:	1	70	11	791
4-ASRS Addition (Warehouse)				
LED: AN: Other:	1	34	230	7806
LED: AW: Other:	1	22	230	5061
LED: B4: Other:	1	29	20	708
LED: AN:EM: Other:	1	32	230	7347
LED: AW:EM: Other:	1	14	230	3214
LED: B4:EM: Other:	1	11	20	220
Total Proposed Watts =				28405

Project Title: 10 and 20 Dunnington Drive
Data filename:

Report date: 09/15/21
Page 5 of 37

Interior Lighting PASSES: Design 57% better than code		
Interior Lighting Compliance Statement Compliance Statement: The proposed interior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2020 New York Energy Conservation Construction Code requirements in COMcheck Version COMcheckWeb and to comply with any applicable mandatory requirements listed in the Inspection Checklist.		
Andrew Berger, AIA, ASLA	09-10-2021	
Name - Title	Signature 	Date
Project Title: 10 and 20 Dunnigan Drive		Report date: 09/15/21
Data Filename:		Page 6 of 37

COMCHECK Software Version COMCHECKWeb

Exterior Lighting Compliance Certificate

Project Information

Energy Code: 2020 New York Energy Conservation Construction Code
 Project Title: 10 and 20 Dunnigan Drive
 Project Type: Addition
 Exterior Lighting Zone: 2 (Light industrial area with limited nighttime use (L2Z))

Construction Site: 10 & 20 Dunnigan Drive
 Owner/Agent: Suffern, New York 10901
 Designer/Contractor:

Allowed Exterior Lighting Power

A Area/Surface Category	B Quantity	C Allowed Watts /	D Tradable Watts	E Allowed Watts (B X C)
Lower Level (Parking area)	59100 R2	0.04	Yes	2364
2nd Mezz (Parking area)	10200 R2	0.04	Yes	408
Underside of Mezzanine 1 (Loading dock)	4746 R2	0.35	Yes	1661
Canopy at 20 Dunnigan (Loading docks)	7630 R2	0.35	Yes	2670
Electrical Yard (illuminated area of facade wall or surface)	5816 R2	0.07	No	436
North Ramp & Truck Access (Parking area)	30986 R2	0.04	Yes	1239
East Loading Dock (Parking area)	79378 R2	0.04	Yes	3175
6 loading 2 Parking (Parking area)	22372 R2	0.04	Yes	895
Total Tradable Watts (a) =				12413
Total Allowed Watts =				12949
Total Allowed Supplemental Watts (b) =				440

(a) Wattage tradeoffs are only equal to tradable areas/surfaces.

(b) A supplemental allowance equal to 400 watts may be applied toward compliance if all non-tradable and tradable areas/surfaces.

Proposed Exterior Lighting Power

Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixture	D Fixture Watt.	E (C X D)
Lower Level (Parking area, 59100 R2): Tradable Wattage LED: Other:	1	54	23	1237
2nd Mezz (Parking area, 10200 R2): Tradable Wattage LED: Other:	1	7	23	160
Underside of Mezzanine 1 (Loading dock, 4746 R2): Tradable Wattage LED: C8: Other:	1	11	40	440
Canopy at 20 Dunnigan (Loading dock, 7630 R2): Tradable Wattage LED: C8: Other:	1	33	40	1320
Electrical Yard (illuminated area of facade wall or surface, 5816 R2): Non-tradable Wattage LED: W: Other:	2	29	58	
North Ramp & Truck Access (Parking area, 30986 R2): Tradable Wattage LED: W: Other:	1	5	29	146
LED: PHIL: Other:	1	1	154	154

Project Title: 10 and 20 Dunnigan Drive

Data filename:

Report date: 09/15/21

Page 7 of 37

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast		B Lamps/ Fixture	C # of Fixture	D Fixture Watt.	(C X D)
LED: PII: Other:		1	1	154	154
Fast Loading Dock (Parking area, 79378 ft2): Tradable Wattage					
LED: W: Other:		1	5	29	146
LED: PII: Other:		1	1	154	154
LED: PIV: Other:		1	2	154	307
LED: PV: Other:		1	2	154	307
6 loading, 2 parking (Parking area, 22372 ft2): Tradable Wattage					
LED: PII: Other:		1	1	154	154
LED: W: Other:		1	1	29	29
Total Tradable Proposed Watts =					4706
Exterior Lighting PASSES: Design 63% better than code					
Exterior Lighting Compliance Statement					
Compliance Statement: The proposed exterior lighting design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed exterior lighting systems have been designed to meet the 2020 New York Energy Conservation Construction Code requirements in COMcheck Version COMcheckweb and to comply with any applicable mandatory requirements listed in the Inspection Checklist.					
Andrew Berger, AIA, ASLA				09-10-2021	
Name - Title		Signature 		Date	

Project Title: 10 and 20 Dumnigan Drive

Data filename:

☐ Report date: 09/15/21

Page 8 of 37

ARCHITECT 	di Domenico + Partners LLP Architecture Landscape Architecture Planning 3743 Crescent Street, 3rd Floor Long Island City, New York 11101 Tel 212-337-0400 Fax 212-337-3567
CIVIL PLANNING ENGINEER 	JMC Planning Engineering Landscape Architecture & Land Surveying, PLLC 120 Bedford Road Armonk, New York 10504 Tel 914-273-5225 Fax 914-273-2102
MEP ENGINEER 	BURNS ENGINEERING, PC. 1261 Broadway, Suite 708 New York, New York 10001 Tel 212-962-3503
STRUCTURAL ENGINEER 	GEI Consultants GEI50 1385 Broadway, 20th FL New York, New York 10018 Tel 212-687-8282
	
MANHATTAN BEER DISTRIBUTORS 100 W. 30th St. New York, NY 10001 Tel 212-691-1000	
MANHATTAN BEER DISTRIBUTORS 20 DUNNIGAN DRIVE SUFFERN, NEW YORK	

INTERIOR LIGHTING COMPLIANCE CERTIFICATE

ENERGY CONSERVATION CODE
NOTES

1. THE BUILDING THERMAL ENVELOPE SHALL MEET THE REQUIREMENTS OF THE 2020 ENERGY CONSERVATION CODE OF NEW YORK STATE.
2. PER TABLE C301.1 SUFFERN, ROCKLAND COUNTY IS CLIMATE ZONE 5A.
3. PER TABLE C402.1.3, MINIMUM R VALUES SHALL BE AS FOLLOW
 - 3.1. ROOF INSULATION SHALL BE R-30 MINIMUM, CONTINUOUS INSULATION.
 - 3.2. MASS WALLS (CONCRETE OR CMU) SHALL BE

ENERGY COMPLIANCE NOTES

COMCHECK Software Version 8.0MCMCheckWeb

Envelope Compliance Certificate

Project Information

Energy Code:	2020 New York Energy Conservation Construction Code
Project Title:	10 and 20 Dunningan Drive
Location:	Suffern, New York
Climate Zone:	5a
Project Type:	Addition
Vertical Glazing / Wall Area:	5%

Construction Site:	Owner/Agent:	Designer/Contractor:
10 & 20 Dunningan Drive Suffern, New York 10901		

Building Area	Floor Area
1-Mezzanine 1 (Office) : Nonresidential	4748
2-Mezzanine 2 (Office) : Nonresidential	5408
3-Administration (Office) : Nonresidential	10963
4-ASRS Addition (Warehouse) : Nonresidential	102307

Envelope Assemblies

Assembly	Gross Area or Perimeter	Cavity R-Value	Cont. R-Value	Proposed U-Factor	Budget U- Factor
Roof: Insulation Entirely Above Deck, [Bldg. Use 3 - Administration] Roof: Insulation Entirely Above Deck, [Bldg. Use 4 - ASRS Addition]	11955 102307	---	30.0 30.0	0.032 0.032	0.048 0.048
Floor: Concrete Floor (over unconditioned space), [Bldg. Use 1 - Mezzanine 1]	4748	---	30.0	0.030	0.074
Floor: Concrete Floor (over unconditioned space), [Bldg. Use 2 - Mezzanine 2]	602	---	30.0	0.030	0.074
Floor: Concrete Floor (over unconditioned space), [Bldg. Use 3 - Administration]	11955	---	30.0	0.030	0.074
Floor: Unheated Slab-On-Grade, [Bldg. Use 4 - ASRS Addition] (c)	1284	---	0.730	0.730	0.730

NORTH					
Ext. Wall: Steel-Framed, 24in. o.c., [Bldg. Use 1 - Mezzanine 1]	1489	13.0	7.5	0.060	0.064
Door: Insulated Metal, Swinging, [Bldg. Use 1 - Mezzanine 1]	21	---	---	0.600	0.700
Door: Insulated Metal, Swinging, [Bldg. Use 1 - Mezzanine 1]	21	---	---	0.600	0.700
Ext. Wall: Steel-Framed, 24in. o.c., [Bldg. Use 2 - Mezzanine 2]	468	13.0	7.5	0.060	0.064
Door: Insulated Metal, Swinging, [Bldg. Use 2 - Mezzanine 2]	21	---	---	0.600	0.700
Ext. Wall: Steel-Framed, 24in. o.c., [Bldg. Use 2 - Mezzanine 2]	419	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, [Bldg. Use 2 - Mezzanine 2]	240	---	---	0.660	0.450
Ext. Wall: Steel-Framed, 24in. o.c., [Bldg. Use 2 - Mezzanine 2]	166	13.0	7.5	0.060	0.064
Ext. Wall: Steel-Framed, 24in. o.c., [Bldg. Use 2 - Mezzanine 2]	1231	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, [Bldg. Use 3 - Administration]	16	---	---	0.650	0.450

Project Title: 10 and 20 Dunningan Drive

Data Filename:

Report date: 09/15/21

Page 1 of 37

Assembly	Gross Area or Perimeter	R-Value	Cont. R-Value	Proposed U-Factor	Budget U-Factor ₀
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Ext. Wall: Steel-Framed, 24in. oc., (Bldg. Use 3 - Administration)	730	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	292	---	---	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450
Ext. Wall: Other (U-Factor option), Heat capacity 0.0, (Bldg. Use 4 - ASRS Addition) (b)	1980	---	---	0.031	0.064
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	121	---	---	0.030	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Door: Other (U-Factor option), Non-Swinging, (Bldg. Use 4 - ASRS Addition)	80	---	---	1.200	0.179
Ext. Wall: Steel-Framed, 24in. oc., (Bldg. Use 3 - Administration) (b)	750	---	---	0.031	0.064
Ext. Wall: Other (U-Factor option), Heat capacity 0.0, (Bldg. Use 3 - Administration) (b)	6150	---	---	0.031	0.064
EAST					
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 1 - Mezzanine 1)	273	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 1 - Mezzanine 1)	122	---	---	0.650	0.450
Door: Insulated Metal, Swing, (Bldg. Use 2 - Mezzanine 2)	276	13.0	7.5	0.060	0.064
Door: Insulated Metal, Swing, (Bldg. Use 2 - Mezzanine 2)	21	---	---	0.600	0.700
Project Title: 10 and 20 Dumping Drive					Report date: 09/15/21
Data Filename:					Page 2 of 37

Assembly	Gross Area or Perimeter	R-Value	Cont. R-Value	U-Factor	Budget U-Factor _H
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 2 - Mezzanine 2)	400	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 2 - Mezzanine 2)	122	—	—	0.650	0.450
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg Use 3 - Administration)	400	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 3 - Administration)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 3 - Administration)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 3 - Administration)	16	—	—	0.650	0.450
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg Use 3 - Administration)	275	13.0	7.5	0.060	0.064
Door: Insulated Metal, Swinging, (Bldg. Use 3 - Administration)	42	—	—	0.600	0.700
Ext. Wall: Other Exterior Wall, Heat capacity 0.0, (Bldg Use 3 - Administration) (b)	2600	—	—	0.031	0.064
Ext. Wall: Other Exterior Wall, Heat capacity 0.0, (Bldg Use 3 - Administration) (b)	2960	—	—	0.031	0.064
SOUTH					
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 1 - Mezzanine 1)	1489	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 1 - Mezzanine 1)	16	—	—	0.650	0.450
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg Use 2 - Mezzanine 2)	2221	13.0	7.5	0.060	0.064
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 2 - Mezzanine 2)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 2 - Mezzanine 2)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 2 - Mezzanine 2)	16	—	—	0.650	0.450
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg Use 2 - Mezzanine 2)	16	—	—	0.650	0.450
Project Title: 10 and 20 Dumburn Drive	Report date: 09/15/21				
Data filename:	Page 3 of 37				

Assembly	Gross Area or Perimeter	R-Value	Cont. R-Value	Proposed U-Factor	Budget U-Factor ₁₀			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 2 - Mezzanine 2)	16	---	---	0.650	0.450			
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 3 - Administration)	260	13.5	7.5	0.059	0.064			
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 3 - Administration)	1651	13.0	7.5	0.060	0.064			
Ext. Wall: Other Exterior Wall, Heat capacity 0.0, (Bldg. Use 3 - Administration) (b)	14550	---	---	0.031	0.064			
WCST								
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 1 - Mezzanine 1)	273	13.0	7.5	0.060	0.064			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.38, (Bldg. Use 1 - Mezzanine 1)	80	---	---	0.650	0.450			
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 2 - Mezzanine 2)	407	13.0	7.5	0.060	0.064			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 2 - Mezzanine 2)	16	---	---	0.650	0.450			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 2 - Mezzanine 2)	16	---	---	0.650	0.450			
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 2 - Mezzanine 2)	262	13.0	7.5	0.060	0.064			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 2 - Mezzanine 2)	104	---	---	0.650	0.450			
Door: ... Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 2 - Mezzanine 2)	48	---	---	0.800	0.800			
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 3 - Administration)	318	13.0	7.5	0.060	0.064			
Door: Insulated Metal, Swinging, (Bldg. Use 3 - Administration)	42	---	---	0.600	0.700			
Ext. Wall: Steel-Framed, 24in. o.c., (Bldg. Use 3 - Administration)	686	13.5	7.5	0.059	0.064			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450			
Window: Metal Frame with Thermal Break: Fixed, Perf. Type: Energy code default, Double Pane with Low-E, Clear, SHGC 0.70, (Bldg. Use 3 - Administration)	16	---	---	0.650	0.450			
Ext. Wall: Other Exterior Wall, Heat capacity 0.0, (Bldg. Use 4 - ASRS Addition) (b)	7020	---	---	0.031	0.064			
(a) Budget U-factors are used for software baseline calculations ONLY, and are not code requirements. (b) Other components require supporting documentation for proposed U-factors. (c) Sub-On-Grade proposed and budget U-factors shown in table are R-factors.								
Envelope PASSES: Design 23% better than code								
Envelope Compliance Statement								
Compliance Statement: The proposed envelope design represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed envelope systems have been designed to meet the 2020 New York Energy Conservation Construction Code requirements in COMcheckVersion COMcheckWeb and are consistent with any applicable mandatory requirements listed in the Inspection Checklist.								
Andrew Berger, AIA, ASLA				09-10-2021				
Name - Title	Signature 			Date				
Project Title: 10 and 20 Dummigan Drive								
Data Filename:				Report date: 09/15/21				
				Page 4 of 37				

REV	DESCRIPTION	DATE
—	ISSUED FOR DOB SUBMISSION	9.10.21
—	ISSUED FOR BID	10.15.21
—	ISSUED FOR CONSTRUCTION	11.30.21
—	REVISED BID SET	01.20.22
—	REVISED FOR CONSTRUCTION	04.05.22
—	PER METAL PANEL REDESIGN	07.26.22
—	REVISED FOR CONSTRUCTION	08.15.22
DRAWN BY :		S. WOO
CHECKED BY :		D. TOBAR, R.A.
APPROVED BY :		A. BERGER, R.A.
DATE :		07.30.2021
SCALE :		AS NOTED
DRAWING TITLE :		
ENERGY CODE COMPLIANCE		
		DWG NUMBER :
		A 000

ENVELOPE COMPLIANCE CERTIFICATE

A-003