

ACCESSORY & FIXTURE SCHEDULE/SYMBOL DESCRIPTION			REF DWG	MAKE	MODEL	SYMBOL		
						PLAN	ELEV.	SIDE ELEV.
FIXTURE AND MISC.	A	WALL MOUNTED WATER CLOSET FOR ADA MOUNTING HEIGHT 1’–7” MAXIMUM ABOVE FINISHED FLOOR WITH TOILET FLUSH VALVE AND ELONGATED FRONT OPEN SEAT	A–508	TOTO	CT708UG WITH TET1UA AND SC534			
	B	WALL MOUNTED LAVATORY. ADA MOUNTING HEIGHT 2’–10” MAXIMUM ABOVE FINISHED FLOOR	A–508	TOTO	LTG69			
	C	WALL MOUNTED URINAL FOR HANDICAPPED. MOUNTING HEIGHT 1’–5” MAXIMUM ABOVE FINISHED FLOOR	A–508	TOTO	UT104E WITH TETU1LA			
	D	SURFACE MOUNTED ELECTRIC SENSOR HAND DRYER WITH STAINLESS STEEL BRUSHED FINISH. INSTALL BOTTOM OF UNIT ABOVE FINISH FLOOR IN ACCORDANCE TO ADA GUIDELINES	A–508	DYSON	HU02SPRAYED NICKEL 307172–01			
	E	SLOP/SERVICE SINK WITH UTILITY FAUCET. MOUNTING HEIGHT 2’–2” ABOVE FINISHED FLOOR	A–508	AMERICAN STANDARD	LAKEWELL SERVICE SINK 7692.000 W/ 8344.012			
	F	MOP SINK WITH UTILITY FAUCET	A–508	FIAT/AMERICAN STANDARD	TSB3001 W/ 8344.012			
	G	WALL MOUNTED WATER COOLER FOR HANDICAPPED. WATER SPOUT OUTLET SHALL BE NO HIGHER THAN 3’–0” ABOVE FINISHED FLOOR	A–508					
	H	FIRE EXTINGUISHER. HANDLE AT 48” ABOVE FINISH FLOOR	A–511					
	I	FIRE EXTINGUISHER WITH ENCLOSURE, RECESSED	A–511					
ACCESSORIES	J	RECESSED MOUNTED PAPER TOWEL DISPENSER AND WASTE RECEPTACLE, TOP OF UNIT MOUNTED 48” MAX. ABOVE FINISHED FLOOR	A–508					
	K	SURFACE MOUNTED STAINLESS STEEL SINGLE JUMBO–ROLL TOILET TISSUE DISPENSER MOUNTED 20” ABOVE FINISHED FLOOR TO BOTTOM OF DISPENSER	A–508	BOBRICK	B2890			
	L	CUSTODIAN UTILITY SHELF WITH MOP & BROOM HOLDERS & RAG HOOKS MOUNTED 4’–0” ABOVE FINISHED FLOOR	A–508					
	M	18” X 30” STAINLESS STEEL FRAME MIRROR AND SHELF, TOP OF FRAME MOUNTED 6’–6” ABOVE FINISHED FLOOR	A–508					
	N	1 1/4 ” DIA S.S. GRAB BAR W/ CONCEALED MOUNTING, 3’–0” LONG PEENED NON–SLIP GRIPPING SURFACE. SHALL BE INSTALLED IN A HORIZONTAL POSITION, TOP OF BAR MOUNTED 3’–0” MAX. ABOVE FINISH FLOOR	A–508					
	O	1 1/4 ” DIA S.S. GRAB BAR W/ CONCEALED MOUNTING, 3’–6” LONG PEENED NON–SLIP GRIPPING SURFACE. SHALL BE INSTALLED IN A HORIZONTAL POSITION, TOP OF BAR MOUNTED 3’–0” MAX. ABOVE FINISH FLOOR	A–508					
	P	1 1/4 ” DIA S.S. GRAB BAR W/ CONCEALED MOUNTING, 18” LONG PEENED NON–SLIP GRIPPING SURFACE. SHALL BE INSTALLED IN A VERTICAL POSITION, BOTTOM OF BAR MOUNTED 39” A.F.F. AND 39”–41” AWAY FROM WALL	A–508					
	Q	SOLID CAST ALUMINUM COAT HOOK WITH BUMPER IN EVERY TOILET COMPARTMENT. CENTER LINE OF HOOK SHALL BE MOUNTED 3’–3” (4’–0” MAX.) ABOVE FINISHED FLOOR AT ADA LOCATIONS AND 5’–6” ABOVE FINISHED FLOOR AT ALL OTHER LOCATIONS.	A–508					
	R	LIQUID SOAP DISPENSER WITH SHATTERPROOF TRANSLUCENT REFILL WINDOW. TOP OF UNIT MOUNTED 4’–2 1/2” ABOVE FINISHED FLOOR.	A–508					

[illegible]