



4

3

1



- 1 DISCONNECT AND REMOVE CEILING EXHAUST FANS INCLUDING ASSOCIATED 4" ROUND FLEXIBLE DUCTWORK TERMINATED OPEN-ENDED ABOVE TOILET ROOM CEILING.
- DISCONNECT AND REMOVE 3/4" HWS/R DROPS DOWN TO FIN TUBE RADIATION BACK TO SHUT-OFF VALVES 2 DISCONNECT AND REMOVE 3/4" HWS/R DROPS DOWN TO FIN TO BE RADIATION DROP TO GLO FOR A ADDITION DROP TO GLO FOR ADDITICO ADDITION DROP TO GLO FOR ADDITION D

3 DISCONNECT AND REMOVE EA DUCTWORK AND ASSOCIATED SURFACE MOUNTED EA REGISTER BACK TO DISCONNECTION POINT SHOWN.

(4) DISCONNECT AND REMOVE UN-DUCTED CEILING MOUNTED REGISTER OPEN TO CEILING PLENUM.

THROUGH TOILET ROOM WALL, THEN DOWN THROUGH FLOOR TO BOILER ROOM BELOW.

ENCLOSURE, HORIZONTAL FIN TUBE ENCLOSURE, AND 2-WAY CONTROL VALVE. MAINTAIN SPACE TEMPERATURE SENSOR AT LOCATION SHOWN FOR REUSE.

4

